## ш3schools.com

THE WORLD'S LARGEST WEB DEVELOPER SITE



# JavaScript Functions

< Previous</pre>

Next >

A JavaScript function is a block of code designed to perform a particular task.

A JavaScript function is executed when "something" invokes it (calls it).

#### Example

```
function myFunction(p1, p2) {
  return p1 * p2;  // The function returns the product of p1 and p2
}
```

Try it Yourself »

# JavaScript Function Syntax

A JavaScript function is defined with the function keyword, followed by a name, followed by parentheses ().

Function names can contain letters, digits, underscores, and dollar signs (same rules as variables).

The parentheses may include parameter names separated by commas:

```
(parameter1, parameter2, ...)
```

The code to be executed, by the function, is placed inside curly brackets: {}

```
function name(parameter1, parameter2, parameter3) {
  // code to be executed
}
```

Function **parameters** are listed inside the parentheses () in the function definition.

Function arguments are the values received by the function when it is invoked.

Inside the function, the arguments (the parameters) behave as local variables.

A Function is much the same as a Procedure or a Subroutine, in other programming languages.

#### **Function Invocation**

The code inside the function will execute when "something" **invokes** (calls) the function:

- When an event occurs (when a user clicks a button)
- When it is invoked (called) from JavaScript code
- Automatically (self invoked)

You will learn a lot more about function invocation later in this tutorial.

### **Function Return**

When JavaScript reaches a return statement, the function will stop executing.

If the function was invoked from a statement, JavaScript will "return" to execute the code after the invoking statement.

Functions often compute a return value. The return value is "returned" back to the "caller":

#### Example

Calculate the product of two numbers, and return the result:

The result in x will be:

12

Try it Yourself »

# Why Functions?

You can reuse code: Define the code once, and use it many times.

You can use the same code many times with different arguments, to produce different results.

### Example

Convert Fahrenheit to Celsius:

```
function toCelsius(fahrenheit) {
  return (5/9) * (fahrenheit-32);
}
document.getElementById("demo").innerHTML = toCelsius(77);
```

Try it Yourself »

# The () Operator Invokes the Function

Using the example above, toCelsius refers to the function object, and toCelsius() refers to the function result.

Accessing a function without () will return the function definition instead of the function result:

#### Example

```
function toCelsius(fahrenheit) {
  return (5/9) * (fahrenheit-32);
}
document.getElementById("demo").innerHTML = toCelsius;
Try it Yourself »
```

### Functions Used as Variable Values

Functions can be used the same way as you use variables, in all types of formulas, assignments, and calculations.

#### Example

Instead of using a variable to store the return value of a function:

```
var x = toCelsius(77);
var text = "The temperature is " + x + " Celsius";
```

You can use the function directly, as a variable value:

```
var text = "The temperature is " + toCelsius(77) + " Celsius";
Try it Yourself »
```

You will learn a lot more about functions later in this tutorial.

## **Local Variables**

Variables declared within a JavaScript function, become **LOCAL** to the function.

Local variables can only be accessed from within the function.

#### Example

```
// code here can NOT use carName
function myFunction() {
  var carName = "Volvo";
```

```
// code here CAN use carName
}
// code here can NOT use carName
Try it Yourself »
```

Since local variables are only recognized inside their functions, variables with the same name can be used in different functions.

Local variables are created when a function starts, and deleted when the function is completed.

## Test Yourself With Exercises

## Exercise:

Execute the function named myFunction.

```
function myFunction() {
  alert("Hello World!");
}
```

Submit Answer »

#### Start the Exercise

Previous

Next >

COLOR PICKER



#### HOW TO

Tabs Dropdowns Accordions Side Navigation Top Navigation **Modal Boxes Progress Bars** Parallax Login Form HTML Includes Google Maps Range Sliders **Tooltips** Slideshow Filter List Sort List

#### **SHARE**







#### CERTIFICATES

 $\mathsf{HTML}$ 

CSS

JavaScript

SQL

Python

PHP

jQuery

Bootstrap

 $\mathsf{XML}$ 

Read More »



# الفيلم العربي ركلام

"الواقع المر لبنات الليل فيلم ركلام متوفر الآن على تطبيق Viu"

viu.c



REPORT ERROR PRINT PAGE FORUM ABOUT

**Top Tutorials** 

**Top References** 

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
jQuery Tutorial
Java Tutorial
C++ Tutorial

#### Top Examples

HTML Examples
CSS Examples
JavaScript Examples
How To Examples
SQL Examples
Python Examples
W3.CSS Examples
Bootstrap Examples
PHP Examples
jQuery Examples
Java Examples
XML Examples

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors
jQuery Reference
Java Reference
Angular Reference

#### Web Certificates

HTML Certificate
CSS Certificate
JavaScript Certificate
SQL Certificate
Python Certificate
jQuery Certificate
PHP Certificate
Bootstrap Certificate
XML Certificate

Get Certified »

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

