



JavaScript Let

[< Previous](#)[Next >](#)

ECMAScript 2015

ES2015 introduced two important new JavaScript keywords: `let` and `const`.

These two keywords provide **Block Scope** variables (and constants) in JavaScript.

Before ES2015, JavaScript had only two types of scope: **Global Scope** and **Function Scope**.

Global Scope

Variables declared **Globally** (outside any function) have **Global Scope**.

```
var carName = "Volvo";

// code here can use carName

function myFunction() {
  // code here can also use carName
}
```

Try it Yourself »

Global variables can be accessed from anywhere in a JavaScript program.

Function Scope

Variables declared **Locally** (inside a function) have **Function Scope**.

Example

```
// code here can NOT use carName

function myFunction() {
  var carName = "Volvo";
  // code here CAN use carName
}
```



Try it Yourself »

Local variables can only be accessed from inside the function where they are declared.

JavaScript Block Scope

Variables declared with the **var** keyword can not have **Block Scope**.

Variables declared inside a block **{}** can be accessed from outside the block.

Example

```
{  
  var x = 2;  
}  
// x CAN be used here
```

Before ES2015 JavaScript did not have **Block Scope**.

Variables declared with the **let** keyword can have Block Scope.

Variables declared inside a block **{}** can not be accessed from outside the block:



```
{  
  let x = 2;  
}  
// x can NOT be used here
```

Redeclaring Variables

Redeclaring a variable using the **var** keyword can impose problems.

Redeclaring a variable inside a block will also redeclare the variable outside the block:

Example

```
var x = 10;  
// Here x is 10  
{  
  var x = 2;  
  // Here x is 2  
}  
// Here x is 2
```

Try it Yourself »

Redeclaring a variable inside a block will not redeclare the variable outside the block:

Example

```
var x = 10;  
// Here x is 10  
{  
  let x = 2;  
  // Here x is 2  
}  
// Here x is 10
```

Try it Yourself »

Browser Support

The **let** keyword is not fully supported in Internet Explorer 11 or earlier.

The following table defines the first browser versions with full support for the **let** keyword:

Chrome 49	Edge 12	Firefox 44	Safari 11	Opera 36
Mar, 2016	Jul, 2015	Jan, 2015	Sep, 2017	Mar, 2016



HTML

CSS

JAVASCRIPT

MORE ▼



Loop Scope

Using **var** in a loop:

Example

```
var i = 5;
for (var i = 0; i < 10; i++) {
  // some statements
}
// Here i is 10
```

Try it Yourself »

Using **let** in a loop:

Example

```
let i = 5;
for (let i = 0; i < 10; i++) {
  // some statements
}
// Here i is 5
```

In the first example, using `var`, the variable declared in the loop redeclares the variable outside the loop.

In the second example, using `let`, the variable declared in the loop does not redeclare the variable outside the loop.

When `let` is used to declare the `i` variable in a loop, the `i` variable will only be visible within the loop.

Function Scope

Variables declared with `var` and `let` are quite similar when declared inside a function.

They will both have **Function Scope**:

```
function myFunction() {  
  var carName = "Volvo"; // Function Scope  
}
```

```
function myFunction() {  
  let carName = "Volvo"; // Function Scope  
}
```



Global Scope

Variables declared with `var` and `let` are quite similar when declared outside a block.

They will both have **Global Scope**:

```
var x = 2;      // Global scope
```

```
let x = 2;      // Global scope
```

Global Variables in HTML

With JavaScript, the global scope is the JavaScript environment.

In HTML, the global scope is the window object.

Global variables defined with the `var` keyword belong to the window object:

Example



HTML

CSS

JAVASCRIPT

MORE ▼



Try it Yourself »

Global variables defined with the **let** keyword do not belong to the window object:

Example

```
let carName = "Volvo";  
// code here can not use window.carName
```

Try it Yourself »

Redeclaring

Redeclaring a JavaScript variable with **var** is allowed anywhere in a program:

Example

```
var x = 2;  
  
// Now x is 2
```



```
// Now x is 3
```

Try it Yourself »

Redeclaring a **var** variable with **let**, in the same scope, or in the same block, is not allowed:

Example

```
var x = 2;      // Allowed
let x = 3;      // Not allowed

{
  var x = 4;    // Allowed
  let x = 5     // Not allowed
}
```

Redeclaring a **let** variable with **let**, in the same scope, or in the same block, is not allowed:

Example

```
let x = 2;      // Allowed
let x = 3;      // Not allowed
```

```
let x = 5;    // Not allowed
}
```

Redeclaring a `let` variable with `var`, in the same scope, or in the same block, is not allowed:

Example

```
let x = 2;    // Allowed
var x = 3;    // Not allowed

{
  let x = 4;   // Allowed
  var x = 5;   // Not allowed
}
```

Redeclaring a variable with `let`, in another scope, or in another block, is allowed:

Example

```
let x = 2;    // Allowed

{
  let x = 3;   // Allowed
}
```



HTML

CSS

JAVASCRIPT

MORE ▼



}

[Try it Yourself »](#)

Hoisting

Variables defined with **var** are **hoisted** to the top (if you don't know what Hoisting is, read our [Hoisting Chapter](#)).

You can use a variable before it is declared:

Example

```
// you CAN use carName here  
var carName;
```

[Try it Yourself »](#)

Variables defined with **let** are not hoisted to the top.

Using a **let** variable before it is declared will result in a **ReferenceError**.

The variable is in a "temporal dead zone" from the start of the block until it is declared:



HTML

CSS

JAVASCRIPT

MORE ▼



```
// you can NOT use carName here  
let carName;
```

[< Previous](#)[Next >](#)

COLOR PICKER



HOW TO

- Tabs
- Dropdowns
- Accordions
- Side Navigation
- Top Navigation
- Modal Boxes

[HTML](#)[CSS](#)[JAVASCRIPT](#)[MORE ▼](#)

[Login Form](#)
[HTML Includes](#)
[Google Maps](#)
[Range Sliders](#)
[Tooltips](#)
[Slideshow](#)
[Filter List](#)
[Sort List](#)

SHARE



CERTIFICATES

[HTML](#)
[CSS](#)
[JavaScript](#)
[SQL](#)
[Python](#)
[PHP](#)
[jQuery](#)
[Bootstrap](#)
[XML](#)

[Read More »](#)

[HTML](#)[CSS](#)[JAVASCRIPT](#)[MORE ▼](#)[REPORT ERROR](#)[PRINT PAGE](#)[FORUM](#)[ABOUT](#)

Top Tutorials

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [How To Tutorial](#)
- [SQL Tutorial](#)
- [Python Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [PHP Tutorial](#)
- [jQuery Tutorial](#)
- [Java Tutorial](#)
- [C++ Tutorial](#)

Top Examples

Top References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [SQL Reference](#)
- [Python Reference](#)
- [W3.CSS Reference](#)
- [Bootstrap Reference](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [jQuery Reference](#)
- [Java Reference](#)
- [Angular Reference](#)

Web Certificates

[HTML](#)[CSS](#)[JAVASCRIPT](#)[MORE ▼](#)[JavaScript Examples](#)[How To Examples](#)[SQL Examples](#)[Python Examples](#)[W3.CSS Examples](#)[Bootstrap Examples](#)[PHP Examples](#)[jQuery Examples](#)[Java Examples](#)[XML Examples](#)[JavaScript Certificate](#)[SQL Certificate](#)[Python Certificate](#)[jQuery Certificate](#)[PHP Certificate](#)[Bootstrap Certificate](#)[XML Certificate](#)[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2020 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

