



HTML

CSS

JAVASCRIPT

MORE ▼



JavaScript Object Constructors

[< Previous](#)[Next >](#)

Example

```
function Person(first, last, age, eye) {  
  this.firstName = first;  
  this.lastName = last;  
  this.age = age;  
  this.eyeColor = eye;  
}
```

[Try it yourself »](#)

It is considered good practice to name constructor functions with an upper-case first letter.

Object Types (Blueprints) (Classes)

The examples from the previous chapters are limited. They only create single objects.

Sometimes we need a "**blueprint**" for creating many objects of the same "type".

The way to create an "object type", is to use an **object constructor function**.

In the example above, `function Person()` is an object constructor function.

Objects of the same type are created by calling the constructor function with the `new` keyword:

```
var myFather = new Person("John", "Doe", 50, "blue");  
var myMother = new Person("Sally", "Rally", 48, "green");
```

Try it yourself »

The **this** Keyword

In JavaScript, the thing called `this` is the object that "owns" the code.

The value of `this` , when used in an object, is the object itself.

In a constructor function `this` does not have a value. It is a substitute for the new object. The value of `this` will become the new object when a new object is created.

Note that `this` is not a variable. It is a keyword. You cannot change the value of `this` .

Adding a Property to an Object

Adding a new property to an existing object is easy:

Example

```
myFather.nationality = "English";
```

Try it Yourself »

The property will be added to myFather. Not to myMother. (Not to any other person objects).

Adding a Method to an Object

Adding a new method to an existing object is easy:

Example

```
myFather.name = function () {  
    return this.firstName + " " + this.lastName;  
};
```

Try it Yourself »

The method will be added to myFather. Not to myMother. (Not to any other person objects).

Adding a Property to a Constructor

You cannot add a new property to an object constructor the same way you add a new property to an existing object:

Example

```
Person.nationality = "English";
```

Try it Yourself »

To add a new property to a constructor, you must add it to the constructor function:

Example

```
function Person(first, last, age, eyecolor) {  
    this.firstName = first;  
    this.lastName = last;  
}
```

```
this.age = age;  
this.eyeColor = eyecolor;  
this.nationality = "English";  
}
```

Try it Yourself »

This way object properties can have default values.

Adding a Method to a Constructor

Your constructor function can also define methods:

Example

```
function Person(first, last, age, eyecolor) {  
  this.firstName = first;  
  this.lastName = last;  
  this.age = age;  
  this.eyeColor = eyecolor;  
  this.name = function() {return this.firstName + " " + this.lastName;};  
}
```

Try it Yourself »

You cannot add a new method to an object constructor the same way you add a new method to an existing object.

Adding methods to an object constructor must be done inside the constructor function:

Example

```
function Person(firstName, lastName, age, eyeColor) {  
  this.firstName = firstName;  
  this.lastName = lastName;  
  this.age = age;  
  this.eyeColor = eyeColor;  
  this.changeName = function (name) {  
    this.lastName = name;  
  };  
}
```

The changeName() function assigns the value of name to the person's lastName property.

Now You Can Try:

```
myMother.changeName("Doe");
```

Try it Yourself »

JavaScript knows which person you are talking about by "substituting" **this** with **myMother**.

Built-in JavaScript Constructors

JavaScript has built-in constructors for native objects:

Example

```
var x1 = new Object();    // A new Object object
var x2 = new String();    // A new String object
var x3 = new Number();    // A new Number object
var x4 = new Boolean();   // A new Boolean object
var x5 = new Array();     // A new Array object
var x6 = new RegExp();    // A new RegExp object
var x7 = new Function();  // A new Function object
var x8 = new Date();      // A new Date object
```

Try it Yourself »

The `Math()` object is not in the list. `Math` is a global object. The `new` keyword cannot be used on `Math`.

Did You Know?

As you can see above, JavaScript has object versions of the primitive data types `String`, `Number`, and `Boolean`. But there is no reason to create complex objects. Primitive values are much faster.

ALSO:

Use object literals `{}` instead of `new Object()`.

Use string literals `""` instead of `new String()` .

Use number literals `12345` instead of `new Number()` .

Use boolean literals `true` / `false` instead of `new Boolean()` .

Use array literals `[]` instead of `new Array()` .

Use pattern literals `/()/` instead of `new RegExp()` .

Use function expressions `() {}` instead of `new Function()` .

Example

```
var x1 = {};           // new object
var x2 = "";           // new primitive string
var x3 = 0;            // new primitive number
var x4 = false;        // new primitive boolean
var x5 = [];           // new array object
var x6 = /()/          // new regexp object
var x7 = function(){}; // new function object
```

Try it Yourself »

String Objects

Normally, strings are created as primitives: `var firstName = "John"`

But strings can also be created as objects using the `new` keyword: `var firstName = new String("John")`

Learn why strings should not be created as object in the chapter [JS Strings](#).

Number Objects

Normally, numbers are created as primitives: `var x = 123`

But numbers can also be created as objects using the `new` keyword: `var x = new Number(123)`

Learn why numbers should not be created as object in the chapter [JS Numbers](#).

Boolean Objects

Normally, booleans are created as primitives: `var x = false`

But booleans can also be created as objects using the `new` keyword: `var x = new Boolean(false)`

Learn why booleans should not be created as object in the chapter [JS Booleans](#).

[< Previous](#)[Next >](#)

COLOR PICKER



HOW TO

Tabs
Dropdowns
Accordions
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List

SHARE



CERTIFICATES

HTML

CSS

JavaScript

SQL

Python


PHP

jQuery

Bootstrap

XML

[Read More »](#)



[REPORT ERROR](#)

[PRINT PAGE](#)

[FORUM](#)

[ABOUT](#)

[Top Tutorials](#)

[Top References](#)

- HTML Tutorial
- CSS Tutorial
- JavaScript Tutorial
- How To Tutorial
- SQL Tutorial
- Python Tutorial
- W3.CSS Tutorial
- Bootstrap Tutorial
- PHP Tutorial
- jQuery Tutorial
- Java Tutorial

Top Examples

- HTML Examples
- CSS Examples
- JavaScript Examples
- How To Examples
- SQL Examples
- Python Examples
- W3.CSS Examples
- Bootstrap Examples
- PHP Examples
- jQuery Examples
- Java Examples
- XML Examples

- HTML Reference
- CSS Reference
- JavaScript Reference
- SQL Reference
- Python Reference
- W3.CSS Reference
- Bootstrap Reference
- PHP Reference
- HTML Colors
- jQuery Reference
- Angular Reference
- Java Reference

Web Certificates

- HTML Certificate
- CSS Certificate
- JavaScript Certificate
- SQL Certificate
- Python Certificate
- jQuery Certificate
- PHP Certificate
- Bootstrap Certificate
- XML Certificate

[Get Certified »](#)

W3Schools is optimized for learning, testing, and training. Examples might be simplified to improve reading and basic understanding. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using this site, you agree to have read and accepted our terms of use, cookie and privacy policy. Copyright 1999-2019 by Refsnes Data. All Rights Reserved.

Powered by W3.CSS.

