

JAVA TUTORIAL

#INDEX POSTS

#INTERVIEW QUESTIONS

RESOURCES

Design Patterns Tutorial

Java Design Patterns

Creational Design Patterns

- > [Singleton](#)
- > [Factory](#)
- > [Abstract Factory](#)
- > [Builder](#)
- > [Prototype](#)

Structural Design Patterns

- > [Adapter](#)
- > [Composite](#)
- > [Proxy](#)
- > [Flyweight](#)
- > [Facade](#)
- > [Bridge](#)
- > [Decorator](#)

Behavioral Design

YOU ARE HERE: [HOME](#) » [JAVA](#) » [DESIGN PATTERNS](#) » BRIDGE DESIGN PATTERN IN JAVA

Instantly Search Tutorials...

Bridge Design Pattern in Java

PANKAJ — 26 COMMENTS

Today we will look into Bridge [Design Pattern](#) in java. When we have interface hierarchies in both interfaces as well as implementations, then **bridge design pattern** is used to decouple the interfaces from implementation and hiding the implementation details from the client programs.

Bridge Design Pattern

Just like [Adapter pattern](#), bridge design pattern is one of the **Structural design pattern**.

According to GoF bridge design pattern is:

Patterns

- > [Template Method](#)
- > [Mediator](#)
- > [Chain of Responsibility](#)
- > [Observer](#)
- > [Strategy](#)
- > [Command](#)
- > [State](#)
- > [Visitor](#)
- > [Interpreter](#)
- > [Iterator](#)
- > [Memento](#)

Miscellaneous Design Patterns

- > [Dependency Injection](#)
- > [Thread Safety in Java Singleton](#)

Recommended Tutorials


- + [Java Tutorials](#)
- + [Java EE Tutorials](#)

“ Decouple an abstraction from its implementation so that the two can vary independently


The implementation of bridge design pattern follows the notion to prefer **Composition** over **inheritance**.

Bridge Design Pattern in Java Example

If we look into bridge design pattern with example, it will be easy to understand. Lets say we have an interface hierarchy in both interfaces and implementations like below image.



Now we will use bridge design pattern to decouple the interfaces from implementation. UML diagram for the classes and interfaces after applying bridge pattern will look like below image.



Notice the bridge between `Shape` and `Color` interfaces and use of composition in implementing the bridge pattern.

Here is the java code for Shape and Color interfaces.

Color.java

```
package com.journaldev.design.bridge;
```

```
public interface Color {
```

```
    public void applyColor();
```

```
}
```

Shape.java

```
package com.journaldev.design.bridge;
```

```
public abstract class Shape {
```

```
    //Composition - implementor
```

```
    protected Color color;
```

```
    //constructor with implementor as input argument
```

```
    public Shape(Color c){
```

```
        this.color=c;
```

```
    }
```

```
    abstract public void applyColor();
```

```
}
```

We have Triangle and Pentagon implementation classes as below.

Triangle.java

```
package com.journaldev.design.bridge;
```

```
public class Triangle extends Shape{
```

```
    public Triangle(Color c) {  
        super(c);  
    }
```

```
    @Override
```

```
    public void applyColor() {  
        System.out.print("Triangle filled with color  
");  
        color.applyColor();  
    }
```

```
}
```

Pentagon.java

```
package com.journaldev.design.bridge;
```

```
public class Pentagon extends Shape{
```

```
    public Pentagon(Color c) {  
        super(c);  
    }
```

```
        @Override
        public void applyColor() {
            System.out.print("Pentagon filled with color
");
            color.applyColor();
        }
    }
}
```

Here are the implementation classes for RedColor and GreenColor.

RedColor.java

```
package com.journaldev.design.bridge;

public class RedColor implements Color{

    public void applyColor(){
        System.out.println("red.");
    }
}
```

GreenColor.java

```
package com.journaldev.design.bridge;

public class GreenColor implements Color{
```

```
        public void applyColor(){
            System.out.println("green.");
        }
    }
}
```

Lets test our bridge pattern implementation with a test program.

BridgePatternTest.java

```
package com.journaldev.design.test;

import com.journaldev.design.bridge.GreenColor;
import com.journaldev.design.bridge.Pentagon;
import com.journaldev.design.bridge.RedColor;
import com.journaldev.design.bridge.Shape;
import com.journaldev.design.bridge.Triangle;

public class BridgePatternTest {

    public static void main(String[] args) {
        Shape tri = new Triangle(new RedColor());
        tri.applyColor();


        Shape pent = new Pentagon(new GreenColor());
        pent.applyColor();
    }
}
```

Output of above bridge pattern example program is:


Triangle filled with color red.

Pentagon filled with color green.


Bridge design pattern can be used when both abstraction and implementation can have different hierarchies independently and we want to hide the implementation from the client application.



Composite Design Pattern in Java




Adapter Design Pattern in Java




Facade Design Pattern in Java




Mediator Design Pattern in Java



DAO Design Pattern



Proxy Design Pattern



Java (JVM) Memory Model - Memory Management in Java



Java Exan

« **PREVIOUS**

Adapter Design Pattern in Java

NEXT »

Composite Design Pattern in Java

**About Pankaj**

If you have come this far, it means that you liked what you are reading. Why not reach little more and connect with me directly on **Google Plus**, **Facebook** or **Twitter**.

I would love to hear your thoughts and opinions on my articles directly.

Recently I started creating video tutorials too, so do check out my videos on **Youtube**.

FILED UNDER: **DESIGN PATTERNS**

Comments

Sumeet Aggarwal says

JANUARY 21, 2019 AT 10:00 AM

Do we have any reference in JAVA JDK/API where Bridge pattern is used ?

Reply

lukas says

OCTOBER 3, 2018 AT 11:28 AM

code is not displayed properly. go to html view of your browser to see the code nevertheless

KG

[Reply](#)**Pankaj says**

OCTOBER 3, 2018 AT 10:47 PM

What do you mean by code is not displayed properly. Can you please clear your cookie and cache? The code is properly formatted using syntax highlighter.

[Reply](#)**lukas says**

OCTOBER 4, 2018 AT 5:09 AM

My browser seemed to have troubles to display the code examples. Now it works again without making any changes, btw: good work!

[Reply](#)**Rasa says**

MAY 16, 2017 AT 1:41 AM

If I understood this article correct, first schema addresses the state before, and UML diagram addresses the state after applying Bridge pattern. If that's what you meant to show, I guess that schema is not correct. Arrows from RedColor and GreenColor towards Triangle and Pentagon, should be pointing vice-versa.

[Reply](#)

Rasa1 says

MAY 16, 2017 AT 2:05 AM

In that case, RedColor and GreenColor would have been abstract classes meant to be extended from Triangle, or Pentagon. Triangle and Pentagon would have to implement Shape interface too.

Or, maybe the names of RedColor and GreenColor are such by mistake and should have been called RedColorTriangle, RedColorPentagon, GreenColorTriangle and GreenColorPentagon. This makes more sense according to the scheme drawing.

[Reply](#)

Anupama says

FEBRUARY 23, 2017 AT 1:35 AM

Hi Pankaj,

Thanks for the explanation. I am not fully clear on the example. In the example we could create the color instances and pass it to the

shapes. Then why can not we call the apply color directly on the color objects themselves? Why we are going thru the shape objects?

Thanks in advance,

[Reply](#)

urbandroid says

AUGUST 5, 2017 AT 4:16 AM

because shape should have that property the color is not a independent from the shape and other way will be bloated with if and elses try to convince yourself.

[Reply](#)

Paul says

FEBRUARY 6, 2017 AT 5:40 AM

Great article, I read 2 prior articles which described this pattern, but in no way demonstrated why you would ever have a need to use it. This article does both, and very simply.

[Reply](#)

Anurag says

SEPTEMBER 15, 2016 AT 10:23 PM

Please modify UML diagram, you draw association and describing it as composition.

[Reply](#)

12 says

MAY 27, 2016 AT 7:07 AM

Please, change builder to bridge in the first line of the article

[Reply](#)**Jay says**

MARCH 5, 2016 AT 4:11 AM

Thanks Pankaj for the wonderful article on Design patterns, but you may want to correct the first line on this "Bridge pattern" page:

"When we have interface hierarchies in both interfaces as well as implementations, then builder design "

It is supposed to be bridge pattern and not builder.

[Reply](#)**Anil says**

JULY 23, 2015 AT 2:20 AM

Cool explanation as always.

Which tool are you using for UML diagram.?

[Reply](#)**yousuf says**

APRIL 27, 2015 AT 12:39 AM

The opening sentence,

"When we have interface hierarchies in both interfaces as well as implementations"..

Did you mean 'inheritance hierarchies', when you say 'interface hierarchies'..?

[Reply](#)

Ashakant says

OCTOBER 3, 2014 AT 2:39 PM

Hi Pankaj ,

Nice , simple explanation , after googling so many Design Pattern , its is one of most simple , that why i have saved as screen shoot . It would be favor for all , if u just shared the code as downloadable .

[Reply](#)

KranthiC says

MAY 19, 2014 AT 2:47 AM

Please elaborate on how the decoupling has happened between abstraction and implementation here. Still if we add any abstract method in Shape abstract class, implementation for it is to be provided in Triangle and Pentagon classes. Similarly if any method is declared in interface Color, its implementation needs to be provided in RedColor and GreenColor classes, so how is the decoupling achieved here...

[Reply](#)

Himansu Nayak says

JUNE 10, 2014 AT 9:13 PM

Hi Kranthi,

When we say De-Coupling it means "loose coupling" or "no coupling" at all. Pankaj example perfectly shows the loosely coupling of 2 different hierarchy of class and how it is bridged using composition and not interface.

Please don't confused De-Coupling to some T.V. with Remote both communicating via Radio Signal.

[Reply](#)**Pravin Katkar says**

AUGUST 29, 2014 AT 5:26 AM

This example decouples the shape abstraction from specific apply Color implementation

[Reply](#)**Dilip Kumar Pandey says**

APRIL 11, 2014 AT 5:41 PM

Thanks Pankaj

Very self explanatory tutorials.

Any chance of that you will upload design-pattern vedioes?

[Reply](#)

Pankaj says

APRIL 11, 2014 AT 9:48 PM

I haven't planned for videos in near future, but who knows I might find time to get them too. ☐

[Reply](#)**Prasad says**

DECEMBER 17, 2013 AT 7:37 AM

Hi Pankaj,

Nice explanation. Can you please clarify below.

If implementation of applyColor() method is different for both Triangle and Pentagon classes, then this design patterns is not suitable right?

[Reply](#)**Pankaj says**

DECEMBER 17, 2013 AT 8:33 AM

Implementation will obviously be different because both classes have different tasks to do, and this pattern is suitable for this scenario.

[Reply](#)**Prasad says**

DECEMBER 17, 2013 AT 6:20 PM

Sorry for the confusion i have created here. Let me elaborate my question.

Suppose i write the below code in main() method.

```
Shape tri = new Triangle(new RedColor());
tri.applyColor();
Shape pent = new Pentagon(new RedColor());
pent.applyColor();
```

Here i would like to get the below output.

Triangle filled with color light red.

Pentagon filled with color dark red.

How can we achieve this using bridge pattern?

[Reply](#)

Pankaj says

DECEMBER 18, 2013 AT 1:27 AM

Change the System.out.print() value in Triangle as:

System.out.print("Triangle filled with color light");

and Pentagon as:

System.out.print("Triangle filled with color dark");

[Reply](#)

Nitsan says

APRIL 23, 2015 AT 4:55 AM

I would say add two new color implementations called DarkRedColor and LightRedColor, and keep the Shape implementations unaware of that change.

Basil George says

JULY 27, 2015 AT 4:30 AM

In this case:

```
Shape tri = new Triangle(new RedColor(new Dark()));
```

```
tri.applyColor();
```

```
Shape pent = new Pentagon(new GreenColor(new  
Light()));
```

```
pent.applyColor();
```

```
public interface Density {  
}
```

```
public class Dark implements Density {  
}
```

```
public class Light implements Density {  
}
```

```
public class GreenColor extends Color {  
    public GreenColor(Density d) {  
        super(d);  
    }  
}
```

```
@Override  
public void applyColor(){  
    if(density instanceof Dark)  
        System.out.println("Dark green.");  
    if(density instanceof Light)  
        System.out.println("Light green.");  
}
```

```
public class RedColor extends Color {
    public RedColor(Density d) {
        super(d);
    }
    @Override
    public void applyColor(){
        if(density instanceof Dark)
            System.out.println("Dark red.");
        if(density instanceof Light)
            System.out.println("Light red.");
    }
}

public abstract class Color {
    protected Density density;
    //constructor with implementor as input argument
    public Color(Density d) {
        this.density = d;
    }
    public abstract void applyColor();
}
```

Reply

Comment Policy: Please submit comments to add value to the post. Comments like "Thank You" and "Awesome Post" will be not published. If you want to post code then wrap them inside <pre> tags. For example **<pre>class Foo { }</pre>**.

If you want to post XML content, then please escape < with < and > with > otherwise they will not be shown properly.

Leave a Reply

Your email address will not be published. Required fields are marked *

Comment

Name *

Email *

POST COMMENT