


[Courses](#)[Login](#)[Suggest an Article](#)

Software Engineering | Coupling and Cohesion

Introduction: The purpose of Design phase in the Software Development Life Cycle is to produce a solution to a problem given in the SRS(Software Requirement Specification) document. The output of the design phase is Software Design Document (SDD).

Basically, design is a two-part iterative process. First part is Conceptual Design that tells the customer what the system will do. Second is Technical Design that allows the system builders to understand the actual hardware and software needed to solve customer's problem.



**Conceptual design of system:**

- Written in simple language i.e. customer understandable language.
- Detail explanation about system characteristics.
- Describes the functionality of the system.
- It is independent of implementation.
- Linked with requirement document.

Technical Design of system:

- Hardware component and design.
- Functionality and hierarchy of software component.
- Software architecture
- Network architecture
- Data structure and flow of data.




- I/O component of the system.
- Shows interface.

Modularization: Modularization is the process of dividing a software system into multiple independent modules where each module works independently. There are many advantages of Modularization in software engineering. Some of these are given below:

- Easy to understand the system.
- System maintenance is easy.
- A module can be used many times as their requirements. No need to write it again and again.

Coupling: Coupling is the measure of the degree of interdependence between the modules. A good software will have low coupling.




Types of Coupling:



- **Data Coupling:** If the dependency between the modules is based on the fact that they communicate by passing only data, then the modules are said to be data coupled. In data coupling, the components are independent to each other and communicating through data. Module communications don't contain tramp data. Example-customer billing system.
- **Stamp Coupling** In stamp coupling, the complete data structure is passed from one module to another module. Therefore, it involves tramp data. It may be necessary due to efficiency factors- this choice made by the insightful designer, not a lazy programmer.
- **Control Coupling:** If the modules communicate by passing control information, then they are said to be control coupled. It can be bad if parameters indicate completely different behavior and good if parameters allow factoring and reuse of functionality. Example- sort function that takes comparison function as an argument.
- **External Coupling:** In external coupling, the modules depend on other modules, external to the software being developed or to a particular type of hardware. Ex- protocol, external file, device format, etc.
- **Common Coupling:** The modules have shared data such as global data structures. The changes in global data mean tracing back to all modules which access that data to evaluate the effect of the change. So it has got disadvantages like difficulty in reusing modules, reduced ability to control data accesses and reduced maintainability.
- **Content Coupling:** In a content coupling, one module can modify the data of another module or control flow is passed from one module to the other module. This is the worst form of coupling and should be avoided.

Cohesion: Cohesion is a measure of the degree to which the elements of the module are functionally related. It is the degree to which all elements directed towards performing a single task are contained in the component. Basically, cohesion is the internal glue that keeps the module together. A good software design will have high cohesion.





Types of Cohesion:

- **Functional Cohesion:** Every essential element for a single computation is contained in the component. A functional cohesion performs the task and functions. It is an ideal situation.
- **Sequential Cohesion:** An element outputs some data that becomes the input for other element, i.e., data flow between the parts. It occurs naturally in functional programming languages.
- **Communicational Cohesion:** Two elements operate on the same input data or contribute towards the same output data. Example- update record into the database and send it to the printer.
- **Procedural Cohesion:** Elements of procedural cohesion ensure the order of execution. Actions are still weakly connected and unlikely to be reusable. Ex- calculate student GPA, print student record, calculate cumulative GPA, print cumulative GPA.
- **Temporal Cohesion:** The elements are related by their timing involved. A module connected with temporal cohesion all the tasks must be executed in the same time-span. This cohesion contains the code for initializing all the parts of the system. Lots of different activities occur, all at init time.
- **Logical Cohesion:** The elements are logically related and not functionally. Ex- A component reads inputs from tape, disk, a network. All the code for these functions is in the same component. Operations are related, but the functions are significantly different.

- **Coincidental Cohesion:** The elements are not related(unrelated). The elements have no conceptual relationship other than location in source code. It is accidental and the worst form of cohesion. Ex- print next line and reverse the characters of a string in a single component.

Recommended Posts:

[Software Engineering | Requirements Engineering Process](#)

[Software Engineering | Introduction to Software Engineering](#)

[Software Engineering | Jelinski Moranda software reliability model](#)

[Software Engineering | Schick-Wolverton software reliability model](#)

[Software Engineering | Role and Responsibilities of a software Project Manager](#)

[Software Engineering | Software Project Management Complexities](#)

[Software Engineering | Identifying Software Development Metrics](#)

[Software Engineering | Software Business and Development](#)

[Software Engineering | Software Quality Assurance \(SQA\) Set 2](#)

[Software Engineering | Agile Software Development](#)

[Software Engineering | Seven Principles of software testing](#)

[Software Engineering | Changing Nature of Software](#)

[Software Engineering | Classification of Software Requirements](#)

[Software Engineering | Halstead's Software Metrics](#)

[Software Engineering | Software Quality Assurance](#)



**Josikakar**Check out this Author's [contributed articles](#).

If you like GeeksforGeeks and would like to contribute, you can also write an article using contribute.geeksforgeeks.org or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please Improve this article if you find anything incorrect by clicking on the "Improve Article" button below.

**Article Tags :** [Computer Subject](#) [Software Engineering](#)

3

☐ To-do ☐ Done

0

No votes yet.

[Feedback/ Suggest Improvement](#)[Add Notes](#)[Improve Article](#)

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.



Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

[Load Comments](#)[Share this post!](#)

A computer science portal for geeks

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305
feedback@geeksforgeeks.org

COMPANY

[About Us](#)
[Careers](#)
[Privacy Policy](#)
[Contact Us](#)

PRACTICE

[Company-wise](#)
[Topic-wise](#)
[Contests](#)
[Subjective Questions](#)

LEARN

[Algorithms](#)
[Data Structures](#)
[Languages](#)
[CS Subjects](#)
[Video Tutorials](#)

CONTRIBUTE

[Write an Article](#)
[Write Interview Experience](#)
[Internships](#)
[Videos](#)

@geeksforgeeks, Some rights reserved

