

```

((base) a7mad@MacBook-Pro-alkhas-bAhmad Desktop % mkdir git-test
((base) a7mad@MacBook-Pro-alkhas-bAhmad Desktop % cd git-test
((base) a7mad@MacBook-Pro-alkhas-bAhmad git-test % mkdir test01
((base) a7mad@MacBook-Pro-alkhas-bAhmad git-test % cd test01
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git init
hint: Using 'master' as the name for the initial branch. This default branch name
hint: is subject to change. To configure the initial branch name to use in all
hint: of your new repositories, which will suppress this warning, call:
hint:
hint:   git config --global init.defaultBranch <name>
hint:
hint: Names commonly chosen instead of 'master' are 'main', 'trunk' and
hint: 'development'. The just-created branch can be renamed via this command:
hint:
hint:   git branch -m <name>
Initialized empty Git repository in /Users/a7mad/Desktop/git-test/test01/.git/
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % nano first.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git add first.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git commit -m "first"
[master (root-commit) 753b85a] first
 1 file changed, 1 insertion(+)
 create mode 100644 first.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % nano second.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git add second.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git commit -m "second"
[master 7ab4a5f] second
 1 file changed, 1 insertion(+)
 create mode 100644 second.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % nano third.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % nano fourth.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git status
On branch master
Untracked files:
  (use "git add <file>..." to include in what will be committed)
    fourth.txt
    third.txt

nothing added to commit but untracked files present (use "git add" to track)
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git add .
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git status
On branch master
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
    new file:   fourth.txt
    new file:   third.txt

((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git commit -m "add third and fourth"
[master ffb8be6] add third and fourth
 2 files changed, 2 insertions(+)
 create mode 100644 fourth.txt
 create mode 100644 third.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git log
commit ffb8be6c265a378551850e3349645f8043c9bf28 (HEAD -> master)
Author: ahmad <contact.alsubhi@gmail.com>
Date:   Tue Jul 23 20:03:46 2024 +0300

    add third and fourth

commit 7ab4a5fa4b72b8120dfb481d0c200231eb926415
Author: ahmad <contact.alsubhi@gmail.com>
Date:   Tue Jul 23 20:01:46 2024 +0300

    second

commit 753b85a6a2ec62c48d7acffb5c5f16d846206678
Author: ahmad <contact.alsubhi@gmail.com>
Date:   Tue Jul 23 20:01:07 2024 +0300

    first
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git brache
git: 'brache' is not a git command. See 'git --help'.

The most similar command is
    branch

```



```

first
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git brache
git: 'brache' is not a git command. See 'git --help'.

The most similar command is
    branch
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git braches
git: 'braches' is not a git command. See 'git --help'.
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git branch
* master
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git branch new-feature
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git branch
* master
  new-feature
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git checkout new-feature
Switched to branch 'new-feature'
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git branch
  master
* new-feature
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % nano lab02.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git add lab02.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git status
On branch new-feature
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
    new file:   lab02.txt

((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git commit -m "lab02"
[new-feature eb0f739] lab02
 1 file changed, 1 insertion(+)
 create mode 100644 lab02.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % ls
first.txt      fourth.txt     lab02.txt      second.txt      third.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git checkout master
Switched to branch 'master'
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git branch
* master
  new-feature
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git merge new-feature
Updating ffb8be6..eb0f739
Fast-forward
 lab02.txt | 1 +
 1 file changed, 1 insertion(+)
 create mode 100644 lab02.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % ls
first.txt      fourth.txt     lab02.txt      second.txt      third.txt
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git remote -v
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git remote add lab-3 https://github.com/AhmadAlsubhi/Day-3.git
((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git push
fatal: The current branch master has no upstream branch.
To push the current branch and set the remote as upstream, use

    git push --set-upstream lab-3 master

To have this happen automatically for branches without a tracking
upstream, see 'push.autoSetUpRemote' in 'git help config'.

((base) a7mad@MacBook-Pro-alkhas-bAhmad test01 % git push -u lab-3 master
Enumerating objects: 13, done.
Counting objects: 100% (13/13), done.
Delta compression using up to 8 threads
Compressing objects: 100% (7/7), done.
Writing objects: 100% (13/13), 934 bytes | 934.00 KiB/s, done.
Total 13 (delta 2), reused 0 (delta 0), pack-reused 0 (from 0)
remote: Resolving deltas: 100% (2/2), done.
remote:
remote: Create a pull request for 'master' on GitHub by visiting:
remote:   https://github.com/Ahmad-Alsubhi/Day-3/pull/new/master
remote:
To https://github.com/Ahmad-Alsubhi/Day-3.git
 * [new branch]      master -> master
branch 'master' set up to track 'lab-3/master'.
(base) a7mad@MacBook-Pro-alkhas-bAhmad test01 %

```

Ahmad-Alsubhi / Day-3

Q Type to search

+ 🔍 📄 📧 👤

<> Code 🔍 Pull requests ⚙️ Actions 📁 Projects 📖 Wiki 🛡️ Security 📈 Insights ⚙️ Settings

👤 Day-3Public

forked from Tuwaiq-DS-ML-bootcamp-V-7/Day-3

📌 Pin

👁 Watch 0

🍴 Fork 0

☆ Star 0

🔥 master had recent pushes 27 seconds ago

Compare & pull request

🔥 master 2 Branches 0 Tags

🔍 Go to file t

Add file

<> Code

This branch is 4 commits ahead of, 3 commits behind Tuwaiq-DS-ML-bootcamp-V-7/Day-3:main

🔍 Contribute

🔄 Sync fork

👤 Ahmad-Alsubhi lab02

eb01739 · 4 minutes ago · 4 Commits

📄 first.txt	first	10 minutes ago
📄 fourth.txt	add third and fourth	8 minutes ago
📄 lab02.txt	lab02	4 minutes ago
📄 second.txt	second	10 minutes ago
📄 third.txt	add third and fourth	8 minutes ago

📖 README

📖

Add a README

Help people interested in this repository understand your project by adding a README.

Add a README

About

No description, website, or topics provided.

👤 Activity

☆ 0 stars

👁 0 watching

🍴 0 forks

Releases

No releases published

Create a new release

Packages

No packages published

Publish your first package

Languages

🔴 Jupyter Notebook 100.0%

👤 @ 2024 GitHub, Inc.

Terms Privacy Security Status Docs Contact Manage cookies Do not share my personal information