Recommendation and Information Diffusion on Epinions

SNTP Assignment 2 — Technical Report

Student	Ahmad Fareed
Roll number	23F3008
Course	Social Network Theory and Programming (SNTP)
Institution	National University of Computer and Emerging Sciences
Campus	Chiniot-Faisalabad Campus
Submission	21 October 2026
Dataset	Epinions ratings + trust network
Measured run	Bounded fast demo (full data files, 2-hop diffusion graph)

This report is generated from the saved JSON artifacts of the measured fast-demo run. It covers all eight requirements: data preparation, baseline recommenders, trust-aware recommendation, ICM/SIR diffusion, influence maximization, group recommendation, comprehensive evaluation, and the diffusion-limiting intervention with CELF and cost scaling. All cascade and satisfaction-after-intervention results are simulations; the dataset contains no adoption timestamps.

The measured fast-demo wall-clock runtime was 264.5 s (~4.4 min), including data loading, model fitting, all experiment stages, and result serialization. The larger full-scale configuration was not executed; no full-scale result is claimed.

Contents

1. Executive summary and requirement map

2. Dataset, split, and leakage protocol

3. Requirement 1 — data preparation

4. Requirement 2 — baseline recommendation

5. Requirement 3 — trust-aware recommendation

6. Requirement 4 — ICM, SIR, and preference-aware diffusion

7. Requirement 5 — influence maximization

8. Requirement 6 — group recommendation

9. Requirement 7 — comprehensive evaluation

10. Requirement 8 — intervention, CELF, and scaling

11. Verification, tests, and reproducibility

12. Limitations and conclusions

Source of reported numbers

Every numeric value in the tables is read from `results/fast_demo/*.json` at report-generation time. The stage timing table comes from `stage_timings.json`. The report is regenerated with the command shown in Section 11. This makes the PDF searchable and keeps the prose synchronized with the saved artifacts rather than with hand-copied values.

1. Executive summary and requirement map

The dataset contains 49,289 users, 139,738 items, 664,824 ratings, and 487,002 trust edges. The split is 463,663 train / 100,603 validation / 100,558 test ratings. Models are fitted on train; validation selects the social weight; test is used only for the final observed evaluation.

The strongest measured result is that matrix factorization and the trust-aware social model substantially outperform item-based CF on rating error. The social model is best on test MAE/RMSE and on all top-K ranking metrics in this run. Rankings are ordered by unclipped model scores; only the reported predicted ratings are clipped to [1, 5]. Influence maximization does not show greedy superiority: on the restricted top-degree candidate pool, degree centrality wins at budgets 3 and 5, and the paired greedy−degree difference at budget 5 is negative. Group-strategy satisfaction differences are small, and the spread comparison is dominated by rare large cascades. The threshold intervention has a cliff at 0.8: it removes 99.09% of simulated spread while changing the simulator-side adopter rating proxy by 0.0265, but it is not an online experiment. CELF used 24.24% fewer evaluations and was 1.62× faster in this single noisy Monte-Carlo measurement, while selecting different seeds; a deterministic controlled check reproduced standard greedy exactly.

Requirement	Implementation	Headline measured outcome
1. Data	Parse ratings/trust, validate, split, represent	49,289 users; 463,663/100,603/100,558 split
2. Recommenders	Item-based CF and MF; top-K; raw-score ordering	MF test MAE 0.8324, RMSE 1.0677
3. Trust-aware	Social blend; λ selected on validation	λ=0.3; test MAE 0.8284
4. Diffusion	ICM, SIR, preference-aware; rare + moderate targets; controlled network null	p=0.05 rare canonical 4,684; moderate 3,111
5. Influence	Random/degree/greedy; shared pool and seeds	Degree best at budgets 3 and 5
6. Groups	Average / least misery / most pleasure; train-only groups	Mean satisfaction 4.827 / 4.825 / 4.815
7. Evaluation	MAE/RMSE/P/R/F1/HR/nDCG/coverage/diversity	Social best ranking; ICF broadest coverage
8. Intervention	Threshold, CELF, network/item/budget scaling	0.8: -99.09% spread, proxy 0.0265; CELF 1.62×

Table 1. Requirement map and headline outcomes from the fast-demo run.

What is and is not claimed

- All diffusion, influence, group-spread, simulated-interaction, and intervention outcomes are simulations. The data has no adoption histories.
- The submitted results use a 2-hop ego subgraph for diffusion. They do not describe the full 49,289-user graph.
- No statistical significance is claimed for small differences. Monte Carlo standard deviations and sample scopes are reported.
- The full-scale config is documented but not run; the report makes no full-scale performance claim.

2. Dataset, split, and leakage protocol

2.1 Dataset

Property	Value
Users	49,289
Items	139,738
Ratings	664,824
Trust edges	487,002
Rating matrix sparsity	0.999903
Mean / median ratings per user	16.55 / 6.0
Mean / median ratings per item	4.76 / 1.0
Reciprocal trust edges	105,966
Users with both ratings and trust	40,162

Table 2. Parsed Epinions dataset summary.

Trust rows use the convention “A trusts B”. Influence propagates in the opposite direction: a propagation edge B → A means B can influence A. All parsing counters for malformed, out-of-range, and duplicate records are saved in `data_summary.json`; this run found zero malformed rating lines, zero out-of-range ratings, and zero duplicate rating records.

2.2 Split and evaluation discipline

The split seed is 42 with fractions 0.70/0.15/0.15. Users with at least three ratings contribute at least one record to each split; users with fewer records are kept for training but excluded from evaluation. The split sizes are 463,663 / 100,603 / 100,558. 28,487 users are eligible for evaluation and 11,676 are excluded.

2.3 Leakage prevention

- Model fitting: only training triples. Validation is used for the social λ; test is used only for final reported metrics.
- Group construction (R6): a matrix built explicitly from the training triples. The full `dataset.rating_matrix` is never passed into R6. A regression test mutates the full matrix and asserts that the groups do not change.
- Target item (R4/R7/R8): selected from a training-only popularity band, with the rule and counts saved in JSON.
- Seed sets (R4/R6/R8): generated once and reused across comparable settings. Common random numbers are used for paired comparisons.
- Observed vs simulated: test ratings are labels, not recommender inputs. Simulated diffusion uses predicted affinity, not held-out ratings.
- Candidate pools: all catalogue items except the user's training history for ranking; an explicit shared top-degree pool for R5. The restriction is documented, not hidden.

3. Requirement 1 — data preparation

The loader validates every rating line, builds contiguous user/item indices, a sparse rating matrix, and a directed propagation graph. The splitter enforces the per-user minimum and records the exact sizes. The inspection command is:

```
python -m sntp.cli inspect --data-dir Assignment
```

The item popularity distribution is extremely long-tailed: 99,715 items have only 1–5 training/test interactions in the item-popularity analysis, while 3,449 items have 21+. This is why top-K ranking metrics are low. Part 4 retains the original one-training-rating rare target and adds a separate 6–20-training-rating moderate target for comparison; neither is drawn from the popular head of the distribution.

4. Requirement 2 — baseline recommendation

4.1 Models

Item-based CF uses cosine similarity between item interaction vectors, at most 20 neighbours, and at least 2 co-rated items. Matrix factorization uses 10 latent factors, learning rate 0.005, L2 regularization 0.02, 6 epochs, and seed 42. Both are fitted on the training split. MF tracks which users and items have at least one training observation; untrained rows have zero bias and zero latent factors, so the fallback is μ+b_i for an untrained user with a trained item, μ+b_u for a trained user with an untrained item, and μ when both are unseen. Random initial factors are never used as a cold-start prediction.

Top-K excludes the user's training items and ranks the remaining catalogue. Items are ordered by the unclipped prediction score; only the predicted rating shown with a returned item is clipped to [1, 5]. This prevents artificial ties at 5.0 from replacing confidence ordering with item-ID ordering. For item-based CF an item with no stored neighbours is unsupported by the item-item model, so its documented fallback uses training data only: the user's training mean, then the global training mean. Ranking metrics use a fixed seeded sample of 500 eligible users; MAE/RMSE use all test ratings. Unobserved items are not treated as negative examples.

Model	MAE	RMSE	P@10	R@10	F1@10	HR@10	nDCG@10	Coverage
Item-based CF	1.0740	1.4519	0.0008	0.00281	0.00105	0.0080	0.00163	0.01715
Matrix factorization	0.8324	1.0677	0.0020	0.00515	0.00238	0.0200	0.00343	0.00011

Table 3. Test rating and top-10 ranking metrics. MF is much better on error; both have low absolute ranking metrics on this sparse catalogue.




Figure 1. Test MAE and RMSE for the two baselines. MF reduces both errors substantially.

4.2 Behaviour and popularity slices

MF is consistently better than item-based CF on short, medium, and long user histories and on rare, moderate, and popular item groups. The largest gap is on moderate-popularity items: item-based CF MAE 1.2514 vs MF 0.8433. Item-based CF is not better on the rare-item group; its MAE is 0.9443 vs MF 0.8301. The complete slices are in `requirement_2_results.json`.

Interpretation: MF's low-rank structure handles sparse users and items better than a neighbour model with few co-rated items. The absolute top-K numbers are low because each user has many unobserved catalogue items and only one held-out positive item is used for relevance; this is a hard, conservative ranking setting, not evidence that the recommender is useless.

5. Requirement 3 — trust-aware recommendation

The social recommender blends the baseline prediction with the mean rating of trusted neighbours: `pred = (1−λ)·baseline + λ·trust_neighbour_mean`. The social weight is selected on validation RMSE only. The saved selection record explicitly states that test was not used.

λ	Validation MAE	Validation RMSE	N
0.0	0.83540	1.06899	100,603
0.3	0.83094	1.06397	100,603
0.5	0.83236	1.06934	100,603

Table 4. Validation selection. λ=0.3 has the lowest validation RMSE and is selected before test is examined.

λ	Test MAE	Test RMSE	P@10	HR@10	nDCG@10
0.0 (baseline)	0.83245	1.06771	0.0020	0.0200	0.00343
0.3 (selected)	0.82837	1.06318	0.0024	0.0220	0.00419
0.5	0.82998	1.06886	0.0028	0.0260	0.00481

Table 5. Test metrics reported after selection. λ=0.3 is the validation-selected row.

Sparse users (1–5 ratings, 21,911 users) improve from MAE 0.87454 to 0.87250 at λ=0.3. The trust-vs-similarity comparison sampled 50 users (165 test ratings): trusted neighbours MAE 0.87692, unconnected similar users 0.86635, baseline 0.87576. The similar-user group is slightly better in this small sample, so the trust signal is not uniformly superior; the result is descriptive.

The post-selection rows are shown for transparency. The selection rule is fixed in advance on validation RMSE; choosing a different λ after seeing test ranking would be test leakage. No test metric is used to change the submitted model.

6. Requirement 4 — ICM, SIR, and preference-aware diffusion

6.1 Design and target popularity

Part 4 keeps the original rare-item experiment and adds a separate moderate-popularity target. Both are selected from the training-only rating-count distribution. The rare rule uses the explicit inclusive band [1, 1] training rating and selects original ID 3 (matrix index 2, 1 training rating); 66,605 items satisfy that band. The moderate rule uses the inclusive 6–20 band and selects original ID 69 (matrix index 68, 9 training ratings); the band contains 10,807 items. The rule chooses the count closest to the band median, with ties by ascending original item ID. This retains the earlier ultra-rare case instead of replacing it.

The three seed sets (five users each) and the Monte Carlo seeds are pre-generated once and reused for every ICM and SIR setting on the rare target. The moderate target uses the same generation seed, model settings, graph, and simulation seeds, but its seed users are drawn from the target-specific eligible set (users without a training rating for that item). This is a target comparison, not a claim that both targets share identical seed users. Rare-target seed sets:

```
[734, 3024, 4170, 7316, 13374]
```

```
[883, 1357, 2386, 2860, 13374]
```

```
[1413, 6945, 7018, 7985, 10792]
```

The fast demo uses 9,883 users and 301,710 propagation edges (2-hop ego subgraph centered on user 0), three simulations per setting, and at most 25 rounds. The SIR recovery probability γ=0 uses all 25 rounds because infected users never recover; those round counts are capped by the configured maximum, not evidence that the cascade naturally lasted 25 rounds.

6.2 Measured spreads — retained rare target

Model	Setting	Mean adopters/infected	Std	Mean rounds	Runtime (s)
Canonical ICM	p=0.01	125.33	167.36	9.00	0.025
Canonical ICM	p=0.05	4,684.33	21.70	11.00	0.232
Preference-aware ICM	p=0.01	6.00	0.82	1.00	0.002
Preference-aware ICM	p=0.05	501.33	351.96	7.67	0.106
SIR	beta=0.01_gamma=0.0	2,024.00	915.16	25.00	1.880
SIR	beta=0.01_gamma=0.2	530.67	692.39	17.67	0.465
SIR	beta=0.05_gamma=0.0	8,180.33	116.48	25.00	3.249
SIR	beta=0.05_gamma=0.2	6,039.67	25.17	25.00	2.965

Table 6. Rare-target diffusion outcomes. Means and standard deviations are across the same three pre-generated seed sets and controlled simulation seeds.




Figure 2. Rare-target diffusion outcomes on a log scale. The p=0.01 canonical ICM is heavy-tailed; preference-aware adoption strongly suppresses spread at the same seeds.

6.3 Interpretation — retained rare target

Canonical ICM at p=0.05 reaches about 4,684 of 9,883 active users (47.4%), consistent with a dense ego graph. Preference-aware adoption requires predicted affinity and cuts the p=0.05 mean to 501 (-89.3%); at p=0.01 it changes the mean by -95.2%. This is a model-design effect, not evidence that real users would adopt at that rate. SIR at β=0.05 reaches 8,180 with γ=0 and 6,040 with γ=0.2; recovery reduces ever-infected counts but the γ=0 runs remain active to the round cap.

The p=0.01 canonical ICM has mean 125.3 but standard deviation 167.4 and a maximum of 362: the three simulations are highly unequal. With only three simulations, the mean is unstable. This is reported explicitly rather than hidden; the full configuration uses 20 simulations.

6.4 Moderate-popularity target comparison

The added target is original ID 69 with 9 training ratings (versus 1 for the retained rare target). The same graph, canonical/preference-aware ICM implementations, propagation probabilities, simulation seeds, and seed size are used; only the target item and its target-specific eligible seed pool differ. This makes the comparison descriptive rather than a claim that popularity alone is identified.

Model	Setting	Rare target mean	Moderate target mean	Difference (moderate−rare)	Relative
Canonical	p=0.01	125.33	5.00	-120.33	-96.01%
Preference-aware	p=0.01	6.00	5.00	-1.00	-16.67%
Canonical	p=0.05	4,684.33	3,111.33	-1,573.00	-33.58%
Preference-aware	p=0.05	501.33	10.67	-490.67	-97.87%

Table 7. Retained rare target versus the added 6–20-training-rating target. Seed users are target-specific; all other controls are shared.




Figure 3. Rare versus moderate target at p=0.05. The comparison is descriptive: targets have different seed pools and different training popularity.

6.5 Controlled network-structure comparison

To test whether the observed edge arrangement matters, the active directed graph is randomized while preserving its node set, edge count, and directed in/out-degree sequence. The canonical ICM then runs on the randomized graph with the same rare-target seed users, simulation seeds, propagation probabilities, and round cap. The null model is one seeded degree-preserving rearrangement, not a fully mixed sample of all graphs with that degree sequence.

Randomization preserved 9,883 nodes and 301,710 directed edges; 521,458 of 603,420 double-edge swaps were accepted (86.4%). The degree sequence equality is checked before the comparison is accepted.

Setting	Observed mean	Randomized mean	Paired difference (random−observed)	Relative
p=0.01	125.33	7.33	-118.00	-94.15%
p=0.05	4,684.33	4,780.00	95.67	+2.04%

Table 8. Canonical ICM on observed versus degree-preserving randomized structure. Differences are simulation outcomes, not observed cascades.




Figure 4. Observed versus degree-preserving randomized graph under the same seeds and canonical ICM. This isolates the edge-arrangement effect within the selected null model.

The largest relative difference in this run is at p=0.01: observed mean 125.3 versus randomized mean 7.3. This is evidence about this seeded null model and three simulations, not a general estimate of how much structure matters in Epinions.

7. Requirement 5 — influence maximization

The comparison uses one propagation graph (9,883 nodes, 301,710 edges), one propagation probability (0.05), budgets 1/3/5, and a shared candidate pool. The pool is the top 15 out-degree users in the propagation graph (ties by ascending user index), identical for all methods. This bound is necessary for a fast demo, but it gives degree centrality a structural advantage. The result describes that pool, not all graph users.

Random selection is repeated for three seeded trials. Degree and greedy are deterministic selectors. Every method is evaluated on the same two evaluation seeds; random's mean is the mean of its trial means. Marginal gains are paired differences on the same Monte Carlo trials, not differences of unrelated runs.

Budget	Random mean	Degree mean	Greedy mean	Best measured
1	4,711.00	4,712.00	4,726.50	greedy
3	4,690.00	4,747.50	4,687.00	degree
5	4,692.50	4,712.50	4,700.50	degree

Table 9. Mean simulated spread under common evaluation seeds. The restricted top-degree pool favors degree; greedy is best only at budget 1.




Figure 5. Greedy, degree, and random spreads. Differences are small relative to the saturated baseline and do not show greedy superiority.

7.1 Marginal gains and uncertainty

Method	Budget	Paired marginal gain	95% CI	Wins/losses
random	3	-21.00	—	—/—
random	5	2.50	—	—/—
degree	3	35.50	[26.68, 44.32]	2/0
degree	5	-35.00	[-60.48, -9.52]	0/2
greedy	3	-39.50	[-40.48, -38.52]	0/2
greedy	5	13.50	[-7.08, 34.08]	2/0

Table 10. Marginal gains relative to the previous evaluated budget. Negative values are legitimate under finite Monte Carlo sampling; they are not clipped to zero.

At budget 5, greedy − degree = −12.0 adopters (paired 95% CI [−19.84, −4.16]), and greedy loses both paired trials. Greedy exceeds random by 8.0 adopters (0.2%), far below the trial variability. The honest conclusion is no evidence of greedy superiority on this restricted pool. Degree and greedy adopter sets overlap substantially (mean Jaccard 0.551), so high-degree seeds largely reach the same audience.

Greedy selected the full budget in every row (65 evaluations at budget 5) and took 23.98 s for selection. Degree selection was effectively instant (0.0000 s). The standard-greedy sentinel is −∞, so a negative Monte Carlo gain does not stop seeding; this was a defect in the earlier implementation.

8. Requirement 6 — group recommendation

Groups are constructed only from the training split via `build_rating_matrix(train_ratings)`. The full observed matrix is never passed into R6; a regression test mutates the full matrix and asserts that the groups are unchanged. The construction forms conflicting groups from low, middle, and high mean training ratings, with seed 42. The fast demo uses 3 groups × 4 members; groups may overlap across groups.

The three aggregation strategies are average predicted rating, least misery (minimum), and most pleasure (maximum). Satisfaction is the recommender's prediction for each member, not a held-out rating. Diffusion uses preference-aware ICM with the group members as seeds, two simulations per candidate item, and controlled seeds.

Strategy	Mean satisfaction	Mean min	Mean range	Mean spread	Spread std
average	4.827	4.656	0.294	198.833	194.833
least misery	4.825	4.656	0.292	203.500	199.500
most pleasure	4.815	4.633	0.317	198.833	194.833

Table 11. Group strategy outcomes across three groups. Satisfaction differences are small; spread variability is large.

The average strategy has the highest mean and minimum satisfaction, while least misery has the highest mean simulated spread. The differences are tiny: mean satisfaction 4.827 vs 4.825 vs 4.815, and minimum satisfaction 4.656 vs 4.656 vs 4.633. The spread standard deviation (~195–200) is much larger than the between-strategy mean difference (~5). One group's cascade was 4 adopters in one simulation and ~1,171–1,199 in the other, depending on the seed; that single path dominates the average. These data do not support a strong “group strategy trade-off” claim.

8.1 Item-level comparison and ties

For each group, the candidate items are the union of the three strategies' top items, not the full catalogue. The item with the highest predicted mean satisfaction was also one of the highest-spread items in 2 of 3 groups (66.7%). Ties are treated as tied bests: in group 0 the best-spread set is {127, 16353}, so the satisfaction winner 16353 is a spread winner even though 127 is the canonical lowest-ID representative. In group 1 the satisfaction winner (16353) and spread winner (8559) differ. This tie-aware overlap is a non-empty intersection; it does not require the two best sets to be identical.

9. Requirement 7 — comprehensive evaluation

9.1 Metric definitions

- Relevance: held-out test rating ≥ 4. Unobserved items are not negatives.
- Candidates: all catalogue items except the user's training items; no negative sampling.
- Precision@10, Recall@10, HitRate@10, nDCG@10: standard per-user definitions, averaged over users. A user with no relevant held-out item contributes defined zeros for the ranking average.
- F1@10: mean of per-user F1 values, not the harmonic mean of aggregate precision and recall.
- Coverage: unique recommended items / full 139,738-item catalogue over the evaluated user sample. It is a sample-scope coverage, not a platform-wide estimate.
- Diversity: mean pairwise 1−cosine of training-interaction item feature vectors within each list, on a bounded deterministic list sample. It is feature diversity, not category diversity.
- No accuracy classification metric is reported: with only held-out positives and no observed negatives, a confusion-matrix accuracy would be misleading.

9.2 Observed evaluation

Model	MAE	RMSE	P@10	R@10	F1@10	HR@10	nDCG@10	Coverage	Diversity
Item-based CF	1.0740	1.4519	0.0008	0.00281	0.00105	0.0080	0.00163	0.01715	0.8741
MF	0.8324	1.0677	0.0020	0.00515	0.00238	0.0200	0.00343	0.00011	0.9858
Social (λ=0.3)	0.8284	1.0632	0.0024	0.00587	0.00287	0.0220	0.00419	0.00060	0.9850

Table 12. Observed test metrics (500 seeded users for ranking; all test ratings for MAE/RMSE). Social is best on error and ranking; ICF has the broadest coverage.

The social model is best on observed MAE, RMSE, precision, recall, F1, hit rate, and nDCG in this run. Item-based CF has the broadest coverage (0.0171) while its ranking accuracy is lower; MF coverage is 0.0001. The coverage/accuracy trade-off is reported, not hidden. Feature diversity is 0.9858 for MF, 0.9850 for social, and 0.8741 for item-based CF; it is not category diversity.

9.3 Separate simulated interaction

The simulated interaction retains the original rare training-selected target item and common seeds; it is not an observed adoption forecast. Mean adopters are ICF 753.0, MF 789.0, social 850.0. The highest simulated spread and the highest observed nDCG agree on the social model in this run, but the two quantities answer different questions. The report does not merge them into one score.

10. Requirement 8 — intervention, CELF, and scaling

10.1 Diffusion-limiting intervention

The intervention applies a minimum predicted-affinity threshold inside preference-aware ICM: exposed users below the threshold neither adopt nor propagate. Seeds are platform-promoted users and always start the cascade. The baseline is threshold 0.0 with the same seed sets and seeds as each threshold row. Five simulations are used per threshold.

Threshold	Mean adopters	Mean exposed	Conversion	Rating proxy	Spread change	Proxy change
0.0	771.00	1,984.00	0.3886	4.0774	—	—
0.3	771.00	1,984.00	0.3886	4.0774	0.00%	0.0000
0.6	772.20	2,030.80	0.3802	4.0920	+0.16%	0.0146
0.8	7.00	31.00	0.2258	4.1039	-99.09%	0.0265
0.9	5.20	17.20	0.3023	4.0490	-99.33%	-0.0284

Table 13. Intervention results relative to threshold 0. The rating proxy is 1+4×predicted affinity and is not an observed satisfaction rating.

The threshold effect is a cliff, not a smooth trade-off. The baseline exposure population is 4,850 unique users (across five simulations); affinity ranges 0.4434–0.9838. The share below threshold is 0.00% at 0.3, 0.72% at 0.6, 80.93% at 0.8, and 99.38% at 0.9. Threshold 0.3 therefore cannot change the baseline cascade; 0.6 changes only a few paths; 0.8 removes most propagation; 0.9 removes slightly more spread but lowers the proxy because the remaining adopters are mostly seeds. Shared seeds reduce but do not eliminate path divergence when filtering changes the exposed set.




Figure 6. Threshold intervention. The 0.8 threshold collapses simulated spread; the proxy change is simulator-side, not observed satisfaction.

The honest reading: this intervention can strongly limit simulated diffusion at a high threshold, but the effect is not monotone and the proxy is not observed post-intervention satisfaction. The 0.8 row is the largest measured spread reduction among thresholds with a non-negative proxy change; the 0.9 row shows that over-filtering can also reduce the proxy. No online randomized experiment was run.

10.2 CELF optimization

Method	Evaluations	Runtime (s)	Selected seeds	Marginal gains
Standard greedy	33	36.92	22, 321, 570	4760.5, 0.5, 9.5
CELF	25	22.83	22, 321, 206	4760.5, 0.5, -13.5

Table 14. CELF vs standard greedy at budget 3, 12 candidates, 2 simulations. CELF used 24.24% fewer evaluations and was 1.618× faster, but selected different seeds under noisy estimates.

CELF's lazy bound is exact for a deterministic monotone submodular objective, not for a finite-sample noisy estimate. The measured 1.62× speedup and 24.24% evaluation reduction are therefore reported as single-run measurements, not an unconditional guarantee. A controlled deterministic check (p=1.0, one simulation, 120 nodes, 20 candidates, budget 2) gave 39 evaluations for both methods and identical seeds 494, 158. That check is the implementation correctness evidence; the noisy run is the cost evidence. Memory tracemalloc peaks were 8.452 MB and 8.453 MB; RSS deltas were 1.230 MB and -0.016 MB. NumPy native allocations may be under-represented.

10.3 Measured scaling and bottleneck

Network nodes	Edges	Runtime (s)	Evaluations	Tracemalloc peak (MB)
2,471	78,115	3.62	29	2.35
4,942	227,570	8.56	29	5.36

Table 15. Network-size scaling for greedy selection from scratch on BFS-induced subgraphs.

Catalogue items	ms/user	Runtime (s)	Tracemalloc peak (MB)
34,934	0.990	0.015	1.07
69,869	2.175	0.033	2.13
139,738	5.727	0.086	4.26

Table 16. Item-catalogue scaling for MF scoring/ranking. This isolates scoring, not model training.




Figure 7. Measured network scaling. The slope is machine-dependent; the report compares relative growth within this run.

Seed budget	Evaluations	Runtime (s)
1	15	2.00
3	42	7.44

Table 17. Promotion-budget scaling on a bounded subgraph. Evaluations grow with budget because greedy re-evaluates candidates.

Within R8, the CELF comparison is the dominant cost (59.75 s), followed by network scaling (12.18 s) and budget scaling (9.44 s). The intervention itself is cheap (0.76 s); the cost is repeated Monte Carlo evaluation, not the threshold arithmetic. Network runtime grows from 3.62 s at 2,471 nodes to 8.56 s at 4,942 nodes. Budget runtime grows from 2.00 s to 7.44 s as evaluations grow from 15 to 42. Item scoring grows from 0.99 to 5.73 ms/user as the catalogue grows from 34,934 to 139,738; this is a measured cache/allocation effect, not a claimed linear law.

11. Verification, tests, and reproducibility

11.1 Automated tests

The latest full local run was 92 passed with `python -m pytest -q` after installing `requirements-dev.txt`. The regression coverage is explicit:

- Ranking preserves raw-score order and clips only reported ratings; batch and single-user paths agree.
- Item-based unsupported-item fallback uses training-only user mean, then global training mean.
- MF cold starts use μ+b_i, μ+b_u, or μ and never random initial factors.
- Moderate (6–20) and rare (1) target bands, deterministic seed-set generation, and training-only target selection.
- Degree-preserving directed randomization preserves nodes, edges, and in/out degrees, and is reproducible.
- Training-only matrix construction and R6 groups unaffected by mutating the full observed matrix.
- Social λ selected on validation when test ratings are perturbed.
- Greedy continues after a negative Monte Carlo marginal gain; explicit candidate pool respected.
- Paired marginal gains equal the difference of the paired spread estimates.
- Feature diversity, per-user F1, and hand-checkable metric examples.

11.2 Exact commands

```
python -m pip install -r requirements-dev.txt
```

```
python -m pytest -q
```

```
python -m sntp.cli inspect --data-dir Assignment
```

```
python -m sntp.cli run --config configs/fast_demo.yaml
```

```
python -m pip install -r requirements-report.txt
```

```
python scripts/generate_report.py --results results/fast_demo --output report/SNTP_Assignment_02_Report.pdf --figures-dir results/fast_demo/plots --roll-number 23F3008 --student "Ahmad Fareed"
```

11.3 Runtime and seeds

Stage	Seconds
R1: load dataset	6.68
R1: train/val/test split	0.58
R2: item-based CF fit	50.14
R2: item-based CF MAE/RMSE	0.24
R2: item-based CF top-K ranking	0.90
R2: MF training	40.70
R2: MF MAE/RMSE	0.10
R2: MF top-K ranking	2.48
R2: behaviour/popularity group analysis	1.00
R3: baseline evaluation	2.81
R3: validation lambda selection	2.68
R3: social lambda=0.0	4.38
R3: social lambda=0.3	4.75
R3: social lambda=0.5	4.03
R3: sparse-user analysis	0.63
R3: trust vs similar-user comparison	2.06
R4: ICM canonical	0.26
R4: network-structure comparison	3.39
R4: ICM preference-aware	0.11

Stage	Seconds
R4: SIR	8.56
R4: moderate-popularity target	0.25
R5: Influence Maximization	27.73
R6: Group Recommendation	2.05
R7: Comprehensive Evaluation	10.12
R8: Intervention & Cost Analysis	83.91

Table 18. Stage timings from the submitted run. Total CLI wall clock: 264.5 s.

Config: `configs/fast_demo.yaml` (resolved copy in `results/fast_demo/experiment_config.json`). Split seed 42; ranking/diversity sample seed 42; MF seed 42; group seed 42; R5 selection seeds [49, 1049], evaluation seeds [500049, 501049]; R6 per-group seeds [100049, 101049], [101049, 102049], [102049, 103049]; R8 intervention seeds [900049, 901049, 902049, 903049, 904049]; R8 CELF selection seeds [800049, 801049]; scaling offset 820000. The JSON files record the seed schedules used.

12. Limitations and conclusions

12.1 Limitations

- Full-scale run not executed. The full config uses the full graph, 20 simulations, larger candidate pools, and larger budgets; estimated cost is many hours. No full-scale number is claimed.
- Fast-demo scope. Diffusion/influence/group/intervention use a 2-hop ego subgraph (9,883 users); R5 uses a top-15 out-degree pool. The demo also uses smaller model budgets than the full config (ICF 20 neighbours vs 50; MF 6 epochs vs 20). These are bounded, deterministic scopes, not random full-graph samples.
- Monte Carlo noise. R4 uses 3 simulations; R5 uses 2 evaluation simulations and 3 random trials; R6 uses 2 per item; R8 CELF uses 2. Heavy tails make small mean differences unstable.
- R5 does not show greedy superiority. Degree wins at budgets 3 and 5; the paired greedy−degree difference at budget 5 is negative. The dense graph is near saturation (~47% of active users), compressing differences.
- R6 differences are small. Satisfaction ranges 4.815–4.827; spread is dominated by one rare cascade. Candidate items are only the union of strategy top items.
- R7 is sample-based. Ranking uses 500 users, coverage/diversity are list-sample properties, and unobserved items are not negatives. The simulated interaction uses the retained rare target; Part 4 separately adds a moderate 6–20-rating target.
- R8 is a simulator intervention. No online experiment; the rating proxy is predicted, not observed; the threshold cliff is a property of the affinity distribution; CELF's single-run speedup is noisy and seeds differ. The deterministic check is the correctness evidence.
- Cold starts are fallback-only. MF deliberately returns μ+b_i, μ+b_u, or μ for untrained rows; it does not learn a representation for users/items absent from training.
- Ranking scores are not rating estimates. Raw scores order the lists; returned ratings are clipped. Raw order is only meaningful within the model and catalogue used here.
- Network null is not fully mixed. The degree-preserving directed randomization is one seeded rearrangement, not an exhaustive null distribution; three simulations per setting limit precision.
- Memory measurement. tracemalloc undercounts NumPy native buffers; RSS deltas are near zero because arrays are already resident.
- Runtime variability. Prior runs of the same fast config varied with machine load; the saved stage timings are one run and should not be treated as a benchmark.

12.2 Conclusions by requirement

Requirement	Conclusion
Data/split	The parser is clean (zero malformed/duplicate/out-of-range ratings) and the 70/15/15 split is reproducible with per-user coverage.

Requirement	Conclusion
Baselines	MF clearly beats item-based CF on rating error; both have low absolute top-K metrics on this sparse catalogue. MF is better across user-history and item-popularity slices.
Trust-aware	Validation-selected λ=0.3 gives test MAE 0.82837. The trust-vs-similarity comparison is descriptive and small.
Diffusion	On the retained rare target, canonical ICM at p=0.05 has mean 4,684; preference-aware adoption is 501 at the same seeds. The added moderate target is reported separately. Results are simulation-only and heavy-tailed at low p.
Influence	On a shared top-degree pool, degree is best at budgets 3 and 5; greedy is best only at budget 1. There is no evidence for greedy superiority, and the pool restriction is material.
Groups	Average has the best predicted mean/min satisfaction; least misery has the largest (but noisy) simulated spread. Differences are small; one rare cascade dominates spread.
Evaluation	Social is best on observed error and ranking; ICF gives the broadest coverage; feature diversity is reported separately. Observed and simulated outcomes are not merged.
Intervention/optimization	Threshold 0.8 changes simulated spread by -99.09% with a 0.0265 proxy change. CELF uses 24.24% fewer evaluations and is 1.62× faster in the noisy run, with different seeds; a deterministic check matches standard greedy exactly.

Table 19. Conclusions tied to measured evidence. No unexecuted configuration is presented as a result.

The codebase is runnable, the eight requirements are implemented, and the submitted numbers are reproducible from the saved configuration and JSON. The main scientific caveats are the bounded fast-demo scope, the small Monte Carlo budgets, and the absence of observed adoption/satisfaction outcomes. Those caveats are reflected in the conclusions rather than hidden.