






ITEM NO.	1
FIXTURE	Recessed Fixed Round Fixture
LOCATION	Lift Lobby
Drawing Symbol	
Lamp Wattage	37 W / 3800 Lumens
Diameter (ø) / Length	125 mm
Depth (h)	111 mm
Lamp Type	COB LED
IP Rating	IP 20
Color Temperature	3000 K
Description	Aluminum Housing w/ In Reflector + Glass Diffuser
Reference Source	EAE STM OR1 Recessed Spot Light or Equivalent








ITEM NO.	2	3
FIXTURE	Surface Mounted Linear Fixture	Wall Mounted Mounted Linear Fixture
LOCATION	Parking/Drive way/Lift	
Drawing Symbol		
Lamp Wattage	30 W / 2800 Lumens	
Length (a)	695	
Width (b)	73 mm	
Lamp Type	LED	
IP Rating	IP 2065	
Color Temperature	4000 K	
Description	The housing is produced by aluminum extrusion method and has a tempered glass with aerography.	
Reference Source	EAE Escalier Danj Surface Mounted or Equivalent	



ITEM NO.	4
FIXTURE	Ceiling Recessed Flat Light
LOCATION	Office
Drawing Symbol	
Lamp Wattage	37 W
Length (a)	695 mm
Width (b)	695 mm
Lamp Type	LED
IP Rating	IP 20
Color Temperature	4000 K
Description	The housing of the product is manufactured from 0.50 mm DCP sheet metal
Reference Source	EAE Bicom Recessed Flat Light or Equivalent



ITEM NO.	5	6	7
FIXTURE	Wall Mounted EXIT Light	One Sided Ceiling suspended	Two Sided Ceiling suspended
LOCATION	EXITS	Exit Routes	
Drawing Symbol			
Lamp Wattage	7 W		
Length (l)	269 mm		
Height (h)	144 mm		
Width (w)	65 mm		
Lamp Type	LED		
IP Rating	IP65		
Light Color	5700K		
Description	Acrylic glass surfaced, maintained type emergency luminaires.		
Reference			
	EAE _ ONTECS or Equivalent		

ITEM NO.	8
FIXTURE	Surface Mounted Round Fixture
LOCATION	Staircase
Drawing Symbol	
Lamp Wattage	20W
Diameter (ø) / Length	Fixture
Depth (h)	327.5 mm
Lamp Type	LED
IP Rating	IP65
Color Temperature	4000 K
Description	The housing is constructed from aluminum injection bottom cap and PC diffuser.
Reference Source	EAE SA TURU Surface Mounted or Equivalent

