Web Design and Programming (0107558) Internet Programming (0107571)¹ PHP Functions

Dr. Naeem Odat



College of Engineering
Department of Computer and Communications Engineering

¹Michael Mendez. The Missing Link: An Introduction to Web Development and Programming. Open SUNY Textbooks 2014.

User Defined Function in PHP

- ▶ A user-defined function declaration starts with the word *function*.
- Syntax:

```
function functionName() {
    code to be executed;
}
```

- ▶ A function name must start with a letter or an underscore.
- Function names are NOT case-sensitive.

Example

```
<?php
function writeMsg() {
    echo "Hello world!";
}
writeMsg(); // call the function
?>
```

Built-in Functions

- strrev(".dlrow olleH"). Returns "Hello world."
- strtoupper("Naeem"). Returns "NAEEM"
- ▶ strlen("What?"). Returns 5

Arguments

```
function greet($lang){
    if($lang=="es") return "Hola";
    if($lang=="fr") return "Bonjour";
    return "Hello";
}
greet('es');//returns "Hola"
greet();//This is an error
```

Default value for the argument

```
function greet($lang='es'){
```

By value and by reference (&)

Arguments are passed to the functions by value (copy).
function foo(\$x){....}

\$x=6;
foo(\$x);//\$x is not affected.

function foo(&\$x){....}

foo(\$x);//Now \$x is affected.

Variable scopes

- ► Local scope. Inside a function.
- ▶ Global scope. Preceded with global keyword.
- ► Super global (\$_GET, \$_POST,...)

```
Check if a function exists
if (function_exists("array_combine")) echo "YES";
PHP configuration
<?php
    phpinfo();
?>
```

Include and require

- ▶ Include. (include "header.php";) if not there there will be no fail.
- Require. (require "header.php";) fail if it is not there.
- ► Require_once. In many files included required only once.

Example

Demo 4-phpfunction.php

Quiz - 1

- ▶ Why should you use functions?
 - Avoid repetitive code
 - ▶ To make it harder for others to use your code
 - Organize your code
 - Break complex code into logical chunks
- ▶ Which keyword defines a new function?
 - new
 - define
 - new functions
 - function
- Return values are type-specific in php functions (a function only returns a value of a specified data type.)
 - ► True
 - False

Quiz - 2

What output does the following code produce?

```
function double($val){
    $val = $val * 2;
    return $val;
}
$val = 15;
$dval = double($val);
echo "Value = $val Doubled = $dval";

    Value = 15 Doubled = 15
    Value = Doubled =
    Value = 30 Doubled = 30
    Value = 30 Doubled = 30
```

Quiz - 3

- Which keyword is used to use code from one php file into a different PHP file?
 - include
 - add
 - append
 - point
- Which function prints out the internal configuration capabilities of your particular PHP installation?
 - phpinfo()
 - phpver()
 - ▶ info()
 - version()

Quiz - 4

- ► The keyword [] will expand the scope of a variable outside of its function.
- ► The [] function is used to check if a function already exists or not.
- ▶ It is common to use uppercase and/or long names for global variables to avoid confusion or mistaken reuse.
 - ► True
 - False