Web Design and Programming (0107558) Internet Programming (0107571)¹

Interactivity with JavaScript (AJAX and JSON)

Dr. Naeem Odat




College of Engineering Department of Computer and Communications Engineering

¹Michael Mendez. The Missing Link: An Introduction to Web Development and Programming. Open SUNY Textbooks 2014.

Introduction to Ajax

- ► AJAX = **A**synchronous **J**avaScript **A**nd **X**ML.
- ► AJAX is not a programming language.
- ► AJAX just uses a combination of:
 - A browser built-in XMLHttpRequest object (to request data from a web server)
 - JavaScript and HTML DOM (to display or use the data)

How Ajax works



How Ajax works

- 1. An event occurs in a web page (the page is loaded, a button is clicked)
- 2. An XMLHttpRequest object is created by JavaScript
- 3. The XMLHttpRequest object sends a request to a web server
- 4. The server processes the request
- 5. The server sends a response back to the web page
- 6. The response is read by JavaScript
- 7. Proper action (like page update) is performed by JavaScript

Demo 16-ajax.html

Quiz

- One of the differences between a GET request and POST is that a GET request passes query parameters as part of the URL whereas POST request passes them as part of the body of the request.
 - ▶ True
 - ► False
- 2. Given the following JavaScript code snippet:

```
var name = "";
// Making an Ajax call here, i.e., sendGetRequest
$ajaxUtils.sendGetRequest("someURL", function (request) {
    name = "TTU";
});
document.querySelector("#content").innerHTML = name;
```

What will be the contents of the element with the 'id' value of 'content' after the execution of this JavaScript code?

- It will be empty
- ► TTU
- Whatever the server returns plus the word TTU

JSON

- ► Stands for: JavaScript Object Notation
- Lightweight data-interchange format.
- Easy for humans to read and write.
- Easy for machines to parse and generate.

JSON Syntax Rules

- Subset of JavaScript object literals but:
 - Property names must be in double quotes.
 - String values must be in double quotes.

Example

```
{
    "firstName": "Naeem",
    "lastName": "Odat",
    "taughtCourse": 2
}
```

Conversion between JSON string and JavaScript object

- ► To convert from JSON string to object: var obj=JSON.parse(jsonString);
- ➤ To convert from JavaScript object to JSON string: var str=JSON.stringify(obj);

Demo 17-json.html

Quiz

- 1. Another name for Object Literal is JSON.
 - ► True
 - False
- 2. Identify invalid JSON string below:

```
1
    "courseName": "InternetProgramming",
    "numberOfStudents": 6
},
, ₹
    "courseName": "InternetProgramming",
    "studentsLoveCourse": true
٦,
۱,
    'courseName': "InternetProgramming",
    'numberOfStudents': 6
},
'{
    "courseName": {"name": "InternetProgramming"},
    "numberOfStudents": 6
٦,
```

Dynamic loading of a webpage

- Using Ajax a template of the webpage content is requested from the server.
- ► The data (in JSON format) that should be filled in the template is requested from the server.
- ► An appropriate JavaScript code will work on both to put each item in its place.

Demo

18-dynamicloading.html