Git, testing and automation for research

Ahmad Ammar

November 2026

Contents

1 Git, testing and automation for research **3**
1.1 What you will learn . . . 3

2 Git basics **4**
2.1 The idea . . . 4
2.2 The everyday cycle . . . 4
2.3 Try it safely . . . 4
2.4 What to track . . . 5
2.5 Good commit messages . . . 5

3 Branches, tags and going back **6**
3.1 Branches . . . 6
3.2 Tags . . . 6
3.3 Going back . . . 6
3.4 A sensible rule for versions . . . 6

4 GitHub and working with others **7**
4.1 Remotes . . . 7
4.2 Issues and pull requests . . . 7
4.3 Making a project welcoming . . . 7
4.4 Sites and releases . . . 7

5 Testing research code **8**
5.1 Why test . . . 8
5.2 Kinds of test for research . . . 8
5.3 Lessons from real faults . . . 9
5.4 What tests cannot do . . . 9

6 Continuous integration **10**
6.1 What the terms mean . . . 10
6.2 A first workflow . . . 10
6.3 From testing to publishing . . . 10
6.4 Practical advice . . . 11
6.5 Hooks: checks before you push . . . 11
6.6 Scheduled checks . . . 11

7 Reproducible pipelines **12**
7.1 The idea . . . 12
7.2 Rules that prevent most errors . . . 12
7.3 A worked example . . . 12
7.4 Tools for larger projects . . . 12

8 Data, backups and releases **13**
8.1 Data . . . 13
8.2 Backups . . . 13
8.3 Releases . . . 13
8.4 Secrets . . . 13

9 Checklists and cheat sheet **14**
9.1 Starting a project 14
9.2 Before sending anything out 14
9.3 Cheat sheet 14

Chapter 1

Git, testing and automation for research

Research code and documents go wrong in quiet ways: a number typed by hand, a figure from last month's data, a script that only ran on one laptop. This guide explains the tools that catch those faults, starting from nothing.

It's based on what I built for my own work, including real mistakes these tools caught. You can see them working in the pamphlet project and its build guide.

1.1 What you will learn

1. **Git** records every version, so that you can go back to any point.
2. **GitHub** shares work, and lets people report problems and suggest changes.
3. **Tests** check that the code still gives the right answers.
4. **Continuous integration** runs those checks by itself on every change.
5. **Pipelines** rebuild everything from the sources, so that nothing drifts apart.
6. **Backups and releases** protect what matters.

Prefer one long page? Read the whole guide on one page. The example files include everything shown here.

Chapter 2

Git basics

2.1 The idea

Git is a program that records versions of a folder. Each saved version, called a *commit*, stores what changed, who changed it, when and why. Nothing committed is lost, so you never need files such as `final_v2_really_final.docx`.

Install it from git-scm.com, then tell it who you are, once:

```
git config --global user.name "Your Name"
git config --global user.email "you@example.org"
```

2.2 The everyday cycle

```
git init                # start tracking this folder, once
git status              # what has changed?
git diff                # show the changes, line by line
git add results.txt     # choose what goes in the next version
git commit -m "Correct the mean"   # save that version, with a reason
git log --oneline       # list the versions
```

The `add` step exists so that one commit can hold one logical change, even if you changed other files too.

2.3 Try it safely

This script makes a new folder and goes through the whole cycle. Read it, then run it.

practice.sh

```
#!/bin/bash
# A safe practice run of everyday Git, in a new folder. Run: bash practice.sh
set -e
mkdir git-practice && cd git-practice
git init -q -b main
git config user.name "A Student"
git config user.email "student@example.org"

# Save a first version
echo "The mean is 10." > results.txt
git add results.txt
git commit -q -m "First results"

# Change it and see exactly what changed
echo "The mean is 12." > results.txt
git diff --stat
git add results.txt
git commit -q -m "Correct the mean"

# Name this version
git tag -a sent-to-supervisor -m "The version I sent"
```

```
# Try an idea safely on a branch, then bring it back
git switch -q -c idea
echo "The median is 11." >> results.txt
git add results.txt
git commit -q -m "Add the median"
git switch -q main
git merge -q idea

# Undo the last change, keeping the history
git revert --no-edit HEAD
git log --oneline
cat results.txt
```

2.4 What to track

Track what you write by hand: text, code and small inputs. Don't track what can be regenerated, large data, or anything secret. A file called `.gitignore` lists what to skip:

```
__pycache__/
*.log
build/
data/raw/
.env
```

2.5 Good commit messages

Write what changed and why, briefly, such as `Correct the living-wage year`. Commit often, in small steps, so that each can be understood or undone by itself.

Chapter 3

Branches, tags and going back

3.1 Branches

A branch is a separate line of work, which lets you try something without touching your working version.

```
git switch -c idea       # make a branch and move to it
# ... work and commit ...
git switch main          # go back
git merge idea           # bring the work in
```

If two branches changed the same lines, Git asks you to choose. Open the file, keep what you want, delete the markers, then `git add` and `git commit`.

3.2 Tags

A tag gives a version a permanent name, such as what you sent to a journal.

```
git tag -a submitted-2026-11-01 -m "Sent to the journal"
git push origin submitted-2026-11-01
```

3.3 Going back

You want to	Use
See an old version	`git switch --detach <tag or commit>`, then `git switch main` to return
Undo a commit, keeping the history	`git revert <commit>`
Get one old file back	`git restore --source <commit> file.txt`
Discard edits you haven't committed	`git restore file.txt`, which can't be undone
Find which commit broke something	`git bisect`

Prefer `revert` over rewriting history. Commands such as `git reset --hard` and `git push --force` can destroy work, so check what they do before using them.

3.4 A sensible rule for versions

Keep one working copy of each file under Git, and stop putting versions in file names. For data, which is too large for Git, use dated read-only folders with recorded checksums, as described in the backups chapter.

Chapter 4

GitHub and working with others

4.1 Remotes

GitHub keeps a copy of your repository online.

```
git remote add origin https://github.com/you/project.git
git push -u origin main     # send your commits
git pull                    # fetch others' commits
git clone <address>         # copy a project to your computer
```

Before making anything public, check it for secrets and for unpublished work. Git keeps history, so deleting a file later doesn't remove it from past commits.

4.2 Issues and pull requests

- **An issue** is a note about something to fix or discuss.
- **A pull request** proposes a change: someone works on a branch, then asks for it to be merged. Others can review it line by line, and automatic checks run on it.

4.3 Making a project welcoming

File	Purpose
`README.md`	What this is, and how to use it
`LICENSE`	What others may do with it. Without one, they have no clear right to reuse it
`CONTRIBUTING.md`	How to help
`CITATION.cff`	How to cite it
`.github/ISSUE_TEMPLATE/`	Forms that ask for the right details

Remember people who don't use GitHub, and offer them a simple way to reach you. The pamphlet's help page is one example.

4.4 Sites and releases

GitHub Pages publishes a website from a repository for free. A GitHub Release attaches files to a tag, while Zenodo can archive a release and give it a citable DOI.

Chapter 5

Testing research code

5.1 Why test

A script that runs without errors can still be wrong. A test runs your code and checks the answer against something you know.

calc.py

```
"""A tiny calculation to test."""


def heat_loss(u, area, delta_t):
    """Heat loss in watts: Q = U A dT."""
    if u < 0 or area < 0:
        raise ValueError("U-value and area cannot be negative")
    return u * area * delta_t
```

test_calc.py

```
"""Tests check the code against answers worked out by hand. Run: python -m pytest"""
import pytest

from calc import heat_loss


def test_known_answer():
    assert heat_loss(2.1, 10, 15) == pytest.approx(315)


def test_no_temperature_difference_means_no_loss():
    assert heat_loss(2.1, 10, 0) == 0


def test_impossible_input_is_refused():
    with pytest.raises(ValueError):
        heat_loss(-1, 10, 15)
```

```
pip install pytest
python -m pytest
```

5.2 Kinds of test for research

Test	Question	Example
Known answer	Does it match a hand calculation?	2.1 x 10 x 15 = 315
Limit case	Does it behave at the extremes?	No temperature gap gives no heat loss
Invariant	Does a rule always hold?	Total price equals total value
Simulated data	Can it recover a truth you planted?	A model finds a jump you added
Data check	Is the data as expected?	No duplicates, values in range
Independent recalculation	Do two separate methods agree?	The same estimate from different code
Rendered output	Does the result look right to readers?	A browser opens each page

5.3 Lessons from real faults

These all happened in my own projects:

- **An independent recalculation** confirmed an estimate exactly, and adding a check for correlated data showed its confidence interval was too narrow.
- **A check of stated numbers against results** found a sample size typed wrongly into a paper.
- **A test for labels** found age groups named for the wrong years, though the numbers ran fine.
- **A browser test** found broken links, unreadable buttons and maths that displayed as raw code. Its first version missed some faults, because it looked for error messages and these made none.

So a passing test only shows that the things you tested held. When a fault gets through, add a test for that kind of fault.

5.4 What tests cannot do

They can’t show that a method is valid, or an argument sound. That takes reasoning and readers.

Chapter 6

Continuous integration

6.1 What the terms mean

- **Continuous integration (CI)** runs your checks automatically on every change, on a clean machine.
- **Continuous delivery or deployment (CD)** then publishes the result, but only if the checks pass.

A clean machine catches the classic fault of a project that only works on your own computer.

6.2 A first workflow

Save this in your repository as `.github/workflows/tests.yml`:

tests.yml

```
# Save as .github/workflows/tests.yml in a GitHub repository.
name: tests
on: [push, pull_request]
jobs:
  test:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@v4
      - uses: actions/setup-python@v5
        with:
          python-version: "3.12"
      - run: pip install pytest
      - run: python -m pytest
```

Reading it line by line:

- `on` says when to run: on each push and pull request.
- `runs-on` picks a fresh virtual machine.
- `steps` run in order. `uses` runs a ready-made action, and `run` runs a command.
- If any step fails, the run fails, and GitHub shows a red cross.

See the results under the repository's *Actions* tab. Read the failing step's log from the bottom up, and find the first real error.

6.3 From testing to publishing

A publishing workflow adds a job that only runs after the checks succeed. This is how my pamphlet's workflow works:

1. Install Pandoc, LaTeX and a browser.
2. Run the equation tests.
3. Rebuild every page and PDF from source.
4. Check links and numbers.
5. Open every page in a browser, and test what readers see.

6. Publish, only if all of that passed. Otherwise, the old site stays up.

6.4 Practical advice

- **Pin versions** of tools that affect output, such as `python-version: "3.12"`.
- **Keep secrets out of files.** Store them in the repository's settings as encrypted secrets.
- **Keep private work private.** A public workflow's logs are public.
- **Watch the time.** Slow checks get ignored, so run the quickest first.

6.5 Hooks: checks before you push

A Git hook runs a script at a moment such as a commit. A file at `.git/hooks/pre-commit` can block a commit containing a secret or broken code, and a `pre-push` hook does the same before sending work online. Hooks aren't copied with a repository, so each person must install them. For a shared setup, look at the pre-commit tool.

6.6 Scheduled checks

CI can also run on a timetable, and on your own computer, Windows Task Scheduler or `cron` can run a daily health report that emails you when something changes. Keep alerts rare, because people stop reading frequent ones.

Chapter 7

Reproducible pipelines

7.1 The idea

If you copy a number from your analysis into a paper by hand, sooner or later they will differ. So store each thing once, and generate the rest.

```
data/figures.json  --->  analysis code  --->  numbers.tex  --->  paper.pdf
                                           \-->  tables and figures
                                            \->  web pages and slides
```

7.2 Rules that prevent most errors

1. **Raw data is read-only.** Scripts read it and write elsewhere.
2. **Numbers in text are generated.** A script writes them as LaTeX commands, for example.
3. **Equations live in one tested function.** Everything calls it.
4. **One command rebuilds everything.** It might be `python build_all.py` or `make`.
5. **Each output records its source**, such as a commit or a checksum.
6. **Generated files say so**, in a comment at the top, so that nobody edits them by hand.
7. **Paths are relative.** `C:\Users\me\data` works only for you.
8. **Random steps have a fixed seed**, so that results repeat exactly.
9. **The environment is recorded**, in a `requirements.txt`, `environment.yml` or container.

7.3 A worked example

My pamphlet project has one LaTeX source and one data file. One command builds the website, the PDF, a report, slides and a calculator from them, then checks that they all agree.

When I switched the pamphlet to shared numbers, a check confirmed that the PDF's text hadn't changed at all. That kind of proof is what makes a large change safe.

7.4 Tools for larger projects

Tool	Good for
`make`, Snakemake, Nextflow	Rebuilding only what changed
Conda, `venv`, `uv`	Python environments
Docker, Apptainer	Whole environments, including on HPC
DVC, DataLad, Git LFS	Versioning large data

Start simple. A short script that runs each step in order goes a long way.

Chapter 8

Data, backups and releases

8.1 Data

Git isn't built for large files, so keep data out of it, and record what you used.

- **Never overwrite.** Write each new run to a dated folder, such as `results_2026-10-31/`.
- **Record checksums**, which are fingerprints that change if a file changes: `sha256sum *.csv > MANIFEST.sha256`, and check later with `sha256sum -c MANIFEST.sha256`.
- **Note the source** of each dataset: its address, date and licence.

8.2 Backups

Git is not a backup until a copy exists elsewhere, and a private repository on one laptop can be lost with that laptop. The common rule is **3-2-1**: three copies, on two kinds of storage, with one somewhere else.

Syncing services such as OneDrive aren't enough on their own, because they also sync deletions and corruption. And **a backup you've never restored is only a hope**, so test one:

```
git bundle create project.bundle --all     # one file holding a repository's whole history
git clone project.bundle restore-test      # prove that it comes back
```

Databases and uploaded files don't live in Git, so they need their own backups, including an encrypted copy off-site.

8.3 Releases

Whenever something leaves your hands, freeze a copy.

1. Commit everything, so that the source is exact.
2. Run all the checks.
3. Build from clean.
4. Put the outputs in a dated, read-only folder, with checksums.
5. Tag the commit.

Then, for anything a reader sends back, you can find precisely what they had. If it needs correcting, make a new release and log the reason, without editing the old one.

8.4 Secrets

Passwords and keys never go in a repository, because history keeps them even after deletion. Use environment variables or a secrets store. If one gets committed, treat it as exposed: change it first, then clean up.

Chapter 9

Checklists and cheat sheet

9.1 Starting a project

- ☐ `git init`, a README and a `.gitignore`
- ☐ A folder layout that separates raw data, code and outputs
- ☐ A recorded environment
- ☐ A first test
- ☐ A remote copy and a backup
- ☐ A licence, if it's going public

9.2 Before sending anything out

- ☐ All changes committed
- ☐ Tests and checks pass
- ☐ Built from clean, on the current source
- ☐ Every stated number traced to a result
- ☐ Links and references tested
- ☐ Read by a person against its sources
- ☐ Frozen as a dated release, with a tag and checksums
- ☐ Backed up

9.3 Cheat sheet

```
git status                # what changed?
git diff                  # how?
git add -A                # choose everything
git commit -m "Why"       # save a version
git log --oneline         # list versions
git switch -c idea        # new branch
git merge idea            # bring it in
git tag -a v1 -m "Note"   # name a version
git push                  # send online
git pull                  # fetch from online
git revert <commit>       # undo, keeping history
python -m pytest          # run tests
sha256sum -c MANIFEST.sha256   # check files are unchanged
```