

# **Security Testing**

WS 2021/2022

Prof. Dr. Andreas Zeller Leon Bettscheider Marius Smytzek

# Exercise 4 (10 Points)

Due: 28. November 2021

The lecture is based on The Fuzzing Book (https://fuzzingbook.org/beta), an interactive textbook that allows you to try out code right in your web browser.

The Fuzzing Book code is additionally available as a Python pip package. To work on the exercises, please install the package locally:

pip3 install fuzzingbook

Submit your solutions as a Zip file on your status page in the CMS (https://cms.cispa.saarland/fuzzing2122/students/view).

We will provide you a structure to submit your solutions where each task has a dedicated file. You can add new files and scripts if you want, but you may not delete any provided ones. You can verify whether your submission is valid by executing verify.py:

```
python3 verify.py
```

The output provides an overview if a required file, variable, or function is missing and if a function pattern was altered. If you do not follow this structure or change it, we cannot evaluate your submission. A non evaluable exercise will result in 0 points, so make sure to verify your work before submitting it. Note that the script does not reveal if your solutions are correct.

#### Exercise 4-1: Of Snakes and Dwarfs (4 Points)

#### a. Snake (2 Points)

Given the following grammar:

```
In [2]:
```

```
SNAKE GRAMMAR = {
    '<start>': ['<snake>', ''],
    '<snake>': ['<digit>', '<snake><digit>'],
    '<digit>': ['0', '1', '2', '3', '4', '5', '6', '7', '8', '9']
```

Add probabilities to this grammar such that the empty string '' will never be produced when feeding this grammar to a probabilistic grammar fuzzer and the probability of adding a new digit to the snake is 9 times higher than ending the snake with a digit. Provide your annotated grammar in exercise\_1a.py.

### b. Heigh-Ho (2 Points)

For this exercise you will work on learning probabilities from samples for an existing grammar. Consider the following grammar for regular expressions, as in exercise 3-2 this is only a subset of the language.

```
In [8]:
```

```
RE GRAMMAR = {
    '<start>': ['<re>'],
    '<re>': ['<alternative>', '^<alternative>', '<alternative>$',
'^<alternative>$'],
    '<alternative>': ['<concat>', '<concat>|<alternative>'],
    '<concat>': ['', '<concat><regex>'],
    '<regex>': ['<symbol>', '<symbol>*', '<symbol>+', '<symbol>?', '<symbol>
{<range>}'],
    '<symbol>': ['.', '<char>', '(<alternative>)'],
```

```
'<char>': ['a', 'b', 'c'],
'<range>': ['<num>', ',<num>','],
'<num>': ['1', '2'],
}
```

We had a beautiful grammar with probabilities but unfortunately we lost it. Luckily we were able to derive examples from this grammar, you can find these 2500 examples in **examples.py**. Can you help us to reconstruct the lost grammar?

To accomplish this please implement the function learn\_probabilities() in exercise\_1b.py. The function should mine the probabilities for the RE\_GRAMMAR from the 2500 examples and should return the mined probabilistic grammar.

## Exercise 4-2: How to get Rich? (6 Points)

In this exercise you will work with International Bank Account Numbers (https://en.wikipedia.org/wiki/International\_Bank\_Account\_Number) or short IBANs. An IBAN consists of a country code (two uppercase letters), two check digits, and a country specific Basic Bank Account Number (BBAN). You will not concentrate on the entire set of possible IBANs, but we limited BBANs to only consist of digits instead of an alphanumerical string. We will provide you a grammar for IBANs that you should extend with generators to produce valid IBANs. Provide all your solutions for this exercise in exercise\_2.py.

#### a. Countries and Lengths (2 Points)

Provide a generator or multiple generators in the grammar to produce only valid country codes and BBANs with the country specific length. **exercise\_2.py** contains a list <code>iban\_cc\_len</code> of valid country codes for all countries using IBAN and the entire length of the IBAN. Note that this length contains the country code and the two check digits. We would recommend to randomly select one element of <code>iban\_cc\_len</code> at the beginning of a generator. You do not have to set the random seed for this exercise. Select smart positions to add your generator or generators.

#### b. Check (3 Points)

Add a generator or multiple generators to the grammar to produce valid check digits. The algorithm for calculating the check digits for an IBAN already containing a country code and a BBAN is described as following (source (https://en.wikipedia.org/wiki/International\_Bank\_Account\_Number)):

- 1. Check that the total IBAN length is correct as per the country. If not, the IBAN is invalid. In this case you should raise a ValueError() exception. If this happens during your generation you should overwork your solution for exercise 4-2 a. because the length should be correct at this point.
- 2. Replace the two check digits by 00 (e.g., GB00 for the UK).
- 3. Move the four initial characters to the end of the string.
- 4. Replace the letters in the string with digits, expanding the string as necessary, such that A or a = 10, B or b = 11, and Z or z = 35. Each alphabetic character is therefore replaced by 2 digits
- 5. Convert the string to an integer (i.e. ignore leading zeroes).
- 6. Calculate mod-97 of the new number, which results in the remainder.
- 7. Subtract the remainder from 98 and use the result for the two check digits. If the result is a single-digit number, pad it with a leading 0 to make a two-digit number.

Select suited positions to add your generator or generators

#### c. But Why? (1 Points)

What you have achieved in this exercise could be easily accomplished programmatically, i.e. without the usage of a grammar but instead writing code to generate an IBAN. But using a grammar provides benefits over such an approach. Could you name one advantage?

Please provide your answer in 1-3 sentences in exercise\_2c.txt.