


Basic Course Information

Lectures Reference



Textbook
2019

Course Objectives

- Learn how to think mathematically.
- Grasp the basic logical and reasoning mechanisms of mathematical thought.
- Acquire logic and proof as the basics for abstract thinking.
- Improve problem-solving skills.
- Grasp the basic elements of induction, recursion, combination and discrete structures.

DM is a Gateway Course

Topics in discrete mathematics will be important in many courses that you will take in the future:

- **Computer Science:** Computer Architecture, Data Structures, Algorithms, Programming Languages, Compilers, Computer Security, Databases, Artificial Intelligence, Networking, Graphics, Game Design, Theory of Computation,
- **Mathematics:** Logic, Set Theory, Probability, Number Theory, Abstract Algebra, Combinatorics, Graph Theory, Game Theory, Network Optimization, ...
- **Other Disciplines:** You may find concepts learned here useful in courses in philosophy, economics, linguistics, and other departments.

Course Syllabus

- The Foundations: Logic and Proofs.
- Basic Structures: Sets, Functions, Sequences, and Sums.
- Algorithms.
- Induction and Recursion.
- Graphs.
- Trees.

Chapter 1: Logic and Proofs

- Introduction to Propositional Logic.
- Compound Propositions.
- Applications of Propositional Logic.
- Propositional Equivalences.
- Predicates and Quantifiers.
- Arguments.
- Proofs Techniques.

What is Logic?

- Logic is the discipline that deals with the methods of reasoning.
- On an elementary level, logic provides rules and techniques for determining whether a given argument is valid.
- Logical reasoning is used in mathematics to prove theorems.

- The basic building blocks of logic is **Proposition**
- A proposition (or statement) is a **declarative sentence** that is either **true** or **false**, but **not both**.
- The area of logic that deals with propositions is called **propositional logics**.



Examples:

Propositions	Truth value
$2 + 3 = 5$	True
$5 - 2 = 1$	False
Today is Friday	False
$x + 3 = 7$, for $x = 4$	True
Cairo is the capital of Egypt	True

Sentences	Is a Proposition
What time is it?	Not propositions
Read this carefully.	Not propositions
$x + 3 = 7$	Not propositions

- We use letters to denote propositional variables p, q, r, s, \dots
- The truth value of a proposition is true, denoted by **T**, if it is a true proposition and false, denoted by **F**, if it is a false proposition.

Compound Proposition

- Compound Propositions are formed from existing propositions using **logical operators**.



Negation

DEFINITION 1

Let p be a proposition. The *negation of p* , denoted by $\neg p$ (also denoted by \bar{p}), is the statement
“It is not the case that p .”

The proposition $\neg p$ is read “not p .” The truth value of the negation of p , $\neg p$, is the opposite of the truth value of p .

Other notations you might see are $\sim p$, $-p$, p' , Np , and $!p$.

Example

Find the negation of the proposition

p : “Cairo is the capital of Egypt”

Example: Solution

Find the negation of the proposition

p : “Cairo is the capital of Egypt”

The negation is

$\neg p$: “It is not the case that Cairo is the capital of Egypt”

This negation can be more simply expressed as

$\neg p$: “Cairo is not the capital of Egypt”

Truth Table

- Truth Table: is a table that gives the truth values of a compound statement.

The Truth Table for the Negation of a Proposition

	p	$\neg p$
Proposition		
Truth Values	T	
	F	

Truth Table

- Truth Table: is a table that gives the truth values of a compound statement.

The Truth Table for the Negation of a Proposition

Proposition	p	$\neg p$
	T	F
Truth Values	F	T

Negation

TABLE 1 The
Truth Table for
the Negation of a
Proposition.

p	$\neg p$
T	F
F	T

Logical Connectives

DEFINITION 2

Let p and q be propositions. The *conjunction* of p and q , denoted by $p \wedge q$, is the proposition “ p and q .” The conjunction $p \wedge q$ is true when both p and q are true and is false otherwise.

Example

p : Today is Friday.

q : It is raining today.

$p \wedge q$: Today is Friday and it is raining today.

TABLE 2 The Truth Table for the Conjunction of Two Propositions.

p	q	$p \wedge q$
T	T	T
T	F	F
F	T	F
F	F	F

Logical Connectives

DEFINITION 3

Let p and q be propositions. The *disjunction* of p and q , denoted by $p \vee q$, is the proposition “ p or q .” The disjunction $p \vee q$ is false when both p and q are false and is true otherwise.

Example

p : Today is Friday.

q : It is raining today.

$p \vee q$: Today is Friday or
it is raining today.

TABLE 3 The Truth Table for the Disjunction of Two Propositions.

p	q	$p \vee q$
T	T	T
T	F	T
F	T	T
F	F	F

Logical Connectives

DEFINITION 4

Let p and q be propositions. The *exclusive or* of p and q , denoted by $p \oplus q$ (or p XOR q), is the proposition that is true when exactly one of p and q is true and is false otherwise.

Example

p : They are parents.

q : They are children.

$p \oplus q$: They are parents or children but not both.

TABLE 4 The Truth Table for the Exclusive Or of Two Propositions.

p	q	$p \oplus q$
T	T	F
T	F	T
F	T	T
F	F	F

Logical Connectives

DEFINITION 5

Let p and q be propositions. The *conditional statement* $p \rightarrow q$ is the proposition “if p , then q .” The conditional statement $p \rightarrow q$ is false when p is true and q is false, and true otherwise. In the conditional statement $p \rightarrow q$, p is called the *hypothesis* (or *antecedent* or *premise*) and q is called the *conclusion* (or *consequence*).

“if p , then q ”
 “if p , q ”
 “ p is sufficient for q ”
 “ q if p ”
 “ q when p ”
 “a necessary condition for p is q ”
 “ q unless $\neg p$ ”

TABLE 5 The Truth Table for the Conditional Statement $p \rightarrow q$.

p	q	$p \rightarrow q$
T	T	T
T	F	F
F	T	T
F	F	T

“ p implies q ”
 “ p only if q ”
 “a sufficient condition for q is p ”
 “ q whenever p ”
 “ q is necessary for p ”
 “ q follows from p ”

Logical Connectives

DEFINITION 5

Let p and q be propositions. The *conditional statement* $p \rightarrow q$ is the proposition “if p , then q .” The conditional statement $p \rightarrow q$ is false when p is true and q is false, and true otherwise. In the conditional statement $p \rightarrow q$, p is called the *hypothesis* (or *antecedent* or *premise*) and q is called the *conclusion* (or *consequence*).

“if p , then q ”
 “if p , q ”
 “ p is sufficient for q ”
 “ q if p ”
 “ q when p ”
 “a necessary condition for p is q ”
 “ q unless $\neg p$ ”

TABLE 5 The Truth Table for the Conditional Statement $p \rightarrow q$.		
p	q	$p \rightarrow q$
T	T	T
T	F	F
F	T	T
F	F	T

“ p implies q ”
 “ p only if q ”
 “a sufficient condition for q is p ”
 “ q whenever p ”
 “ q is necessary for p ”
 “ q follows from p ”

Logical Connectives

EXAMPLE 1

“If you get 100% on the final, then you will get an A.”

If you manage to get a 100% on the final, then you would expect to receive an A. If you do not get 100% you may or may not receive an A depending on other factors. However, if you do get 100%, but the professor does not give you an A, you will feel cheated.

Logical Connectives

EXAMPLE 2

Let p be the statement “Maria learns discrete mathematics” and q the statement “Maria will find a good job.” Express the statement $p \rightarrow q$ as a statement in English.

Logical Connectives

EXAMPLE 2

Let p be the statement “Maria learns discrete mathematics” and q the statement “Maria will find a good job.” Express the statement $p \rightarrow q$ as a statement in English.

“If Maria learns discrete mathematics, then she will find a good job.”

“Maria will find a good job when she learns discrete mathematics.”

Logical Connectives

EXAMPLE 3

“If today is Friday, then $2 + 3 = 6$.”

Logical Connectives

EXAMPLE 3

“If today is Friday, then $2 + 3 = 6$.”

is true every day except Friday, even though $2 + 3 = 6$ is false.

Logical Connectives

DEFINITION 6

Let p and q be propositions. The *biconditional statement* $p \leftrightarrow q$ is the proposition “ p if and only if q .” The biconditional statement $p \leftrightarrow q$ is true when p and q have the same truth values, and is false otherwise. Biconditional statements are also called *bi-implications*.

TABLE 6 The Truth Table for the Biconditional $p \leftrightarrow q$.

p	q	$p \leftrightarrow q$
T	T	T
T	F	F
F	T	F
F	F	T

“ p is necessary and sufficient for q ”
 “if p then q , and conversely”
 “ p iff q .” “ p exactly when q .”

“You can take the flight if and only if you buy a ticket.”

Truth Tables of Compound Propositions

EXAMPLE 1

Construct the truth table of the compound proposition

$$(p \vee \neg q) \rightarrow (p \wedge q).$$

Truth Tables of Compound Propositions

EXAMPLE 1

Construct the truth table of the compound proposition

$$(p \vee \neg q) \rightarrow (p \wedge q).$$

TABLE 7 The Truth Table of $(p \vee \neg q) \rightarrow (p \wedge q)$.					
p	q	$\neg q$	$p \vee \neg q$	$p \wedge q$	$(p \vee \neg q) \rightarrow (p \wedge q)$
T	T				
T	F				
F	T				
F	F				

Truth Tables of Compound Propositions

EXAMPLE 1

Construct the truth table of the compound proposition

$$(p \vee \neg q) \rightarrow (p \wedge q).$$

TABLE 7 The Truth Table of $(p \vee \neg q) \rightarrow (p \wedge q)$.					
p	q	$\neg q$	$p \vee \neg q$	$p \wedge q$	$(p \vee \neg q) \rightarrow (p \wedge q)$
T	T	F			
T	F	T			
F	T	F			
F	F	T			

Truth Tables of Compound Propositions

EXAMPLE 1

Construct the truth table of the compound proposition

$$(p \vee \neg q) \rightarrow (p \wedge q).$$

TABLE 7 The Truth Table of $(p \vee \neg q) \rightarrow (p \wedge q)$.					
p	q	$\neg q$	$p \vee \neg q$	$p \wedge q$	$(p \vee \neg q) \rightarrow (p \wedge q)$
T	T	F	T		
T	F	T	T		
F	T	F	F		
F	F	T	T		

Truth Tables of Compound Propositions

EXAMPLE 1

Construct the truth table of the compound proposition

$$(p \vee \neg q) \rightarrow (p \wedge q).$$

TABLE 7 The Truth Table of $(p \vee \neg q) \rightarrow (p \wedge q)$.					
p	q	$\neg q$	$p \vee \neg q$	$p \wedge q$	$(p \vee \neg q) \rightarrow (p \wedge q)$
T	T	F	T	T	
T	F	T	T	F	
F	T	F	F	F	
F	F	T	T	F	

Truth Tables of Compound Propositions

EXAMPLE 1

Construct the truth table of the compound proposition

$$(p \vee \neg q) \rightarrow (p \wedge q).$$

TABLE 7 The Truth Table of $(p \vee \neg q) \rightarrow (p \wedge q)$.					
p	q	$\neg q$	$p \vee \neg q$	$p \wedge q$	$(p \vee \neg q) \rightarrow (p \wedge q)$
T	T	F	T	T	T
T	F	T	T	F	F
F	T	F	F	F	T
F	F	T	T	F	F

Precedence of Logical Operators

TABLE 8 Precedence of Logical Operators.	
<i>Operator</i>	<i>Precedence</i>
\neg	1
\wedge	2
\vee	3
\rightarrow	4
\leftrightarrow	5

Truth Tables of Compound Propositions

EXAMPLE 2

Construct the truth table of the compound proposition $(p \wedge \neg q) \rightarrow r$

Truth Tables of Compound Propositions

EXAMPLE 2

Construct the truth table of the compound proposition $(p \wedge \neg q) \rightarrow r$

p	q	r	$\neg q$	$p \wedge \neg q$	$p \wedge \neg q \rightarrow r$

Truth Tables of Compound Propositions

EXAMPLE 2

Construct the truth table of the compound proposition $(p \wedge \neg q) \rightarrow r$

p	q	r	$\neg q$	$p \wedge \neg q$	$p \wedge \neg q \rightarrow r$
T	T	T			
T	T	F			
T	F	T			
T	F	F			
F	T	T			
F	T	F			
F	F	T			
F	F	F			

Truth Tables of Compound Propositions

EXAMPLE 2

Construct the truth table of the compound proposition $(p \wedge \neg q) \rightarrow r$

p	q	r	$\neg q$	$p \wedge \neg q$	$p \wedge \neg q \rightarrow r$
T	T	T	F		
T	T	F	F		
T	F	T	T		
T	F	F	T		
F	T	T	F		
F	T	F	F		
F	F	T	T		
F	F	F	T		

Truth Tables of Compound Propositions

EXAMPLE 2

Construct the truth table of the compound proposition $(p \wedge \neg q) \rightarrow r$

p	q	r	$\neg q$	$p \wedge \neg q$	$p \wedge \neg q \rightarrow r$
T	T	T	F	F	
T	T	F	F	F	
T	F	T	T	T	
T	F	F	T	T	
F	T	T	F	F	
F	T	F	F	F	
F	F	T	T	F	
F	F	F	T	F	

Truth Tables of Compound Propositions

EXAMPLE 2

Construct the truth table of the compound proposition $(p \wedge \neg q) \rightarrow r$

p	q	r	$\neg q$	$p \wedge \neg q$	$p \wedge \neg q \rightarrow r$
T	T	T	F	F	T
T	T	F	F	F	T
T	F	T	T	T	T
T	F	F	T	T	F
F	T	T	F	F	T
F	T	F	F	F	T
F	F	T	T	F	T
F	F	F	T	F	T

Logic and Bit Operations

- Computers represent information using **bits**. A bit is a symbol with two possible values, namely, 0 (zero) and 1 (one).

<i>Truth Value</i>	<i>Bit</i>
T	1
F	0

Computer Bit Operations

- We will also use the notation OR, AND, and XOR for the operators \vee , \wedge , and \oplus , as is done in various programming languages.

TABLE 9 Table for the Bit Operators *OR*, *AND*, and *XOR*.

x	y	$x \vee y$	$x \wedge y$	$x \oplus y$
0	0	0	0	0
0	1	1	0	1
1	0	1	0	1
1	1	1	1	0

Bit Strings

- Information is often represented using bit strings, which are lists of zeros and ones. When this is done, operations on the bit strings can be used to manipulate this information.

A *bit string* is a sequence of zero or more bits. The *length* of this string is the number of bits in the string.

101010011 is a bit string of length nine.

Example

- Find the bitwise OR, bitwise AND, and bitwise XOR of the bit strings 01 1011 0110 and 11 0001 1101

01 1011 0110

11 0001 1101

11 1011 1111

bitwise *OR*

01 0001 0100

bitwise *AND*

10 1010 1011

bitwise *XOR*