DAY 21 | PRE-READ

# Opening Day for Your App

A light read before Day 21. About 15 minutes, no code required.

Prepared by **Ahmed** | linkedin.com/in/ahmed-al-imaad

## Why read this?

Yesterday you packed your app into a container and added security gates. Tomorrow you put it on the internet using Microsoft Azure, and set up a pipeline that delivers every approved change automatically.

## 1. The same box, different addresses

A food truck is the same truck whether it parks at a festival or outside an office. Only the location and the menu prices change. A cloud-ready app works the same way: the same container runs in a test environment and in production. Only its settings change, such as which database to use.

## 2. Where to park the truck

| Azure option | Everyday comparison | Good for |
|---|---|---|
| App Service | A rented shop with staff who keep it running | Most web apps and APIs |
| Container Apps | A market stall that grows or shrinks with the crowd | Containers that need automatic scaling |
| Kubernetes (AKS) | Running your own shopping mall | Large platforms with dedicated teams |
| Virtual machine | Renting an empty building | Special or legacy software |

**Key idea:** choose the simplest option that meets the need. Simple systems are easier to keep running.

## 3. Releases with a safety gate

Many teams first release to a test environment, check it, and only then promote the same version to production. A person can approve the final step. Azure DevOps calls these **environments**, and the approval is a gate.

## 4. A safe for passwords NEW (v4)

Apps need passwords, for example to reach a database. Writing them in the code is like taping the shop key to the door. **Azure Key Vault** is a locked safe for passwords and keys. But the app needs a key to open the safe. A **managed identity** solves this: Azure itself vouches for the app, like a staff badge, so there is no key to lose.

## 5. Think about these before class

- What settings would differ between a test and a live version of an app?
- Why should passwords never be written inside the app's code or pipeline files?
- Who in a telecom company would approve a production release, and what would they check?

Shukka (出荷): shipping out, sending goods to customers