


Account Abstraction

Public-Private key pair

- Public Key is generated by the private key
- Message encrypted by one key can be decrypted using the other
- Public and Private keys are very long so we usually use the hashed version of the public key in blockchain which is generally called public address
- Public key can be derived from the private key but not vice versa

Simplified flow of a TX in blockchain



Workflow of creating an EOA and interacting with dapp



Security-related drawbacks of EOAs

1

Cannot recover wallet access without seed phrase

2

Private keys create single points of failure and impose more burden on users for security

3

Considerable risk of losing assets (tokens/NFTs) to malicious actors via phishing, social engineering, hacks, etc.



METAMASK





Intro

Account Abstraction is a blockchain technology that allows users to use smart contracts as their accounts.



The default account for most users is an Externally Owned Account, or EOA. EOAs are accounts controlled by an external private key. On most blockchain networks using the Ethereum Virtual Machine (EVM), only an EOA can trigger transactions so this is the default account model for most users.

Unfortunately EOAs require users to know a lot about how a blockchain works to use them safely. We can create much better user experiences using Contract Accounts.


Here are some of the things contract accounts can enable that aren't possible with EOAs:

-  **Arbitrary verification logic:** Support single and multi sig verification and any arbitrary signature scheme.
-  **Sponsored transactions:** Allow users to pay transaction fees in ERC-20 tokens or build your own fee logic, including sponsoring transaction fees on your app.
-  **Account security:** Enable social recovery and security features like time-locks and withdraw limits.
-  **Atomic multi-operations:** Build flows that better align with your user's intent such as trading in one click rather than approving and swapping separately.

Account abstraction sounds great! But there are some down sides to also consider:


-  **Signing issues:** Ideally, all apps would following EIP-1271 to validate signatures. Unfortunately this is not always the case and those apps would be incompatible with contract accounts.
-  **Higher gas l:** On L2s and other scaling solutions this becomes less of a problem. However more research on how to reduce gas cost in this context, especially on Ethereum mainnet, is required.

Multi-factor authentication for web3 wallets




METAMASK

Normal transactions vs ETH-less transactions



How transaction batching improves the workflow of using a DeFi dapp


DeFi dapps today



DeFi dapps tomorrow (with account abstraction)




Components of ERC-4337



- *UserOperations* are pseudo-transaction objects that are used to execute transactions with contract accounts. These are created by your app.
- *Bundlers* are actors that package *UserOperations* from a mempool and send them to the *EntryPoint* contract on the blockchain.
- *EntryPoint* is a singleton smart contract that handles the verification and execution logic for transactions.
- *Contract Accounts* are smart contract accounts owned by a user.
- *Paymasters* are optional smart contract accounts that can sponsor transactions for *Contract Accounts*.
- *Aggregators* are optional smart contracts that can validate signatures for multiple *Contract Accounts*.

How ERC-4337 works



Existing Libraries and frameworks

- Zerodev
- Stackup
- Biconomy
- UserOp.js

ZeroDev

ZeroDev is a developer framework for creating, using, and extending smart wallets powered by account abstraction (ERC-4337).

- Create: ZeroDev integrates with all popular onboarding and authentication solutions, so that you can easily create *smart wallets* for your users, no matter they are Web2 or Web3.
- Use: ZeroDev provides SDKs and APIs for the most popular smart wallet *features*, including gas sponsoring, transaction batching, automated transactions, session keys, and more.
- Extend: if our smart wallet features don't cover your needs, you can easily build custom smart wallet *plugins* using our plugin framework.

No matter if you are building a wallet or a DApp, you can use ZeroDev to dramatically improve Web3 UX for your users.


APIs

1. Get-user-nonce -> return nonce if exists from an existent user
2. Signup -> if nonce doesn't exists in above case then create a user in database and get a nonce.
3. Login -> send signature and get a token

What does authentication requires?

- 1) Unique Identifier
- 2) Proof of ownership of that unique identifier

Proof of ownership of a wallet



Authentication flow with wallet

