

PENETRATION TESTING REPORT

Enumeration & Network Scanning Phases

Pentester Name	Ahmed
Date	September 2026
Target / Client	networkwalks.com (written permission obtained) / Personal LAN Network
Permission Secured?	Yes — written authorization from Networkwalks
Environment	Kali Linux (Oracle VirtualBox) + Windows (Zenmap)
Phases Covered	Phase 1: Enumeration & Footprinting Phase 2: Network Scanning
Phases Pending	Phases 3–5 (Vulnerability Scanning, Exploitation, Post-Exploitation)

CONFIDENTIAL — FOR AUTHORIZED USE ONLY

1. LIABILITY DISCLAIMER

All activities documented in this report were conducted exclusively on systems and networks for which prior written authorization was obtained. The enumeration activities targeting networkwalks.com were performed with explicit written permission from the domain owner. The network scanning activities were conducted solely on a personal LAN network comprising devices owned and operated by the tester.

This report is produced for educational and professional development purposes as part of a cybersecurity internship program. The techniques, tools, and findings contained herein must not be reproduced against any system without valid written authorization. Unauthorized access to computer systems is a criminal offense in most jurisdictions and may result in prosecution, fines, and permanent professional consequences. The author and affiliated organizations accept no responsibility for any misuse of the information contained in this document.

2. INTRODUCTION

This report covers two practical exercises representing the first two phases of a penetration testing engagement.

In the first exercise, passive and active enumeration was carried out against the public domain networkwalks.com using six Kali Linux tools: WHOIS, WhatWeb, Nslookup, Curl, Wafw00f, and DNSRecon. Each tool was used to extract a specific category of publicly accessible information, including domain registration data, web technology stack, DNS resolution, HTTP response headers, web application firewall presence, and DNS infrastructure records.

In the second exercise, active host discovery was performed on a personal LAN using Zenmap (the graphical interface for Nmap). A ping scan of the 192.168.1.0/24 subnet identified all live hosts, their IP addresses, MAC addresses, device hostnames, and vendor information where available.

Together, these exercises demonstrate the full transition from open-source intelligence gathering on a public target to active host enumeration on an authorized internal network — the foundational steps before any vulnerability assessment or exploitation phase.

3. TOOLS USED

Tool	Phase	Purpose
WHOIS	Enumeration	Domain registration info — registrar, creation/expiry dates, name servers, status flags
WhatWeb	Enumeration	Web technology fingerprinting — CMS, server, plugins, JS libraries, IP, email
Nslookup	Enumeration	DNS resolution of the target domain to its server IP address
Curl -I	Enumeration	HTTP response header inspection — server info, cookies, cache headers, API endpoints
Wafw00f	Enumeration	WAF detection — identifies whether a Web Application Firewall is protecting the site
DNSRecon	Enumeration	Full DNS record enumeration — SOA, NS, A, MX, TXT, SPF, SRV records

Tool	Phase	Purpose
Zenmap (Nmap 7.991)	Network Scanning	Ping scan to discover live hosts, IP/MAC addresses, hostnames, and network topology
Windows CMD / ipconfig	Network Scanning	Identified local IP address and subnet range before running the scan

4. ACTIVITIES PERFORMED

4.1 Enumeration & Footprinting — networkwalks.com

The following enumeration activities were performed from inside Kali Linux running in Oracle VirtualBox. All six tools were run against networkwalks.com with written permission from Networkwalks. The objective of this phase was to collect as much publicly accessible information as possible before any active testing or exploitation.

4.1.1 WHOIS — Domain Registration Lookup

Command:

```
| whois networkwalk.com
```

The WHOIS query returned the following registration data for NETWORKWALK.COM:

- Registrar: GoDaddy.com, LLC | IANA ID: 146 | Abuse contact: abuse@godaddy.com / 480-624-2505
- Creation Date: 2015-04-16 | Last Updated: 2026-04-13 | Expiry Date: 2027-04-16
- Registry Domain ID: 1920256084_DOMAIN_COM-VRSN
- Name Servers: NS35.DOMAINCONTROL.COM, NS36.DOMAINCONTROL.COM
- DNSSEC: unsigned (no cryptographic signing on DNS records)
- Domain Status: clientDeleteProhibited, clientRenewProhibited, clientTransferProhibited, clientUpdateProhibited

The registrar lock flags show the domain owner has applied protections against unauthorized transfer and modification. The absence of DNSSEC means DNS responses are not cryptographically signed, leaving the domain theoretically susceptible to DNS cache poisoning or spoofing attacks.

4.1.2 WhatWeb — Web Technology Fingerprinting

Command:

```
| whatweb networkwalks.com
```

WhatWeb identified the following technologies across all redirect hops (HTTP 301 → HTTPS 200):

- Web Server: Apache (confirmed on all responses)
- CMS: WordPress 7.1
- Plugin: WordPress Download Manager 3.3.58
- JavaScript Libraries: jQuery 3.7.1, Bootstrap 7.1
- Resolved IP: 192.232.216.135 | Country: United States
- Email exposed in metadata: info@networkwalks.com
- Additional detected: Google-Tag-Manager, Open-Graph-Protocol, HTML5, Frame headers

The explicit plugin version (WP Download Manager 3.3.58) being publicly visible allows an attacker to query vulnerability databases such as WPScan or CVE Mitre for known exploits against that specific version without any further probing.

4.1.3 Nslookup — DNS Resolution

Command:

```
| nslookup networkwalks.com
```

Results:

- Local DNS resolver used: 192.168.1.1 (home router)
- Resolved IP address: 192.232.216.135 (non-authoritative answer)

The target resolves to a shared hosting IP (confirmed by the HostGator nameservers found in DNSRecon). Shared hosting means other customer websites likely reside on the same IP, which can have implications for cross-tenant information exposure in certain hosting misconfigurations.

4.1.4 Curl -I — HTTP Header Inspection

Command:

```
| curl -I https://networkwalks.com
```

HTTP/2 200 response headers returned:

- server: Apache
- x-nginx-cache: WordPress
- content-type: text/html; charset=UTF-8
- referrer-policy: no-referrer-when-downgrade
- x-endurance-cache-level: 0
- date: Mon, 14 Sep 2026 09:24:05 GMT
- set-cookie: __wpdm_client (HttpOnly flag set — prevents JavaScript access to cookie)
- link: <https://networkwalks.com/wp-json/>; rel=shortlink (WordPress REST API exposed)
- permissions-policy header present

The Link header exposes the WordPress REST API endpoint /wp-json/. While this is default WordPress behavior, it enables unauthenticated enumeration of users, posts, and site metadata. The HttpOnly cookie flag is a positive security control, but the API exposure is an unnecessary information leak.

4.1.5 Wafw00f — WAF Detection

Command:

```
| wafw00f networkwalks.com
```

Result:

- WAF Identified: ModSecurity (SpiderLabs)
- Requests made: 2

ModSecurity is a widely deployed open-source Web Application Firewall. Its presence indicates proactive traffic filtering is in place. However, identifying the specific WAF product and vendor allows an attacker to research ModSecurity-specific bypass techniques and tune their payloads accordingly before any exploitation attempt.

4.1.6 DNSRecon — DNS Infrastructure Enumeration

Command:

```
| dnsrecon -d networkwalks.com
```

DNSRecon completed enumeration in ~9 seconds and returned 8 records:

- SOA: ns6135.hostgator.com — 50.87.144.87
- NS: ns6135.hostgator.com (192.232.216.131), ns6136.hostgator.com (192.232.216.131)

- Bind Version: 50.87.144.87 — "9.16.23-RH"
- A Record: networkwalks.com → 192.232.216.135
- MX Record: mail.networkwalks.com → 192.232.216.135 (mail and web share same IP)
- TXT/SPF: v=spf1 +a +mx +ip4:50.87.144.87 +include:websitewelcome.com ~all
- TXT: google-site-verification token present
- SRV: Multiple _autodiscover._tcp entries → cpanelmaildiscovery.cpanel.net (184.94.x.x:443)

The hosting infrastructure is now fully identifiable as HostGator / cPanel. The SPF record uses ~all (softfail) rather than -all (hardfail), which means email spoofing attempts using this domain may still reach recipient inboxes under some mail server configurations. The mail server sharing the same IP as the web server is also notable — a compromise of one service could expose both.

4.2 Network Scanning — Personal LAN (192.168.1.0/24)

A ping scan was performed using Zenmap (Nmap 7.991) on Windows against the personal home LAN subnet. The goal was to enumerate all active hosts, identify their IP addresses, MAC addresses, hostnames, and hardware vendors where identifiable.

Subnet scanned:

```
| nmap -sn 192.168.1.9/24
```

Scan duration: 78.70 seconds | Total addresses probed: 256 | Live hosts found: 9

#	Hostname	IP Address	MAC Address	Vendor / Notes
1	(Gateway)	192.168.1.1	90:9F:22:61:09:52	Zyxel Communications — LAN Gateway / Router
2	Redmi-10-2022	192.168.1.2	FE:BC:0C:9D:D3:09	Unknown (MAC randomization active)
3	moto-g54-5G	192.168.1.3	0A:2F:D6:55:35:EA	Unknown (MAC randomization active)
4	POCO-X7-Pro	192.168.1.5	B6:48:3E:DA:C5:66	Unknown (MAC randomization active)
5	Mobina-s-M17e	192.168.1.6	66:67:08:30:9E:08	Unknown (MAC randomization active)
6	RE200	192.168.1.7	3E:64:CF:0E:D8:B0	Likely TP-Link RE200 Wi-Fi Range Extender
7	DESKTOP-3LOOOTEK	192.168.1.8	60:F2:62:4A:CB:F3	Intel Corporate — Windows Desktop PC
8	(Unknown)	192.168.1.100	3E:64:CF:0E:D8:B0	MAC matches RE200 — possible duplicate or DHCP artifact
9	DESKTOP-ODKLD9J	192.168.1.9	— (local host)	Attacker / Scanning Machine — no MAC returned

A network topology map was generated from the Zenmap Topology tab after the scan completed. The topology shows all 9 discovered hosts arranged around the central scanning node (192.168.1.9), confirming a flat star network topology on this subnet. The topology PDF (net-top.pdf) is included as part of the evidence package.

5. RISK ANALYSIS

The table below summarizes all observations from both exercises and their potential security implications. These are findings from information gathering only — no exploitation was attempted. Presence of a version number or DNS record does not by itself confirm a vulnerability; further authorized testing would be required to confirm exploitability.

#	Finding	Tool	Potential Impact	Risk
1	WordPress plugin version publicly visible: WP Download Manager 3.3.58	WhatWeb	Attacker can query CVE databases for known exploits targeting that exact plugin version	Medium
2	WordPress REST API endpoint /wp-json/ exposed in HTTP Link header	Curl -I	Enables unauthenticated user enumeration, post/page metadata access via API	Medium
3	Full CMS and server stack fingerprinted (WordPress 7.1, Apache, jQuery 3.7.1, Bootstrap 7.1)	WhatWeb	Significantly reduces attacker reconnaissance time for targeted exploitation	Medium
4	DNSSEC not enabled on domain	WHOIS / DNSRecon	DNS responses not signed — domain susceptible to cache poisoning or spoofing in theory	Low
5	SPF record uses ~all (softfail) instead of -all (hardfail)	DNSRecon	Email spoofing using this domain may reach recipient inboxes in some mail server configurations	Medium
6	Hosting provider identifiable: HostGator / cPanel via NS and SRV records	DNSRecon	Allows attacker to target hosting-provider-specific vulnerabilities or social engineering	Low
7	WAF product identified: ModSecurity (SpiderLabs)	Wafw00f	Knowledge of specific WAF enables research of bypass techniques before exploitation	Low
8	Web and mail server share the same IP (192.232.216.135)	DNSRecon + Nslookup	Compromise of one service on the host may expose the other running on the same server	Low
9	Contact email exposed: info@networkwalks.com	WhatWeb	Can be used for phishing, social engineering, or targeted credential stuffing attacks	Low
10	9 live hosts discovered on personal LAN	Zenmap	Full device visibility — any unauthorized or unknown device should be investigated	Informational
11	Multiple devices using randomized MAC addresses (mobile phones)	Zenmap	Vendor identification not possible; device ownership verification recommended	Informational
12	RE200 range extender detected (192.168.1.7) with shared MAC at .100	Zenmap	Additional network equipment extends the LAN attack	Informational

#	Finding	Tool	Potential Impact	Risk
			surface; firmware should be kept updated	

Risk Key: ■ High ■ Medium ■ Low ■ Informational

6. RECOMMENDATIONS

#	Recommendation	Addresses
1	Suppress HTTP headers that expose CMS version, plugin names, and server software. Use a WordPress hardening plugin or server-level config (e.g. mod_headers) to strip or mask these values.	#1, #3
2	Restrict the WordPress REST API to authenticated users only. Disable unauthenticated access to /wp-json/users/ and other sensitive endpoints using a security plugin or custom code.	#2
3	Audit all installed WordPress plugins and keep them updated. Subscribe to the WPScan vulnerability database for notifications when new CVEs are published for installed plugins.	#1
4	Enable DNSSEC on networkwalks.com through the GoDaddy registrar control panel to cryptographically sign DNS records and protect against cache poisoning.	#4
5	Update the SPF TXT record from ~all (softfail) to -all (hardfail) to reject unauthorized senders and reduce the risk of email spoofing using this domain.	#5
6	Consider moving the mail server to a separate IP address to isolate it from the web server, limiting the blast radius if either service is compromised.	#8
7	Perform regular internal LAN scans to maintain an up-to-date device inventory. Investigate any unrecognized or unauthorized devices promptly.	#10, #11, #12
8	Enable network access controls on the router (e.g. MAC address filtering or guest network isolation) to limit which devices can communicate on the main LAN.	#10, #11

7. CONCLUSION

This report documented two foundational phases of a penetration testing methodology: enumeration and footprinting of a public web target, and active host discovery on a personal LAN network.

During the enumeration phase, six Kali Linux tools were used to gather publicly available information about networkwalks.com. The exercise confirmed that even before any active exploitation, a significant amount of infrastructure detail is freely accessible — including the CMS and plugin versions, hosting provider, name server software, mail server configuration, WAF implementation, and administrative contact information.

During the network scanning phase, Zenmap successfully identified 9 live hosts on the 192.168.1.0/24 subnet, along with their IP addresses, MAC addresses, device hostnames, and vendor information. A topology map was generated to visualize the network layout.

Key takeaways:

- Information gathering is one of the most critical pre-exploitation phases. The data collected in these two exercises directly informs the approach for all subsequent penetration testing phases.
- Public-facing infrastructure exposes considerably more information than most administrators realize, often without requiring any active probing or exploitation.
- Active network scanning quickly produces a complete picture of the internal network — highlighting why device inventory management and network access controls are essential.
- All findings in this report are observations from authorized enumeration only. No exploitation was attempted at any stage. Confirmation of actual vulnerabilities would require further authorized penetration testing.

Phases 3 through 5 (vulnerability scanning, exploitation, and post-exploitation) are currently in progress and will be documented in separate reports.

8. EVIDENCE / SCREENSHOTS

The screenshots below were captured during the practical exercises and serve as primary evidence for all findings described in Section 4. Screenshots are referenced by filename and should be attached alongside this report.

File	Tool	What it shows
Screenshot_156.png	WHOIS	Full WHOIS output for networkwalk.com — registrar, dates, name servers, domain status flags
Screenshot_157.png	WhatWeb	WhatWeb fingerprint output across all redirects — CMS, plugins, server, jQuery, email, IP
Screenshot_158.png	Nslookup	DNS resolution of networkwalks.com resolving to 192.232.216.135
Screenshot_159.png	Curl -I	HTTP/2 200 response headers — server, cache, cookie, Link header with /wp-json/
Screenshot_160.png	Wafw00f	WAF detection confirming ModSecurity (SpiderLabs) is protecting the site
Screenshot_161.png	DNSRecon	Full DNS enumeration — 8 records returned including SOA, NS, A, MX, TXT, SPF, SRV
Screenshot_170.png	Zenmap	Ping scan output listing all 9 live hosts with hostnames, IPs, and MAC addresses
net-top.pdf	Zenmap Topology	Network topology diagram exported from Zenmap showing all discovered hosts and connections

```
kali 1 (Snapshot 1) [Running] - Oracle VirtualBox
File Machine View Input Devices Help

amad@kali:~$ whois networkwalks.com
Domain Name: NETWORKWALKS.COM
Registry Domain ID: 1920256804_DOMAIN_COM-VRSN
Registrar WHOIS Server: whois.godaddy.com
Registrar URL: http://www.godaddy.com
Updated Date: 2026-04-12T02:24:12Z
Creation Date: 2015-04-16T06:46:05Z
Registry Expiry Date: 2027-04-16T06:46:05Z
Registrar: GoDaddy.com, LLC
Registrar IANA ID: 146
Registrar Abuse Contact Email: abuse@godaddy.com
Registrar Abuse Contact Phone: 480-624-2505
Domain Status: clientDeleteProhibited https://icann.org/epp#clientDeleteProhibited
Domain Status: clientRenewProhibited https://icann.org/epp#clientRenewProhibited
Domain Status: clientTransferProhibited https://icann.org/epp#clientTransferProhibited
Domain Status: clientUpdateProhibited https://icann.org/epp#clientUpdateProhibited
Name Server: NS35.DOMAINCONTROL.COM
Name Server: NS36.DOMAINCONTROL.COM
DNSSEC: unsigned
URL of the ICANN Whois Inaccuracy Complaint Form: https://www.icann.org/wicf/
>>> Last update of whois database: 2026-09-14T09:13:37Z <<<

For more information on Whois status codes, please visit https://icann.org/epp

NOTICE: The expiration date displayed in this record is the date the
registrar's sponsorship of the domain name registration in the registry is
currently set to expire. This date does not necessarily reflect the expiration
date of the domain name registrant's agreement with the sponsoring
registrar. Users may consult the sponsoring registrar's Whois database to
view the registrar's reported date of expiration for this registration.

TERMS OF USE: You are not authorized to access or query our Whois
database through the use of electronic processes that are high-volume and
automated except as reasonably necessary to register domain names or
modify existing registrations; the Data in VeriSign Global Registry
Services' ("VeriSign") Whois database is provided by VeriSign for
information purposes only, and to assist persons in obtaining information
about or related to a domain name registration record. VeriSign does not
guarantee its accuracy. By submitting a Whois query, you agree to abide
by the following terms of use: You agree that you may use this Data only
for lawful purposes and that under no circumstances will you use this Data
to: (1) allow, enable, or otherwise support the transmission of mass
unsolicited, commercial advertising or solicitations via e-mail, telephone,
or facsimile; or (2) enable high volume, automated, electronic processes
that apply to VeriSign (or its computer systems). The compilation,
repackaging, dissemination or other use of this Data is expressly
prohibited without the prior written consent of VeriSign. You agree not to
use electronic processes that are automated and high-volume to access or
query the Whois database except as reasonably necessary to register
domain names or modify existing registrations. VeriSign reserves the right
to restrict your access to the Whois database in its sole discretion to ensure
operational stability. VeriSign may restrict or terminate your access to the
Whois database for failure to abide by these terms of use. VeriSign
```

```
kali 1 (Snapshot 1) [Running] - Oracle VirtualBox
File Machine View Input Devices Help

amad@kali:~$ curl -s https://networkwalks.com/ | grep -oE "(Apache|Cookies|Country|HTTPServer|HttpOnly|IP|RedirectLocation|UncommonHeaders|permissions-policy|x-redirect-by|upgrade|referrer-policy|x-endurance-cache-level|x-nginx-cache)"
Apache, Cookies[_wpdm_client], Country[UNITED STATES], HTTPServer[Apache], HttpOnly[_wpdm_client], IP[192.232.216.135], RedirectLocation[https://networkwalks.com/], UncommonHeaders[permissions-policy,link,upgrade,referrer-policy,x-endurance-cache-level,x-nginx-cache], WordPress[7.1], jQuery[3.7.1], MetaGenerator[WordPress 7.1,WordPress Download Manager 3.3.58], Open-Graph-Protocol[website], Script[4684NR-1P186amp;pidvar2=s85116amp;prtvar2=16amp;scvvar2=12,application/json,application/ld+json,module,speculationrules,text/javascript], Title[Networkwalks Academy], UncommonHeaders[permissions-policy,link,upgrade,referrer-policy,x-endurance-cache-level,x-nginx-cache], WordPress[7.1], jQuery[3.7.1], MetaGenerator[WordPress 7.1,WordPress Download Manager 3.3.58], Open-Graph-Protocol[website], Script[4684NR-1P186amp;pidvar2=s85116amp;prtvar2=16amp;scvvar2=12,application/json,application/ld+json,module,speculationrules,text/javascript], Title[Networkwalks Academy], UncommonHeaders[permissions-policy,link,upgrade,referrer-policy,x-endurance-cache-level,x-nginx-cache], WordPress[7.1]
```

```
kali 1 (Snapshot 1) [Running] - Oracle VirtualBox
File Machine View Input Devices Help
1 2 3 4

axmad@kali: ~$ nslookup networkwalks.com
Server: 192.168.1.1
Address: 192.168.1.1#53

Non-authoritative answer:
Name: networkwalks.com
Address: 192.232.216.135

axmad@kali: ~$
```

```
kali 1 (Snapshot 1) [Running] - Oracle VirtualBox
File Machine View Input Devices Help
1 2 3 4

axmad@kali: ~$ curl https://networkwalks.com
HTTP/2 200
permissions-policy: private-state-token-redemption=(self "https://www.google.com" "https://www.gstatic.com" "https://recaptcha.net" "https://challenges.cloudflare.com" "https://hcaptcha.com"), private-state-token-issuance=(self "https://www.google.com" "https://www.gstatic.com" "https://recaptcha.net" "https://challenges.cloudflare.com" "https://hcaptcha.com")
Link: <https://networkwalks.com/wp-json/?rel="https://api.w.org"/>, <https://networkwalks.com/wp-json/wp/v2/pages/53/>; rel="alternate"; title="JSON"; type="application/json", <https://networkwalks.com/>; rel="shortlink"
set-cookie: __wpdm_client=c36928db5b1a8af4712a38c7865c77a5; path=/; domain=networkwalks.com; secure; HttpOnly
referrer-policy: no-referrer-when-downgrade
x-endurance-cache-level: 0
x-nginx-cache: WordPress
content-type: text/html; charset=UTF-8
date: Mon, 14 Sep 2020 09:24:05 GMT
server: Apache

axmad@kali: ~$
```


Zenmap

Scan Tools Profile Help

Target: 192.168.1.9/24 Profile: Scan Cancel

Command: nmap -sn 192.168.1.9/24

Hosts Services

OS Host

192.168.0.101

192.168.1.1

Redmi-10-2022

moto-g54-5G

POCO-X7-Pro

Mobina-s-M17

RE200 (192.168.1.7)

DESKTOP-3LOO

DESKTOP-ODK

192.168.1.100

192.168.9.1

192.168.56.1

192.168.137.1

Filter Hosts

Nmap Output Ports / Hosts Topology Host Details Scans

nmap -sn 192.168.1.9/24

Starting Nmap 7.991 (<https://nmap.org>) at 2026-09-17 23:02 +0530

Nmap scan report for 192.168.1.1

Host is up (0.027s latency).

MAC Address: 90:9F:22:61:09:52 (Zyxel Communications)

Nmap scan report for Redmi-10-2022 (192.168.1.2)

Host is up (0.037s latency).

MAC Address: FE:BC:0C:9D:D3:09 (Unknown)

Nmap scan report for moto-g54-5G (192.168.1.3)

Host is up (0.035s latency).

MAC Address: 0A:2F:D6:55:35:EA (Unknown)

Nmap scan report for POCO-X7-Pro (192.168.1.5)

Host is up (0.064s latency).

MAC Address: B6:48:3E:DA:C5:66 (Unknown)

Nmap scan report for Mobina-s-M17e (192.168.1.6)

Host is up (0.026s latency).

MAC Address: 66:67:08:30:5E:08 (Unknown)

Nmap scan report for RE200 (192.168.1.7)

Host is up (0.062s latency).

MAC Address: 3E:64:CF:0E:D8:B0 (Unknown)

Nmap scan report for DESKTOP-3LOOOTEK (192.168.1.8)

Host is up (0.074s latency).

MAC Address: 60:F2:62:4A:0B:F3 (Intel Corporate)

Nmap scan report for 192.168.1.100


Host is up (0.71s latency).

MAC Address: 3E:64:CF:0E:D8:B0 (Unknown)

Nmap scan report for DESKTOP-ODKLD9J (192.168.1.9)

Host is up.

Nmap done: 256 IP addresses (9 hosts up) scanned in 78.70 seconds



— End of Report —

Author: Ahmed

Cybersecurity Intern B083

Linkedin: <https://www.linkedin.com/in/ahmed-ahmed-a328363a6/>

September 2026

Project Info:

Program Name: Cybersecurity program at Networkwalks | **Week:** 02 | **Repository:** <https://github.com/suvsys/NETWORKWALKS-WK2-FOOTPRINTING-NETWORK-SCANNING-PHASES>