

Object Oriented Programming (OOP)

Mohamed Ezz

Lecture 5

Review

- Draw the class diagram showing has-a relationship for:
 - ✓ Family, Father, Mother, Son, Daughter classes
 - ✓ Building, Address, Contact classes
 - ✓ LinkedList, Node
- Which of the access specifiers are suitable for the following :
 - ✓ password in customer class
 - ✓ GetName in customer class
 - ✓ PI in Math class
- Write signature of two or more overloaded methods for the following classes:
 - ✓ constructors of Student class
 - ✓ constructors of Point class
 - ✓ drawDiagram for Paint class (for point, rectangle, circle, triangle)
 - ✓ calculatePaint for Paint class (for point, rectangle, circle, triangle)
- Write static method & variable for the counter of Student class

Lecture Objectives

- ✓ Review Array in Java
- ✓ Understand how to create Array of user-defined Objects
- ✓ Understand how to analysis & design advanced Composition
- ✓ Understand ArrayList & HashMap built-in collection/container java classes
- ✓ Practice composition example using built-in collection java classes


Review : Arrays

An array is an indexed list of values.

You can make an array of any type
int, double, String, etc..


All elements of an array must have the same type.

Arrays



Arrays

Example: double []



Arrays

The index starts at zero and ends at length-1.

Example:

```
int[] values = new int[5];  
values[0] = 12; // CORRECT  
values[4] = 12; // CORRECT  
values[5] = 12; // WRONG!! compiles but  
                // throws an Exception  
                // at run-time
```

Have a demo with runtime exception

Arrays

An array is defined using TYPE `[]`.

Arrays are just another type.

```
int[] values;    // array of int
```

```
int[][] values;  // int[] is a type
```

Arrays

To create an array of a given size, use the operator `new` :

```
int[] values = new int[5];
```

or you may use a variable to specify the size:

```
int size = 12;  
int[] values = new int[size];
```

Array Initialization

Curly braces can be used to initialize an array.

It can **ONLY** be used when you declare the variable.

```
int[] values = { 12, 24, -23, 47 };
```

Accessing Arrays

To access the elements of an array, use the `[]` operator:

```
values[index]
```

Example:

```
int[] values = { 12, 24, -23, 47 };  
values[3] = 18;           // {12, 24, -23, 18}  
int x = values[1] + 3;    // {12, 24, -23, 18}
```

The *length* variable

Each array has a `length` variable built-in that contains the length of the array.

```
int[] values = new int[12];  
int size = values.length; // 12
```

```
int[] values2 = {1,2,3,4,5}  
int size2 = values2.length; // 5
```

String arrays

A side note

```
public static void main (String[] arguments){  
    System.out.println(arguments.length);  
    System.out.println(arguments[0]);  
    System.out.println(arguments[1]);  
}
```

Looping through an array

Example 1:

```
int[] values = new int[5];

for (int i=0; i<values.length; i++) {
    values[i] = i;
    int y = values[i] * values[i];
    System.out.println(y);
}
```

Looping through an array

Example 2:

```
int[] values = new int[5];  
int i = 0;  
while (i < values.length) {  
    values[i] = i;  
    int y = values[i] * values[i];  
    System.out.println(y);  
    i++;  
}
```


Other way to access array

- Traditional way to access the array

```
String[] names = {"Ahmed","Mohamed", "Aly"};
for ( int i=0;i< names.length;i++){
    String s= names[i];
    System.out.println( s);
}
```

- Instead of looping & access array using index, use the following form:

```
String[] names = {"Ahmed","Mohamed", "Aly"};
for(String s: names){
    System.out.println( s);
}
```


Array of Object “Object”

- Facebook
- Gmail/Hotmail/Yahoo
- Forum: has array of Members
- Faculty: has array of Students

Faculty & Student Relations



Faculty Class has member variable student array (of type student[])



Faculty & Student Classes

Student.java

```
class Student{
    String firstName;
    String LastName;
    int classNo;// 1,2,3,4
    int examID;
    public Student(String fName, String lName, int classNo){
        firstName = fName
        lastName = lName;
        this.classNo=classNo;
    }
    public void print(){
        System.out.println(firstName + " " + lastName+ " ID=" + examID);
    }
}
```

Faculty & Student Classes

Faculty.java

```
class Faculty {  
    private Student[] students;  
    private int index;  
    private int max;  
    public Faculty(int NoOfStudent){  
        students = new Student[NoOfStudent];  
        index=0;  
        max= NoOfStudent;  
    }  
    public void registerStudent(Student s){  
        if (index < max){  
            students[index]= s;  
            index++;  
        }  
        else  
            System.out.println("Faculty is full");  
    }  
}
```

```
public Student getStudent(String name){  
    for (int i=0;i<index;i++){  
        String sName = students[i].firstName;  
        if (sName.equals(name))  
            retrun students[i];  
    }  
    return Null;  
}
```

```
public void printStudents(int cID){  
    for (int i=0;i<index;i++){  
        if (students[i].classNo= cID)  
            students[i].print();  
    }  
}
```

Test Faculty & Student

TestFaculty.java

```
class TestFaculty {  
    public static void main(String arg[]){  
        Faculty engFaculty = new Faculty (100);  
        Student  student1 = new Student("Amal","Amer",1);  
        Student  student2 = new Student("Wael","Aziz",2);  
        Student  student3 = new Student("Sayed","Yousef",3);  
        engFaculty. registerStudent(student1);  
        engFaculty. registerStudent(student2);  
        engFaculty. registerStudent(student3);  
        engFaculty. registerStudent(new Student("Moh","Ezz",4) );  
        engFaculty.updateExamID();  
        Student student = engFaculty getStudent("Wael");  
        student.classNo=1;  
        engFaculty.printStudent(1);  
    }  
}
```

ArrayList & HashMap

ArrayList & HashMap

Limitations of traditional Array :

- ✓ complexity of delete operation : deleteStudent
- ✓ Search operation is low speed: FindStudent (image search for user in facebook)
- ✓ Fixed list of items which is not scalable

**This is the time to learn ArrayList & HashMap classes of
java.util to overcome these limitations**

ArrayList

- Class in **java.util** java package
- Support list of any object type (such as String, Point, Rectangle...)
- Declaration:
 ArrayList var_listName = new ArrayList ();
 e.g.
 ArrayList names = new ArrayList ();
 ArrayList points= new ArrayList ();
- Add Element :
 void add(Object type): Appends the element to the end of this vector.
 e.g.
 names.add("Omar");
 points.add(p1);
- Get Element :
 Object type get(int index): Returns the object at the specified index
 e.g.
 String name= names.get(2);
 Point p= points.get(1);

ArrayList Example

TestArrayList.java

```
Class TestArrayList{  
    public static void main(String arg[])  
        ArrayList friends = new ArrayList ();  
        friends.add("Ahmed");  
        friends.add("Mohamed");  
        friends.add("Ali");  
  
        for(int i=0;i<friends.size();i++){  
            System.out.println(friends.get(i));  
        }  
        friends.remove (1);  
  
        for(int i=0;i<friends.size();i++){  
            System.out.println(friends.get(i));  
        }  
    }  
}
```

Other way to access array

```
•ArrayList friends = new ArrayList();  
  friends.add("Ahmed");  
  friends.add("Mohamed");  
  for ( int i;i< friends .size();i++){  
    String f= friends [i];  
    System.out.println( f);  
  }
```

Instead of looping & access array or ArrayList using index, use the following form:

```
ArrayList friends = new ArrayList();  
friends.add("Ahmed");  
friends.add("Mohamed");  
for(String f: friends){  
  System.out.println(f);  
}
```

Other way to access array

```
ArrayList points = new ArrayList();
points.add(new Point(1,1));
points.add(new Point(2,3));
for(Point p: points){
    System.out.println("x=" +p.x + " y =" +p.y);
}
```

Syntax:

```
for(Object_type variable_name : arrayName){
    // inside this for you will use variable_name directly

}
```

Notes: array_name is either array name or ArrayList object ref.

Faculty Class using ArrayList

```
Import java.util.*;
class Faculty {
    private ArrayList students;
    public Faculty(){
        students = new ArrayList();
    }
    public void registerStudent(Student s){
        students.add(s);
    }
    public Student getStudent(String name){
        for ( Student s: students){
            if (s.firstName.equals(name))
                return s;
        }
        return null
    }
}
```

```
public void printStudent(int cID){
    for ( Student s: student){
        if (s.classNo == cID)
            s.print();
        }
    }

    public void updateExamID(){
        int c1=0,c2=0,c3=0,c4=0;
        for ( Student s: student){
            switch (s.classNo){
                case 1: c1++; s.examID=c1;break;
                case 2: c2++; s.examID=c2; break;
                case 3: c3++; s.examID=c3; break;
                case 4: c4++; s.examID=c4; break;
            }
        }
    }
}
```

Test Faculty with ArrayList

```
class TestFaculty {  
    public static void main(String arg[]){  
        Faculty engfaculty = new Faculty ();  
        Student student1 = new Student("Amal","Amer",1);  
        Student student2 = new Student("Wael","Aziz",2);  
        Student student3 = new Student("Sayed","Yousef",3);  
        engfaculty.registerStudent(student1);  
        engfaculty.registerStudent(student2);  
        engfaculty.registerStudent(student3);  
        engfaculty.registerStudent(new Student("Moh","Ezz",4) );  
        engfaculty.updateExamID();  
        Student student = engfaculty . getStudent("Wael");  
        student.classNo=1;  
        engfaculty.printStudent(1);  
    }  
}
```

// Any change on consumer side?

HashMap

- Class in **java.util** java package
- Support list of any object type (such as String, Point, Rectangle...) with **key**

- Declaration:

```
HashMap var_listName = new HashMap();
```

e.g.

```
HashMap mails = new HashMap();
```

```
HashMap points= new HashMap();
```

- Add Element :

void put(key, object): put the element to the table.

e.g.

```
mails.put("Omar", "omar@gmail.com");
```

- Get Element :

Object get (key): Returns the object corresponding to key

e.g.

```
String email= mails.get("Omar");
```

This is faster than `getStudent(String name)` in ArrayList version

HashMap Example

```
import java.util.*;
Class TestHashMap{
    public static void main(String arg[])
    {
        HashMap contacts = new HashMap();
        contacts.put("Ahmed", "ahmed@gmail.com");
        contacts.put("Mohamed", "mohamed@gmail.com");
        contacts.put("Ali", "ali@gmail.com");

        System.out.println( contacts.get("Ali") );
    }
}
```


Faculty Class using HashMap

```
Import java.util.*;
class Faculty {
    private HashMap students;
    public Faculty(){
        students=new HashMap();
    }
    public void registerStudent(Student s){
        students.put(s.name, s);
    }
    public Student getStudent(String name){
        return students.get(name);
    }
}
```

....

Test Faculty with HashMap

```
class TestFaculty {  
    public static void main(String arg[]){  
        Faculty faculty = new Faculty ();  
        Student student1 = new Student("Amal","Amer",1);  
        Student student2 = new Student("Wael","Aziz",2);  
        Student student3 = new Student("Sayed","Yousef",3);  
        faculty.registerStudent(student1);  
        faculty.registerStudent(student2);  
        faculty.registerStudent(student3);  
        faculty.registerStudent(new Student("Moh","Ezz",4) );  
        faculty.updateExamID();  
        Student student = faculty.getStudent("Wael");  
        student.classNo=1;  
        faculty.printStudent(1);  
    }  
}
```

// Any change on consumer side?

Homework

➤ UML of **Facebook** Application

❑ List of User Profiles

✓ User profile

- Username
- Name
- E-mail
- Mobile
- **Wall** : list posts from Me & my friends
 - **Post**:
 - Description
 - Media (image/video)
 - List of comments
 - List of like/dislike
- **photo** : List of images
- **Friends**: list of users

Homework

Design an email system with define Classes relationship