



Technical Information

ANTIFOAM COMPOUND – SILAF PDR (POWDER FORM)

DESCRIPTION

Powder antifoams are used in a wide variety of foaming systems and in very small concentrations usually only a few parts per million. Foam can cause major inconvenience in industry resulting in damage to goods, loss of valuable products and reduced plant efficiency.

SILAF PDR is a free flowing powder containing silicone antifoam compound. This product has excellent long lasting foam control in Industrial application. eg. Dry flowable Agrichemicals, wettable Agrochemical powders, cement admixtures, patch and repair in concrete formulations.

SILAF PDR is a specially formulated product that it used for various applications in different industries. It is a versatile product that combines stability with excellent defoaming action. Silicone defoamers are generally preferred for better stability and more lasting defoaming power in very small concentrations. **SILAF PDR** is extremely cost effective, as it is designed to work efficiently and economically.

GENERAL CHARACTERISTICS*

Appearance : White free flowing powder.
Density (g/l) uncompressed : 700 to 900
Active content : 15%

*These values are not intended for preparing specifications. Specification writers may please contact OTCPL before writing specifications on these products.

SPECIAL FEATURES:

- Highly effective in foam control.
- Outstanding versatility, effective in most.
- Foaming systems.
- Low addition levels.
- Extremely stable, both on storage and in the foaming system itself.
- Readily compounded with other powdered formulations.
- Easy dispersibility in aqueous media.
- Bio-acceptable and eco-friendly.

INSTRUCTIONS FOR USE

SILAF PDR can be used by incorporating in the Agrochemicals. Suggested starting dosage is in the range of 0.5 - 2.0%. However, the exact dosage has to be determined by the user by conducting actual trials as foaming conditions are unique to each system..

HANDLING AND SAFETY

Material safety data sheets are available upon request from OTCPL.

OM TEX CHEM PVT. LTD.

Plot No. 243/244, Jawahar Co-op. Ind. Estate, Village Kamothe, Kalamboli, Tal. Panvel, Dist. Raigad, Navi Mumbai - 410 209.
Tel.: 022 6455 3516/21 Fax No. : 022 2500 2155 E-mail : omtexchem@vsnl.net / omtexchem@mtnl.net.in / omtexchem@gmail.com
Web : www.omtexchem.com



Technical Information

STORAGE WARRANTY PERIOD

To ensure safety, the following conditions are recommended:

Keep the original containers closed at a temperature of around 25°C.

Seal the containers properly during intervals when not in use.

When stored in original, sealed containers at or below 25°C, **SILAF PDR** has no known limits on shelf life.

The warranty period is 12 months from the date of shipment if stored in the original unopened container as dictated above.

PACKING AND AVAILABILITY

Available in 50kgs HDPE containers.

IMPORTANT

OTCPL warrants only that its product will meet its specifications. OTCPL'S liability is limited to the refund of purchase price or replacement of the product. OTCPL will not be responsible for incidental or consequential damages of any kind. It is the user's responsibility to determine the suitability of use.

Issue : Tentative

Issue date : 25/07/03

OM TEX CHEM PVT. LTD.

Plot No. 243/244, Jawahar Co-op. Ind. Estate, Village Kamothe, Kalamboli, Tal. Panvel, Dist. Raigad, Navi Mumbai - 410 209.
Tel.: 022 6455 3516/21 Fax No. : 022 2500 2155 E-mail : omtexchem@vsnl.net / omtexchem@mtnl.net.in / omtexchem@gmail.com
Web : www.omtexchem.com