fontforge.github.com

- Download
  - For each: Win, OS X, GNU+Linux, VMS
  - From a Pre-built package
  - From source
    - Before you build
    - Dependencies
    - Patches
    - Build
    - Install
    - desktop integration
  - Uninstall
- Tutorial
  - Type Design Intro + Workflow
    - Starting FF + crash recovery
    - Brief tour of interface
    - Editor and Type Terminology
    - Encodings
  - Make a new font
    - Drawing vectors
    - Building letters
    - Metrics: spacing, kerning
    - PS Hinting
    - Testing
    - Names
    - OT Features
    - Generating Font for use
  - Making families
    - Style Functions
    - Interpolation
    - MM
  - Bitmap Fonts
    - TT Hinting
- Documentation
  - Interface
    - Windows
    - Menus
    - Hot Keys
    - CLI Commands
  - Customizing
    - Files used by FontForge
    - Preferences
    - Themes (X resources)
    - Icons
    - Hot Keys
  - Scripting
    - Python
    - Native
    - Overview
    - Tutorial
    - Commands
    - Using FF with TEX
  - Developing
    - SFD Format
    - Internals
      - Sourcefile Overview
      - Code Style
      - Editor tools
      - Plugins
      - FF bezier curves
      - FF Math
    - Building packages
      - Debian
      - Windows
      - MacOSX
      - Fedora
  - Companion Programs
    - fontlint
    - sfddiff
    - fontimage
    - acorn2sfd
    - random font utilities
    - Related tools
  - Reference
    - Glossary of typographic terms
    - Font formats
    - Unicode
    - OpenType
    - Libre font development efforts
    - Bibliography
- About
  - FAQ
  - Screenshots (key features)
  - Donate
  - Volunteer
  - The Project
    - License
    - Acknowlegements
    - Known bugs
    - Lacks/Things Missing
    - History
    - Changelog
  - This site
    - Contributors
    - Site index
    - Site map