	Name	▽	Instance ID	Instance state	▽	Instance type	▽	Status check	Alarm status		Availability Zone	▽	Public
☑	sprints		i-00a57ce7fa1dea9a8	⊘ Running	🔍🔍	t2.micro		⊘ 2/2 checks passed	No alarms	+	eu-central-1a		–

=

Instance: i-00a57ce7fa1dea9a8 (sprints)   ⚙ ✕

Details | Security | Networking | Storage | Status checks | Monitoring | Tags

▼ Instance summary Info

Instance ID 🗗 i-00a57ce7fa1dea9a8 (sprints)	Public IPv4 address 🗗 3.121.114.160 | open address 🔗	Private IPv4 addresses 🗗 10.0.0.116
IPv6 address –	Instance state ⊘ Running	Public IPv4 DNS –
Hostname type IP name: ip-10-0-0-116.eu-central-1.compute.internal	Private IP DNS name (IPv4 only) 🗗 ip-10-0-0-116.eu-central-1.compute.internal	
Answer private resource DNS name	Instance type	Elastic IP addresses

Edit user data Info

Instance ID

🗗 i-00a57ce7fa1dea9a8 (sprints)

Current user data
User data currently associated with this instance

```
#!/bin/bash
sudo apt update -y
sudo apt install  apache2 -y
sudo systemctl start apache2
sudo systemctl enable apache2
```

🗗 Copy user data

ⓘ To edit your instance's user data you first need to stop your instance.

System log

Review system log for instance i-00a57ce7fa1dea9a8 as of Fri Dec 30 2022 19:48:32 GMT+0200 (Eastern European Standard Time)

[Copy log]

```
[   34.923310] cloud-init[1193]: The following additional packages will be installed:
[   34.931534] cloud-init[1193]:   apache2-bin apache2-data apache2-utils libapr1 libaprutil1
[   34.943662] cloud-init[1193]:   libaprutil1-dbd-sqlite3 libaprutil1-ldap libjansson4 liblua5.2-0 ssl-cert
[   34.951877] cloud-init[1193]: Suggested packages:
[   34.955908] cloud-init[1193]:   apache2-doc apache2-suexec-pristine | apache2-suexec-custom www-browser
[   34.966913] cloud-init[1193]:   openssl-blacklist
[   35.034829] cloud-init[1193]: The following NEW packages will be installed:
[   35.042895] cloud-init[1193]:   apache2 apache2-bin apache2-data apache2-utils libapr1 libaprutil1
[   35.055928] cloud-init[1193]:   libaprutil1-dbd-sqlite3 libaprutil1-ldap libjansson4 liblua5.2-0 ssl-cert
[   35.090800] cloud-init[1193]: 0 upgraded, 11 newly installed, 0 to remove and 18 not upgraded.
[   35.140960] cloud-init[1193]: Need to get 1867 kB of archives.
[   35.145756] cloud-init[1193]: After this operation, 8095 kB of additional disk space will be used.
[   35.153648] cloud-init[1193]: Get:1 http://eu-central-1.ec2.archive.ubuntu.com/ubuntu focal/main amd64 libapr1 amd64 1.6.5-1ubuntu1 [91.4 kB]
[   35.163824] cloud-init[1193]: Get:2 http://eu-central-1.ec2.archive.ubuntu.com/ubuntu focal/main amd64 libaprutil1 amd64 1.6.1-4ubuntu2 [84.7 kB]
[   35.176026] cloud-init[1193]: Get:3 http://eu-central-1.ec2.archive.ubuntu.com/ubuntu focal/main amd64 libaprutil1-dbd-sqlite3 amd64 1.6.1-4ubuntu2 [10.5
[   35.195935] cloud-init[1193]: Get:4 http://eu-central-1.ec2.archive.ubuntu.com/ubuntu focal/main amd64 libaprutil1-ldap amd64 1.6.1-4ubuntu2 [8736 B]
[   35.211950] cloud-init[1193]: Get:5 http://eu-central-1.ec2.archive.ubuntu.com/ubuntu focal/main amd64 libjansson4 amd64 2.12-1build1 [28.9 kB]
[   35.223480] cloud-init[1193]: Get:6 http://eu-central-1.ec2.archive.ubuntu.com/ubuntu focal/main amd64 liblua5.2-0 amd64 5.2.4-1.1build3 [106 kB]
[   35.239921] cloud-init[1193]: Get:7 http://eu-central-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 apache2-bin amd64 2.4.41-4ubuntu3.12 [1181
[   35.255909] cloud-init[1193]: Get:8 http://eu-central-1.ec2.archive.ubuntu.com/ubuntu focal-updates/main amd64 apache2-data all 2.4.41-4ubuntu3.12 [159 kB
```

For boot or networking issues, use the EC2 serial console for troubleshooting. Choose the **Connect** button to start a session.

Apache2 Ubuntu Default Page

It works!

This is the default welcome page used to test the correct operation of the Apache2 server after installation on Ubuntu systems. It is based on the equivalent page on Debian, from which the Ubuntu Apache packaging is derived. If you can read this page, it means that the Apache HTTP server installed at this site is working properly. You should **replace this file** (located at /var/www/html/index.html) before continuing to operate your HTTP server.

If you are a normal user of this web site and don't know what this page is about, this probably means that the site is currently unavailable due to maintenance. If the problem persists, please contact the site's administrator.

Configuration Overview

Ubuntu's Apache2 default configuration is different from the upstream default configuration, and split into several files optimized for interaction with Ubuntu tools. The configuration system is **fully documented in /usr/share/doc/apache2/README.Debian.gz**. Refer to this for the full documentation. Documentation for the web server itself can be found by accessing the **manual** if the apache2-doc package was installed on this server.

The configuration layout for an Apache2 web server installation on Ubuntu systems is as follows:

```
/etc/apache2/
|-- apache2.conf
|       `--  ports.conf
|-- mods-enabled
|       |-- *.load
|       `-- *.conf
|-- conf-enabled
|       `-- *.conf
|-- sites-enabled
|       `-- *.conf
```

- apache2.conf is the main configuration file. It puts the pieces together by including all remaining configuration files when starting up the web server.
- ports.conf is always included from the main configuration file. It is used to determine the listening ports for incoming connections, and this file can be customized anytime.