

A SMALL THEME FOR MODERN SLIDES

OWL, POS & External APIs

Reactive frontend, POS customization, XML-RPC

Weblearns Academy
weblearns@training.local
Odoo Full-Stack Developer Program
Lecture materials / July 2026



Agenda

- 1 OWL components, state, and templates
- 2 Patching, rpc, and custom widgets
- 3 POS buttons, popups, and translations
- 4 XML-RPC authentication and CRUD

TOC

1 A theme for modern talks

How this deck is taught

AWESOME-STYLE FRAME

Number rails, angled title art, and section slides are built in.

METROPOLIS DEFAULTS

Progress bars, block styles, and fonts are set from theme options.

DENSE TEACHING

Two-column frames pack objectives, examples, and pitfalls.

OWL

POS

RPC

XML-RPC

1 W01 – W05

OWL, POS & External APIs · teaching block 1

W01 OWL Architecture and Reactive Rendering

Objectives, key points, and lab target

Objectives

- Explain how OWL components render from reactive state.
 - Identify the role of services, registries, and templates.
 - Avoid direct DOM manipulation in normal component logic.
- ## Key points
- Reactive state changes trigger rerendering.
 - Templates describe UI; components own behavior.
 - Services centralize shared capabilities such as rpc and notifications.
 - Registries let addons extend the web client.
 - Direct DOM writes are a last resort.

Lab target

Create a small client action that increments a counter and logs when the component rerenders.

W01 OWL Architecture and Reactive Rendering

Teaching notes

OWL Architecture and Reactive Rendering belongs to the client-side layer where user intent, browser state, and Odoo services meet. OWL is Odoo's component framework and provides the reactive mental model behind many modern web client features. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Decide which component owns state, which services provide data, and which children only render props. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Use Component classes, static templates, setup methods, hooks, and the registry rather than creating global scripts. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Inspect rerenders, service calls, and asset loading in...
- In production, owl architecture and reactive rendering decisions affect performance, offline behavior, cache...

W01 OWL Architecture and Reactive Rendering

Example and pitfalls

Small reactive counter component

The state object is reactive, so incrementing value rerenders the template that displays it.

```
/** @odoo-module */

import { Component, useState } from "@odoo/owl";
import { registry } from "@web/core/registry";

export class TrainingCounter extends Component {
    static template = "training.TrainingCounter";

    setup() {
        this.state = useState({ value: 0 });
    }
    # ...
}
```

Common mistakes

- Changing random DOM nodes instead of changing component state.
- Putting global variables in asset files for shared state.
- Forgetting to register the component under the correct registry category.
- Treating OWL like jQuery with templates attached.

W01 OWL Architecture and Reactive Rendering

Extra patterns

OWL building blocks

- Component
- Template
- State
- Services

W02 Component Structure and Lifecycle Hooks

Objectives, key points, and lab target

Objectives

- Organize component files and templates cleanly.
- Use lifecycle hooks for setup and cleanup.
- Keep asynchronous loading predictable.

Key points

- setup is the main hook registration point.
- onWillStart can await data before first render.
- onMounted is safe for DOM-dependent integrations.
- onWillUnmount cleans up listeners and timers.
- Asset paths should mirror feature names.

Lab target

Build a dashboard component that loads statistics before render and refreshes every minute without leaking timers.

W02 Component Structure and Lifecycle Hooks

Teaching notes

Component Structure and Lifecycle Hooks belongs to the client-side layer where user intent, browser state, and Odoo services meet. Component structure matters because Odoo assets are bundled, upgraded, translated, and extended by other modules. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Keep JavaScript behavior, XML templates, and SCSS names aligned so another developer can find the complete feature quickly. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Use `setup` for hooks, `onWillStart` for initial asynchronous work, `onMounted` for browser-only integration, and `onWillUnmount` for cleanup. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Test navigation away from the component while requests are...
- In production, component structure and lifecycle hooks decisions affect performance, offline behavior, cache...

W02 Component Structure and Lifecycle Hooks

Example and pitfalls

Lifecycle with cleanup

The component loads initial data before rendering and removes its refresh timer when it is destroyed.

```
/** @odoo-module **/  
  
import { Component, onMounted, onWillStart, onWillUnmount } from "@web/core/utils/hooks";  
import { useService } from "@web/core/utils/hooks";  
  
export class CourseDashboard extends Component {  
    static template = "training.CourseDashboard";  
  
    setup() {  
        this.orm = useService("orm");  
    }  
    # ...  
}
```

Common mistakes

- Starting intervals without clearing them.
- Calling browser APIs before the component is mounted.
- Loading data in the constructor instead of setup hooks.
- Ignoring navigation races during slow RPC responses.

W03 useState, useRef, Events, and Props

Objectives, key points, and lab target

Objectives

- Use state for mutable component data.
- Use refs for specific DOM elements.
- Pass behavior through events and props cleanly.

Key points

- State is mutable and reactive inside the component.
- Props are inputs from the parent.
- Refs point to DOM nodes after render.
- Events should describe user intent.
- Derived values should not be duplicated unnecessarily.

Lab target

Create a child filter component that receives an onApply callback and prove it remains reusable in two parent components.

W03 useState, useRef, Events, and Props

Teaching notes

useState, useRef, Events, and Props belongs to the client-side layer where user intent, browser state, and Odoo services meet. OWL gives developers clear tools for local state, DOM references, parent-to-child data, and child-to-parent communication. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Before writing code, decide whether a value is owned by the component, passed by the parent, derived from services, or simply stored in the DOM. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Use useState for reactive values, useRef for controlled DOM access, props for inputs, and callback props or triggered events for outputs. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Verify that a child component still works when props change...
- In production, usestate, useref, events, and props decisions affect performance, offline behavior, cache invalidation,...

W03 useState, useRef, Events, and Props

Example and pitfalls

Filter input with ref and callback prop

The component owns the input text, calls the parent callback when applied, and uses a ref only to restore focus.

```
/** @odoo-module **/  
  
import { Component, useRef, useState } from "@odoo/owl"  
  
export class CourseFilter extends Component {  
  static template = "training.CourseFilter";  
  static props = { onApply: Function };  
  
  setup() {  
    this.state = useState({ text: "" });  
    # ...  
  }  
}
```

Common mistakes

- Mutating props directly.
- Using refs as general state storage.
- Passing large objects when a small prop would do.
- Creating event names that describe implementation instead of intent.

W04 QWeb XML Directives: t-if, t-foreach, and t-model

Objectives, key points, and lab target

Objectives

- Render conditional content in OWL XML templates.
- Loop over arrays safely with keys.
- Bind form controls with t-model where appropriate.

Key points

- Every t-foreach should have a stable t-key.
- t-if removes or inserts template branches.
- t-model is useful for simple local form values.
- Complex formatting belongs in component methods or getters.
- XML must remain valid and escaped.

Lab target

Write a template that lists courses, shows an empty state, and filters from a t-model input stored in component state.

W04 QWeb XML Directives: t-if, t-foreach, and t-model

Teaching notes

QWeb XML Directives: t-if, t-foreach, and t-model belongs to the client-side layer where user intent, browser state, and Odoo services meet. OWL templates use QWeb-style XML directives to describe dynamic browser UI. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Keep templates declarative: conditions should select presentation, loops should render prepared lists, and form bindings should update local state. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Use t-if for conditions, t-foreach with t-as and t-key for repeatable data, and t-model for simple two-way form input binding. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Test empty arrays, duplicate labels, and rapid typing...
- In production, qweb xml directives: t-if, t-foreach, and t-model decisions affect performance, offline behavior, cache...

W04 QWeb XML Directives: t-if, t-foreach, and t-model

Example and pitfalls

OWL template directives

The template handles search input, empty state, and stable list rendering with a key per course.

```
<templates xml:space="preserve">
  <t t-name="training.CourseList">
    <input t-ref="filterInput" t-model="state.query" />
    <p t-if="!state.courses.length">No courses found.</p>
    <ul>
      <li t-foreach="state.courses" t-as="course" t-key="course.id">
        <span t-esc="course.name"/>
        <span class="text-muted" t-esc="course.teacher"/>
      </li>
    </ul>
  </t>
# ...
```

Common mistakes

- Looping without t-key.
- Putting business queries inside template expressions.
- Forgetting XML escaping for comparison operators.
- Using t-model against props instead of local state.

W05 Custom Form Field Widgets

Objectives, key points, and lab target

Objectives

- Register a field widget in the web client.
- Respect standard field props and update behavior.
- Use widgets to improve editing without changing model semantics.

Key points

- Field widgets are registered in the fields registry.
- `props.value` is the current field value.
- `props.update` writes a new value to the record buffer.
- Support readonly mode explicitly.
- Widgets should not own persistent business state.

Lab target

Create a five-star rating widget for an integer field and test it in readonly and editable form modes.

W05 Custom Form Field Widgets

Teaching notes

Custom Form Field Widgets belongs to the client-side layer where user intent, browser state, and Odoo services meet. A custom field widget changes how one field is displayed or edited while keeping the model field as the source of truth. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Use a widget when the default field component is correct semantically but not expressive enough for the workflow. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Register the widget in the fields registry, accept standard props, and call `props.update` when the user changes the value. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Test readonly mode, required fields, invalid values, and...
- In production, custom form field widgets decisions affect performance, offline behavior, cache invalidation, and...

W05 Custom Form Field Widgets

Example and pitfalls

Rating field widget

The widget follows the standard field contract and updates the form record through props.update.

```
/** @odoo-module **/  
  
import { Component } from "@odoo/owl";  
import { registry } from "@web/core/registry";  
import { standardFieldProps } from "@web/views/fields/standard_field_props";  
  
export class RatingField extends Component {  
    static template = "training.RatingField";  
    static props = { ...standardFieldProps };  
  
    # ...
```

Common mistakes

- Writing directly to the server from the widget instead of using props.update.
- Ignoring readonly mode.
- Registering a widget with a generic key likely to collide.
- Supporting field types the component cannot handle.

2 W06 – W10

OWL, POS & External APIs · teaching block 2

W06 Overriding JavaScript Components with the Patch Utility

Objectives, key points, and lab target

Objectives

- Patch existing components narrowly.
- Call super behavior when extending methods.
- Minimize upgrade risk when overriding Odoo web code.

Key points

- Patch is powerful and should be narrow.
- Prefer public extension points first.
- Call super when preserving behavior matters.
- Version upgrades can break patches.
- Name modules and methods clearly for traceability.

Lab target

Patch a small controller method to emit a custom event, then remove the patch and confirm the rest of the feature is isolated.

W06 Overriding JavaScript Components with the Patch Utility

Teaching notes

Overriding JavaScript Components with the Patch Utility belongs to the client-side layer where user intent, browser state, and Odoo services meet. The patch utility is the preferred way to adjust existing JavaScript classes when registries or props are not enough. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Patch only the method or getter you need, and first ask whether a registry extension, service, or template inheritance would be safer. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Import the target class and patch it with a small object that adds or extends behavior while preserving upstream logic where required. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Test against the exact Odoo version and read upstream...
- In production, overriding javascript components with the patch utility decisions affect performance, offline behavior,...

W06 Overriding JavaScript Components with the Patch Utility

Example and pitfalls

Patch a method to add a training flag

The patch adds a small event before save while delegating the actual save behavior to the original controller.

```
/** @odoo-module **/  
  
import { patch } from "@web/core/utils/patch";  
import { FormController } from "@web/views/form/form_controller";  
  
patch(FormController.prototype, {  
  async saveButtonClicked(params = {}) {  
    this.env.bus.trigger("training:before-form-save", {  
      resModel: this.props.resModel,  
    });  
  }  
});  
  
# ...
```

Common mistakes

- Patching large methods by copying upstream source.
- Forgetting to call super when extending behavior.
- Using patch when a registry extension exists.
- Not reviewing patches during every major upgrade.

W07 RPC and ORM Services

Objectives, key points, and lab target

Objectives

- Use orm and rpc services appropriately.
- Call model methods from OWL components.
- Handle loading and errors cleanly.

Key points

- useService injects framework services.
- orm.call invokes model methods.
- rpc is useful for custom routes.
- Always represent loading and failure states.
- Server methods must still validate access.

Lab target

Replace a direct fetch call with orm.call and add a loading indicator plus a notification on failure.

W07 RPC and ORM Services

Teaching notes

RPC and ORM Services belongs to the client-side layer where user intent, browser state, and Odoo services meet. Odoo provides services so client code does not need to know every HTTP detail or session convention. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Use orm for model operations and rpc for custom endpoints or lower-level calls where the ORM service does not fit. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Inject services with `useService`, keep request code in explicit methods, and store loading or error state so the UI communicates what is happening. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Test server access rights, record rules, network failures,...
- In production, rpc and orm services decisions affect performance, offline behavior, cache invalidation, and upgrade...

W07 RPC and ORM Services

Example and pitfalls

Load dashboard data through orm

The component uses framework services and exposes loading and error feedback to users.

```
/** @odoo-module **/  
  
import { Component, useState } from "@odoo/owl";  
import { useService } from "@web/core/utils/hooks";  
  
export class TrainingDashboard extends Component {  
    static template = "training.TrainingDashboard";  
  
    setup() {  
        this.orm = useService("orm");  
    }  
    # ...  
}
```

Common mistakes

- Calling fetch directly for ORM work.
- Ignoring errors and leaving stale UI state.
- Trusting client parameters without server validation.
- Making one RPC call per row when a batched method would do.

W08 Custom Kanban and Dashboard OWL Views

Objectives, key points, and lab target

Objectives

- Design a dashboard as a client action or custom view.
- Register components in the correct registry.
- Keep dashboard data server-side and aggregated.

Key points

- Client actions are good for standalone dashboards.
- Custom views are deeper integrations with the view system.
- Aggregate on the server, render on the client.
- Use action tags and registries consistently.
- Dashboard cards should link to filtered records.

Lab target

Build a client action dashboard with three KPI cards and one card that opens a filtered course list.

W08 Custom Kanban and Dashboard OWL Views

Teaching notes

Custom Kanban and Dashboard OWL Views belongs to the client-side layer where user intent, browser state, and Odoo services meet. Dashboards should present decisions, exceptions, and navigation paths rather than becoming a second database browser. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Choose a client action for a standalone dashboard and a custom view only when it truly replaces how users inspect a model. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Register the component, define an action tag, load aggregated data from model methods, and keep cards reusable where possible. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Verify performance on realistic data because dashboards are...
- In production, custom kanban and dashboard owl views decisions affect performance, offline behavior, cache...

W08 Custom Kanban and Dashboard OWL Views

Example and pitfalls

Client action registration

The action tag connects the server-side `ir.actions.client` record to the OWL component.

```
/** @odoo-module **/  
  
import { registry } from "@web/core/registry";  
import { TrainingDashboard } from "../training_dashboard";  
  
registry.category("actions").add("training.dashboard", TrainingDashboard);  
  
// XML action  
// <record id="action_training_dashboard" model="ir.actions.client">  
//     <field name="name">Training Dashboard</field>  
# ...
```

Common mistakes

- Loading raw records in the browser and aggregating there.
- Creating dashboards without drill-down actions.
- Using a custom view when a client action is enough.
- Forgetting access rights on the server statistics method.

W09 POS Custom Buttons and Click Events

Objectives, key points, and lab target

Objectives

- Add a custom control button to a POS screen.
- Handle click events with OWL methods.
- Keep POS actions compatible with offline behavior.

Key points

- POS buttons should be screen-specific.
- Click handlers should be idempotent where possible.
- Offline behavior must be considered.
- Use POS registries and services instead of globals.
- User feedback must be immediate.

Lab target

Add a POS ProductScreen button that shows a notification and disable it when no order is active.

W09 POS Custom Buttons and Click Events

Teaching notes

POS Custom Buttons and Click Events belongs to the client-side layer where user intent, browser state, and Odoo services meet. POS extensions run in a high-speed operational UI where every button must be obvious and resilient. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Decide which screen owns the action and whether the feature can work offline or must warn the cashier that connectivity is required. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Register a button component, attach it to the target POS screen, and handle click events with methods that use POS services or models. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Test with barcode scanning, touch screens, and rapid...
- In production, pos custom buttons and click events decisions affect performance, offline behavior, cache invalidation,...

W09 POS Custom Buttons and Click Events

Example and pitfalls

Simple POS control button

The button is added to the ProductScreen and handles the click through a component method.

```
/** @odoo-module **/  
  
import { Component } from "@odoo/owl";  
import { ProductScreen } from "@point_of_sale/app/screens/product_screen/product_screen";  
  
export class CourseInfoButton extends Component {  
    static template = "training.CourseInfoButton";  
  
    onClick() {  
        this.env.services.notification.add("Training mode is active.", {  
# ...
```

Common mistakes

- Adding a button globally when it belongs to one screen.
- Not debouncing expensive click operations.
- Assuming a cashier has back-office permissions.
- Ignoring offline mode when the click needs the server.

W10 Hiding POS Buttons Safely

Objectives, key points, and lab target

Objectives

- Hide or show POS UI based on configuration.
- Distinguish visibility from authorization.
- Keep hidden actions protected server-side.

Key points

- Visibility improves workflow but is not security.
- Button conditions can read POS configuration.
- Sensitive methods need server checks.
- Different POS configs may show different controls.
- Use clear disabled feedback when possible.

Lab target

Add a Boolean POS configuration field that controls a custom button and prove the server method still rejects unauthorized calls.

W10 Hiding POS Buttons Safely

Teaching notes

Hiding POS Buttons Safely belongs to the client-side layer where user intent, browser state, and Odoo services meet. Hiding a POS button can simplify cashier flow, but it must not be confused with security. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Decide whether the control is hidden because it is irrelevant, disabled because a condition is missing, or forbidden because the user lacks a role. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Use button conditions, configuration values loaded into POS, and server-side validation for any sensitive operation. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Test every cashier role and POS configuration because a...
- In production, hiding pos buttons safely decisions affect performance, offline behavior, cache invalidation, and...

W10 Hiding POS Buttons Safely

Example and pitfalls

Configuration-based button condition

The button appears only for POS configurations where the feature is enabled.

```
ProductScreen.addControlButton({  
  component: CourseInfoButton,  
  condition() {  
    const config = this.pos.config;  
    return Boolean(config.module_training && config.show_training_button);  
  },  
});
```

Common mistakes

- Treating a hidden button as access control.
- Hard-coding user ids in JavaScript.
- Forgetting to load the configuration field into POS data.
- Making the button disappear without explaining why.

3 W11 – W15

OWL, POS & External APIs · teaching block 3

W11 POS Popups and Dialog Flow

Objectives, key points, and lab target

Objectives

- Show confirmation and input popups in POS.
- Handle popup results correctly.
- Design cashier-friendly dialog flows.

Key points

- Use popups for short high-value interruptions.
- Always handle cancel and confirm paths.
- Do not put long forms in POS popups.
- Keep focus behavior cashier-friendly.
- Validate data after the popup closes.

Lab target

Create a confirmation popup that asks before applying a manager discount or clearing an order.

W11 POS Popups and Dialog Flow

Teaching notes

POS Popups and Dialog Flow belongs to the client-side layer where user intent, browser state, and Odoo services meet. POS popups interrupt the fastest workflow in Odoo, so they must be short, intentional, and recoverable. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Use a popup when the cashier needs confirmation, small input, or a warning that cannot be ignored before continuing. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Call the dialog or popup service, await the result where the framework supports it, and update the order only after the user confirms. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Test keyboard, touch, barcode scanner focus, and cancel...
- In production, pos popups and dialog flow decisions affect performance, offline behavior, cache invalidation, and...

W11 POS Popups and Dialog Flow

Example and pitfalls

Confirmation before clearing order

The destructive action is performed only from the confirmation callback.

```
async clearCurrentOrder() {
  const order = this.pos.get_order();
  if (!order || !order.get_orderlines().length) {
    return;
  }
  this.dialog.add(ConfirmationDialog, {
    title: "Clear order",
    body: "Remove all current order lines?",
    confirm: () => {
      for (const line of [...order.get_orderlines()]) {
        # ...
      }
    }
  });
}
```

Common mistakes

- Using a popup for information that could be a non-blocking notification.
- Forgetting the cancel path.
- Mutating orders before the user confirms.
- Creating popups that require too much typing at checkout.

W12 JavaScript Translations

Objectives, key points, and lab target

Objectives

- Mark JavaScript strings for translation.
- Avoid concatenation that breaks translators' context.
- Test translated POS and web screens.

Key points

- Use `_t` for user-facing JavaScript strings.
- Translate complete messages, not fragments.
- Avoid concatenation with translated text.
- Test labels in narrow screens.
- Do not translate technical keys or registry names.

Lab target

Mark three JavaScript labels and one notification for translation, export terms, and verify them in another language.

W12 JavaScript Translations

Teaching notes

JavaScript Translations belongs to the client-side layer where user intent, browser state, and Odoo services meet. JavaScript translations matter because OWL and POS features often introduce user-facing labels outside Python and XML fields. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Write complete sentences for translators and pass variables as placeholders rather than building messages from fragments. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Import `_t` or the appropriate translation helper, mark strings in components, and export translation terms through the normal Odoo i18n process. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Test in a secondary language and look for layout overflow,...
- In production, javascript translations decisions affect performance, offline behavior, cache invalidation, and upgrade...

W12 JavaScript Translations

Example and pitfalls

Translated notification

The full sentence is translatable and the course name is inserted as a placeholder.

```
/** @odoo-module **/  
  
import { _t } from "@web/core/l10n/translation";  
  
this.notification.add(  
    _t("Course %(course)s was added to the training order.", {  
        course: course.name,  
    }),  
    { type: "success" }  
);
```

Common mistakes

- Concatenating translated fragments.
- Forgetting strings inside POS-only components.
- Translating technical identifiers.
- Not testing how long translated labels affect layout.

W13 POS RPC and Server Synchronization

Objectives, key points, and lab target

Objectives

- Call server methods from POS safely.
- Respect offline and cashier permissions.
- Batch data where possible.

Key points

- Prefer session-loaded data for frequently used reference data.
- Use RPC only when freshness is required.
- Batch calls to avoid checkout delays.
- Handle offline failures explicitly.
- Server methods must check permissions.

Lab target

Implement one POS RPC method for live data and document exactly what the cashier sees when the network is down.

W13 POS RPC and Server Synchronization

Teaching notes

POS RPC and Server Synchronization belongs to the client-side layer where user intent, browser state, and Odoo services meet. POS RPC is tempting for every feature, but online calls can slow checkout and fail during network interruptions. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Decide whether data must be loaded at session start, cached in POS, sent with the order, or fetched on demand. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Use services to call model methods, batch requests, and show clear failure feedback when the POS must be online for the operation. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Test disconnected network behavior and low permissions...
- In production, pos rpc and server synchronization decisions affect performance, offline behavior, cache invalidation,...

W13 POS RPC and Server Synchronization

Example and pitfalls

Fetch live loyalty balance

The method calls the server only when a partner exists and gives a cashier-friendly warning on failure.

```
async getLoyaltyBalance(partnerId) {  
  if (!partnerId) {  
    return 0;  
  }  
  try {  
    return await this.orm.call(  
      "training.loyalty",  
      "pos_get_balance",  
      [partnerId],  
      { context: this.pos.user.context }  
    );  
  }  
  # ...  
}
```

Common mistakes

- Making one RPC call per product scan.
- Blocking payment on optional online data.
- Ignoring the POS user's access rights.
- Not deciding what happens offline.

W14 Rendering Dynamic POS Data

Objectives, key points, and lab target

Objectives

- Load additional fields into POS data.
- Render dynamic data on products or order lines.
- Keep display values synchronized with order state.

Key points

- Session-loaded data is fast but can become stale.
- Order-line data should be stored if needed later.
- Templates should render prepared values.
- Reload and restore behavior must be tested.
- Do not overload product tiles with too much data.

Lab target

Load a training_level field into POS products and render it on the product card with an empty-state fallback.

W14 Rendering Dynamic POS Data

Teaching notes

Rendering Dynamic POS Data belongs to the client-side layer where user intent, browser state, and Odoo services meet. Dynamic POS rendering lets cashiers see availability, warnings, course metadata, or customer-specific information at the point of action. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. First decide whether the data is static for the session, changes during the session, or belongs on the order for accounting and audit. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Load required fields through POS data loaders or model extensions, store display-ready values on POS models, and render them through OWL templates. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Test reloads, order restore, and product cache updates...
- In production, rendering dynamic pos data decisions affect performance, offline behavior, cache invalidation, and...

W14 Rendering Dynamic POS Data

Example and pitfalls

Product tile showing course level

The template extension displays an extra product field only when the POS product data includes it.

```
<t t-name="training.ProductCard" t-inherit="point_of_sale.ProductCard" t-inherits="point_of_sale.ProductCard"
  <xpath expr="//div[hasclass('product-name')]" position="before"
    <div t-if="props.product.training_level" class="text-center"
      <t t-esc="props.product.training_level" />
    </div>
  </xpath>
</t>
```

Common mistakes

- Rendering fields that were never loaded into POS.
- Showing stale stock or capacity without a refresh policy.
- Putting audit-critical values only in the UI.
- Making product cards unreadable with too many badges.

W15 Clearing Order Lines and Mutating POS Orders

Objectives, key points, and lab target

Objectives

- Mutate current orders through POS model APIs.
- Avoid unsafe direct array changes.
- Protect destructive actions with confirmation.

Key points

- Use order APIs, not internal array mutation.
- Copy line arrays before removing while iterating.
- Confirm destructive actions.
- Recompute totals through framework behavior.
- Test special line types.

Lab target

Add a clear-order control that confirms first, removes lines through the order API, and verifies totals return to zero.

W15 Clearing Order Lines and Mutating POS Orders

Teaching notes

Clearing Order Lines and Mutating POS Orders belongs to the client-side layer where user intent, browser state, and Odoo services meet. POS order mutation must use framework methods so totals, taxes, discounts, and UI state remain consistent. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Before clearing or changing lines, decide whether the action is reversible and whether a manager confirmation is required. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Iterate over a copy of the current order lines and remove them with the POS order API rather than splicing internal arrays. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Test lines with discounts, lots, taxes, notes, and combo...
- In production, clearing order lines and mutating pos orders decisions affect performance, offline behavior, cache...

W15 Clearing Order Lines and Mutating POS Orders

Example and pitfalls

Clear all order lines safely

The method iterates over a copy and delegates removal to the POS order API.

```
clearOrderLines(order) {  
  if (!order) {  
    return;  
  }  
  for (const line of [...order.get_orderlines()]) {  
    order.removeOrderline(line);  
  }  
  this.notification.add("The order was cleared.", { type: "success" });  
}
```

Common mistakes

- Splicing order.orderlines directly.
- Removing lines while iterating over the live array.
- Skipping confirmation for destructive cashier actions.
- Forgetting special cases such as lot-tracked products.

4 W16 – W20

OWL, POS & External APIs · teaching block 4

W16 XML-RPC Integration Fundamentals

Objectives, key points, and lab target

Objectives

- Authenticate with Odoo over XML-RPC.
- Call model methods through `execute_kw`.
- Understand database, uid, password, model, method, and args.

Key points

- Authenticate on `/xmlrpc/2/common`.
- Call models through `/xmlrpc/2/object execute_kw`.
- Use service users with limited groups.
- XML-RPC respects Odoo access rules.
- Never hard-code production passwords in code.

Lab target

Create a script that authenticates over XML-RPC and reads the first ten confirmed courses with only three fields.

W16 XML-RPC Integration Fundamentals

Teaching notes

XML-RPC Integration Fundamentals belongs to the client-side layer where user intent, browser state, and Odoo services meet. XML-RPC remains a practical integration interface for scripts, legacy systems, and training labs. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Design integrations around explicit service users with narrow groups, not administrator credentials copied into scripts. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Authenticate against common, then call `object.execute_kw` with model, method, positional args, and keyword options such as fields and limit. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Verify access rights and record rules with the same service...
- In production, xml-rpc integration fundamentals decisions affect performance, offline behavior, cache invalidation,...

W16 XML-RPC Integration Fundamentals

Example and pitfalls

Python XML-RPC login and search_read

The script authenticates once and calls search_read as the integration user.

```
import xmlrpc.client

url = "https://odoo.example.com"
db = "prod"
username = "integration@example.com"
password = "change-me"

common = xmlrpc.client.ServerProxy(f"{url}/xmlrpc/2/common")
uid = common.authenticate(db, username, password, {})

# ...
```

Common mistakes

- Using the admin account for integrations.
- Forgetting that record rules affect API results.
- Fetching all fields and all records by default.
- Logging passwords or full credential URLs.

W17 External API Authentication

Objectives, key points, and lab target

Objectives

- Select an authentication pattern for external integrations.
- Store secrets outside source code.
- Validate callbacks and inbound requests.

Key points

- Do not commit API credentials.
- Use least-privilege provider scopes.
- Validate webhook signatures when available.
- Handle token expiry deliberately.
- Log identifiers, not secrets.

Lab target

Design an authentication plan for one outbound API and one inbound webhook, including where each secret is stored.

W17 External API Authentication

Teaching notes

External API Authentication belongs to the client-side layer where user intent, browser state, and Odoo services meet. External APIs add another trust boundary around Odoo, so authentication design is part of the feature, not deployment cleanup. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Choose API keys, OAuth2, signed webhooks, or basic authentication based on the provider and risk of the data being exchanged. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Store secrets in system parameters, environment variables, or a secret manager, and wrap outbound calls in a service class or model method. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Test expired credentials, revoked tokens, replayed webhooks,...
- In production, external api authentication decisions affect performance, offline behavior, cache invalidation, and...

W17 External API Authentication

Example and pitfalls

Signed outbound request helper

The token is read from configuration at runtime and never appears in the source file.

```
import requests
from odoo import models

class TrainingExternalClient(models.AbstractModel):
    _name = "training.external.client"
    _description = "Training External API Client"

    def _headers(self):
        token = self.env["ir.config_parameter"].sudo().get_param("training.api_token")
    # ...
```

Common mistakes

- Committing secrets to the repository.
- Using broad OAuth scopes because they are easier during testing.
- Accepting inbound webhooks without signature validation.
- Logging Authorization headers during debugging.

W18 Fetch and Export Workflows with XML-RPC

Objectives, key points, and lab target

Objectives

- Export selected records over XML-RPC.
- Paginate large result sets.
- Make fetch jobs restartable.

Key points

- Export only required fields.
- Paginate results instead of fetching everything.
- Use deterministic ordering.
- Persist checkpoints for restartability.
- Design for duplicates or idempotent downstream writes.

Lab target

Write a paginated export for enrollments and simulate a restart after two batches.

W18 Fetch and Export Workflows with XML-RPC

Teaching notes

Fetch and Export Workflows with XML-RPC belongs to the client-side layer where user intent, browser state, and Odoo services meet. Export integrations fail in production when they assume the dataset is small and the network is perfect. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Define the export domain, fields, ordering, and checkpoint strategy before writing the loop. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Use search with offset or keyset-style domains, read only required fields, and persist the last successful checkpoint outside the transient process. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Verify duplicates, skipped records, and interrupted runs by...
- In production, fetch and export workflows with xml-rpc decisions affect performance, offline behavior, cache...

W18 Fetch and Export Workflows with XML-RPC

Example and pitfalls

Paged XML-RPC export

The loop exports in deterministic batches instead of loading the complete table at once.

```
offset = 0
batch_size = 100
while True:
    rows = models.execute_kw(
        db, uid, password,
        "training.enrollment", "search_read",
        [[["write_date", ">=", "2026-01-01 00:00:00"]]],
        {
            "fields": ["id", "student_id", "course_id", "state", "write_date"],
            "order": "id",
        }
    )
    # ...
```

Common mistakes

- Exporting all records into memory.
- Using no order while paginating.
- Not handling retries or partial downstream failure.
- Exporting display names when stable ids are required.

W19 CRUD Operations over XML-RPC

Objectives, key points, and lab target

Objectives

- Create, read, update, and delete records through XML-RPC.
- Pass relational field commands correctly.
- Respect constraints and security during API writes.

Key points

- create returns the new record id.
- write returns True when the update succeeds.
- unlink deletes records if access and rules allow it.
- Relational commands use tuple-like command lists.
- Onchange behavior is not a substitute for server validation.

Lab target

Create a course and enrollment over XML-RPC, update one field, and attempt an invalid write to confirm constraints are enforced.

W19 CRUD Operations over XML-RPC

Teaching notes

CRUD Operations over XML-RPC belongs to the client-side layer where user intent, browser state, and Odoo services meet. XML-RPC CRUD uses the same ORM methods that server code uses, so constraints, onchange gaps, access rights, and record rules all matter. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. Design write payloads from the model contract, not from the current form layout, because UI-only onchange logic may not run during API calls. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Use create, write, unlink, search_read, and relational command lists for one2many or many2many fields when needed. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Verify bad payloads, duplicate submissions, and permission...
- In production, crud operations over xml-rpc decisions affect performance, offline behavior, cache invalidation, and...

W19 CRUD Operations over XML-RPC

Example and pitfalls

Create and update enrollment

The API creates a draft enrollment and then updates its state through normal ORM security and constraints.

```
enrollment_id = models.execute_kw(
    db, uid, password,
    "training.enrollment", "create",
    [{
        "student_id": student_id,
        "course_id": course_id,
        "state": "draft",
    }],
)

# ...
```

Common mistakes

- Expecting form onchange methods to run during create.
- Sending display names instead of database ids for many2one fields.
- Deleting records with unlink when archiving would preserve audit history.
- Retrying creates without an external idempotency key.

W20 Postman Authentication and CRUD Testing

Objectives, key points, and lab target

Objectives

- Use Postman to document and test API calls.
- Authenticate against Odoo endpoints deliberately.
- Build repeatable CRUD request collections.

Key points

- Use environments for base URL and credentials.
- Store ids from responses for later requests.
- Add negative authorization tests.
- Do not export real secrets in shared collections.
- Document request purpose in the collection.

Lab target

Build a Postman collection with login, search_read, create, write, and negative-access requests using environment variables only.

W20 Postman Authentication and CRUD Testing

Teaching notes

Postman Authentication and CRUD Testing belongs to the client-side layer where user intent, browser state, and Odoo services meet. Postman is useful for training and integration discovery because it makes request shape, authentication, and responses visible. Senior developers treat JavaScript changes as product behavior, not decoration, because a small patch can alter every user session that loads the bundle.

The design starts with ownership of state and boundaries. For Odoo JSON-RPC or controller endpoints, define environment variables for base URL, database, credentials, token, and record ids. Keep components small, pass data through props where possible, and call services at clear workflow edges instead of scattering RPC calls through templates.

Implementation should follow Odoo's asset, registry, service, and template patterns. Create a collection that authenticates, stores returned values in variables, and then performs create, read, update, and delete or archive requests. Favor explicit imports, named templates, stable registry keys, and patches that are narrow enough to survive upstream changes.

Also remember

- Verification requires more than refreshing the page once. Verify negative cases such as missing auth, wrong database,...
- In production, postman authentication and crud testing decisions affect performance, offline behavior, cache...

W20 Postman Authentication and CRUD Testing

Example and pitfalls

JSON-RPC body for search_read

The request uses Postman environment variables so the same collection can run against staging or local databases.

```
{
  "jsonrpc": "2.0",
  "method": "call",
  "params": {
    "service": "object",
    "method": "execute_kw",
    "args": [
      "{{db}}",
      {{uid}},
      "{{password}}",
      # ...
    ]
  }
}
```

Common mistakes

- Exporting collections with real passwords.
- Hard-coding record ids that differ by database.
- Testing only successful CRUD operations.
- Confusing web session authentication with integration authentication.

W20 Postman Authentication and CRUD Testing

Extra patterns

Postman collection sections

-

Σ You should now be able to...

Section wrap-up

- W01 OWL Architecture and Reactive Rendering
- W02 Component Structure and Lifecycle Hooks
- W03 useState, useRef, Events, and Props
- W04 QWeb XML Directives: t-if, t-foreach, and t-model
- W05 Custom Form Field Widgets
- W06 Overriding JavaScript Components with the Patch Utility
- W07 RPC and ORM Services
- W08 Custom Kanban and Dashboard OWL Views
- Complete every lab before the next section
- Keep a command/error journal
- Prefer disposable databases for experiments
- Re-read pitfalls before production changes

OWL

POS

RPC

XML-RPC

NEXT STEP

Complete the section labs

Open the next presentation deck

Section 06 · OWL / POS / API

