DATOMS®

connecting machines

Datoms Public API

Endpoint Reference

Version – v4

Last updated: 16 Sep 2026

Phoenix Robotix Pvt. Ltd.

© 2026 Phoenix Robotix Pvt. Ltd.

Table of Contents

List Assets **2**
- Endpoint 2
- Authentication 2
- Path Parameters 2
- Query Parameters 2
- Rate Limiting 3
- Response — 200 OK 3
- Error Responses 4
- Code Samples 5

Get Latest Telemetry Data for an Asset **6**
- Endpoint 6
- Authentication 6
- Path Parameters 6
- Rate Limiting 6
- Response — 200 OK 7
- Error Responses 8
- Code Samples 8

Bulk Fetch Latest Asset Telemetry **10**
- Endpoint 10
- Authentication 10
- Path Parameters 11
- Request Body 11
- Rate Limiting 11
- Response — 200 OK 12
- Error Responses 14
- Code Samples 15

© 2026 Phoenix Robotix Pvt. Ltd.

List Assets

Returns a paginated list of assets (machines) within an organization. This is a plain listing — use the page and limit query parameters to walk the result set. There are no search, filter, sort, or field-selection parameters.

Each asset record carries the core fields `(id, name, created_at)` plus an `asset_info` object holding the asset's nameplate metadata (make, model, serial number, DG rated power, fuel tank capacity). The response includes a pagination object describing the full result set.

Endpoint

```
GET /v4/orgs/{orgId}/assets
```

Base URL (Production): `https://api.datoms.io`

Full request URL:
`https://api.datoms.io/v4/orgs/{orgId}/assets?page=1&limit=20`

Authentication

Every request must be authenticated using a Bearer token, passed in the Authorization header. Obtain it from the Datoms login API or from your administrator.

Request headers

Header	Required	Description
`Authorization`	Yes	Bearer authentication. Format: Bearer <token>.

Path Parameters

Parameter	Type	Required	Description
`orgId`	string	Yes	Organization ID (numeric). Enforces multi-tenancy — only data belonging to this organization is accessible. Example: 3001.

Query Parameters

Parameter	Type	Default	Description
`page`	integer	1	Page number (1-indexed). Minimum: 1.
`limit`	integer	20	Items per page. Minimum: 1, Maximum: 1000.

© 2026 Phoenix Robotix Pvt. Ltd.

Rate Limiting

This endpoint uses the standard rate-limit tier: a per-IP limit of 60 requests per 60-second window. The current limit state is reported in the response headers below.

Rate-limit headers returned: `X-RateLimit-Limit, X-RateLimit-Remaining, X-RateLimit-Reset, Retry-After`

Response — 200 OK

Returns a paginated list of assets for the requested page.

Response body fields

Field	Type	Description
`success`	boolean	Always true for a successful (2xx) response.
`status`	string	Always "success" for a successful response.
`data`	array	Assets in the org for the requested page. Each record carries the core fields (id, name, created_at) plus asset_info (see below).
`data[].id`	string	Asset identifier. Currently the legacy integer id (returned as a string); net-new assets without a legacy id fall back to the asset UUID. Example: 36390.
`data[].name`	string	Human-readable asset name. Example: Generator Set A.
`data[].created_at`	string (date-time)	When the asset was created. ISO 8601, UTC. Example: 2026-01-15T09:30:00Z.
`data[].asset_info`	object	Nameplate metadata from the asset's stored config (config.asset_info). Returned as {} when not set.
`data[].asset_info.make`	string	Manufacturer / make. Example: Cummins.
`data[].asset_info.model`	string	Model designation. Example: C500.
`data[].asset_info.sl_no`	string	Serial number. Example: SN-00421.
`data[].asset_info.kva`	string	DG rated power (kVA). Example: 500.
`data[].asset_info.capacity`	string	Fuel tank capacity in litres (L). Example: 990.
`pagination`	object	Pagination metadata for the result set.
`pagination.total`	integer	Total number of matching assets. Example: 47.
`pagination.page`	integer	Current page number. Example: 1.
`pagination.limit`	integer	Items per page. Example: 20.

© 2026 Phoenix Robotix Pvt. Ltd.

Field	Type	Description
`pagination.total_pages`	integer	Total number of pages. Example: 3.

Sample response

```
{
  "success": true,
  "status": "success",
  "data": [
    {
      "id": "36390",
      "name": "Generator Set A",
      "created_at": "2026-01-15T09:30:00Z",
      "asset_info": {
        "make": "Cummins",
        "model": "C500",
        "sl_no": "SN-00421",
        "kva": "500",
        "capacity": "990"
      }
    }
  ],
  "pagination": {
    "total": 47,
    "page": 1,
    "limit": 20,
    "total_pages": 3
  }
}
```

Error Responses

Errors use a standard envelope: success is false, status is "failure", and an error object contains a machine-readable code and a human-readable message.

Status	Code	Cause
401	`UNAUTHORIZED`	Missing or invalid Bearer token.
403	`FORBIDDEN`	Authenticated, but not permitted — the path orgId does not match the organization your credential is scoped to.
429	`RATE_LIMIT_EXCEEDED`	Too many requests — wait for the Retry-After header before retrying.
502	`BAD_GATEWAY`	An upstream service returned an error.
503	`SERVICE_UNAVAILABLE`	The service is temporarily unavailable.

© 2026 Phoenix Robotix Pvt. Ltd.

Sample error response (403)

```
{
  "success": false,
  "status": "failure",
  "error": {
    "code": "FORBIDDEN",
    "message": "Your credential is not scoped to this organization."
  }
}
```

Code Samples

cURL

```
curl 'https://api.datoms.io/v4/orgs/1000/assets?page=1&limit=20' \
  -H 'Authorization: Bearer <token>'
```

Node.js (fetch)

```
const res = await fetch(
  'https://api.datoms.io/v4/orgs/1000/assets?page=1&limit=20',
  { headers: { Authorization: 'Bearer <token>' } }
);
const { data, pagination } = await res.json();
console.log(`Page ${pagination.page}/${pagination.total_pages}`, data);
```

Python (requests)

```
import requests

resp = requests.get(
    "https://api.datoms.io/v4/orgs/1000/assets",
    params={"page": 1, "limit": 20},
    headers={"Authorization": "Bearer <token>"},
)
body = resp.json()
for asset in body["data"]:
    print(asset['id'], asset['name'])
```

© 2026 Phoenix Robotix Pvt. Ltd.

Get Latest Telemetry Data for an Asset

Returns the most recent telemetry data point for a specific asset. Data is updated as each asset transmits — typically once per minute.

Timestamps: All timestamps in the response are in ISO 8601 format and are always in UTC (for example, `2026-06-01T18:30:00.000Z`).

This endpoint is designed for real-time polling dashboards. Each asset produces approximately one data point per minute, so polling once per minute per asset is sufficient to stay current. The rate limits are calibrated to allow exactly this pattern with generous headroom for retries and burst restarts.

Endpoint

```
GET /v4/orgs/{orgId}/assets/{assetId}/data/latest
```

Base URL (Production): `https://api.datoms.io`

Full request URL:
`https://api.datoms.io/v4/orgs/{orgId}/assets/{assetId}/data/latest`

Authentication

Every request must be authenticated using a Bearer token. The token can be a session token or a fixed API token, and is passed in the Authorization header. Obtain it from the Datoms login API or from your administrator.

Request headers

Header	Required	Description
`Authorization`	Yes	Bearer authentication. Format: Bearer <token>.

Path Parameters

Parameter	Type	Required	Description
`orgId`	string	Yes	Organization ID (numeric). Enforces multi-tenancy — only data belonging to this organization is accessible. Example: 3001.
`assetId`	integer (bigint)	Yes	Numeric asset ID (bigint) — the id returned by the List Assets endpoint. Example: 36390.

© 2026 Phoenix Robotix Pvt. Ltd.

Rate Limiting

This endpoint enforces per-credential, per-asset rate limits using a multi-window token bucket. Three windows run concurrently; the tightest active window is the one reported in the response headers. Rate limits are applied independently per asset, so polling asset A does not affect your quota for asset B.

Window	Limit	Headroom
5 minutes	8 calls	60% over normal 1/min polling
1 hour	80 calls	33% headroom
24 hours	1,500 calls	4% headroom — tight daily safety net

Rate-limit headers returned: `X-RateLimit-Limit, X-RateLimit-Remaining, X-RateLimit-Reset, Retry-After`

Response — 200 OK

Returns the latest telemetry data point for the asset.

Response body fields

Field	Type	Description
`success`	boolean	Always true for a successful response.
`status`	string	Always "success" for a successful response.
`data`	object	Container for the telemetry data point.
`data.time`	string (date-time)	Device-reported time of the data point. ISO 8601, always UTC. Example: 2026-06-01T18:30:00.000Z.
`data.parameters`	object	Key-value map of sensor readings. Keys are parameter names; values are the measured values (typically numbers, but may be strings or booleans depending on the sensor type).

© 2026 Phoenix Robotix Pvt. Ltd.

Sample response

```
{
  "success": true,
  "status": "success",
  "data": {
    "time": "2026-06-01T18:30:00.000Z",
    "parameters": {
      "temperature": 45.2,
      "pressure": 3.1,
      "speed": 0,
      "fuel_level": 72.5
    }
  }
}
```

Response headers

Header	Type	Description
`X-RateLimit-Limit`	integer	Maximum requests for the tightest active window (e.g. 8).
`X-RateLimit-Remaining`	integer	Remaining requests in the tightest window (e.g. 5).
`X-RateLimit-Reset`	integer	Seconds until the tightest window resets (e.g. 180).

Error Responses

Errors use a standard envelope: success is false, status is "failure", and an error object contains a machine-readable code and a human-readable message.

Status	Code	Cause
401	`UNAUTHORIZED`	Missing or invalid credentials.
404	`NO_DATA`	No telemetry data available for this asset. The asset may not have reported data yet.
404	`NOT_FOUND`	The referenced asset does not exist in this organization.
429	`RATE_LIMIT_EXCEEDED`	Per-asset rate limit exceeded — see response headers for retry timing.
503	`SERVICE_UNAVAILABLE`	Service is temporarily unavailable. Retry after a short delay.

On a `429` response, a `Retry-After` header (seconds to wait) is returned alongside the rate-limit headers, and X-RateLimit-Remaining is always 0.

© 2026 Phoenix Robotix Pvt. Ltd.

Sample error response (429)

```
{
  "success": false,
  "status": "failure",
  "error": {
    "code": "RATE_LIMIT_EXCEEDED",
    "message": "Asset latest-data rate limit exceeded (80/hour). Retry after
124 seconds."
  }
}
```

Code Samples

cURL

```
curl 'https://api.datoms.io/v4/orgs/1000/assets/1234/data/latest' \
  -H 'Authorization: Bearer <token>'
```

Node.js (fetch)

```
const res = await fetch(
  'https://api.datoms.io/v4/orgs/1000/assets/1234/data/latest',
  { headers: { Authorization: 'Bearer <token>' } }
);
const { data } = await res.json();
console.log(`Temperature: ${data.parameters.temperature}°C at ${data.time}`);
```

Python (requests)

```
import requests

resp = requests.get(
    "https://api.datoms.io/v4/orgs/1000/assets/1234/data/latest",
    headers={"Authorization": "Bearer <token>"},
)
data = resp.json()["data"]
print(f"Temperature: {data['parameters']['temperature']}°C at {data['time']}")
```

© 2026 Phoenix Robotix Pvt. Ltd.

Bulk Fetch Latest Asset Telemetry

Returns one latest-at-read-time telemetry result per asset in a single POST request. The request body selects one of two mutually exclusive modes, so you can pull the whole fleet a page at a time or fetch a specific set of assets by id.

Fleet mode (`page`, `limit`, both optional): one result for every asset in your read scope, in fixed order, with a `pagination` object. An empty body or `{}` is fleet mode at page 1 and the default limit. Use `limit=500` for full-fleet polling; process and release each page before the next, and upsert by asset_id.

Id mode (`asset_ids`, 1 to 500): one row per requested id, in request order, with no `pagination` object — the ids must be unique, so `data.length` equals the number of ids sent.

The two modes cannot be combined: sending asset_ids together with page or limit returns 400. There is no filtered paging — the 500-id cap is the page, so a caller with 3,000 ids sends six requests.

Failure rows: an asset with no usable latest packet is returned as the minimal `{ "asset_id": "…", "success": false }` — no data and no error object. Successful rows contain exactly the current DG projection (103 parameters). This is not an atomic fleet snapshot and does not return events produced between polls.

Compression: the application offers gzip when `Accept-Encoding: gzip` is sent and the body exceeds 1 KiB; identity encoding remains supported. Responses are private and not cacheable (`Cache-Control: private, no-store`).

Endpoint

```
POST /v4/orgs/{orgId}/assets/telemetry/latest/query
```

Base URL (Production): `https://api.datoms.io`

Full request URL:
`https://api.datoms.io/v4/orgs/{orgId}/assets/telemetry/latest/query`

Authentication

Every request must be authenticated using a Bearer token, passed in the Authorization header. Obtain it from the Datoms login API or from your administrator.

Access to this endpoint must be enabled on your API credential. If a request returns 403, contact Datoms to have access granted.

© 2026 Phoenix Robotix Pvt. Ltd.

Request headers

Header	Required	Description
`Authorization`	Yes	Bearer authentication. Format: Bearer <token>.
`Content-Type`	Yes	application/json — the request carries a JSON body.
`Accept-Encoding`	No	Send gzip to receive a gzip-compressed response when the body exceeds 1 KiB. Identity encoding is also supported.

Path Parameters

Parameter	Type	Required	Description
`orgId`	string	Yes	Organization ID (numeric). Enforces multi-tenancy — only data belonging to this organization is accessible. Example: 3001.

Request Body

The body is JSON and selects one mode. An empty body or {} is fleet mode at page 1 with the default limit.

Field	Type	Required	Description
`asset_ids`	string[]	Id mode	1 to 500 asset IDs, which must be unique — duplicate ids return 400. Returns one row per id, in request order, with no pagination, so each row maps positionally to your input. Cannot be combined with page or limit.
`page`	integer	No	Fleet mode only. One-based page number. Default 1.
`limit`	integer	No	Fleet mode only. Assets per page. Maximum 500, default 100. Use 500 for full-fleet polling.

Fleet mode and id mode cannot be mixed — `asset_ids` together with `page` or `limit` is a 400. There is no filtered paging: the 500-id cap is the page, so 3,000 ids means six requests.

Rate Limiting

This endpoint is metered on an exact asset-credit basis: the organization-wide quota charges the exact number of in-fleet asset rows returned (whether or not they carried data), independent of page size. In id mode, ids that are not in your fleet are not charged. There is a separate request limit of 240 requests per 60 seconds, per credential and organization.

In the caps below, `F` is your fleet size — the number of assets you can access — rounded up to the nearest 500 (and never less than 500). For example, up to 500 assets gives F = 500, and 1,200 assets gives F = 1,500. The credit caps are:

© 2026 Phoenix Robotix Pvt. Ltd.

Window	Credit limit
1 minute	`4F`
5 minutes	`8F`
1 hour	`100F`
24 hours (rolling)	`2,500F`
30 days (rolling)	`60,000F`

The 30-day cap is a misuse-prevention ceiling, not a limit normal use should reach. It is set at 60,000F — roughly 40 days of once-a-minute full-fleet polling, i.e. a full 30-day month plus about ten extra days of headroom for intermittent retries and catch-up. There is no separate weekly limit.

Every response carries an `X-RateLimit-Unit` header naming what the other three rate-limit headers count on that response. Check it before reading `X-RateLimit-Remaining`, because the number means different things in each case:

X-RateLimit-Unit	When you get it	What Limit / Remaining / Reset then count
`asset-read-credits`	The response charged for at least one in-fleet asset — the normal case.	Asset-read credits, measured against the windows above (4F to 60,000F).
`requests`	The response charged nothing (e.g. an empty page, or id mode with no in-fleet ids).	Plain request count, measured against the request limit of 240 requests per 60 seconds.

Rate-limit headers returned: `X-RateLimit-Unit, X-RateLimit-Limit, X-RateLimit-Remaining, X-RateLimit-Reset`

Response — 200 OK

Returns the selected rows. In fleet mode the response includes a pagination object; in id mode there is no pagination and data.length equals the number of ids you sent, one row per id in request order.

A row with no telemetry is the minimal `{ "asset_id": "…", "success": false }` — no data and no error object. In id mode this also covers ids that are not in your fleet (foreign, deleted, or nonexistent), indistinguishably, so do not infer ownership from this endpoint; refresh your id list from List Assets on a schedule.

© 2026 Phoenix Robotix Pvt. Ltd.

Response body fields

Field	Type	Description
`success`	boolean	Always true for a successful (2xx) response.
`status`	string	Always "success".
`data`	array	One row per asset (fleet mode: the page; id mode: one per requested id, in order). Each row is either a success row or a failure row (see below).
`data[].asset_id`	string	Asset identifier — legacy numeric id rendered as a string, or the canonical UUID fallback. Example: 36390.
`data[].success`	boolean	true when the row carries telemetry (data present); false when none is available (the row is then just asset_id and success).
`data[].data`	object	Present only when success is true. The latest telemetry packet for the asset.
`data[].data.time`	string (date-time)	Device-reported packet timestamp. ISO 8601, UTC.
`data[].data.parameters`	object	The DG latest-parameters projection — a key-value map of the current 103-parameter DG set (e.g. hz, rpm, curr, watt, volt, pf, fuel, temp, press).
`pagination`	object	Fleet mode only; omitted entirely in id mode.
`pagination.total`	integer	Total number of assets selected across all pages.
`pagination.page`	integer	Current page number.
`pagination.limit`	integer	Assets per page (1–500).
`pagination.total_pages`	integer	Total number of pages.

© 2026 Phoenix Robotix Pvt. Ltd.

Sample response (fleet mode)

```
{
  "success": true,
  "status": "success",
  "data": [
    {
      "asset_id": "36390",
      "success": true,
      "data": {
        "time": "2026-09-16T06:54:38.597Z",
        "parameters": {
          "hz": 50.0, "rpm": 1500, "volt": 415,
          "curr": 120.5, "watt": 86000, "pf": 0.99,
          "fuel": 72.5, "temp": 78.4, "press": 3.1
        }
      }
    },
    { "asset_id": "36391", "success": false }
  ],
  "pagination": {
    "total": 47,
    "page": 1,
    "limit": 500,
    "total_pages": 1
  }
}
```

Id mode (request and response)

```
Request body:
{ "asset_ids": ["36390", "36391"] }

Response (no pagination):
{
  "success": true,
  "status": "success",
  "data": [
    { "asset_id": "36390", "success": true, "data": { "time": "…",
"parameters": { … } } },
    { "asset_id": "36391", "success": false }
  ]
}
```

Error Responses

Page-level errors use the standard envelope: success is false, status is "failure", and an error object contains a machine-readable code and message. (Per-asset no-data is returned inline as a failure row, not as a page-level error.)

© 2026 Phoenix Robotix Pvt. Ltd.

Status	Code	Cause
400	VALIDATION_ERROR	Malformed body, more than 500 asset_ids, duplicate asset_ids, or asset_ids combined with page or limit (the modes cannot be mixed).
401	UNAUTHORIZED	Missing or invalid credential.
403	FORBIDDEN	The path organization does not match your credential, or your credential is not authorized for this endpoint.
422	PAGE_RESPONSE_TOO_LARGE	The encoded page exceeds the transport size bound. Reduce the page and resume (see below).
429	RATE_LIMIT_EXCEEDED	A rate limit was exceeded — the request limit or the asset-credit quota.
502	BAD_GATEWAY	An upstream service returned an unexpected error.
503	SERVICE_UNAVAILABLE	The service is temporarily unavailable.
504	GATEWAY_TIMEOUT	An upstream call timed out.

Handling 422 (PAGE_RESPONSE_TOO_LARGE)

A 422 is not retried unchanged, and the charge is refunded. In fleet mode, halve the limit and resume from the equivalent boundary; in id mode, split the id list into two requests.

```
new_limit   = max(1, floor(old_limit / 2))
resume_page = floor(((old_page - 1) * old_limit) / new_limit) + 1
```

This can replay some rows but does not skip the failed page's start while fleet membership is stable.

Code Samples

cURL — fleet mode

```
curl --compressed -X POST \
  'https://api.datoms.io/v4/orgs/1000/assets/telemetry/latest/query' \
  -H 'Authorization: Bearer <token>' \
  -H 'Content-Type: application/json' \
  -d '{ "limit": 500 }'
```

cURL — id mode

```
curl --compressed -X POST \
  'https://api.datoms.io/v4/orgs/1000/assets/telemetry/latest/query' \
  -H 'Authorization: Bearer <token>' \
  -H 'Content-Type: application/json' \
  -d '{ "asset_ids": ["36390", "36391"] }'
```

© 2026 Phoenix Robotix Pvt. Ltd.

Node.js — fleet-mode page loop

```
for (let page = 1; ; page += 1) {
  const response = await fetch(
    'https://api.datoms.io/v4/orgs/1000/assets/telemetry/latest/query',
    {
      method: 'POST',
      headers: {
        Authorization: 'Bearer <token>',
        'Content-Type': 'application/json',
      },
      body: JSON.stringify({ page, limit: 500 }),
    }
  );
  if (!response.ok) throw new Error(`HTTP ${response.status}`);
  const body = await response.json();
  for (const row of body.data) await upsertByAssetId(row);
  if (page >= body.pagination.total_pages) break;
}
```

Python — id mode

```
import requests

asset_ids = ["36390", "36391"]  # up to 500 per request
response = requests.post(
    "https://api.datoms.io/v4/orgs/1000/assets/telemetry/latest/query",
    json={"asset_ids": asset_ids},
    headers={
        "Authorization": "Bearer <token>",
        "Content-Type": "application/json",
    },
    timeout=30,
)
response.raise_for_status()
for row in response.json()["data"]:
    upsert_by_asset_id(row)
```

© 2026 Phoenix Robotix Pvt. Ltd.