Orvane

Guide

Installation and care.

Laying large porcelain so it stays flat, matched and easy to keep.

Before you lay

Check every crate on arrival: the batch, the shade (S1 to S4) and the caliber (C1 to C3) are printed on each. Lay one batch, one shade and one caliber in a room.

Slabs printed in sequence are numbered on the back. Lay them in order, and turn every other one for a bookmatch.

Let the porcelain stand in the room for a day before laying, and check the floor is flat to within 3 mm under a 2 m straightedge.

Moving large slabs

Carry slabs upright, never flat, on a slab frame or with vacuum lifters: two people for anything up to 1600 × 3200 mm, four beyond.

Lift and set down along the long edge; do not let a slab bend across its width.

Adhesive

Use a polymer-modified cementitious adhesive of class C2TE S1 (EN 12004), or S2 for thin panels of 3.5 and 6 mm and for slabs on walls.

Spread on the floor with a notched trowel and back-butter every piece over 600 mm, so the adhesive covers at least 95% of the back: no hollow spots, no cracks under load.

Joints

Rectified edges take a joint of 2 mm indoors and 3 mm outdoors. Leave a movement joint round the edges of every room, and across large floors about every 25 m² indoors and 16 m² outdoors.

Grout in a tone near the stone: it reads as one surface.

Cutting and drilling

Cut on a wet saw or a rail cutter with a porcelain blade. Start holes at an angle with a diamond core bit, keep it wet, then bring it upright.



General guidance for a demo company. Follow your local standards and the adhesive maker's instructions.

The first clean

A day or two after grouting, take off the cement film with a cleaner made for it, diluted as the maker says, then rinse with clean water.

Every day

A soft mop and a pH-neutral cleaner. Polished Specchio and Glossy faces come up best with a microfibre cloth; avoid waxes and sealers, porcelain does not need them.

Wine, coffee, oil and turmeric wipe off with warm water while fresh. Dried stains come off with a neutral cleaner.

Grip and relief finishes

Presa, Grip and Carving keep their grip when they are clean: wash them with a neutral detergent and a soft brush, and rinse.

Outside

Twenty-millimetre porcelain can be laid dry: on grass, on a compacted gravel bed, or on adjustable pedestals over a roof membrane. Brush it down and rinse; a low-pressure washer is fine.

Frost does not harm porcelain of group Bla. Clear standing water from pedestal systems in winter.

Kitchens

Hot pans can go straight down on Cucina slabs, and knives will not mark them, but always use a board to keep the knife sharp.



General guidance for a demo company. For demo purposes only. Claims show how a manufacturer's own records would be presented.

Orvane

Samples, prices and visits

studio@orvane.example

WhatsApp +91 00000 00000
Orvane Works, Plot 00, Ceramic Cluster
Morbi, Gujarat, India

Orvane Ceramica is a fictional company. This site is a demo, and nothing on it is for sale. Sample figures for a demo company. Interiors are AI-generated for this demo, with Orvane's rendered surfaces. Installation and care, 2026.