

Exemple 1 :

Code SQL : Corps de la procédure stockée

```
CREATE PROCEDURE `exemple` (IN inputParam INT, INOUT param VARCHAR(30))
BEGIN
SELECT CONCAT('Hello ', param, inputParam, ' avec JDBC !!!') INTO param;
END
```

Code Java :

```
import java.io.*;
import java.sql.*;

public class TestCallableStatement {

    private static String url = "jdbc:mysql://localhost:3306/webstore";
    private static String user = "root";
    private static String pwd = "isimg";

    public static void main(String[] args) throws FileNotFoundException, IOException, SQLException
    {

        String sql = "{call exemple(?,?)}";

        try (Connection con = DriverManager.getConnection(url, user, pwd);
            CallableStatement st = con.prepareCall(sql)) {

            st.setInt(1, 2);

            st.registerOutParameter(2, java.sql.Types.VARCHAR);

            st.setString(2, "CPI");

            st.execute();

            String resultat = st.getString(2);

            System.out.println("Résultat = " + resultat);

        }

    }

}
```

Exemple 2 :

Code SQL : Corps de la procédure stockée

```
CREATE PROCEDURE `nombreAbonnes` (OUT nb INTEGER)
BEGIN
    SELECT COUNT(*) INTO nb FROM users;
END
```

Code Java :

```
import java.io.*;
import java.sql.*;

public class TestCallStatement {

    private static String url = "jdbc:mysql://localhost:3306/webstore";
    private static String user = "root";
    private static String pwd = "isimg";

    public static void main(String[] args) throws FileNotFoundException, IOException, SQLException
    {
        String sql = "{call nombreAbonnes(?)}";

        try (Connection con = DriverManager.getConnection(url, user, pwd);
            CallableStatement st = con.prepareCall(sql)) {

            st.registerOutParameter(1, java.sql.Types.INTEGER);
            st.execute();

            int resultat = st.getInt(1);

            System.out.println("Nombre d'abonnés = "+resultat);

        }

    }
}
```