

ecointl
ECOWALL
10 kWh Battery



Technical specification:

	GGESSM-51.2V-200AH（A）
Battery Type	LiFePO4
Normal Battery Voltage(v)	51.2V
Normal Capacity (25℃ 0.2C)(Ah)	200Ah
Rated Power (25℃ 0.2C)(Wh)	10240
Folat Charge Voltage(V)	56
Operation Voltge range (V)	44.8~58.4
Max.Continuous Charge Current(A)	80A
Max. Continvous Discharge Qument(A)	150A
Max.Pulse Discharge Current(A)	200A 0.5Sec
Terminal	M8
Storage temperature	-10℃~50℃
IP degree	IP20
Storage duration	6 months at 25℃
Safety standard	UN38.3,MSDS
Display (Optional)	/
Communication Port(Optional)	RS485,CAN,DRY
PROTECTION AMBIENT	
	Overcharge protection, Overdischarge protection, Overcurrent protection, Shortcircuit protection, Overtemperature protection,
Working Temperature	20℃~+60℃
Humidity	O~95%(no condensation)
Sea Level(m)	≤2000
DIMENSION	
LxWxD (products size, mm)	540*190*670mm (With wall mount bracket 228mm)
LxWxD (package size, mm)	750*650*310mm
NW Kg	≈83.8Kg
GW Kg	95.2Kg

sales@ecointl.com