

ecointl
ECOWALL
16 kWh Battery



Technical specification:

	PowerCool-WLL016E1
Total Energy	16.07kWh
Usable Energy*	15.27kWh
Voltage	44.8~57.6Vd.c.
Nominal Voltage	51.2Vd.c.
Rated Capacity	314Ah
Max. Charge Voltage Nominal	57.6Vd.c.
Discharging Current Nominal	150A(1P) /160A(2P~6P)
Charging Current Weight	150A(1P) /160A(2P~6P)
Dimension(mm)(H*L *W)	120kg
Recommended DOD	800*450*250mm
Operating Condition	95%
Operating Temperature	Indoor
Humidity Charge	0~55°C
Discharge	-15~55°C
	15%～85%RH (No Condensation)
Over Voltage Category	II
Cooling Type	Natural cooling
Installation	floor-standing
IP Rating	IP 20
Heating unit(optional)	150W
Screen (Optional)	LED
Protective Class	I
Max. Connection Number	15P
Communication	CAN / RS485
WiFI	Yes
Protection	Over-current/Over-voltage/Short circuit/ Under-voltage/Over-temperature
Certificates	CE,UN38.3,MSDS
Warranty	5 years

*Testing conditions based on temperature 25°C at the beginning of life. Total Energy/Usable Energy are measured with a standard test method: 0.2C Charge and Discharge. As per the characteristics of lithium batteries, such parameters as the charge/ discharge current and efficiency listed above are subject to change.

The final interpretation shall be reserved by YINERGY DIGITAL POWER TECHNOLOGY CO., LTD.

www.eco-intl.co
sales@ecointl.com