

ecointl
ECOWALL
4 kWh Battery



Technical specification:

GENERAL INFORMATION			
Battery model	GGESS-51.2-8kWh	GGESS-25.6-4kWh	
Cell type			
Rated voltage	51.2V	25.6V	
Operation voltage range	43.2V~58.4V	21.6V~29.2V	
Rated energy	155AH	155AH	
System energy capacity	8kWh	4kWh 150A	
Max continuous discharging current	150A	80A	
Rated charge current	80A	80A	
Rated discharging current	80A		
DOD % @25℃	80%DOD		
Self-discharge	<3% per Month @25℃		
Cycle life	>6000 Cycles @25℃ 80%DOD		
Warranty	5 Years		
Dimension(W×H×D)	L420×W190×H660mm	L400×W270×H570mm	L460×W150×H520mm
Package	Individual Wooden Box		
System function	Over-Charge protection; over-discharge protection; short-circuit protection; over-voltage protection; Under-voltage protection; over-current protection; Over-temperature protection; State of Charge Display; Anti- Surge protection; Smart BMS with First Level protection, Second Level Protection and Third Level protection; and Circuit Breaker protection;		

ENVIRONMENTAL REQUIREMENTS			
Charge temperature	0~60℃		
Discharge temperature	-20~60℃		
Recommended storage temperature	20~35℃		
Cooling concept	Natural cooling		
Max.operating altitude	3000m		
Installation type	Ground	Ground	Wall-mounted
Ingress protection	IP20		
Environment	Indoor		

COMMUNICATION INTERFACES	
Display	LED Strip Light
PACE BMS Communication interfaces	RS485/RS232/CAN

STANDARD	
Hazardous material classification	Class 9
Transport testing requirement	UN38.3
Protection class	Class 1
Certifications	CE/IEC62619

www.eco-intl.co
sales@ecointl.com