

ecointl
ECOWALL
5 kWh Wall Mounted Li-Ion Battery



Technical specification:

MModduulele T Tyyppee	PPoowweerYrCCNoo-oWolL-l-LW00LL5L1L0101100AA11
Rated capacity	104Ah
Total energy	5.32kWh
Usable energy*	5.05kWh
Voltage range	44.8~57.6Vd.c.
Nominal voltage	51.2V
Max. charging voltage	57.6V
Nominal continuous charging current	50A
Max. continuous charging current	100A(30min)
Nominal continuous discharge current	50A
Max. continuous discharge current	100A(30min)
DOD	95%
Communication Interface	CAN/RS485/WiFi
Maxm parallel quantity	6
Dimension(L*W*H)	(418±2)*(160±2)*(610±2)mm
Net weight	(45±1)kg
Operating condition	Indoor
Operating Charging	0~55°C
Temperature Discharge	-15~55°C
Ttrip :The trip temperature of Overheating protection	57℃
Humidity	15% ~ 85%(RH)(No Condensation)
Cooling type	Natural Cooling
WIFI Frequency Range	2412MHz~2472MHz
WIFI Maximum Transmission Power	20dBm
Heating film power (optional)	130W
	IP20
Configuration	16S
Installation method	Wall-mounted
Supply connection	Fixed power cord
Warranty	5 years
Authentication Level	UN38.3/CE

ed above are subject to change.

*Testing conditions based on temperature 25℃ at the beginning of life. Total Energy/Usable Energy are measured with a standard test method: 0.2C Charge and Discharge. As per the characteristics of lithium batteries, such parameters as the charge/ discharge current and efficiency list
The final interpretation shall be reserved by YINERGY DIGITAL POWER TECHNOLOGY CO., LTD.