

tsvc_c2/k27 · k27.c · full_b1_nospeed_v4 · claude-haiku-4-5-20251001 · FASTER

```
-2 / +8 lines of 14      · 2 parallel region(s) added      · 6 of 6 candidate(s) kept      · RESTRUCTURING (6 code line(s) added, 2 removed)      · restructuring level 0
```

BEFORE

```
1  #include "data.h"
```

```
3 real t kernel k27(void)
```

4 {

```
5     for (int nl = 0; nl < iterations; nl++) {
```

```
6     for (long i = 1; i < LEN 1D; i++) {
```

```
7         u[ju[i]] += w[kw[i]] * c[i];
```

```
8         v[jv[i]] = u[ku[i]] * d[i] + c[i];
```

```
9         w[jw[i]] = v[kv[i]] * e[i] + d[i];
```

$$10 \quad \}$$

```
11 dummy(a, b, c, d, e);
```

12 }

```
13     return (real t)0;
```

14 }

AFTER

```
1  #include "data.h"
```

```
3 real t kernel k27(void)
```

4 {

```
5     for (int nl = 0; nl < iterations; nl++) {
```

```
6      #pragma omp parallel for
```

```
7         for (long i = 1; i < LEN_1D; i++) {
```

```
8         v[jv[i]] = u[ku[i]] * d[i] + c[i];
```

9 }

```
10      #pragma omp parallel for
```

```
11     for (long i = 1; i < LEN_1D; i++) {
```

```
12         w[jw[i]] = v[kv[i]] * e[i] + d[i];
```

13 }

```
14     for (long i = 1; i < LEN_1D; i++) {
```

```
15         u[ju[i]] += w[kw[i]] * c[i];
```

16 }

```
17 dummy(a, b, c, d, e);
```

18

```
19     return (real t)0;
```

20

file