

tsvc/s000 · s000.c · default · claude-haiku-4-5-20251001 · no-change · RIGHT = the program the agent built, then dropped (never shipped)
-1 / +5 lines of 175 · 1 parallel region(s) added · 2 of 3 candidate(s) kept · RESTRUCTURING (4 code line(s) added, 1 removed) · restructuring level 0

BEFORE	THE PROGRAM THE AGENT BUILT, THEN DROPPED	file
131 #endif	131 #endif	
132 }	132 }	
133	133	
134 static real_t kernel_s000(void)	134 static real_t kernel_s000(void)	
135 {	135 {	
	136 real_t *b_snapshot = (real_t*)malloc((size_t)LEN_1D * sizeof(real_t));	
136 for (int nl = 0; nl < R; nl++) {	137 for (int nl = 0; nl < R; nl++) {	
	138 memcpy(b_snapshot, b, (size_t)LEN_1D * sizeof(real_t));	
	139 #pragma omp parallel for shared(b_snapshot)	
137 for (int i = 0; i < LEN_1D; i++) {	140 for (int i = 0; i < LEN_1D; i++) {	
138 a[i] = b[i] + 1;	141 a[i] = b_snapshot[i] + 1;	
139 }	142 }	
140 pb_mix(nl);	143 pb_mix(nl);	
141 }	144 }	
	145 free(b_snapshot);	
142 return (real_t)0;	146 return (real_t)0;	
143 }	147 }	
144	148	
145 int main(int argc, char** argv)	149 int main(int argc, char** argv)	
146 {	150 {	