

tsvc/s121 · s121.c · default · claude-haiku-4-5-20251001 · no-change · RIGHT = the program the agent built, then dropped (never shipped)
-1 / +10 lines of 177 · 2 parallel region(s) added · 3 of 3 candidate(s) kept · RESTRUCTURING (7 code line(s) added, 1 removed) · restructuring level 0

```
BEFORE
132     }
133
134     static real_t kernel_s121(void)
135     {
136         int j;

137         for (int nl = 0; nl < R; nl++) {

138             for (int i = 0; i < LEN_1D-1; i++) {
139                 j = i + 1;
140                 a[i] = a[j] + b[i];

141             }
142             pb_mix(nl);
143         }

144         return (real_t)0;
145     }
146
147     int main(int argc, char** argv)
148     {
```

```
THE PROGRAM THE AGENT BUILT, THEN DROPPED
132     }
133
134     static real_t kernel_s121(void)
135     {
136         int j;
137         real_t *temp = (real_t*)malloc((size_t)LEN_1D * sizeof(real_t));
138         if (!temp) return (real_t)0;
139
140         for (int nl = 0; nl < R; nl++) {
141             #pragma omp parallel for private(j) shared(temp)
142             for (int i = 0; i < LEN_1D-1; i++) {
143                 j = i + 1;
144                 temp[i] = a[j] + b[i];
145             }
146             #pragma omp parallel for shared(temp)
147             for (int i = 0; i < LEN_1D-1; i++) {
148                 a[i] = temp[i];
149             }
150             pb_mix(nl);
151         }
152         free(temp);
153         return (real_t)0;
154     }
155
156     int main(int argc, char** argv)
157     {
```

