

tsvc/s313 · s313.c · default · claude-haiku-4-5-20251001 · FASTER · RIGHT = attempt 2 of 3, rejected by the gate at 'tsan'

-3 / +5 lines of 177 · 1 parallel region(s) added · 2 of 3 candidate(s) kept · RESTRUCTURING (4 code line(s) added, 3 removed) · restructuring level 0

BEFORE	ATTEMPT 2 OF 3, REJECTED BY THE GATE AT 'TSAN'	file
131 #endif	131 #endif	
132 }	132 }	
133	133	
134 static real_t kernel_s313(void)	134 static real_t kernel_s313(void)	
135 {	135 {	
136 real_t dot;	136 real_t final_dot = (real_t)0.;	
137 for (int nl = 0; nl < R; nl++) {	137 for (int nl = 0; nl < R; nl++) {	
138 dot = (real_t)0.;	138 real_t dot = (real_t)0.;	
	139 #pragma omp parallel for reduction(+:dot)	
139 for (int i = 0; i < LEN_1D; i++) {	140 for (int i = 0; i < LEN_1D; i++) {	
140 dot += a[i] * b[i];	141 dot += a[i] * b[i];	
141 }	142 }	
	143 final_dot = dot;	
142 pb_mix(nl);	144 pb_mix(nl);	
143 }	145 }	
144 return dot;	146 return final_dot;	
145 }	147 }	
146	148	
147 int main(int argc, char** argv)	149 int main(int argc, char** argv)	
148 {	150 {	
149 a = (real_t*)malloc((size_t)LEN_1D * sizeof(real_t));	151 a = (real_t*)malloc((size_t)LEN_1D * sizeof(real_t));	