llnl_c1/lulesh · lulesh.cc · llm_pragmas_v5_exact · claude-haiku-4-5-20251001 · FASTER

−171 / +344 lines of 1967 · 26 parallel region(s) added · 34 of 77 candidate(s) kept · RESTRUCTURING (260 code line(s) added, 153 removed) · restructuring level 0

BEFORE

```
65                                const Index_t* elemToNode,
66                                Real_t elemX[8],
67                                Real_t elemY[8],
68                                Real_t elemZ[8])
69  {
70     Index_t nd0i = elemToNode[0] ;
71     Index_t nd1i = elemToNode[1] ;
72     Index_t nd2i = elemToNode[2] ;
73     Index_t nd3i = elemToNode[3] ;
74     Index_t nd4i = elemToNode[4] ;
75     Index_t nd5i = elemToNode[5] ;
76     Index_t nd6i = elemToNode[6] ;
77     Index_t nd7i = elemToNode[7] ;
78
79     elemX[0] = domain.x(nd0i);
80     elemX[1] = domain.x(nd1i);
81     elemX[2] = domain.x(nd2i);
82     elemX[3] = domain.x(nd3i);
83     elemX[4] = domain.x(nd4i);
84     elemX[5] = domain.x(nd5i);
85     elemX[6] = domain.x(nd6i);
86     elemX[7] = domain.x(nd7i);
87
88     elemY[0] = domain.y(nd0i);
89     elemY[1] = domain.y(nd1i);
90     elemY[2] = domain.y(nd2i);
91     elemY[3] = domain.y(nd3i);
92     elemY[4] = domain.y(nd4i);
93     elemY[5] = domain.y(nd5i);
94     elemY[6] = domain.y(nd6i);
95     elemY[7] = domain.y(nd7i);
96
97     elemZ[0] = domain.z(nd0i);
98     elemZ[1] = domain.z(nd1i);
99     elemZ[2] = domain.z(nd2i);
100    elemZ[3] = domain.z(nd3i);
101    elemZ[4] = domain.z(nd4i);
102    elemZ[5] = domain.z(nd5i);
103    elemZ[6] = domain.z(nd6i);
104    elemZ[7] = domain.z(nd7i);
105
106 }
107
108 static inline
109 void InitStressTermsForElems(Domain &domain,
110                              Real_t *sigxx, Real_t *sigyy, Real_t *sigzz,
…
303 static inline
304 void IntegrateStressForElems( Domain &domain,
305                               Real_t *sigxx, Real_t *sigyy, Real_t *sigzz,
306                               Real_t *determ, Index_t numElem, Index_t numNode
307 {
308
309    Real_t fx_local[8] ;
310    Real_t fy_local[8] ;
311    Real_t fz_local[8] ;
312
313    for( Index_t k=0 ; k<numElem ; ++k )
314    {
315       const Index_t* const elemToNode = domain.nodelist(k);
316       Real_t B[3][8] ;
317       Real_t x_local[8] ;
318       Real_t y_local[8] ;
319       Real_t z_local[8] ;
…
327                            x_local, y_local, z_local );
328
329       SumElemStressesToNodeForces( B, sigxx[k], sigyy[k], sigzz[k],
330                                    fx_local, fy_local, fz_local ) ;
331
332       for( Index_t lnode=0 ; lnode<8 ; ++lnode ) {
333          Index_t gnode = elemToNode[lnode];
334          domain.fx(gnode) += fx_local[lnode];
335          domain.fy(gnode) += fy_local[lnode];
336          domain.fz(gnode) += fz_local[lnode];
337       }
338
339    }
340
```

AFTER

```
65                                const Index_t* elemToNode,
66                                Real_t elemX[8],
67                                Real_t elemY[8],
68                                Real_t elemZ[8])
69  {
70     for (int i = 0; i < 8; ++i) {
71        Index_t ndi = elemToNode[i];
72        elemX[i] = domain.x(ndi);
73        elemY[i] = domain.y(ndi);
74        elemZ[i] = domain.z(ndi);
75     }
76  }
77
78  static inline
79  void InitStressTermsForElems(Domain &domain,
80                               Real_t *sigxx, Real_t *sigyy, Real_t *sigzz,
…
273 static inline
274 void IntegrateStressForElems( Domain &domain,
275                               Real_t *sigxx, Real_t *sigyy, Real_t *sigzz,
276                               Real_t *determ, Index_t numElem, Index_t numNode
277 {
278    // Allocate temporary buffers for storing forces per element
279    Index_t numElemNodes = numElem * 8;
280    Real_t *elem_fx = Allocate<Real_t>(numElemNodes);
281    Real_t *elem_fy = Allocate<Real_t>(numElemNodes);
282    Real_t *elem_fz = Allocate<Real_t>(numElemNodes);
283    Index_t *elem_nodes = Allocate<Index_t>(numElemNodes);
284
285    // Parallel loop: compute forces and store them (no shared writes)
286    #pragma omp parallel for
287    for( Index_t k=0 ; k<numElem ; ++k )
288    {
289       Real_t fx_local[8] ;
290       Real_t fy_local[8] ;
291       Real_t fz_local[8] ;
292
293       const Index_t* const elemToNode = domain.nodelist(k);
294       Real_t B[3][8] ;
295       Real_t x_local[8] ;
296       Real_t y_local[8] ;
297       Real_t z_local[8] ;
…
305                            x_local, y_local, z_local );
306
307       SumElemStressesToNodeForces( B, sigxx[k], sigyy[k], sigzz[k],
308                                    fx_local, fy_local, fz_local ) ;
309
310       // Store forces and node indices for later sequential application
311       Index_t base = k * 8 ;
312       for( Index_t lnode=0 ; lnode<8 ; ++lnode ) {
313          elem_fx[base + lnode] = fx_local[lnode] ;
314          elem_fy[base + lnode] = fy_local[lnode] ;
315          elem_fz[base + lnode] = fz_local[lnode] ;
316          elem_nodes[base + lnode] = elemToNode[lnode] ;
317       }
318    }
319
320    // Sequential loop: apply forces in element order to preserve floating-point
321    for( Index_t k=0 ; k<numElem ; ++k )
322    {
323       Index_t base = k * 8 ;
```

red = removed green = added yellow = parallel region (#pragma omp) right strip = the whole file: green where changed, yellow where a parallel region now is