

-2 / +13 lines of 13 · 2 parallel region(s) added · 6 of 10 candidate(s) kept · RESTRUCTURING (11 code line(s) added, 2 removed) · restructuring level 0

BEFORE	AFTER	file
<pre>1 #include "data.h" 2 3 real_t kernel_k53(void) 4 { 5 for (int nl = 0; nl < iterations; nl++) {</pre>	<pre>1 #include <stdlib.h> 2 #include "data.h" 3 4 real_t kernel_k53(void) 5 { 6 for (int nl = 0; nl < iterations; nl++) {</pre>	
	<pre>7 real_t* u_temp = (real_t*)malloc(sizeof(real_t) * LEN_1D); 8 #pragma omp parallel for shared(u_temp) 9 for (long i = 0; i < LEN_1D; i++) { 10 u_temp[i] = u[i]; 11 }</pre>	
<pre>6 for (long i = 1; i < LEN_1D; i++) { 7 u[ju[i]] += v[kv[i]] * c[i]; 8 v[jv[i]] = u[ku[i]] * d[i] + c[i]; 9 }</pre>	<pre>12 for (long i = 1; i < LEN_1D; i++) { 13 u_temp[ju[i]] += v[kv[i]] * c[i]; 14 v[jv[i]] = u_temp[ku[i]] * d[i] + c[i]; 15 }</pre>	
	<pre>16 #pragma omp parallel for shared(u_temp) 17 for (long i = 0; i < LEN_1D; i++) { 18 u[i] = u_temp[i]; 19 } 20 free(u_temp);</pre>	
<pre>10 dummy(a, b, c, d, e); 11 } 12 return (real_t)0; 13 }</pre>	<pre>21 dummy(a, b, c, d, e); 22 } 23 return (real_t)0; 24 }</pre>	