

BEFORE	THE PROGRAM THE AGENT BUILT, THEN DROPPED	file
132 } 133 134 static real_t kernel_s241(void) 135 { 136 for (int nl = 0; nl < R; nl++) { 137 for (int i = 0; i < LEN_1D-1; i++) { 138 a[i] = b[i] * c[i] * d[i]; 139 b[i] = a[i] * a[i+1] * d[i]; 140 } 141 pb_mix(nl); 142 } 143 return (real_t)0; 144 } 145	132 } 133 134 static real_t kernel_s241(void) 135 { 136 for (int nl = 0; nl < R; nl++) { 137 real_t *a_old = (real_t*)malloc((size_t)LEN_1D * sizeof(real_t)); 138 memcpy(a_old, a, (size_t)LEN_1D * sizeof(real_t)); 139 140 #pragma omp parallel for 141 for (int i = 0; i < LEN_1D-1; i++) { 142 a[i] = b[i] * c[i] * d[i]; 143 } 144 145 #pragma omp parallel for shared(a_old) 146 for (int i = 0; i < LEN_1D-1; i++) { 147 b[i] = a[i] * a_old[i+1] * d[i]; 148 } 149 150 free(a_old); 151 pb_mix(nl); 152 } 153 return (real_t)0; 154 } 155	