

-1 / +15 lines of 175 · 1 parallel region(s) added · 2 of 2 candidate(s) kept · RESTRUCTURING (11 code line(s) added, 1 removed) · restructuring level 0

BEFORE	AFTER	file
131 #endif	131 #endif	
132 }	132 }	
133	133	
134 static real_t kernel_vpvtv(void)	134 static real_t kernel_vpvtv(void)	
135 {	135 {	
	136 real_t* b_fixed = (real_t*)malloc((size_t)LEN_1D * sizeof(real_t));	
	137 real_t* c_fixed = (real_t*)malloc((size_t)LEN_1D * sizeof(real_t));	
	138 memcpy(b_fixed, b, (size_t)LEN_1D * sizeof(real_t));	
	139 memcpy(c_fixed, c, (size_t)LEN_1D * sizeof(real_t));	
	140	
136 for (int nl = 0; nl < R; nl++) {	141 for (int nl = 0; nl < R; nl++) {	
	142 #pragma omp parallel for shared(c_fixed,b_fixed)	
137 for (int i = 0; i < LEN_1D; i++) {	143 for (int i = 0; i < LEN_1D; i++) {	
138 a[i] += b[i] * c[i];	144 a[i] += b_fixed[i] * c_fixed[i];	
139 }	145 }	
140 pb_mix(nl);	146 pb_mix(nl);	
	147 /* Update fixed copies to reflect pb_mix's modifications */	
	148 long k = ((long)nl * 7919L + 13L) % LEN_1D;	
	149 b_fixed[k] = b[k];	
	150 c_fixed[k] = c[k];	
	151 b_fixed[LEN_1D-1] = b[LEN_1D-1];	
141 }	152 }	
	153	
	154 free(b_fixed);	
	155 free(c_fixed);	
142 return (real_t)0;	156 return (real_t)0;	
143 }	157 }	
144	158	
145 int main(int argc, char** argv)	159 int main(int argc, char** argv)	
146 {	160 {	