

-13 / +15 lines of 169 · 1 parallel region(s) added · 2 of 2 candidate(s) kept · RESTRUCTURING (14 code line(s) added, 13 removed) · restructuring level 0

```
BEFORE
79  {
80      int i, j, k;
81
82      #pragma scop
83      /* D := alpha*A*B*C + beta*D */
84
85      for (i = 0; i < _PB_NI; i++)
86          for (j = 0; j < _PB_NJ; j++)
87              {
88                  tmp[i][j] = 0;
89                  for (k = 0; k < _PB_NK; ++k)
90                      tmp[i][j] += alpha * A[i][k] * B[k][j];
91              }
92      for (i = 0; i < _PB_NI; i++)
93          for (j = 0; j < _PB_NL; j++)
94              {
95                  D[i][j] *= beta;
96                  for (k = 0; k < _PB_NJ; ++k)
97                      D[i][j] += tmp[i][k] * C[k][j];
98              }
99
100      #pragma endscop
101  }
102
```

```
AFTER
79  {
80      int i, j, k;
81
82      #pragma scop
83      /* D := alpha*A*B*C + beta*D */
84      #pragma omp parallel for firstprivate(beta,nk,nj,alpha,nl,ni) private(k,j) sh
85          for (i = 0; i < _PB_NI; i++)
86              {
87                  for (j = 0; j < _PB_NJ; j++)
88                      {
89                          tmp[i][j] = 0;
90                          for (k = 0; k < _PB_NK; ++k)
91                              tmp[i][j] += alpha * A[i][k] * B[k][j];
92                      }
93                  for (j = 0; j < _PB_NL; j++)
94                      {
95                          D[i][j] *= beta;
96                          for (k = 0; k < _PB_NJ; ++k)
97                              D[i][j] += tmp[i][k] * C[k][j];
98                      }
99              }
100      #pragma endscop
101
102  }
103
104
```

file