

tsvc/s322 · s322.c · default · claude-haiku-4-5-20251001 · no-change · RIGHT = the program the agent built, then dropped (never shipped)
-1 / +4 lines of 175 · 0 parallel region(s) added · 1 of 10 candidate(s) kept · RESTRUCTURING (4 code line(s) added, 1 removed) · restructuring level 0

BEFORE	THE PROGRAM THE AGENT BUILT, THEN DROPPED	file
131 #endif	131 #endif	
132 }	132 }	
133	133	
134 static real_t kernel_s322(void)	134 static real_t kernel_s322(void)	
135 {	135 {	
	136 real_t *a_old = (real_t*)malloc((size_t)LEN_1D * sizeof(real_t));	
136 for (int nl = 0; nl < R; nl++) {	137 for (int nl = 0; nl < R; nl++) {	
	138 memcpy(a_old, a, (size_t)LEN_1D * sizeof(real_t));	
137 for (int i = 2; i < LEN_1D; i++) {	139 for (int i = 2; i < LEN_1D; i++) {	
138 a[i] = a[i] + a[i - 1] * b[i] + a[i - 2] * c[i];	140 a[i] = a_old[i] + a[i - 1] * b[i] + a[i - 2] * c[i];	
139 }	141 }	
140 pb_mix(nl);	142 pb_mix(nl);	
141 }	143 }	
	144 free(a_old);	
142 return (real_t)0;	145 return (real_t)0;	
143 }	146 }	
144	147	
145 int main(int argc, char** argv)	148 int main(int argc, char** argv)	
146 {	149 {	