

-0 / +18 lines of 177 · 3 parallel region(s) added · 0 of 0 candidate(s) kept · RESTRUCTURING (4 code line(s) added, 0 removed) · restructuring level 0

BEFORE	AFTER	file
132 } 133 134 static real_t kernel_s243(void) 135 { 136 for (int nl = 0; nl < R; nl++) { 137 for (int i = 0; i < LEN_1D-1; i++) { 138 a[i] = b[i] + c[i] * d[i]; 139 b[i] = a[i] + d[i] * e[i]; 140 a[i] = b[i] + a[i+1] * d[i]; 141 } 142 pb_mix(nl); 143 } 144 return (real_t)0; 145 } 146	132 } 133 134 static real_t kernel_s243(void) 135 { 136 for (int nl = 0; nl < R; nl++) { 137 /* Phase 1: compute a[i] from b[i], c[i], d[i] 138 * No loop-carried dependencies; all iterations independent */ 139 #pragma omp parallel for 140 for (int i = 0; i < LEN_1D-1; i++) { 141 a[i] = b[i] + c[i] * d[i]; 142 } 143 144 /* Phase 2: compute b[i] from newly computed a[i], d[i], e[i] 145 * No loop-carried dependencies; all iterations independent */ 146 #pragma omp parallel for 147 for (int i = 0; i < LEN_1D-1; i++) { 148 b[i] = a[i] + d[i] * e[i]; 149 } 150 151 /* Phase 3: compute a[i] from newly computed b[i] and a[i+1] computed 152 * No loop-carried dependencies; all iterations independent 153 * (a[i+1] was computed in phase 1 for i < LEN_1D-2; 154 * a[LEN_1D-1] is untouched by the kernel) */ 155 #pragma omp parallel for 156 for (int i = 0; i < LEN_1D-1; i++) { 157 a[i] = b[i] + a[i+1] * d[i]; 158 } 159 160 pb_mix(nl); 161 } 162 return (real_t)0; 163 } 164	