

tsvc/s211 · s211.c · bare llm · claude-haiku-4-5-20251001 · BROKEN

```
-0 / +12 lines of 176 · 2 parallel region(s) added · 0 of 0 candidate(s) kept · RESTRUCTURING (2 code line(s) added, 0 removed) · restructuring level 0
```

BEFORE

132 }

133

```
134 static real_t kernel_s211(void)
```

135 {

```
136     for (int nl = 0; nl < R; nl++) {
```

```
137     for (int i = 1; i < LEN 1D-1; i++) {
```

```
138         a[i] = b[i - 1] + c[i] * d[i];
```

```
139         b[i] = b[i + 1] - e[i] * d[i];
```

140 }

```
141         pb mix(nl);
```

142 }

```
143     return (real_t)0;
```

144 }

145

AFTER

132 }

133

```
134 static real_t kernel_s211(void)
```

135 {

```
136     for (int nl = 0; nl < R; nl++) {
```

```
137      /* First statement: compute a[i] from b[i-1], c[i], d[i] in parallel.
```

```
138      * Each thread i writes to distinct a[i] and reads non-conflicting ele
```

```
139      * No loop-carried dependence. */
```

```
140      #pragma omp parallel for
```

```
141     for (int i = 1; i < LEN 1D-1; i++) {
```

```
142         a[i] = b[i - 1] + c[i] * d[i];
```

```
145      /* Second statement: compute b[i] from b[i+1], e[i], d[i] in parallel.
```

```
147      * No loop-carried dependence. */
```

```
148         #pragma omp parallel for
```

```
149     for (int i = 1; i < LEN_ID-1; i++) {
```

```
150         b[i] = b[i + 1] - e[i] * d[i];
```

151 }

```
153         pb mix(nl);
```

154 }

```
155     return (real_t)0;
```

156 }

157

file