

Module Interface Specification for Software Engineering

Team 8 – Rhythm Rangers

Ansel Chen

Muhammad Jawad

Mohamad-Hassan Bahsoun

Matthew Baleanu

Ahmed Al-Hayali

January 17, 2025

1 Revision History

Date	Version	Notes
Date 1	1.0	Notes
Date 2	1.1	Notes

2 Symbols, Abbreviations and Acronyms

See SRS Documentation at [\[give url —SS\]](#)

[\[Also add any additional symbols, abbreviations or acronyms —SS\]](#)

Contents

1	Revision History	i
2	Symbols, Abbreviations and Acronyms	ii
3	Introduction	1
4	Notation	1
5	Module Decomposition	1
6	GUI Module	3
6.1	GUI Module	3
6.2	Uses	3
6.3	Syntax	3
6.3.1	Exported Constants	3
6.3.2	Exported Access Programs	3
6.4	Semantics	3
6.4.1	State Variables	3
6.4.2	Environment Variables	3
6.4.3	Assumptions	3
6.4.4	Access Routine Semantics	3
6.4.5	Local Functions	4
7	MIS of Audio File Input Module	4
7.1	Audio File Input Module	4
7.2	Uses	4
7.3	Syntax	4
7.3.1	Exported Constants	4
7.3.2	Exported Access Programs	4
7.4	Semantics	4
7.4.1	State Variables	4
7.4.2	Environment Variables	4
7.4.3	Assumptions	5
7.4.4	Access Routine Semantics	5
7.4.5	Local Functions	5
8	MIS of Search Query Module	5
8.1	Search Query Module	5
8.2	Uses	5
8.3	Syntax	5
8.3.1	Exported Constants	5
8.3.2	Exported Access Programs	6

8.4	Semantics	6
8.4.1	State Variables	6
8.4.2	Environment Variables	6
8.4.3	Assumptions	6
8.4.4	Access Routine Semantics	6
8.4.5	Local Functions	6
9	MIS of Client Communication Module	7
9.1	Client Communication Module	7
9.2	Uses	7
9.3	Syntax	7
9.3.1	Exported Constants	7
9.3.2	Exported Access Programs	7
9.4	Semantics	7
9.4.1	State Variables	7
9.4.2	Environment Variables	7
9.4.3	Assumptions	7
9.4.4	Access Routine Semantics	8
9.4.5	Local Functions	8
10	MIS of Server Communication Module	8
10.1	Server Communication Module	8
10.2	Uses	8
10.3	Syntax	8
10.3.1	Exported Constants	8
10.3.2	Exported Access Programs	9
10.4	Semantics	9
10.4.1	State Variables	9
10.4.2	Environment Variables	9
10.4.3	Assumptions	9
10.4.4	Access Routine Semantics	9
10.4.5	Local Functions	9
11	MIS of Driver Module	10
11.1	Driver Module	10
11.2	Uses	10
11.3	Syntax	10
11.3.1	Exported Constants	10
11.3.2	Exported Access Programs	10
11.4	Semantics	10
11.4.1	State Variables	10
11.4.2	Environment Variables	10
11.4.3	Assumptions	10

11.4.4	Access Routine Semantics	11
11.4.5	Local Functions	11
12	MIS of Audio Lookup Module	11
12.1	Module	11
12.2	Uses	11
12.3	Syntax	12
12.3.1	Exported Constants	12
12.3.2	Exported Access Programs	12
12.4	Semantics	12
12.4.1	State Variables	12
12.4.2	Environment Variables	12
12.4.3	Assumptions	12
12.4.4	Access Routine Semantics	12
12.4.5	Local Functions	13
13	MIS of Featurizer Module	13
13.1	Featurizer Module	13
13.2	Uses	14
13.3	Syntax	14
13.3.1	Exported Constants	14
13.3.2	Exported Access Programs	14
13.4	Semantics	14
13.4.1	State Variables	14
13.4.2	Environment Variables	14
13.4.3	Assumptions	14
13.4.4	Access Routine Semantics	15
13.4.5	Local Functions	15
14	MIS of Tempo (BPM) Feature Extraction Module	16
14.1	Tempo (BPM) Feature Extraction Module	16
14.2	Uses	16
14.3	Syntax	16
14.3.1	Exported Constants	16
14.3.2	Exported Access Programs	16
14.4	Semantics	16
14.4.1	State Variables	16
14.4.2	Environment Variables	16
14.4.3	Assumptions	16
14.4.4	Access Routine Semantics	16
14.4.5	Local Functions	16

15 MIS of Key and Scale Feature Extraction Module	17
15.1 Key and Scale Feature Extraction Module	17
15.2 Uses	17
15.3 Syntax	17
15.3.1 Exported Constants	17
15.3.2 Exported Access Programs	17
15.4 Semantics	17
15.4.1 State Variables	17
15.4.2 Environment Variables	17
15.4.3 Assumptions	17
15.4.4 Access Routine Semantics	17
15.4.5 Local Functions	18
16 MIS of Instrument Type Feature Extraction Module	18
16.1 Instrument Type Feature Extraction Module	18
16.2 Uses	18
16.3 Syntax	18
16.3.1 Exported Constants	18
16.3.2 Exported Access Programs	18
16.4 Semantics	18
16.4.1 State Variables	18
16.4.2 Environment Variables	18
16.4.3 Assumptions	18
16.4.4 Access Routine Semantics	18
16.4.5 Local Functions	19
17 MIS of Vocal Gender Feature Extraction Module	19
17.1 MIS of Vocal Gender Feature Extraction Module	19
17.2 Uses	19
17.3 Syntax	19
17.3.1 Exported Constants	19
17.3.2 Exported Access Programs	19
17.4 Semantics	19
17.4.1 State Variables	19
17.4.2 Environment Variables	19
17.4.3 Assumptions	20
17.4.4 Access Routine Semantics	20
17.4.5 Local Functions	20
18 MIS of Dynamic Range Feature Extraction Module	20
18.1 Dynamic Range Feature Extraction Module	20
18.2 Uses	20
18.3 Syntax	20

18.3.1	Exported Constants	20
18.3.2	Exported Access Programs	20
18.4	Semantics	20
18.4.1	State Variables	20
18.4.2	Environment Variables	21
18.4.3	Assumptions	21
18.4.4	Access Routine Semantics	21
18.4.5	Local Functions	21
19	MIS of Instrumentalness Feature Extraction Module	21
19.1	Instrumentalness Feature Extraction Module	21
19.2	Uses	21
19.3	Syntax	21
19.3.1	Exported Constants	21
19.3.2	Exported Access Programs	22
19.4	Semantics	22
19.4.1	State Variables	22
19.4.2	Environment Variables	22
19.4.3	Assumptions	22
19.4.4	Access Routine Semantics	22
19.4.5	Local Functions	22
20	MIS of Contour Feature Extraction Module	22
20.1	Contour Feature Extraction Module	22
20.2	Uses	22
20.3	Syntax	23
20.3.1	Exported Constants	23
20.3.2	Exported Access Programs	23
20.4	Semantics	23
20.4.1	State Variables	23
20.4.2	Environment Variables	23
20.4.3	Assumptions	23
20.4.4	Access Routine Semantics	23
20.4.5	Local Functions	23
21	MIS of Mood Feature Extraction Module	23
21.1	Mood Feature Extraction Module	23
21.2	Uses	23
21.3	Syntax	24
21.3.1	Exported Constants	24
21.3.2	Exported Access Programs	24
21.4	Semantics	24
21.4.1	State Variables	24

21.4.2	Environment Variables	24
21.4.3	Assumptions	24
21.4.4	Access Routine Semantics	24
21.4.5	Local Functions	24
22	MIS of Genre Feature Extraction Module	24
22.1	Module	24
22.2	Uses	25
22.3	Syntax	25
22.3.1	Exported Constants	25
22.3.2	Exported Access Programs	25
22.4	Semantics	25
22.4.1	State Variables	25
22.4.2	Environment Variables	25
22.4.3	Assumptions	25
22.4.4	Access Routine Semantics	25
22.4.5	Local Functions	26
23	MIS of Recommendation Module	26
23.1	Recommendation Module	26
23.2	Uses	26
23.3	Syntax	27
23.3.1	Exported Constants	27
23.3.2	Exported Access Programs	27
23.4	Semantics	27
23.4.1	State Variables	27
23.4.2	Environment Variables	27
23.4.3	Assumptions	27
23.4.4	Access Routine Semantics	27
23.4.5	Local Functions	27
24	MIS of Program Results Interface Module	27
24.1	Program Results Interface Module	27
24.2	Uses	27
24.3	Syntax	28
24.3.1	Exported Constants	28
24.3.2	Exported Access Programs	28
24.4	Semantics	28
24.4.1	State Variables	28
24.4.2	Environment Variables	28
24.4.3	Assumptions	28
24.4.4	Access Routine Semantics	28
24.4.5	Local Functions	29

3 Introduction

The following document details the Module Interface Specifications for [Fill in your project name and description —SS]

Complementary documents include the System Requirement Specifications and Module Guide. The full documentation and implementation can be found at [provide the url for your repo —SS]

4 Notation

[You should describe your notation. You can use what is below as a starting point. —SS]

The structure of the MIS for modules comes from Hoffman and Strooper (1995), with the addition that template modules have been adapted from Ghezzi et al. (2003). The mathematical notation comes from Chapter 3 of Hoffman and Strooper (1995). For instance, the symbol $:=$ is used for a multiple assignment statement and conditional rules follow the form $(c_1 \Rightarrow r_1 | c_2 \Rightarrow r_2 | \dots | c_n \Rightarrow r_n)$.

The following table summarizes the primitive data types used by Software Engineering.

Data Type	Notation	Description
character	char	a single symbol or digit
integer	\mathbb{Z}	a number without a fractional component in $(-\infty, \infty)$
natural number	\mathbb{N}	a number without a fractional component in $[1, \infty)$
real	\mathbb{R}	any number in $(-\infty, \infty)$

The specification of Software Engineering uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, Software Engineering uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

5 Module Decomposition

The following table is taken directly from the Module Guide document for this project.

Level 1	Level 2
Hardware-Hiding	
Behaviour-Hiding	GUI Module Audio File Input Module Search Query Module Client Communication Module Server Communication Module Driver Module Tempo (BPM) Feature Extraction Module Key and Scale Feature Extraction Module Instrument Type Feature Extraction Module Vocal Gender Feature Extraction Module Dynamic Range Feature Extraction Module Instrumentalness Feature Extraction Module Contour Feature Extraction Module Mood Feature Extraction Module Recommendation Module Program Results Interface
Software Decision	Database Spotify API Deezer API Genre Feature Module

Table 1: Module Hierarchy

6 GUI Module

6.1 GUI Module

6.2 Uses

- First-Match Text Field Input Module
- URL Input module
- Audio File Input Module
- Spotify Query Search & Select

6.3 Syntax

6.3.1 Exported Constants

N/A

6.3.2 Exported Access Programs

Name	In	Out	Exceptions
Consolidate Inputs	Up to 4 collection(s) of reference(s) to track(s)	Merged collection of track references	-

6.4 Semantics

6.4.1 State Variables

- Data type of the collection of track reference(s)

6.4.2 Environment Variables

N/A

6.4.3 Assumptions

N/A

6.4.4 Access Routine Semantics

consolidate_inputs():

- output: parses the user input and returns the songs that are sent to be processed

6.4.5 Local Functions

- `parse_wav_file(file)`

—

- `parse_url(url)`

—

- `parse_text(text)`

—

7 MIS of Audio File Input Module

7.1 Audio File Input Module

User inputs an audio file to the system to analyze.

7.2 Uses

N/A

7.3 Syntax

7.3.1 Exported Constants

N/A

7.3.2 Exported Access Programs

Name	In	Out	Exceptions
On Input Button Press	Audio File	Collection of song reference(s)	Invalid File Type

7.4 Semantics

7.4.1 State Variables

- Collection of track reference(s)

7.4.2 Environment Variables

N/A

7.4.3 Assumptions

- User has a properly named Audio File.
- User audio file input is actually a song.

7.4.4 Access Routine Semantics

[accessProg —SS]():

- transition: [if appropriate —SS]
- output: [if appropriate —SS]
- exception: [if appropriate —SS]

[A module without environment variables or state variables is unlikely to have a state transition. In this case a state transition can only occur if the module is changing the state of another module. —SS]

[Modules rarely have both a transition and an output. In most cases you will have one or the other. —SS]

7.4.5 Local Functions

[As appropriate —SS] [These functions are for the purpose of specification. They are not necessarily something that is going to be implemented explicitly. Even if they are implemented, they are not exported; they only have local scope. —SS]

8 MIS of Search Query Module

8.1 Search Query Module

User inputs a song and that is turned into a spotify search query where the top 10 matches are available for user to select

8.2 Uses

N/A

8.3 Syntax

8.3.1 Exported Constants

N/A

8.3.2 Exported Access Programs

Name	In	Out	Exceptions
Search Query Request	text input	top 10 matches from spotify query search	-
Output result selection	user selection	Collection containing track reference	-

8.4 Semantics

8.4.1 State Variables

- Collection containing track reference

8.4.2 Environment Variables

- Spotify Client ID
- Spotify Client Secret

8.4.3 Assumptions

N/A

8.4.4 Access Routine Semantics

[accessProg —SS]():

- transition: [if appropriate —SS]
- output: [if appropriate —SS]
- exception: [if appropriate —SS]

[A module without environment variables or state variables is unlikely to have a state transition. In this case a state transition can only occur if the module is changing the state of another module. —SS]

[Modules rarely have both a transition and an output. In most cases you will have one or the other. —SS]

8.4.5 Local Functions

[As appropriate —SS] [These functions are for the purpose of specification. They are not necessarily something that is going to be implemented explicitly. Even if they are implemented, they are not exported; they only have local scope. —SS]

9 MIS of Client Communication Module

9.1 Client Communication Module

User inputs a song and that is turned into a spotify search query where the top 10 matches are available for user to select

9.2 Uses

N/A

9.3 Syntax

9.3.1 Exported Constants

N/A

9.3.2 Exported Access Programs

Name	In	Out	Exceptions
Search Query Request	text input	top 10 matches from spotify query search	-
Output re- sult selec- tion	user selection	Collection containing track reference	-

9.4 Semantics

9.4.1 State Variables

- Collection containing track reference

9.4.2 Environment Variables

- Spotify Client ID
- Spotify Client Secret

9.4.3 Assumptions

N/A

9.4.4 Access Routine Semantics

[accessProg —SS]():

- transition: [if appropriate —SS]
- output: [if appropriate —SS]
- exception: [if appropriate —SS]

[A module without environment variables or state variables is unlikely to have a state transition. In this case a state transition can only occur if the module is changing the state of another module. —SS]

[Modules rarely have both a transition and an output. In most cases you will have one or the other. —SS]

9.4.5 Local Functions

[As appropriate —SS] [These functions are for the purpose of specification. They are not necessarily something that is going to be implemented explicitly. Even if they are implemented, they are not exported; they only have local scope. —SS]

10 MIS of Server Communication Module

10.1 Server Communication Module

User inputs a song and that is turned into a spotify search query where the top 10 matches are available for user to select

10.2 Uses

N/A

10.3 Syntax

10.3.1 Exported Constants

N/A

10.3.2 Exported Access Programs

Name	In	Out	Exceptions
Search Query Request	text input	top 10 matches from spotify query search	N/A
Output result selection	user selection	Collection containing track reference	N/A

10.4 Semantics

10.4.1 State Variables

- Collection containing track reference

10.4.2 Environment Variables

- Spotify Client ID
- Spotify Client Secret

10.4.3 Assumptions

N/A

10.4.4 Access Routine Semantics

[accessProg —SS]():

- transition: [if appropriate —SS]
- output: [if appropriate —SS]
- exception: [if appropriate —SS]

[A module without environment variables or state variables is unlikely to have a state transition. In this case a state transition can only occur if the module is changing the state of another module. —SS]

[Modules rarely have both a transition and an output. In most cases you will have one or the other. —SS]

10.4.5 Local Functions

[As appropriate —SS] [These functions are for the purpose of specification. They are not necessarily something that is going to be implemented explicitly. Even if they are implemented, they are not exported; they only have local scope. —SS]

11 MIS of Driver Module

11.1 Driver Module

Controls all the functions of the server

11.2 Uses

- Featurizer Module
- Server Communication Module
- Database Module
- Recommendation Module
- Deezer API Module

11.3 Syntax

11.3.1 Exported Constants

N/A

11.3.2 Exported Access Programs

Name	In	Out	Exceptions
-	-	-	-

11.4 Semantics

11.4.1 State Variables

N/A

11.4.2 Environment Variables

- Deezer App ID
- Deezer Secret

11.4.3 Assumptions

N/A

11.4.4 Access Routine Semantics

`get_features()`:

- output: Invokes the Featurizer Module to get the features for the requested song

`generate_deezer_connection()`:

- output: Creates a connection to the deezer api that can be called be used in other modules

`unpack_request()`:

- output: Converts the request from the Server Communication Module into a song object that can be passed to the Featurizer Module

`get_recommendations()`:

- output: Invokes the Recommendation Module to get the song recommendations

`query_database()`:

- output: Asks the database if the song in the request already exists in the databse, preventing the re-computation of song features

`package_response()`:

- output: Converts the song recommendations into a response object that the Server Communication Module can send back to the Client Communication Module

11.4.5 Local Functions

N/A

12 MIS of Audio Lookup Module

12.1 Module

Audio Lookup Module

12.2 Uses

- Driver Module: Receives the International Standard Recording Code (ISRC) from the Driver Module. - Deezer API: Responsible for retrieving the audio file, genre, and associated metadata for the provided ISRC.

12.3 Syntax

12.3.1 Exported Constants

None.

12.3.2 Exported Access Programs

Name	In	Out	Exceptions
getAudioDetails	isrc: String	audioDetails: dioDetails	AuthenticationFailure, APIRequestError

12.4 Semantics

12.4.1 State Variables

- **isrc**: The International Standard Recording Code for identifying the requested song. - **authToken**: The authentication token used for accessing the Deezer API. - **audioDetails**: A structure containing the audio file, genre, and other metadata.

12.4.2 Environment Variables

- The Audio Lookup Module interacts with the Deezer API over the internet to fetch the requested audio file, genre, and metadata.

12.4.3 Assumptions

- The ISRC provided by the Driver Module is valid and corresponds to an existing song. - The authentication token for the Deezer API is valid and not expired. - The Deezer API is available and operational at the time of the request.

12.4.4 Access Routine Semantics

getAudioDetails(isrc: String):

- **Transition**: - Authenticates with the Deezer API using **authToken**. - Sends a request to the Deezer API with the provided ISRC to retrieve the audio file, genre, and metadata.
- **Output**: - Returns the **audioDetails** structure, which includes:
 - **audioFile**: The retrieved audio file.
 - **genre**: The genre of the song.
 - **metadata**: Additional metadata such as song title, artist, and album information.

- **Exceptions:** - `AuthenticationFailure`: Raised if the API authentication fails (e.g., invalid or expired token). - `APIRequestError`: Raised if there is an issue with the API request, such as a network error or invalid ISRC.

12.4.5 Local Functions

authenticateWithDeezer:

- Purpose: Handles authentication with the Deezer API and retrieves a valid `authToken`.
- Input: None.
- Output: `authToken`.

fetchAudioFile:

- Purpose: Sends the ISRC to the Deezer API and retrieves the corresponding audio file.
- Input: `isrc`.
- Output: `audioFile`.

fetchGenreAndMetadata:

- Purpose: Retrieves the genre and metadata associated with the song from the Deezer API.
- Input: `isrc`.
- Output: `genre, metadata`.

13 MIS of Featurizer Module

13.1 Featurizer Module

The Featurizer Module is responsible for extracting 9 distinct feature values from audio files:

- Tempo
- Key and Scale
- Instrument Type
- Vocal Gender
- Dynamic Range
- Instrumentalness

- Contour
- Mood
- Genre

The module invokes sub-feature modules to compute these feature values. It consolidates the results into a single **FeatureValues** object and returns it to the Driver Module.

13.2 Uses

- ****Driver Module****: Sends requests to the Featurizer Module and receives feature values.
- ****Sub-Feature Modules****: Each responsible for computing a specific feature (e.g., Tempo, Key and Scale).

13.3 Syntax

13.3.1 Exported Constants

None.

13.3.2 Exported Access Programs

Name	In	Out	Exceptions
extractFeatures	audioFile: AudioFile	featureValues: FeatureValues	Fea- UnsupportedFileFormatException

13.4 Semantics

13.4.1 State Variables

- **audioFile**: The input audio file provided for feature extraction.
- **featureValues**: An object containing the extracted values for all 9 features.

13.4.2 Environment Variables

None.

13.4.3 Assumptions

- Input audio files are in supported formats (e.g., WAV, MP3).
- All sub-feature modules are functional and return valid outputs for their respective features.

13.4.4 Access Routine Semantics

extractFeatures:

- **Precondition:**
 - `audioFile` is a valid audio file in a supported format.
- **Postcondition:**
 - `featureValues` contains valid results for all 9 features:
 - * Tempo
 - * Key and Scale
 - * Instrument Type
 - * Vocal Gender
 - * Dynamic Range
 - * Instrumentalness
 - * Contour
 - * Mood
 - * Genre
 - If the input file format is unsupported, an `UnsupportedFileFormatException` is raised.

13.4.5 Local Functions

invokeSubFeatureModule:

- Purpose: Calls a specific sub-feature module (e.g., for Tempo, Genre) and retrieves its computed value.
- Input: `audioFile`, `featureType`
- Output: Value of the requested feature.

aggregateFeatureValues:

- Purpose: Consolidates all feature values into a `FeatureValues` object.
- Input: A list of feature values retrieved from sub-feature modules.
- Output: `FeatureValues` object.

14 MIS of Tempo (BPM) Feature Extraction Module

14.1 Tempo (BPM) Feature Extraction Module

14.2 Uses

N/A

14.3 Syntax

14.3.1 Exported Constants

N/A

14.3.2 Exported Access Programs

Name	In	Out	Exceptions
Extract Tempo	Audio time series (np.ndarray)	Song Tempo $\in \mathbb{R}$	-

14.4 Semantics

14.4.1 State Variables

N/A

14.4.2 Environment Variables

N/A

14.4.3 Assumptions

Valid audio file with coherent song information.

14.4.4 Access Routine Semantics

ExtractTempo():

- transition: N/A
- output: Song_Tempo := ExtractTempo(Audio_Time_Series)
- exception: N/A

14.4.5 Local Functions

N/A

15 MIS of Key and Scale Feature Extraction Module

15.1 Key and Scale Feature Extraction Module

15.2 Uses

N/A

15.3 Syntax

15.3.1 Exported Constants

N/A

15.3.2 Exported Access Programs

Name	In	Out	Exceptions
Extract Key & Scale	Audio time series (np.ndarray)	Song Key, Scale $\in \mathbb{Z}^2$	-

15.4 Semantics

15.4.1 State Variables

N/A

15.4.2 Environment Variables

N/A

15.4.3 Assumptions

Valid audio file with coherent song information.

15.4.4 Access Routine Semantics

ExtractKeyScale():

- transition: N/A
- output: Song_Key, Song_Scale := ExtractKeyScale(Audio_Time_Series)
- exception: N/A

15.4.5 Local Functions

N/A

16 MIS of Instrument Type Feature Extraction Module

16.1 Instrument Type Feature Extraction Module

16.2 Uses

N/A

16.3 Syntax

16.3.1 Exported Constants

N/A

16.3.2 Exported Access Programs

Name	In	Out	Exceptions
Extract Instrument Type	Audio time series (np.ndarray)	Instrument Type $\in \mathbb{Z}^k$	-

16.4 Semantics

16.4.1 State Variables

N/A

16.4.2 Environment Variables

N/A

16.4.3 Assumptions

Valid audio file with coherent song information.

16.4.4 Access Routine Semantics

ExtractInstrumentType():

- transition: N/A

- output: `Instrument_Type := ExtractInstrumentType(Audio_Time_Series)`
- exception: N/A

16.4.5 Local Functions

N/A

17 MIS of Vocal Gender Feature Extraction Module

17.1 MIS of Vocal Gender Feature Extraction Module

This feature seeks to quantify whether the voices features in the inputted audio file are largely more feminine or masculine sounding. This is represented by a float with a range between 0 and 1 where 0 means only "masculine" sound signatures are contained and 1 means only "feminine" sounds, where values in-between represent a blend.

17.2 Uses

N/A

17.3 Syntax

17.3.1 Exported Constants

N/A

17.3.2 Exported Access Programs

Name	In	Out	Exceptions
Extract Vocal Gender	Audio time series (np.ndarray)	Vocal Gender $\in \mathbb{R}$	-

17.4 Semantics

17.4.1 State Variables

N/A

17.4.2 Environment Variables

N/A

17.4.3 Assumptions

Valid audio file with coherent song information.

17.4.4 Access Routine Semantics

ExtractVocalGender():

- transition: N/A
- output: `Vocal_Gender := ExtractVocalGender(Audio_Time_Series)`
- exception: N/A

17.4.5 Local Functions

N/A

18 MIS of Dynamic Range Feature Extraction Module

18.1 Dynamic Range Feature Extraction Module

Feature extracts the range of sounds (difference between peak and trough) of the audio signal.

18.2 Uses

N/A

18.3 Syntax

18.3.1 Exported Constants

N/A

18.3.2 Exported Access Programs

Name	In	Out	Exceptions
Extract	Audio time series	Dynamic Range	-
Dynamic Range	(np.ndarray)	(decibels) $\in \mathbb{R}$	

18.4 Semantics

18.4.1 State Variables

N/A

18.4.2 Environment Variables

N/A

18.4.3 Assumptions

Valid audio file with coherent song information.

18.4.4 Access Routine Semantics

`ExtractDynamicRange()`:

- transition: N/A
- output: `Dynamic_Range := ExtractDynamicRange(Audio_Time_Series)`
- exception: N/A

18.4.5 Local Functions

N/A

19 MIS of Instrumentalness Feature Extraction Module

19.1 Instrumentalness Feature Extraction Module

Extracts the how prominent instrumental sounds are within the song. Represented by a float variable where the range is between 0 and 1, where higher values mean more instrumental sounds and lower means less. Eg, 0 would mean an acapella piece of music, 1 would be something that purely features instruments.

19.2 Uses

N/A

19.3 Syntax

19.3.1 Exported Constants

N/A

19.3.2 Exported Access Programs

Name	In	Out	Exceptions
ExtractInstrumentalness	Audio time series (np.ndarray)	Instrumentalness $\in \mathbb{R}$	-

19.4 Semantics

19.4.1 State Variables

N/A

19.4.2 Environment Variables

N/A

19.4.3 Assumptions

Valid audio file with coherent song information.

19.4.4 Access Routine Semantics

ExtractInstrumentalness():

- transition: N/A
- output: `Instrumentalness := ExtractInstrumentalness(Audio_Time_Series)`
- exception: N/A

19.4.5 Local Functions

N/A

20 MIS of Contour Feature Extraction Module

20.1 Contour Feature Extraction Module

20.2 Uses

N/A

20.3 Syntax

20.3.1 Exported Constants

N/A

20.3.2 Exported Access Programs

Name	In	Out	Exceptions
Extract	Audio time series	Contour	-
Melodic	(np.ndarray)		
Contour			

20.4 Semantics

20.4.1 State Variables

N/A

20.4.2 Environment Variables

N/A

20.4.3 Assumptions

Valid audio file with coherent song information.

20.4.4 Access Routine Semantics

ExtractMelodicContour():

- transition: N/A
- output: `Contour := ExtractMelodicContour(Audio_Time_Series)`
- exception: N/A

20.4.5 Local Functions

N/A

21 MIS of Mood Feature Extraction Module

21.1 Mood Feature Extraction Module

21.2 Uses

N/A

21.3 Syntax

21.3.1 Exported Constants

N/A

21.3.2 Exported Access Programs

Name	In	Out	Exceptions
Extract	Audio time series	Mood $\in \mathbb{Z}$	-
Mood	(np.ndarray)		

21.4 Semantics

21.4.1 State Variables

N/A

21.4.2 Environment Variables

N/A

21.4.3 Assumptions

Valid audio file with coherent song information.

21.4.4 Access Routine Semantics

ExtractMood():

- transition: N/A
- output: Mood := ExtractMood(Audio_Time_Series)
- exception: N/A

21.4.5 Local Functions

N/A

22 MIS of Genre Feature Extraction Module

22.1 Module

Genre Feature Extraction Module

22.2 Uses

- Featurizer Module: Receives metadata from the Featurizer Module and extracts the genre attribute from it. - Metadata Structure: Utilizes the metadata structure to locate and retrieve the genre attribute.

22.3 Syntax

22.3.1 Exported Constants

None.

22.3.2 Exported Access Programs

Name	In	Out	Exceptions
extractGenre	metadata: Metadata	genre: String	MissingGenreException, Invalid-Meta-dataException

22.4 Semantics

22.4.1 State Variables

- **metadata:** The metadata provided by the Featurizer Module, which contains the genre attribute.

22.4.2 Environment Variables

None.

22.4.3 Assumptions

- The metadata provided by the Featurizer Module is valid and includes the genre attribute.
- The genre attribute in the metadata is correctly formatted and accessible.

22.4.4 Access Routine Semantics

extractGenre(metadata: Metadata):

- **Transition:** - Extracts the genre attribute from the provided metadata.
- **Output:** - Returns the extracted genre as a string.

- **Exceptions:** - `MissingGenreException`: Raised if the genre attribute is not found in the metadata. - `InvalidMetadataException`: Raised if the provided metadata is improperly formatted or invalid.

22.4.5 Local Functions

validateMetadata:

- Purpose: Ensures the provided metadata is valid and contains the necessary attributes.
- Input: `metadata`.
- Output: Boolean (true if valid, false otherwise).

retrieveGenre:

- Purpose: Locates and retrieves the genre attribute from the metadata.
- Input: `metadata`.
- Output: `genre` (String).

23 MIS of Recommendation Module

23.1 Recommendation Module

23.2 Uses

- Tempo (BPM) Feature Extraction Module
- Key and Scale Feature Extraction Module
- Instrument Type Feature Extraction Module
- Vocal Gender Feature Extraction Module
- Dynamic Range Feature Extraction Module
- Instrumentalness Feature Extraction Module
- Contour Feature Extraction Module
- Mood Feature Extraction Module
- Driver Module
- Spotify API

23.3 Syntax

23.3.1 Exported Constants

N/A

23.3.2 Exported Access Programs

Name	In	Out	Exceptions
Generate	Song_Features	Rec_Tracks	-
Recs	(np.ndarray ∈ Feature)	np.ndarray ∈ Track	

23.4 Semantics

23.4.1 State Variables

N/A

23.4.2 Environment Variables

N/A

23.4.3 Assumptions

N/A

23.4.4 Access Routine Semantics

GenerateRecommendations():

- transition: N/A
- output: Recommended_Songs : = GenerateRecommendations(Song_Features)
- exception: N/A

23.4.5 Local Functions

N/A

24 MIS of Program Results Interface Module

24.1 Program Results Interface Module

24.2 Uses

- Spotify API

24.3 Syntax

24.3.1 Exported Constants

N/A

24.3.2 Exported Access Programs

Name	In	Out	Exceptions
Generate Spotify Embed	Rec_Track (np.ndarray ∈ Track)	Tracks_Embed (Spo- tify Embed Element)	-
Display Features	Song_Features (np.ndarray ∈ Feature)	Features_Display (UI Image)	-

24.4 Semantics

24.4.1 State Variables

N/A

24.4.2 Environment Variables

N/A

24.4.3 Assumptions

N/A

24.4.4 Access Routine Semantics

GenerateSpotifyEmbed():

- transition: N/A
- output: Tracks_Embed_Widget: = GenerateSpotifyEmbed(Tracks)
- exception: N/A

DisplayFeatures():

- transition: N/A
- output: Features_Display: = DisplayFeatures(Song_Features)
- exception: N/A

24.4.5 Local Functions

N/A

References

- Carlo Ghezzi, Mehdi Jazayeri, and Dino Mandrioli. *Fundamentals of Software Engineering*. Prentice Hall, Upper Saddle River, NJ, USA, 2nd edition, 2003.
- Daniel M. Hoffman and Paul A. Strooper. *Software Design, Automated Testing, and Maintenance: A Practical Approach*. International Thomson Computer Press, New York, NY, USA, 1995. URL <http://citeseer.ist.psu.edu/428727.html>.

25 Appendix

[Extra information if required —SS]

Appendix — Reflection

[Not required for CAS 741 projects —SS]

The information in this section will be used to evaluate the team members on the graduate attribute of Problem Analysis and Design.

The purpose of reflection questions is to give you a chance to assess your own learning and that of your group as a whole, and to find ways to improve in the future. Reflection is an important part of the learning process. Reflection is also an essential component of a successful software development process.

Reflections are most interesting and useful when they're honest, even if the stories they tell are imperfect. You will be marked based on your depth of thought and analysis, and not based on the content of the reflections themselves. Thus, for full marks we encourage you to answer openly and honestly and to avoid simply writing “what you think the evaluator wants to hear.”

Please answer the following questions. Some questions can be answered on the team level, but where appropriate, each team member should write their own response:

1. What went well while writing this deliverable?
2. What pain points did you experience during this deliverable, and how did you resolve them?
3. Which of your design decisions stemmed from speaking to your client(s) or a proxy (e.g. your peers, stakeholders, potential users)? For those that were not, why, and where did they come from?
4. While creating the design doc, what parts of your other documents (e.g. requirements, hazard analysis, etc), if any, needed to be changed, and why?
5. What are the limitations of your solution? Put another way, given unlimited resources, what could you do to make the project better? (LO_ProbSolutions)
6. Give a brief overview of other design solutions you considered. What are the benefits and tradeoffs of those other designs compared with the chosen design? From all the potential options, why did you select the documented design? (LO_Explores)