

Harbor Life in Jaffa

Input file: standard input
Output file: standard output
Time limit: 10 seconds
Memory limit: 256 megabytes



Aamer immerses himself in the vibrant harbor life of Jaffa, where maritime activity has shaped its identity as a gateway for trade and cultural interaction. Navigating through its bustling waters, Jaffa's strategic importance and historical role as a hub of connectivity come alive amidst the ebb and flow of commerce.

You are given an array a of n integer numbers. You need to process q queries each of which follows one of the following formats:

- 1 $l\ r\ x$. For each integer number a_i where $(l \leq i \leq r)$, apply $a_i := a_i \& x$, where $\&$ is the bitwise AND operator.
- 2 $i\ x$. Apply $a_i := x$.
- 3 $l\ r$. For the subarray $a_l, a_{l+1}, a_{l+2} \dots a_r$, print the maximum XOR of a subset of integers of the subarray.

A subarray is a contiguous part of the array.

A subset of an array is a tuple that can be obtained from the array by removing some (possibly all) elements of it.

Input

The first line of the input contains a single integer number t ($1 \leq t \leq 10^4$) — The number of test cases.

The first line of each test case contains two space separated integer numbers n and q ($1 \leq n, q \leq 10^5$). The number of integer numbers of a and the number of queries, respectively.

The second line of each test contains n space separated integer numbers a_i ($1 \leq a_i \leq 10^5$), where a_i is the i — th integer number of a .

Each of the following q lines follows one of the following formats.

- 1 $l\ r\ x$ ($1 \leq l \leq r \leq n, 1 \leq x \leq 10^5$).
- 2 $i\ x$. ($1 \leq i \leq n, 1 \leq x \leq 10^5$).
- 3 $l\ r$. ($1 \leq l \leq r \leq n$).

It is guaranteed that the sum of n over all of the test cases does not exceed 10^5 .

It is guaranteed that the sum of q over all of the test cases does not exceed 10^5 .

Output

For each query of the third type for each test case, print a single line containing a single integer number.
The maximum XOR of a subset of integers of the subarray given in the query.

Example

standard input	standard output
1	8
5 5	11
4 1 8 9 6	11
1 1 5 8	
3 2 4	
2 2 3	
3 2 4	
3 2 4	