

PROBLEMS SUBMIT STATUS STANDINGS CUSTOM TEST

D. Kefa and Dishes

time limit per test: 2 seconds
memory limit per test: 256 megabytes

When Kefa came to the restaurant and sat at a table, the waiter immediately brought him the menu. There were n dishes. Kefa knows that he needs exactly m dishes. But at that, he doesn't want to order the same dish twice to taste as many dishes as possible.

Kefa knows that the i -th dish gives him a_i units of satisfaction. But some dishes do not go well together and some dishes go very well together. Kefa set to himself k rules of eating food of the following type — if he eats dish x exactly before dish y (there should be no other dishes between x and y), then his satisfaction level raises by c .

Of course, our parrot wants to get some maximal possible satisfaction from going to the restaurant. Help him in this hard task!

Input

The first line of the input contains three space-separated numbers, n , m and k ($1 \leq m \leq n \leq 18$, $0 \leq k \leq n * (n - 1)$) — the number of dishes on the menu, the number of portions Kefa needs to eat to get full and the number of eating rules.

The second line contains n space-separated numbers a_i , ($0 \leq a_i \leq 10^9$) — the satisfaction he gets from the i -th dish.

Next k lines contain the rules. The i -th rule is described by the three numbers x_i , y_i and c_i ($1 \leq x_i, y_i \leq n$, $0 \leq c_i \leq 10^9$). That means that if you eat dish x_i right before dish y_i , then the Kefa's satisfaction increases by c_i . It is guaranteed that there are no such pairs of indexes i and j ($1 \leq i < j \leq k$), that $x_i = x_j$ and $y_i = y_j$.

Output

In the single line of the output print the maximum satisfaction that Kefa can get from going to the restaurant.

Examples

input	Copy
2 2 1 1 1 2 1 1	
output	Copy
3	

input	Copy
4 3 2 1 2 3 4 2 1 5 3 4 2	
output	Copy
12	

Note

In the first sample it is best to first eat the second dish, then the first one. Then we get one unit of satisfaction for each dish and plus one more for the rule.

In the second test the fitting sequences of choice are 4 2 1 or 2 1 4. In both cases we get satisfaction 7 for dishes and also, if we fulfill rule 1, we get an additional satisfaction 5.

Codeforces Round 321 (Div. 2)

Finished

Practice

→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

Start virtual contest

→ Clone Contest to Mashup

You can clone this contest to a mashup.

Clone Contest

→ Submit?

Language: GNU G++20 13.2 (64 bit, win

Choose file: Choose File No file chosen

Submit

→ Last submissions

Submission	Time	Verdict
280385983	Sep/09/2024 04:52	Accepted

→ Problem tags

bitmasks dp *1800

No tag edit access

→ Contest materials

Announcement

Tutorial