

HOME TOP CATALOG CONTESTS GYM PROBLEMSET GROUPS RATING EDU API CALENDAR HELP

PROBLEMS SUBMIT CODE MY SUBMISSIONS STATUS STANDINGS CUSTOM INVOCATION

#### I. Summarize to the Power of Two

time limit per test: 3 seconds memory limit per test: 256 megabytes

A sequence  $a_1, a_2, \ldots, a_n$  is called good if, for each element  $a_i$ , there exists an element  $a_j$  ( $i \neq j$ ) such that  $a_i + a_j$  is a power of two (that is,  $2^d$  for some non-negative integer d).

For example, the following sequences are good:

- [5,3,11] (for example, for  $a_1=5$  we can choose  $a_2=3$ . Note that their sum is a power of two. Similarly, such an element can be found for  $a_2$  and  $a_3$ ),
- [1, 1, 1, 1023]
- [7, 39, 89, 25, 89],
- []

Note that, by definition, an empty sequence (with a length of 0) is good.

For example, the following sequences are not good:

- [16] (for  $a_1=16$ , it is impossible to find another element  $a_i$  such that their sum is a power of two),
- [4,16] (for  $a_1=4$ , it is impossible to find another element  $a_j$  such that their sum is a power of two),
- [1,3,2,8,8,8] (for  $a_3=2$ , it is impossible to find another element  $a_j$  such that their sum is a power of two).

You are given a sequence  $a_1, a_2, \ldots, a_n$ . What is the minimum number of elements you need to remove to make it good? You can delete an arbitrary set of elements.

#### Input

The first line contains the integer n ( $1 \le n \le 120000$ ) — the length of the given sequence.

The second line contains the sequence of integers  $a_1, a_2, \ldots, a_n$  ( $1 \le a_i \le 10^9$ ).

#### **Output**

Print the minimum number of elements needed to be removed from the given sequence in order to make it good. It is possible that you need to delete all *n* elements, make it empty, and thus get a good sequence.

#### **Examples**

input	Сору
6 4 7 1 5 4 9	
output	Сору
1	
input	Сору
5 1 2 3 4 5	
output	Сору
2	
input	Сору
1 16	
output	Сору
1	
input	Сору
4 1 1 1 1023	
output	Сору
0	

### Note

In the first example, it is enough to delete one element  $a_4=5$ . The remaining elements form the sequence [4,7,1,4,9], which is good.


#### ICPC Assiut University Training -Juniors Phase 1 Sheets-2022

#### **Public**

#### **Participant**



#### → Group Contests



- Juniors Phase 1 Practice #4 ( Binary search , Two pointers )
- Juniors Phase 1 Practice #3 (STL 2)
- Juniors Phase 1 Practice #2 (STL 1)
- Juniors Phase 1 Practice #1 ( Prefix sum , Frequency Array )

# Juniors Phase 1 Practice #3 ( STL 2 )

Finished

**Practice** 



#### → About Time Scaling

This contest uses time limits scaling policy (depending on a programming language). The system automatically adjusts time limits by the following multipliers for some languages. Despite scaling (adjustment), the time limit cannot be more than 30 seconds. Read the details by the link.

## ightarrow Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you -solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you -solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

Start virtual contest

## → Submit?

Language: GNU G++20 13.2 (64 bit, win ➤

Choose file:

Choose File No file chosen

Submit

$\rightarrow$	Last	Sur	m	ISSI	ons
-		-			

Submission	Time	Verdict
311939043	Mar/23/2025 02:25	Accepted