

## C. Boats Competition

time limit per test: 2 seconds  
memory limit per test: 256 megabytes

There are  $n$  people who want to participate in a boat competition. The weight of the  $i$ -th participant is  $w_i$ . Only teams consisting of **two** people can participate in this competition. As an organizer, you think that it's fair to allow only teams with **the same total weight**.

So, if there are  $k$  teams  $(a_1, b_1), (a_2, b_2), \dots, (a_k, b_k)$ , where  $a_i$  is the weight of the first participant of the  $i$ -th team and  $b_i$  is the weight of the second participant of the  $i$ -th team, then the condition  $a_1 + b_1 = a_2 + b_2 = \dots = a_k + b_k = s$ , where  $s$  is the total weight of **each** team, should be satisfied.

Your task is to choose such  $s$  that the number of teams people can create is the **maximum** possible. Note that each participant can be in **no more than one** team.

You have to answer  $t$  independent test cases.

### Input

The first line of the input contains one integer  $t$  ( $1 \leq t \leq 1000$ ) — the number of test cases. Then  $t$  test cases follow.

The first line of the test case contains one integer  $n$  ( $1 \leq n \leq 50$ ) — the number of participants. The second line of the test case contains  $n$  integers  $w_1, w_2, \dots, w_n$  ( $1 \leq w_i \leq n$ ), where  $w_i$  is the weight of the  $i$ -th participant.

### Output

For each test case, print one integer  $k$ : the **maximum** number of teams people can compose with the total weight  $s$ , if you choose  $s$  optimally.

### Example

input	Copy
5 5 1 2 3 4 5 8 6 6 6 6 6 6 8 8 8 1 2 2 1 2 1 1 2 3 1 3 3 6 1 1 3 4 2 2	
output	Copy
2 3 4 1 2	

### Note

In the first test case of the example, we can reach the optimal answer for  $s = 6$ . Then the first boat is used by participants 1 and 5 and the second boat is used by participants 2 and 4 (indices are the same as weights).

In the second test case of the example, we can reach the optimal answer for  $s = 12$ . Then first 6 participants can form 3 pairs.

In the third test case of the example, we can reach the optimal answer for  $s = 3$ . The answer is 4 because we have 4 participants with weight 1 and 4 participants with weight 2.

In the fourth test case of the example, we can reach the optimal answer for  $s = 4$  or  $s = 6$ .

In the fifth test case of the example, we can reach the optimal answer for  $s = 3$ . Note that participant with weight 3 can't use the boat because there is no suitable pair for him in the list.

Codeforces Round 661 (Div. 3)

Finished

Practice

→ Virtual participation

Virtual contest is a way to take part in past contest, as close as possible to participation on time. It is supported only ICPC mode for virtual contests. If you've seen these problems, a virtual contest is not for you - solve these problems in the archive. If you just want to solve some problem from a contest, a virtual contest is not for you - solve this problem in the archive. Never use someone else's code, read the tutorials or communicate with other person during a virtual contest.

Start virtual contest

→ Clone Contest to Mashup

You can clone this contest to a mashup.

Clone Contest

→ Submit?

Language: GNU G++20 13.2 (64 bit, win

Choose file: Choose File No file chosen

Submit

→ Last submissions

Submission	Time	Verdict
<a href="#">228298473</a>	Oct/15/2023 15:56	Accepted
<a href="#">228298296</a>	Oct/15/2023 15:55	Wrong answer on test 2

→ Problem tags

brute force greedy two pointers

\*1200

No tag edit access

→ Contest materials

Announcement

Tutorial