

Bootstrap Instructions

- 1. To use the bootstrap first close your Dynamic wallet and navigate to your Dynamic data directory and BACKUP THE DATA DIRECTORY SOMEWHERE SAFE:
 - Windows: c:\users\<username>\appdata\roaming\Dynamic\
 - **Linux**: ~/.dynamic
 - OSX: ~/Library/Application\ Support/Dynamic
 - * Replace <username> with your username.
- 2. Delete all data apart from your wallet.dat, conf files and backup folder.
- 3. Download the bootstrap.dat to the Dynamic data directory:

Windows

- Download the latest bootstrap http://dyn.coin-info.net/bootstrap/
- Unzip and place contents in c:\users\<username>\appdata\roaming\Dynamic\

Linux

• Open terminal and type "cd ~/.dynamic && wget http://dyn.coin-info.net/bootstrap/bootstrap-latest.tar.gz && tar -xvf bootstrap-latest.tar.gz" and hit enter.

OSX

- Open terminal, type "cd ~/Library/Application\ Support/Dynamic && wget http://dyn.coin-info.net/bootstrap/bootstrap-latest.tar.gz && tar -xvf bootstrap-latest.tar.gz" and hit enter.
- * Replace <username> with your username.
- 4. Start Dynamic and import from bootstrap.dat:
 - 4a. Qt users just need to start the wallet.
 - 4b. Daemon users need to use the "-loadblock=" argument when starting Dynamic, for example:
 - Linux: -loadblock=~/.dynamic/bootstrap.dat
 - Windows: -loadblock=c:\users\<username>\appdata\roaming\Dynamic\bootstrap.dat
 - OSX: -loadblock=~/Library/Application\ Support/Dynamic/bootstrap.dat
 - * Replace <username> with your username.
- 5. Grab a coffee, tea or other preference of beverage and relax.