coorb QA Assessment – Ahmed Gabr

What's where

Folder	Task	Main file
`task-1/`	Test design & risk coverage (Local Fund Transfer)	`task-1-test-design.md`
`task-2/`	Exploratory testing & bug reports (ParaBank)	`task-2-bug-reports.md`, evidence in `evidence/`
`task-3/part-a/`	Postman collection for the FX rates API	Collection, environment, data file, note and run output
`task-3/part-b/`	Testing the payments endpoint (written)	`task-3-part-b-payments-endpoint.md`
`task-4/`	Automation design (bank operations console)	`task-4-automation-design.md`

Time spent

Task	Time spent
Task 1	90 min
Task 2	40 min
Task 3	60 min
Task 4	45 min

Assumptions, and the questions I'd have asked

Task 1: the full list of 14 questions, each with the assumption I tested against, is in `task-1/` (section 1.1). The six that block test design are:

- Does "local" include other banks?
- What does the customer see when we don't know whether a transfer went through?
- How is the daily limit counted?
- What are the OTP rules?
- What is the fee model?
- What are the failure reasons, and how are reversals handled?

Task 2:

- *Where my expectations come from:* the app's own text (for example, "A minimum of $100.00 must be deposited"), its own numbers (Available $0.00), its other screens (Account Activity versus Find Transactions), and basic banking rules.
- *Question for the PO:* is opening an account from an overdrawn account ever allowed, for example with an agreed overdraft? I assumed it isn't.

Task 3:

- *Questions for the PO:*
  - How old can an indicative rate be?
  - Which currencies must be supported?
  - What happens if the rates provider is down: is there a fallback provider?
  - For the payments endpoint: the real limits, how long the Idempotency-Key is kept, and the missing 401, 403 and 404 responses.

Task 4:

- *Assumptions:*
  - Settings can be backed up and restored through an API.
  - The settings are shared, so tests that change them run one at a time.
  - Each setting's wrapper has a `data-testid`.
- *Question:* can developers add a `data-testid` to every setting wrapper that's missing one?

What I deliberately left out, and why

Task	Left out	Why
1	Every fee amount, load testing, full security testing, layout, accessibility and devices	The 12-case cap. These belong to developer unit tests, separate load and security tests, and design reviews. See section 1.4.
2	Repeating the negative cases for every currency	They don't depend on the data file, so they run on the first iteration only.