

# ASP.NET



# MVC NOTES

---

Ahmed Zaher



# ASP.NET MVC Notes

## Day 1: Routing & Action Results

### 1. Routing and Endpoints

- ♦ **Routing Map:** Defines how URLs map to controllers and actions.

```
/Emp/<ClassName>/Index<FunctionName>
```

- ♦ **Endpoint:** The URL path that leads to a function.
- ♦ **Action:** The function that performs the operation.

### 2. Action Result Types

Different return types in controllers:

Return Type	Class
string	ContentResult
View	ViewResult
json	JsonResult
File	FileResult
NotFound()	NotFoundResult
Unauthorized()	UnauthorizedResult

### Example: Returning Different Results

Ahmed Zaher



```

public IActionResult Show()
{
    ViewResult view = new();
    view.ViewName = "View1";
    return view;
}
public IActionResult Say()
{
    ContentResult content = new();
    content.Content = "Hello World";
    return content;
}
public IActionResult Mix(dynamic id)
{
    if (id % 2 == 0)
    {
        return Content("Hello From Content Result");
    }
    return View("View1");
}

```

#### Note :

*IActionResult* is an **interface** in ASP.NET Core MVC that represents the result of an action method in a controller. It allows you to return different types of responses, such as views, JSON data, HTTP status codes, or redirections.

#### How o Write Code At View :

```

<h1>Hellow World From First View</h1>
<style>
h1{
    color:red
}
</style>

```

Ahmed Zaher



```

<script>
console.log("Hello");
</script>
<!--Razor Engin-->
<!--Block Code-->
@{
    int x =10 ;
    int y = x +10;

}
<!--Inline Statment-->
<h2>@x</h2>
@y
<!--Condition statment-->
@if (x > y){

    <h2>X ggreater than y</h2>
}
else
{
    <h2>X = @x Less than y =@y</h2>
}

<!--Looping Statment-->
@for(int i = 0; i < 10; i++)
{
    <li>@i</li>
}

```



# Day 2: Data Passing Methods

## 1. Passing Data from Action to View

@model takes **one data type**, but we have three methods to pass multiple data types:

### 1. ViewData

```
ViewData["str"] = Object;
```

- Type: Dictionary<string, Object>
- Requires **casting** when retrieving data.

### 2. ViewBag

```
ViewBag.Property = dynamicValue;
```

- Type is **determined at runtime** (no need for casting).
- **Both ViewData and ViewBag Not Strongly Typed** (detect to runtime errors)
- ViewData and ViewBag both use **the same dictionary internally**, So You **can** use them interchangeably, but you **cannot** use the same key separately in both without one overwriting the other.

### 3. ViewModel (Recommended)

- Create a **class** to hold all required data and pass an object to the view.
- Strong Typed View
- Example :

## At Controller

```
public IActionResult Details(int id)
{
    string msg = "Hello From Action";
}
```

Ahmed Zaher



```

int temp = 50;
List<string> brancnes= new List<string>();

bracnches.Add("Assiut");
bracnches.Add("Alex");
bracnches.Add("Cario");
//Additional info send to View from Action
ViewData["Msg"] = msg;
ViewData["Temp"] = temp;
ViewData["brch"] = bracnches;

ViewData["Color"] = "Blue";
ViewBag.Color = "REd";
//ViewData.Model=empMo
Employee EmpMDeI= context.Employee.FirstOrDefault(e => e.Id == id);
return View("Details", EmpMDeI);
}

```

## At View:

```

@model Employee

@{
    ViewData["Title"] = "ITI Details";
}

<h1>Details</h1>

<h2 style="color:@ViewBag.Color">@Model.Name</h2>
<h1>@ViewData["Msg"]</h1>
<h2>@(int.Parse(ViewData["Temp"]).ToString())-10</h2>

<h2>@(ViewBag.Temp - 10)</h2>

```

Ahmed Zaher



```

<select class="form form-control">
    @foreach (var item in (List<string>)ViewData["brch"])
    {
        <option>@item</option>
    }
</select>

<select class="form form-control">
    @foreach (var item in ViewBag.brch)
    {
        <option>@item</option>
    }
</select>

```

## StateManagement

### 2. Data Persistence (Session, TempData, Cookies)

When a request is made, the **controller object is created and destroyed** after execution.

To persist data across requests or getting some data from the Object , use:

Feature	TempData	Session	Cookies
<b>Scope</b>	Request + Next request (unless Peek() or Keep() is used)	Multiple requests during a session	Persistent across requests & browsers
<b>Storage</b>	Stored in <b>Session (by default)</b>	Stored in <b>Server memory</b>	Stored <b>on the client's browser</b>

Ahmed Zaher



Feature	TempData	Session	Cookies
<b>Lifetime</b>	Expires after <b>one request</b> (unless <code>Keep()</code> is used)	Expires <b>when session ends</b> ( <code>IdleTimeout</code> )	Expires <b>based on Expires property</b>
<b>Persistence</b>	Survives <b>redirects</b> but not full refreshes	Survives <b>full refresh, redirects, and navigation</b>	Survives <b>browser restarts (if not expired)</b>
<b>Use Case</b>	Passing temporary data <b>between two actions</b>	Storing <b>user-specific data</b> during a session	Storing <b>small, persistent user preferences</b>

## 1. TempData

- Stored temporarily between **two actions** (request-to-request).
- By default, **TempData is deleted after being read**.
- Use `.Keep("Key")` to persist data across multiple requests.
- Use `.Peek("Key")` to read without deleting.

### Example Using TempData

```

public IActionResult Index()
{
    TempData["Msg"] = "Hello From Session";
    TempData.Keep("Msg"); // Prevents deletion
    return Content($"{TempData["Msg"].ToString()}");
}

public IActionResult Test()
{
    string? msg = TempData["Msg"]?.ToString() ?? "Default Value";
    TempData.Keep("Msg");
    return Content(msg);
}

```





✓ Instead of `Keep()` , use `Peek("Key")` to prevent deletion.

```
public IActionResult Index()
{
    TempData["Msg"] = "Hello From Session";
    return Content($"{TempData.Peek("Msg").ToString()}");
}

public IActionResult Test()
{
    string? msg = TempData.Peek("Msg").ToString();
    return Content(msg);
}
```

## 2. Session

### ♦ 1. Session Creation:

- ♦ When a user first sends a request to the server (e.g., by visiting a website), the server creates a **session** for that user.
- ♦ The server generates a **unique session ID**, typically a random string or number.
- ♦ This **Session ID** is stored in a **Cookie** on the user's browser , but the **actual data** stored in **Server**

### 2. Session ID Sent with Each Request:

- ♦ For every subsequent request, the browser **automatically sends the session ID** (usually as a cookie) along with the request.
- ♦ The server checks the session ID that it receives from the request and compares it with the sessions it has stored on the server (typically in memory or a session database).

### 3. Session Validation:

- ♦ If the session ID matches an active session stored on the server, the server knows that this is a **valid session** and continues to associate the user's actions with that session.

Ahmed Zaher



- ♦ If the session ID is missing or invalid (e.g., expired), the server may either create a new session or prompt the user to log in again.

#### 4. Session Expiration/End:

- ♦ Sessions typically have a **timeout period**, after which they expire automatically. If the user doesn't interact with the server within that timeout, the session is considered **expired**.
- ♦ The session can also be explicitly destroyed by the server when the user logs out, or after a predefined time.
- ♦ Data is stored **on the server** and accessible across multiple actions/views.

### Example Using Session

```
public IActionResult SetSession(string name)
{
    HttpContext.Session.SetString("Name", name);
    HttpContext.Session.SetInt32("Age", 21);
    return Content("Data Session Save Success");
}

public IActionResult GetSession()
{
    string n = HttpContext.Session.GetString("Name");
    int? a = HttpContext.Session.GetInt32("Age");

    return Content($"name={n} \t age={a}");
}

// For Object instance
public IActionResult Set_SessionObj(Student obj)
{
    var key = "My_Key";
    var str = JsonConvert.SerializeObject(obj);
    HttpContext.Session.SetString(key, str);
    return Content("Object is Set Successfully");
}
```



```

}

public IActionResult Get_SessionObj(string key)
{
    var str = HttpContext.Session.GetString(key);
    var str = HttpContext.Session.GetString(key);
    var obj = JsonConvert.DeserializeObject<Student>(str);
    return Content("Obj Is Retrieved ");
}

```

- ◆ Requires **configuration in Program.cs** .

## At Main Function :

```

builder.Services.AddSession(options => {
    options.IdleTimeout = TimeSpan.FromMinutes(30);
});

//or
builder.Services.AddSession(); // Default Time is 20 min

// then After or Before ` app.UseRouting(); ` Put :
app.UseSession();

```

so ,

```

public static void Main(string[] args)
{
    var builder = WebApplication.CreateBuilder(args);

    // Add services to the container.//Day8
    builder.Services.AddControllersWithViews();
}

```

Ahmed Zaher



```

builder.Services.AddSession(options => {
    options.IdleTimeout = TimeSpan.FromMinutes(30);
});
var app = builder.Build();

# region Built-in Middleware
// Configure the HTTP request pipeline.//Day4 (Middleware)
if (!app.Environment.IsDevelopment())
{
    app.UseExceptionHandler("/Home/Error");
}
app.UseStaticFiles();

app.UseSession();

app.UseRouting();

app.UseAuthorization();

app.MapControllerRoute(
    name: "default",
    pattern: "{controller=Home}/{action=Index}/{id?}");
//app.Map("/djhsdjh", (app) => { });
#endregion

app.Run();
}

```

### 3. Cookies

Ahmed Zaher



- ♦ The session ID stored in the cookie is only used by the browser to **identify the session**
- ♦ it doesn't store user data (just the ID).
- ♦ Cookie Data is stored **on the client's browser**.
- ♦ **Cookies** are sent back to the server automatically with each request, allowing the server to retrieve session-specific data (like user authentication, preferences, etc.).
- ♦ Can set expiration time.
- ♦ Cookies Are Added in **Response**
- ♦ **Request** is used for **Read Only**

## Example Using Cookies

```
public IActionResult SetCookie()
{
    CookieOptions options=new CookieOptions();
    options.Expires = DateTime.Now.AddDays(1);
    //Session Cookie
    HttpContext.Response.Cookies.Append("Name", "Ahmed");
    //Presistent cookie
    HttpContext.Response.Cookies.Append("Age", "12", options);
    // Note That Cookies receive String "12" not int 12
    return Content("Cookie Save");
}

public IActionResult GetCookie()
{
    string name= HttpContext.Request.Cookies["Name"];
    string age = HttpContext.Request.Cookies["Age"];
    return Content($"name={name} \t age={age}");
}
```



## Day 3: Model Binding

# Model Binding in ASP.NET Core

Model Binding is the process of mapping data from HTTP requests (URL, form inputs, etc.) to action method parameters in a controller.

## 1. Passing Data Through the URL (Query String)

- ♦ Example:

```
Bind/ClassName/FunctionName?name=ahmed&age=20
```

- ♦ By default, this method uses the **GET** HTTP method.
- ♦ The function will retrieve request data from:

```
Request.QueryString
```

## Important Notes

- ♦ ✓ **Extra parameters** will be **ignored** if not required by the function.
- ♦ ✓ **Missing parameters** will take **default values**:
  - ♦ `int` → `0`
  - ♦ `string` → `null`

## Understanding URL Segments

- ♦ Example:

Ahmed Zaher



```
/Bind/ClassName/FunctionName?name=ahmed&age=20
```

- ♦ /Bind/ → **Segment**
- ♦ /ClassName/ → **Segment**
- ♦ /FunctionName?name=ahmed&age=20 → **Query String Parameters**

## Handling IDs in URLs

1. Using a query string:

```
Bind/ClassName/FunctionName?id=10
```

2. Using route parameters when method parameter is called id :

```
Bind/ClassName/FunctionName/10
```

- ♦ This method retrieves the ID from:

```
Request.RouteValues
```

- ♦ **RouteValues take priority** over query string parameters. If both are present, ASP.NET will use **RouteValues**.

## Handling Collections & Objects in Query Strings

- ♦ **Collections (Lists, Arrays, etc.)** are handled as is.
- ♦ **Objects require specifying parameters individually** in the query string:

```
/Binding/Emp?id=1&name=ahmed&salary=1000  
or /Binding/Emp/1?&name=ahmed&salary=1000 // id is added as a segment
```

Ahmed Zaher



- This will automatically map to an Employee ( Emp ) object with properties Id , Name , and Salary .

## Redirecting Between Actions & Controllers

**Redirect to an action in the same controller:**

```
return RedirectToAction("ActionName", new { id = userId /* the parameters for Action*/});
```

**Redirect to an action in a different controller:**

```
return RedirectToAction("ActionName", "OtherControllerName");  
return RedirectToAction("ActionName", "OtherControllerName", new { id = userId /* the parameters for  
Action*/});
```

---

## 2. Passing Data Through Form Submission (Request.Form)

- When submitting data via an HTML form, ASP.NET retrieves it from:

```
Request.Form
```

## Handling HTTP Methods

By default, an action method can handle **both GET and POST** requests.

To specify a method explicitly:

**Handle only GET requests:**

Ahmed Zaher





```
[HttpGet] // This action will only respond to GET requests
public IActionResult Test(string name, List<int> grades)
{
    return View("View1");
}
```

**Handle only POST requests:**

```
[HttpPost] // This action will only respond to POST requests
public IActionResult Test(string name, List<int> grades)
{
    return View("View1");
}
```

---

## Day 4

### HTML Helper in ASP.NET MVC

#### Before: Writing HTML with Embedded C#

Before HTML Helpers, we used to write **raw HTML** and insert **C# code** inside it.

Example:

```
<input type="text" name="Username" value="@Model.Username" />
```

---

Ahmed Zaher



# 1- HTML Helper (Pure C#)

## What are HTML Helpers?

**HTML Helpers** are **utility methods** in ASP.NET MVC that generate **HTML elements dynamically** inside a View instead of writing static HTML manually.

- ◆ It is a **loosely typed helper** (does not have strong type checking).

## Example: Using HTML Helper

```
@Html.TextBox("Username", Model.Username, new { @class = "form-control" })  
           //name      //Value
```

- ◆ **Generates:**

```
<input type="text" name="Username" value="JohnDoe" class="form-control" />
```

---

## Advantages of HTML Helpers

- ◆ Less HTML code, more **C#-centric** approach.
- ◆ Generates **standard HTML elements** dynamically.
- ◆ Supports adding **CSS classes and attributes** easily.

---

## Common HTML Helpers

Ahmed Zaher



HTML Helper	Generates
@Html.TextBox("name")	<input type="text" name="name">
@Html.Password("pass")	<input type="password" name="pass">
@Html.DropDownList("country")	<select name="country">...</select>
@Html.CheckBox("agree")	<input type="checkbox" name="agree">

## Strongly Typed HTML Helper for Name

Example: Strongly Typed HTML Helper for Name

### 1 Create a Model ( UserModel.cs )

```
public class UserModel
{
    [Display(Name="Full_Name")]
    public string Name { get; set; }
}
```

### 2 Create a Controller ( HomeController.cs )

```
public class HomeController : Controller
{
    public ActionResult Index()
    {
        var user = new UserModel(); // Creating an empty model
        return View(user);
    }
}
```

Ahmed Zaher



```

[HttpPost]
public ActionResult Index(UserModel model)
{
    if (ModelState.IsValid) // will explained in detail at day 5
    {
        // Process form data
        ViewBag.Message = "Submitted Name: " + model.Name;
    }
    return View(model);
}
}

```

### 3 Create a View ( Index.cshtml )

```

@model UserModel

@using (Html.BeginForm())
{
    <div class="form-group">
        @Html.LabelFor(b=>b.name);
        // will make the label name for the attribute in the class but
        // if it found [Display (name="Name")] will put it to the label

        @Html.TextBoxFor(m => m.Name, new { @class = "form-control", placeholder = "Enter your name" })
    </div>

    <button type="submit" class="btn btn-primary">Submit</button>
}

@if (ViewBag.Message != null)
{

```



```
<p>@ViewBag.Message</p>
}
```

## Explanation

- `Html.TextBoxFor(m => m.Name)` binds directly to the `Name` property in `UserModel`.
- The model ensures **type safety** and allows data validation.
- When the form is submitted, the controller receives the model with user input.
- If valid, the name is displayed in `ViewBag.Message`.

## Html.EditorFor() Examples

### Example 1: Without Data Annotation (Simple Text Input)

#### 1 Model ( UserModel.cs )

```
public class UserModel
{
    public string Name { get; set; }
}
```

#### 2 View ( Index.cshtml )

```
@model UserModel

@using (Html.BeginForm())
{
    <div class="form-group">
        <label>Name:</label>
```



```

        @Html.EditorFor(m => m.Name, new { htmlAttributes = new { @class = "form-control", placeholder =
"Enter name" } })
    </div>

    <button type="submit" class="btn btn-primary">Submit</button>
}

```

## Example 2: With Data Annotation (Password Input)

### 1 Model ( UserModel.cs )

```

using System.ComponentModel.DataAnnotations;

public class UserModel
{
    public string Name { get; set; }

    [DataType(DataType.Password)]
    [Display(Password="User Password")]
    public string Password { get; set; }
}

```

### 2 View ( Index.cshtml )

```

@model UserModel

@using (Html.BeginForm())
{
    <div class="form-group">

```



```

        <label>Password:</label>
        @Html.EditorFor(m => m.Password, new { htmlAttributes = new { @class = "form-control", placeholder =
"Enter password" } })
    </div>

    <button type="submit" class="btn btn-primary">Submit</button>
}

```

I choose the data type because EditorFor detect numeric a string

## ✓ Key Differences:

Example	Uses Data Annotation?	Input Type
Name Input	✗ No	Text ( <input type="text"> )
Password Input	✓ Yes ( [DataType(DataType.Password)] )	Password ( <input type="password"> )

EditorFor() automatically detects the input type based on the model's data annotation! ✂

## V2 - Tag Helper

### Full Tag Helper Example in ASP.NET Core

## ✓ Updated Razor View ( Index.cshtml )

```

@model UserModel

<form method="post" asp-action="" asp-controller="" asp-route-id="">

```

Ahmed Zaher



```

<div class="form-group">
    <label asp-for="Name"></label>
    <input asp-for="Name" class="form-control" placeholder="Enter your name" />
    <span asp-validation-for="Name" class="text-danger"></span>
</div>

<div class="form-group">
    <label asp-for="Password"></label>
    <input asp-for="Password" class="form-control" placeholder="Enter your password" />
    <span asp-validation-for="Password" class="text-danger"></span>
</div>

<button type="submit" class="btn btn-primary">Submit</button>
</form>

@if (!string.IsNullOrEmpty(ViewBag.Message))
{
    <p>@ViewBag.Message</p>
}

@section Scripts {
    <partial name="_ValidationScriptsPartial" />
}

```

## Another Example with Selected List

```

@model EmpWithDEptListViewModel
@{
    ViewData["Title"] = "Edit";
    SelectList selectLists = new SelectList(Model.DeptList, "Field_Value", "Field_Name"); /* to make casting
to IEnumerable */
}

<h1>Edit</h1>

```

Ahmed Zaher





```

<form method="post" asp-action="SAveEdit">
  <div>
    <input asp-for="StId" type="hidden" />
    <label asp-for="DepartmentID"></label>
    @* <input type="number" value="@Model.DepartmentID" id="DepartmentID" name="DepartmentID"
class="form form-control" /> *@
    <select asp-for="DepartmentID" asp-items="selectLists" ></select>
  </div>
  <input type="submit" value="Save" class="btn btn-success" />
</form>

```

By default, when using `<form asp-action="SomeAction">` , the method is **POST**, unless specified otherwise.

## Changes & Enhancements:

Feature	Usage
<code>&lt;form&gt;</code> (No <code>asp-controller</code> or <code>asp-action</code> )	Since it's in the same view, <code>method="post"</code> is enough
<code>asp-for</code> on <code>&lt;input&gt;</code> & <code>&lt;label&gt;</code>	Automatically binds fields to the model
<code>asp-validation-for</code>	Displays validation messages dynamically
<code>@section Scripts</code>	Ensures client-side validation works

**Tag Helpers** make Razor views more HTML-friendly, reducing the need for `HtmlHelpers` .

When using **Tag Helpers** for a form's submit button, you explicitly set the `type="submit"` attribute to ensure it functions correctly.

**Note :**

Ahmed Zaher



asp-for="X" does...	Result in HTML
Sets name	name="X"
Sets id	id="X"
Sets value	value="Model.X"
Works with validation	<span asp-validation-for="X">...</span>

---

## Layout & RenderBody in ASP.NET Core MVC

### What is a Layout?

Microsoft provides a **default shared layout** that acts as a **template** for multiple views.

It contains a special object called `@RenderBody`, which is **replaced by the actual View** when rendered.

---

### Naming Rule for Layouts

- ♦ The default layout follows a **naming convention**:

```
_Layout.cshtml
```

- ♦ It is usually stored in:

```
Views/Shared/_Layout.cshtml
```

Ahmed Zaher



- ♦ You can have multiple layout styles and apply them selectively.

---

## How to Apply a Custom Layout in a View?

You can specify a different layout in a View using the `Layout` property:

```
@model EmpWithDeptListModel
@{
    ViewData["Title"] = "Edit";
    Layout = "NewLayout"; // You can set it to null to remove layout
}
```

- ♦ This applies `"NewLayout.cshtml"` instead of the default `_Layout.cshtml`.

---

## RenderBody vs RenderSection

### 1) @RenderBody (Main Content Placeholder)

- ♦ The **View replaces** `@RenderBody` inside the Layout.
- ♦ **Required** in a Layout.

Example in `_Layout.cshtml` :

```
<!DOCTYPE html>
<html>
<head>
    <title>@ViewData["Title"]</title>
</head>
```

Ahmed Zaher



```

<body>
  <header>My Header</header>
  <div>
    @RenderBody() <!-- The view will be injected here -->
  </div>
  <footer>My Footer</footer>
</body>
</html>

```

## 2 @RenderSection (Optional Sections)

- A **Layout** can have multiple `@RenderSection` placeholders.
- These allow **specific sections** in Views to be inserted into the Layout.
- It takes a **section name** and a **boolean** (optional, default = `true` means required).

Example in `_Layout.cshtml` :

```

<!DOCTYPE html>
<html>
<head>
  <title>@ViewData["Title"]</title>
</head>
<body>
  <header>My Header</header>

  <div>
    @RenderBody() <!-- The main content of the View will be here -->
  </div>

  <div>
    @RenderSection("Sidebar", required: false) <!-- Optional Section -->
  </div>
</body>
</html>

```

Ahmed Zaher



```
</div>

<footer>My Footer</footer>
</body>
</html>
```

---

## How to Implement Sections in a View?

### Inside View.cshtml

```
@section Sidebar {
    <p>This is the Sidebar content</p>
}
```

✓ This will be **inserted** into `@RenderSection("Sidebar")` inside the layout.

---

## Summary

Feature	Purpose
<code>@RenderBody</code>	Inserts the <b>main view content</b> inside the layout.
<code>@RenderSection</code>	Allows <b>custom sections</b> to be injected into the layout.
<code>Layout = "NewLayout"</code>	Changes the default layout for a specific view.



# DAY 5

## Validation

### [ValidateAntiForgeryToken] in ASP.NET MVC & Core

#### What is [ValidateAntiForgeryToken] ?

[ValidateAntiForgeryToken] is an attribute used in ASP.NET MVC & ASP.NET Core to **prevent Cross-Site Request Forgery (CSRF) attacks** by ensuring that form submissions are legitimate and come from the same site.

---

#### Why is it Important?

Without CSRF protection, an attacker could trick a logged-in user into unknowingly submitting a form that performs malicious actions, such as:

- ♦ Transferring money
- ♦ Changing an account password
- ♦ Deleting a user account

This attribute ensures that **every POST request contains a valid anti-forgery token**, making it harder for attackers to forge requests.

---

#### ✓ How to Use [ValidateAntiForgeryToken]

#### 1 Secure Controller Action

Ahmed Zaher



In your **controller**, apply the `[ValidateAntiForgeryToken]` attribute to the POST action to enforce CSRF protection.

```
[HttpPost]
[ValidateAntiForgeryToken]
public IActionResult SubmitForm(UserModel model)
{
    if (ModelState.IsValid)
    {
        // Process form submission
        return RedirectToAction("Success");
    }
    return View(model);
}
```

## 2 Secure Razor View (Form)

To ensure the token is included in the form, you must use either **Tag Helpers (ASP.NET Core)** or **HtmlHelpers (ASP.NET MVC & Core)**.

### ⚡ Using Tag Helpers (ASP.NET Core)

✓ **ASP.NET Core automatically adds the CSRF token** For Tag Helper, so you don't need to manually include `@Html.AntiForgeryToken()` .

```
<form asp-action="SubmitForm" method="post">
<input asp-for="Email" class="form-control" />
<button type="submit">Submit</button> </form>
```

✓ The hidden input **is automatically generated**:

```
<input name="__RequestVerificationToken" type="hidden" value="random-token-value">
```

Ahmed Zaher



## ⚡ Using HtmlHelpers (ASP.NET MVC & Core)

✓ If you're using `Html.BeginForm()`, you **must manually add**

```
@Html.AntiForgeryToken().
@using (Html.BeginForm("SubmitForm", "Home", FormMethod.Post))
{
    @Html.AntiForgeryToken();
    <label> Email:</label >
    @Html.TextBoxFor(model => model.Email, new { @class = "form-control" }) < button type = "submit" >
    Submit </ button >
}
```

✓ Without `@Html.AntiForgeryToken()`, the request will fail with **HTTP 403 Forbidden**.

---

## - How Does It Work?

1. **When the form is generated**, `@Html.AntiForgeryToken()` inserts a hidden input field with a CSRF token :
2. **When the form is submitted**, the browser **sends this token** along with the request.
3. **ASP.NET checks the token** in the `[ValidateAntiForgeryToken]` attribute:
  - ✓ If the token is valid → the request is processed.
  - ✗ If the token is missing or incorrect → the request is **rejected with HTTP 403 Forbidden**.

---

## When Do You Need It?

Ahmed Zaher





Scenario	Should You Use [ValidateAntiForgeryToken] ?
POST request (modifies data)	✓ Yes
GET request (just displays data)	✗ No
Login, Register, Delete, Update actions	✓ Yes
API request (without authentication)	✗ No (Use JWT or OAuth)

## Summary

Feature	[ValidateAntiForgeryToken]
Prevents	CSRF (Cross-Site Request Forgery) attacks
Used in	ASP.NET MVC & ASP.NET Core
Applies to	Only POST requests
Requires	@Html.AntiForgeryToken() in forms (unless using Tag Helpers)
Without It	Hackers can submit unauthorized requests

## Example Code

### Controller

```
public class AccountController : Controller
{
```

Ahmed Zaher



```

[HttpPost]
[ValidateAntiForgeryToken]
public IActionResult Login(LoginModel model)
{
    if (ModelState.IsValid)
    {
        // Authentication logic here
        return RedirectToAction("Dashboard");
    }
    return View(model);
}
}

```

## View (Using Tag Helpers)

```

<form asp-action="Login" method="post">
<input asp-for="Username" class="form-control" />
<input asp-for="Password" type="password" class="form-control" />
<button type="submit">Login</button> </form>

```

## View (Using HtmlHelpers)

```

@using (Html.BeginForm("Login", "Account", FormMethod.Post))
{
    @Html.AntiForgeryToken() ;
    @Html.LabelFor(m => m.Username) ;
    @Html.TextBoxFor(m => m.Username, new { @class = "form-control" }) ;
    @Html.LabelFor(m => m.Password) ;
    @Html.PasswordFor(m => m.Password, new { @class = "form-control" });
    <button type="submit">Login</button>
}

```



# Final Notes

- ♦ **Tag Helpers in ASP.NET Core** automatically include the anti-forgery token.
- ♦ **HtmlHelpers in ASP.NET MVC/Core** require `@Html.AntiForgeryToken()` manually.  
If you forget to add the anti-forgery token, **the request will be rejected (403 Forbidden)**.

Condition	[ValidateAntiForgeryToken]	ModelState.IsValid	Result
No token / invalid token	✗ Fails (403 Forbidden)	✗ Not checked	Request is blocked
Valid token, but invalid form data	✓ Passes	✗ Fails	Returns the form with validation errors
Valid token and valid form data	✓ Passes	✓ Passes	Redirects to "Success"

## Note :

- ♦ We Will Know more about Validation-Token at JWT

---

in ASP.NET MVC/Core, you **cannot override** an action method unless they have **different HTTP verbs** (e.g., GET and POST ) or different method signatures (e.g., different parameters).

### ✓ Correct Approach:

Use **attribute routing** ( [HttpGet] , [HttpPost] , etc.) to differentiate actions.

---

Validation is Done at 3 layers :

- ♦ 1-Mode

Ahmed Zaher



- 2-Controller
- 3-View

## Validation

### Model

```
[Required]
[MaxLength(30)]
[MinLength(3)]
public string Name { get; set; }

[Required]
[RegularExpression(@"(Alex|Assiut)")]
public string Address { get; set; }

[Display(Name="Student Age")]
[Required]
[Range(maximum:50,minimum:20)]
public int Age { get; set; }
```

### Controller

```
[HttpPost]
[ValidateAntiForgeryToken]//intenal calling o
public IActionResult New(Student newStd)
{
    // if (newStd.Name != null)
    if(ModelState.IsValid==true)
    {
        
    }
}
```

**Validation Codition**



**Check**

*Another Example*

Ahmed Zaher



- ♦ At Model

```
using System.ComponentModel.DataAnnotations;

public class UserViewModel
{
    [Required(ErrorMessage = "Username is required")]
    [StringLength(50, ErrorMessage = "Username cannot exceed 50 characters")]
    public string Username { get; set; }

    [Required(ErrorMessage = "Email is required")]
    [EmailAddress(ErrorMessage = "Invalid email format")]
    public string Email { get; set; }

    [Required(ErrorMessage = "Password is required")]
    [MinLength(6, ErrorMessage = "Password must be at least 6 characters")]
    public string Password { get; set; }

    [Compare("Password", ErrorMessage = "Passwords do not match")]
    public string ConfirmPassword { get; set; }

    [Range(18, 100, ErrorMessage = "Age must be between 18 and 100")]
    public int Age { get; set; }
}
```

- ♦ At Controller

```
[HttpPost]
public IActionResult Register(UserViewModel model)
{
    //ModelState is Dictionary
    //it's key is Property name and it's value is property value
    if (!ModelState.IsValid)
```



```

{
    return View(model); // Return the view with validation errors
}

// Process the valid model
return RedirectToAction("Success");
}

```

- ModelState is Dictionary  
it's key is Property name and it's value is property value
- At View

```

<form asp-action="Register">

    <!-- Validation Summary -->
    <div asp-validation-summary="All" class="text-danger"></div>

    <div class="form-group">
        <label>Username</label>
        <input asp-for="Username" class="form-control" />
        <div class="text-danger">
            <span asp-validation-for="Username"></span>
        </div>
    </div>

    <div class="form-group">
        <label>Email</label>
        <input asp-for="Email" class="form-control" />
        <div class="text-danger">
            <span asp-validation-for="Email"></span>
        </div>
    </div>
</form>

```



```
<button type="submit" class="btn btn-primary">Register</button>
</form>
```

- ♦ `<div asp-validation-summary="All" class="text-danger"></div>` : Displays and gather all validation errors at the top of the form.
- ♦ The "All" option shows **both model-level and property-level errors** :
  - 1 **Model-level errors** (e.g., errors added manually in the controller using- `ModelState.AddModelError("", "message")` )
  - 2 **Field-specific errors** (e.g., `[Required]` , `[EmailAddress]` )
- ♦ You can change it to: "ModelOnly" → Displays only model-level validation errors.
- ♦ "None" → Hides the validation summary (not recommended unless you use inline messages only).

---

## Custom Validation Error

`ModelState.AddModelError` is a method in ASP.NET Core and ASP.NET MVC that allows you to manually add validation errors to the `ModelState` dictionary. This is useful when you want to return custom validation errors in your controllers.

### 1- `ModelState.AddModelError("FieldName", "Custom error message.");`

```
Student st = context.Students.FirstOrDefault(b => b.StId == std.StId);

if (std.DeptId == 0)
{
    ModelState.AddModelError("DeptId", "Select Department ");
    return View("View1", std);
}
```



- Select Department

Select Department

- ♦ Note That It is Server-Side

## When Should You Use It ?

1. **Custom Business Logic** – When validation depends on dynamic conditions.
2. **Database or External Checks** – When you need to check the database (e.g., unique email, existing username).
3. **General Errors** – When you want to show an error not related to a specific field.
4. **API Error Handling** – When returning structured validation errors in an API.

---

## 2- Making my Own Attribute (Server-Side)

If I want to create a unique attribute for a name, I need to create a new model (class) and name it with 'Attribute' at the end, like UniqueAttribute .

```
public class UniqueAttribute : ValidationAttribute
{
```

Ahmed Zaher





```

public string msg { get; set; } //to use it by attribute

protected override ValidationResult? IsValid(object? value, ValidationContext validationContext)
{
    if (value == null)
    {
        return null;
    }

    string name = value.ToString();

    var context = new ItiContext();

    Student student = context.Students.
    FirstOrDefault(b => b.StFname == name);

    Student sts =(Student)validationContext.ObjectInstance;
    //To Use the validationContext

    if (student != null)
    {
        return new ValidationResult("Error Message");
    }

    return ValidationResult.Success;
}
}

```

```

//At the Model
[Unique(msg ="Any Message")]
public string StFname { get; set; }

```



## 1. object? value

- ◆ This is the **value** of the property that the attribute is applied to.
- ◆ It contains the data that needs to be validated.
- ◆ It can be `null` , so you must check before using it.
- ◆ You typically cast it to the expected type ( `string` , `int` , etc.).

## 2. ValidationContext validationContext

- ◆ This provides **metadata** about the validation process.
- ◆ It contains details about the **object being validated**.
- ◆ It is the Object of model that `UniqueAttribute` Called from
- ◆ must make explicit casting to use it

### Note Again :

- ◆ it is Server Side

---

To enable **custom client-side validation**, we need to use `jQuery` along with `jQuery Validation` and `jQuery Unobtrusive Validation` .

## Steps to Set Up Client-Side Validation

### 1. Include jQuery and Validation Scripts

You need to include the required JavaScript libraries at the end of the view:

```
<script src="~/lib/jquery/dist/jquery.min.js"></script>
<script src="~/lib/jquery-validation/dist/jquery.validate.min.js"></script> <script src="~/lib/jquery-
```

Ahmed Zaher



```
validation-unobtrusive/jquery.validate.unobtrusive.min.js"></script>
```

### Why at the end?

Placing scripts at the bottom ensures that the entire page loads first, improving performance.

---

## 2. Recommended Approach: Use `_Layout.cshtml` for Script Loading

Instead of adding scripts manually in every view, it's best to load them in the `_Layout.cshtml` file using the built-in `@RenderSectionAsync("Scripts")` method.

**Note** : Can add it by new section at end

In `_Layout.cshtml` (usually before `</body>`):

```
@await RenderSectionAsync("Scripts", required: false)
```

This allows each view to **inject its own scripts** inside a `Scripts` section without duplicating code.

Then, in individual views:

```
@section Scripts {  
  <script src="~/lib/jquery-validation/dist/jquery.validate.min.js"></script>  
  <script src="~/lib/jquery-validation-unobtrusive/jquery.validate.unobtrusive.min.js"></script>  
}
```

### ★ Why don't we include jQuery again?

Because `_Layout.cshtml` typically already includes `jquery.min.js`, so we only add validation scripts where needed.

---

## 3- Making Remote Validation (Remote)

Ahmed Zaher



## (Server-Side & Client-Side)

[Remote] is an **attribute** used for **client-side validation** that makes an **AJAX call to the server** to validate a field **without submitting the entire form**.

- ♦ at model

```
public class UserModel
{
    [Required]
    [Remote(action:"check",controller:"Instructor",ErrorMessage ="MSG")]
    public string Username { get; set; }
}
```

- ♦ at controlled

```
public IActionResult check(string Username)
//name for attribute must be same for property
{
    if(Username.Contains("Mr"))
    {
        return Json(true);
    }
    return Json(false);
}
```

**Note : Function's Parameter must be same name for Model's Property**

- ♦ I Can Put more than property to check ...by :  
At Model

```
public class UserModel
{
```

Ahmed Zaher



```

[Required]
[Remote(action:"check",controller:"Instructor",ErrorMessage ="MSG"
,AdditionalFields ="Address,Email"
)]
public string Username { get; set; }
public string Email { get; set; }
public string Address { get; set; }
}

```

At Controller

```

public IActionResult check(string Username ,string Email ,string Address)
{
    //You Can Check Any of them if there is any relationship between them
}

```

---

**Note: Validation By Remote I Must Call JQuery At View**

---

## Difference Between Remote Validation and Custom Validation in ASP.NET Core

Feature	Remote Validation ( [Remote] )	Custom Validation ( ValidationAttribute )
Where It Runs?	Client-side (AJAX) + Server	Server-side only
Uses AJAX?	✓ Yes	✗ No

Ahmed Zaher



Feature	Remote Validation ( [Remote] )	Custom Validation ( ValidationAttribute )
Ideal For?	Checking <b>existing records</b> (e.g., unique username/email)	Business rules, <b>complex field validation</b>
Requires JavaScript?	✓ Yes	✗ No
Multiple Field Validation?	✓ Yes, with <code>AdditionalFields</code>	✓ Yes, using <code>ValidationContext</code>

## When to Use What?

- ✓ **Use Remote Validation ( [Remote] )** when you need **real-time** checks (like checking if an email is taken).
- ✓ **Use Custom Validation ( ValidationAttribute )** when you need **complex logic** or **server-only validation** (e.g., checking password strength).

## Day 6


### 1 MiddleWare

- MiddleWares are Methods in Web Application
- in .NET Core, when a request arrives at IIS, it forwards the request to the ASP.NET Core runtime Proxy (specifically Kestrel). Kestrel then executes the middleware pipeline configured in the application.
- **Middleware** in ASP.NET Core is a component that is part of the request processing pipeline. It handles:
  - 1 Incoming requests** (before they reach your controller and after the session being created )
  - 2 Outgoing responses** (after the controller action is done).
  - 3 Each middleware can:

Ahmed Zaher



- ♦ 1. Process the request and is called (short-circuit the pipeline) , not call the next middleware.
- 2. Process the request and then invoke the next middleware.
- 3. Do nothing and immediately call the next middleware.



**Note that :**

**M1 -> M2 -> M3 -> M4 -> M3 -> M2 -> M1**

- ♦ We can build our own middleware by providing a delegate, and there are three types of middleware:
  1. Execute then invoke the next component ⇒ Use
  2. Execute and terminate the pipeline ⇒ Run
  3. Branch based on URL and execute a delegate, .Map(url , Exec) ⇒ Map

Example :-

Ahmed Zaher



```

public static void Main(string[] args)
{
    var builder = WebApplication.CreateBuilder(args);

    // Add services to the container.//Day8
    builder.Services.AddControllersWithViews();
    builder.Services.AddSession(options => {
        options.IdleTimeout = TimeSpan.FromMinutes(30);
    });

    var app = builder.Build();

    #region Custom Middleware "inline Middleware"

    app.Use(async (httpContext, Next) =>
    {
        await httpContext.Response.WriteAsync("1)Middleware 1\n");
        await Next.Invoke();
        await httpContext.Response.WriteAsync("1)Middleware 1--\n");

        //
    });
    app.Use(async (httpContext, Next) =>
    {
        await httpContext.Response.WriteAsync("2)Middleware 2\n");
        await Next.Invoke();
        await httpContext.Response.WriteAsync("2)Middleware 2-----\n");

    });
    app.Run(async (httpContext) =>
    {
        await httpContext.Response.WriteAsync("3)Terminate\n");
    }

```





```

});
app.Use(async (httpContext, Next) =>
{
    await httpContext.Response.WriteAsync("4)Middleware 4\n");
    await Next.Invoke();
    //
});

app.Run();
}

```

Output :

```

1) Middleware 1
2) Middleware 2
3) Terminate
2) Middleware 2-----
3) Middleware 1--

```

1 var app = builder.Build();

from here start using my Web Application Object

2 We use app.Run last of all MiddleWares

3 We uses Lambda for Delegate but You can make Your own Function

4 Function Next.Invoke() is Async so we use await and mark the delegate as async to ensure the middleware completes before moving on.

## ♦ Built in MiddleWare

```

public static void Main(string[] args)
{
    var builder = WebApplication.CreateBuilder(args);

```

Ahmed Zaher



```

// Add services to the container.
builder.Services.AddControllersWithViews();

var app = builder.Build();

// Configure the HTTP request pipeline.

#region main middleware

if (!app.Environment.IsDevelopment())
{
    app.UseExceptionHandler("/Home/Error");
}
app.UseStaticFiles(); // for jquery and bootstrap
app.UseRouting();// put for Routing
app.UseAuthorization(); // for Authorization ,

app.MapControllerRoute(
    name: "default",
    pattern: "{controller=Home}/{action=Index}/{id?}");
#endregion

app.Run();
}

```

## Note :

```

if (!app.Environment.IsDevelopment())
{

```

Ahmed Zaher



```
    app.UseExceptionHandler("/Home/Error");  
}
```

it used For end-user not Developer that make it easy for him to explore Errors and exceptions

- ♦ once You need to make Authentication :  
make Authenticate before you authorize

```
app.UseAuthentication();// ← INSERT THIS  
// 4) Authenticate before you authorize  
app.UseAuthorization();
```

Aspect	Authentication	Authorization
Purpose	Establish <b>who</b> you are	Determine <b>what</b> you can do (your permission )
Question answered	“Are you who you claim to be?”	“Are you allowed to perform this action?”
Common methods	Username/password, tokens (JWT), API keys, certificates	Roles, policies, scopes, resource-based permission checks

- ♦ [Click For most popular built-in MiddleWares](#)

---

## 2- StateManagment

- ♦ Explained At [Day\\_2](#) (Page 6 )



# Day 7

the best practice in software architecture (especially in C# and ASP.NET environments) is to follow this flow:

## **Model → Repository → Controller**

This layered approach promotes separation of concerns, maintainability, and testability. Here's what each layer is responsible for:

Note:

A **Repository** is a class (or interface + class) that:

- ◆ Encapsulates the logic required to **access data sources** (e.g., SQL Server, MongoDB, APIs).
- ◆ Provides **CRUD (Create , Read , Update , Delete ) operations** for a specific model.
- ◆ Hides all the low-level database details from the rest of the app

this approach is called **Repository Pattern** we try not to write code at controller

So :

**Controller** interacts with the **Repository**, and the **Repository** interacts with the **Database Context** (often referred to as the **DbContext** in Entity Framework for C#).

## **SOLID Principles in C#**

### **1. Single Responsibility Principle (SRP)**

#### **What It Means:**

A class should have only one reason to change.

Each class should focus on a single task/responsibility, which improves **maintainability**, **testability**, and **readability**.

---

Ahmed Zaher



## ✗ Violates SRP

```
public class UserManager
{
    public void AddUser(string username)
    {
        // Add user logic
    }

    public void SendNotification(string message)
    {
        // Send notification logic
    }
}
```

## ✓ Applies SRP

```
public class UserManager
{
    private readonly IUserRepository _userRepository;

    public UserManager(IUserRepository userRepository)
    {
    }
}
```

Ahmed Zaher



```
        _userRepository = userRepository;
    }

    public void AddUser(string username)
    {
        // Add user logic
    }
}

public class NotificationService
{
    public void SendNotification(string message)
    {
        // Send notification logic
    }
}
```

🔧 Now, each class has **one responsibility** only:

UserManager manages users, NotificationService sends notifications.

Ahmed Zaher



---

## 2. Open/Closed Principle (OCP)

- **What It Means:**

| A class should be **open for extension**, but **closed for modification**.

We should be able to add new functionality without changing existing code.

---

### ✗ Violates OCP

```
public class PaymentProcessor
{
    public void ProcessPayment(string type)
    {
        if (type == "CreditCard")
        {
            // CreditCard logic
        }

        else if (type == "PayPal")
        {
            // PayPal logic
        }
    }
}
```

Ahmed Zaher



```
}  
  
}
```

## Applies OCP

```
public interface IPaymentMethod  
{  
    void ProcessPayment(decimal amount);  
}  
  
public class CreditCardPayment : IPaymentMethod  
{  
    public void ProcessPayment(decimal amount)  
    {  
        // CreditCard logic  
    }  
}  
  
public class PayPalPayment : IPaymentMethod  
{  
    public void ProcessPayment(decimal amount)
```





```
{  
  
    // PayPal logic  
  
}  
  
public class PaymentProcessor  
{  
  
    public void ProcessPayment(IPaymentMethod paymentMethod, decimal amount)  
    // pass credit or paypal obj  
    {  
  
        paymentMethod.ProcessPayment(amount);  
  
    }  
  
}
```

🔧 Add new payment types **without modifying** PaymentProcessor.

### 3. Liskov Substitution Principle (LSP)

#### What It Means:

Subclasses must be replaceable for their base classes **without breaking functionality**.

Ensure subclasses behave correctly when used in place of their parent class.

Ahmed Zaher



## Violates LSP

```
public class Bird
{
    public virtual void Fly()
    {
        // Flying logic
    }
}

public class Ostrich : Bird
{
    public override void Fly()
    {
        throw new NotImplementedException(); // Ostriches can't fly
    }
}
```

## Applies LSP

Ahmed Zaher



```
public abstract class Bird
{
    public abstract void Move();
}

public class Sparrow : Bird
{
    public override void Move()
    {
        // Flying logic
    }
}

public class Ostrich : Bird
{
    public override void Move()
    {
        // Running logic
    }
}
```



All subclasses can now be used **interchangeably** via `Move()` without causing errors.

Ahmed Zaher



---

## 4. Interface Segregation Principle (ISP)

### What It Means:

Clients should not be forced to depend on interfaces they **don't use**.

Split large interfaces into **smaller, role-specific ones**.

---

### ✗ Violates ISP

```
public interface IWorker
{
    void Work();

    void Eat(); // Not needed for Robot
}

public class Robot : IWorker
{
    public void Work() { /* Work logic */ }

    public void Eat()
    {
```

Ahmed Zaher



```
        throw new NotImplementedException(); // Robots don't eat
    }
}
```

## ✓ Applies ISP

```
public interface IWorkable
{
    void Work();
}

public interface IFeedable
{
    void Eat();
}

public class Robot : IWorkable
{
    public void Work() { /* Work logic */ }
}
```



```
public class Human : IWorkable, IFeedable
{
    public void Work() { /* Work logic */ }

    public void Eat() { /* Eat logic */ }
}
```

🔧 Each class **implements only what it needs**, reducing bloated interfaces.

---

## 5. Dependency Inversion Principle (DIP)

### What It Means:

High-level modules should not depend on low-level modules.

Both should depend on **abstractions**.

---

### ✗ Violates DIP

```
public class PaymentProcessor
{
    private readonly CreditCardPayment _payment = new CreditCardPayment();
}
```

Ahmed Zaher



```
public void ProcessPayment(decimal amount)
{
    _payment.Process(amount);
}

public class CreditCardPayment
{
    public void Process(decimal amount)
    {
        // Payment logic
    }
}
```

## Applies DIP

```
public interface IPaymentMethod
{
    void Process(decimal amount);
}

public class CreditCardPayment : IPaymentMethod
{
    public void Process(decimal amount)
    {
        // Payment logic
    }
}
```



```

public class PaymentProcessor
{
    private readonly IPaymentMethod _paymentMethod;

    public PaymentProcessor(IPaymentMethod paymentMethod)
    {
        _paymentMethod = paymentMethod;
    }

    public void ProcessPayment(decimal amount)
    {
        _paymentMethod.Process(amount);
    }
}

```

🔧 The `PaymentProcessor` depends on **abstraction**, not on concrete classes. Easier to switch implementations (e.g., to PayPal or Crypto).

[Strongly Recommended To Read About Dependency Injection](#)

## Final Summary

Principle	Full Name	Key Idea
<b>S</b>	Single Responsibility	One job per class
<b>O</b>	Open/Closed	Extend behavior without modifying code
<b>L</b>	Liskov Substitution	Subclasses should fully work in place of parents
<b>I</b>	Interface Segregation	Avoid forcing classes to implement what they don't need

Ahmed Zaher





Principle	Full Name	Key Idea
D	Dependency Inversion	Rely on abstractions, not concrete implementations

- ♦ Suppose we have two models to implement: Employee and Department.

We have three folders:

1. Repository (contains interfaces and repository classes),
2. Model (contains the actual models),
3. Controllers (contains the controllers for the models).

Remember, we try not to write model logic inside the controllers.

example on Employee Method :

1- Employee Model

```
public class Employee
{
    public int Id { get; set; }

    // [Required]
    [MinLength(2, ErrorMessage = "Name Must be greater than 2 char")]
    [MaxLength(25)]
    [Unique]
    public string Name { get; set; }

    //[Range(6000,25000,ErrorMessage = "Salary mustbe range 6000 to 25000")]
    [Remote("CheckSalary","Employee"
        ,AdditionalFields = "JobTitle"
        , ErrorMessage = "Salary greater than 6000 L.E")]
    public int Salary { get; set; }

    public string JobTitle { get; set; }
```

Ahmed Zaher



```

[RegularExpression(@"\w+\.(\jpg|png)",ErrorMessage ="Image must Be jpg or png")]
public string ImageURL { get; set; }

public string? Address { get; set; }

[ForeignKey("Department")]
[Display(Name="Department")]
public int DepartmentID { get; set; }

public Department? Department { get; set; }
}

```

## 2- Employee Repository:

- Employee Interface

```

public interface IEmployeeRepository
{
    public void Add(Employee obj);

    public void Update(Employee obj);

    public void Delete(int id);

    public List<Employee> GetAll();
    public Employee GetById(int id);

    public void Save();
}

```

- Employee Repository



```

public class EmployeeRepository: IEmployeeRepository
{
    ITIContext context;
    public EmployeeRepository()
    {
        context = new ITIContext();
    }
    //CRUD
    public void Add(Employee obj)
    {
        context.Add(obj);
    }
    public void Update(Employee obj)
    {
        context.Update(obj);
    }

    public void Delete(int id)
    {
        Employee Emp = GetByld(id);
        context.Remove(Emp);
    }
    public List<Employee> GetAll()
    {
        return context.Employee.ToList();
    }
    public Employee GetByld(int id)
    {
        return context.Employee.FirstOrDefault(e => e.Id == id);
    }
    public void Save()
    {
        context.SaveChanges();
    }
}

```



```
}  
}
```

### 3- Employee Controller (inject By Constructor):

```
public class EmployeeController : Controller  
{  
    // ITIContext context = new ITIContext();  
    IEmployeeRepository EmployeeRepository;  
    public EmployeeController(IEmployeeRepository EmpRepo)  
    {  
        EmployeeRepository = EmpRepo;  
    }  
}  
  
// Actions to implement
```

- ♦ After this implementation we have a problem that the Controller Factory can't create an instance of EmployeeRepository to pass it as a parameter to the controller constructor because :
    - ♦ The EmployeeController needs an IEmployeeRepository passed **into** its constructor.
    - ♦ But ASP.NET MVC **by default** does not know *how to create* an IEmployeeRepository .
    - ♦ So the **Controller Factory** (the part that creates controllers) **throws an error** because it can't build EmployeeController automatically
- 
- ♦ To Fix the exception we implement IoC Container ( **Inversion of Control** ).  
: Instead of a class creating its own dependencies, someone else (usually a framework or container) injects those dependencies into the class or creating the needed objects?
  - ♦ in .net IoC Called Service Provider , how IoC containers work :



- We usually deal with **three key operations**:

Term	Meaning (Simple)	Example
<b>Register</b>	Tell the IoC container <i>which classes</i> to create when asked for an interface.	<code>builder.Services.AddScoped&lt;IEmployeeRepository, EmployeeRepository&gt;();</code>
<b>Resolve</b>	Ask the IoC container <i>to give you an instance</i> of a registered service. (Happens automatically in Controllers.)	Controller constructor parameter: <code>EmployeeController(IEmployeeRepository repo)</code>
<b>Dispose</b>	Free or clean up objects <i>after they finish</i> . This happens automatically if you use DI properly.	The container disposes your repository instance after the request ends.

- **quick summary:**

Step	Action
<b>Register</b>	Add service to the container.
<b>Resolve</b>	Get an instance when needed (e.g., in controller constructor).
<b>Dispose</b>	Automatically clean up the service after use.

## Services Type

Type	Declared	Registered	Example
<b>Framework Services</b>	Already declared	Already registered	<code>ILogger&lt;T&gt; , IHttpContextAccessor</code>
<b>Built-in Services</b>	Already declared	Must be registered manually	<code>AddDbContext&lt;&gt; , AddAuthentication()</code>

Ahmed Zaher



Type	Declared	Registered	Example
Custom Services	Not declared	Not Registered	AddTransient<>() AddScoped<>() AddSingleton<>()

## ♦ 1- Register

- ♦ it's Called by the host before the Configure method to configure the app's services

```
public static void Main(string[] args)
{
    var builder = WebApplication.CreateBuilder(args);
    //Framework service :already declare ,already register
    //built in service :already declare ,need to register
    // Add services to the container.
    builder.Services.AddControllersWithViews();
    //Custom Service "RegisterB
    builder.Services.AddScoped<IEmployeeRepository, EmployeeRepository>();

    var app = builder.Build();

    app.Run();
}
```

```
builder.Services.AddScoped<IEmployeeRepository, EmployeeRepository>();
```

You're telling the ASP.NET Core **Dependency Injection (DI) container** that when a class (like a controller) **requests** an instance of `IEmployeeRepository` , the container should create (resolve) an instance of `EmployeeRepository` .

- ♦ **Life-Time of Custom Service :**

Ahmed Zaher



Lifetime	Behavior
<code>builder.Services.AddTransient&lt;&gt;()</code>	New object is created <b>every time</b> it's requested/injected.
<code>builder.Services.AddScoped&lt;&gt;()</code>	One object <b>per HTTP request</b> (or per created scope).
<code>builder.Services.AddSingleton&lt;&gt;()</code>	One object for the <b>whole application lifetime</b> (same instance always).

## ♦ 2- Resolve (at controller)

1- inject (ask) by **constructor** :

```
public EmployeeController(IEmployeeRepository EmpRepo)
{
    EmployeeRepository = EmpRepo;
}
```

- ♦ In this constructor, ASP.NET Core uses dependency injection to automatically provide an instance of `IEmployeeRepository` when creating the `EmployeeController` , as long as the service is properly registered in the DI container.

2- inject by **Action**


```
public IActionResult Details([FromServices] IEmployeeRepository employeeRepository)
{
    var employee = employeeRepository.GetByld(id);
    return View(employee);
}
```

- ♦ When you use **Action Injection** in a controller, the **[FromServices]** attribute tells the Dependency Injection (DI) system to **inject the service directly into the action parameter**, ignoring any model binding that might otherwise be used.

Ahmed Zaher



- ♦ examples :



Attribute	Where the value comes from	Example
[FromBody]	Request body (usually JSON) (API)	POST data (like a JSON object)
[FromForm]	Form fields (like HTML forms)	<form method="post">
[FromHeader]	HTTP request headers	e.g., Authorization header
[FromKeyedServices]	From DI container <b>by key</b>	Special keyed services in DI (advanced use)
[FromQuery]	URL query string parameters	/api/items?id=5
[FromRoute]	URL route parameters	/api/items/5 (id from route)
[FromServices]	From the <b>dependency injection container</b>	Inject a service like a logger or business service

### 3 - Inject by View

#### Note:

- ♦ Before we talk about injecting services into a view, we can make the Repository folder easier to access everywhere by creating a **global using**.
- ♦ To do this, add the following line (for example, in a GlobalUsings.cs file):

Ahmed Zaher





```
global using MVC.Repository;
```

- ♦ This way, you don't need to manually add `using MVC.Repository;` in every file — it becomes automatically available across the whole project.

- ♦ **How to Inject a Service in a View**

- ♦ Use the `@inject` directive at the top of your `.cshtml` view.

```
@inject IDepartmentRepository deptREpo
@{
    ViewData["Title"] = "Index";
}
<h1>Index</h1>
<h3>Id From View @deptREpo.Id</h3>
```

- ♦ **Note:**

`Id = Guid.NewGuid().ToString();` it returns unique id every time You call it .

- 
- ♦ If You remember at employee repository :

```
public EmployeeRepository()
{
    context = new ITIContext();
}
```

- ♦ the `context = new ITIContext();` inside the constructor of `EmployeeRepository` violates the Dependency Injection (DI) principle. In a Dependency Injection pattern, dependencies (like the `ITIContext` ) should be provided externally, rather than being created inside the class. This allows for easier testing, better flexibility, and separation of concerns.

Ahmed Zaher



- ◆ In this case, you should inject the `ITContext` into the constructor of `EmployeeRepository` instead of creating it directly in the constructor by:
- ◆ 1 - We're using `appsettings.json` to store the connection string, which is a great approach to avoid hardcoding sensitive information like database credentials. The configuration in `appsettings.json` should look like this:

```
{
  "Logging": {
    "LogLevel": {
      "Default": "Information",
      "Microsoft.AspNetCore": "Warning"
    }
  },
  "AllowedHosts": "*",
  "ConnectionStrings": {
    "cs": "Data Source=.;Initial Catalog=ITI;Integrated Security=True;Encrypt=False;Trust Server Certificate=True"
  }
}
```

2- adding a constructor to our `ITContext` class that accepts `DbContextOptions` is required to use the configuration provided through the `appsettings.json` file. The goal here is to pass the configuration (e.g., connection string) to the `DbContext` via the `DbContextOptions` :

```
public class ITContext : DbContext
{
    public ITContext(DbContextOptions<ITContext> options) : base(options){}
    // DbSet, etc.
}
```

- ◆ This constructor ensures that `ITContext` can be configured using the `DbContextOptions` that will be set up via the DI container.

Ahmed Zaher



3- In your `Program.cs` or `Startup.cs` (depending on your ASP.NET Core version), you're registering `ITDbContext` in the DI container. The `UseSqlServer` method will use the connection string from `appsettings.json` :

```
public class Program
{
    public static void Main(string[] args)
    {
        var builder = WebApplication.CreateBuilder(args);

        // Add DbContext to the DI container with the connection string
        builder.Services.AddDbContext<ITDbContext>(options =>
        {
            options.UseSqlServer(builder.Configuration.GetConnectionString("cs"));
        });

        // Other services...

        var app = builder.Build();

        // Other middleware...
    }
}
```

4- our `EmployeeRepository` now has the `ITDbContext` injected via its constructor:

```
public class EmployeeRepository
{
    private readonly ITDbContext _context;
    public EmployeeRepository(ITDbContext context)
    {
        _context = context;
    }
}
```

Ahmed Zaher



```
}  
}
```

## Key Points:

- ♦ **Appsettings.json**: The connection string is pulled from the configuration, so no hardcoding is needed.
- ♦ **DbContext Constructor**: The `ITContext` constructor is modified to accept `DbContextOptions`.
- ♦ **DI Registration**: In `Program.cs` or `Startup.cs`, `ITContext` is registered with the DI container using `AddDbContext`.
- ♦ **Repository Constructor**: `EmployeeRepository` accepts `ITContext` via constructor injection.

## Note :

- ♦ The method `builder.Services.AddDbContext<ITContext>(options => { ... })` registers the `DbContext` (in this case `ITContext`) in the **Dependency Injection (DI)** container. Once you register the `DbContext`, it can be injected into any service or class that requires it.
- ♦ `AddDbContext` registers the `DbContext` to be injected into classes that depend on it. In other words, you cannot directly use `ITContext` unless the class is being injected via **Dependency Injection**.
- ♦ in custom validation, use the **default constructor** (`public ITContext() : base()`), and you don't use DI to inject the context, it will work properly but it violates DI, We apply it by :

```
public class UniqueEmailAttribute : ValidationAttribute  
{  
    protected override ValidationResult IsValid(object value, ValidationContext validationContext)  
    {  
        var dbContext = (ITContext)validationContext  
            .GetService(typeof(ITContext)); // uses DI  
  
        var email = value as string;  
        if (dbContext.Users.Any(u => u.Email == email))  
        {  
            return new ValidationResult("Email already exists");  
        }  
    }  
}
```

Ahmed Zaher



```
        return ValidationResult.Success;
    }
}
```

## Day 8

### 1 - Filters

- 1) block of code ,execute befor ,after ,during action execute
- 2) reduced repeating code
- 3) attribute [action ,contoller,application]
- 4)implement **IFilterMetadata**

- ◆ 1 A filter is a block of code that executes before, after, or around the execution of an action method, result, or other parts of the request pipeline.
- ◆ 2 Filters are used to reduce repetitive code by handling cross-cutting concerns such as logging, caching, authorization, or error handling in a centralized way.
- ◆ 3 Filters can be applied at different scopes: on an action method, on a controller class, or globally at the application level through configuration.
- ◆ 4 At a low level, a custom filter implements specific filter interfaces such as `IActionFilter` , `IResultFilter` , `IExceptionFilter` , or their async counterparts. All these interfaces inherit from the `IFilterMetadata` marker

Ahmed Zaher



interface, which provides metadata about the filter but is not typically implemented directly.

**Note :** Filters is at MVC Level, Unlike MiddleWares is that At Application Level

**Built-in Filters :**

Interface that contains them.

Filter	Interfaces that contains them	Description
Authorization	IAuthorizationFilter, IAsyncAuthorizationFilter	Used to apply authorization and security policy
Action	IActionFilter, IAsyncActionFilter	Used to perform a specify work immediately <b>before</b> or <b>after</b> an action method is performed
Result	IResultFilter, IAsyncResultFilter	Used to perform a specify work immediately <b>before</b> or <b>after</b> the <u>result</u> from an action method is processed
Exception	IExceptionFilter, IAsyncExceptionFilter	Used to handle exceptions

## 1- Authorization Filters

**What they do:**

Run *before everything else* to determine if the current user/request is allowed to continue.

**Built-in example:**

Ahmed Zaher



- ♦ [Authorize] attribute.
- ♦ [AllowAnonymous] to skip authorization or Enter As anonymous

**Example :**

```
[Authorize]
public class SecureController : Controller
{
    public IActionResult Secret()
    {
        return View();
    }
}
```

## 2- Action Filter

The **action filter** is one of the most **common ways to build your own custom filter** in ASP.NET Core.

When you want to create a filter that **runs code before and/or after your action method**, you typically implement:

- ♦ `IFilter` (for synchronous code)
- ♦ or `IFilterAsync` (for async code)

This allows you to **inject custom behavior** around the **action method execution**.

## Why would We use an Action Filter?

To **reduce repetitive code** by handling things like:

- ♦ Logging
- ♦ Validation
- ♦ Modifying input/output

Ahmed Zaher



- ♦ Measuring execution time
- ♦ Adding headers, etc.

Instead of repeating this logic in every action, you **write it once in a filter**.

**Example :**

```
public class LogActionFilter : Attribute, IActionFilter
{
    public void OnActionExecuting(ActionExecutingContext context)
    {
        Console.WriteLine($"[Before] {context.ActionDescriptor.DisplayName}");
    }

    public void OnActionExecuted(ActionExecutedContext context)
    {
        Console.WriteLine($"[After] {context.ActionDescriptor.DisplayName}");
    }
}
```

## 1- OnActionExecuting

### What it does:

- ♦ **Runs before the action method is executed.**
- ♦ This is where you can add custom logic **before the action runs** (e.g., validation, logging, modifying parameters, or even redirecting).

### Parameters:

- ♦ **ActionExecutingContext context:** This object provides information about the action being executed, such as:

Ahmed Zaher





- ♦ The **action descriptor** (details about the action method).
- ♦ The **action parameters** (input data passed to the action). as Key Value Pair

## Typical Use Cases:

- ♦ **Validation**: Check if the data passed into the action is valid.
- ♦ **Logging**: Log the start of the action execution.
- ♦ **Authorization checks**: Ensure the user has the right permissions.
- ♦ **Modify input data**: Manipulate action arguments before the action runs.

## 2 OnActionExecuted

### What it does:

- ♦ **Runs after the action method has executed**, but **before the result is executed** (i.e., before the action's return value is processed by any result filters or sent back to the client).
- ♦ This is where you can perform **post-action processing** (e.g., logging the result, modifying the result, error handling).

### Parameters:

- ♦ **ActionExecutedContext context**: This object provides information about the executed action:
  - ♦ The **action descriptor** (details about the executed action).
  - ♦ The **action result** (the result returned by the action, such as `ViewResult` , `JsonResult` , etc.).

## Typical Use Cases:

- ♦ **Logging**: Log the completion of the action execution.
- ♦ **Error handling**: Handle or log any errors that occurred during the action execution.
- ♦ **Modifying the action result**: Change the result returned by the action before it is processed further.

**Note :**

Ahmed Zaher



- ♦ if Used one method of them, don't make the other throw an Exception

---

## 3- Result Filters

### What they do:

Run *before and after* the **result** (e.g., a View or JSON response) is processed. Used to change the result or log view rendering.

### Built-in example:

No common standalone result filters, but `ResponseCache` acts partly at this level.

### Example:

At Home Controller :

- ♦ It controls **caching behavior** of the HTTP response by setting appropriate **cache-related headers**.

```
[ResponseCache(Duration = 0, Location = ResponseCacheLocation.None, NoStore = true)]
public IActionResult Error()
{
    return View(new ErrorViewModel { RequestId = Activity.Current?.Id ?? HttpContext.TraceIdentifier });
}
```

---

## 4- Exception Filter

### Job:

- ♦ Runs when an **unhandled exception** is thrown in the action or result execution.
- ♦ Used to **log, transform, or handle exceptions gracefully**.

Ahmed Zaher



### Built-in idea:

ASP.NET Core recommends middleware for global error handling now, but in MVC filters:

- ♦ [HandleError] (classic MVC) or exception filters registered in Core.

### Example :

```
public class MyExceptionHandlerAttribute : Attribute, IExceptionHandler
{
    public void OnException(ExceptionContext context)
    {
        Console.WriteLine("Exception caught: " + context.Exception.Message);
        context.Result = new ContentResult
        {
            Content = "An error occurred, but it was handled by a filter."
        };
        context.ExceptionHandled = true; // prevents the exception from propagating
    }
}
```

### Another Example :

```
public class ErrorClassAttribute : Attribute, IExceptionHandler
{
    public void OnException(ExceptionContext context)
    {
        string msg = context.Exception.Message + " excep";
        var viewResult = new ViewResult
        {
            ViewName = "Error",
            ViewData = new ViewDataDictionary(new EmptyModelMetadataProvider(), new ModelStateDictionary())
        };
    }
}
```

Ahmed Zaher



```
viewResult.ViewData["msg"] = msg;
context.Result = viewResult;

    }
}
```

- We must Inherit First from Attribute class then IExceptionHandler interface , to use it as attribute

At Controller:

```
[ErrorClass]
public IActionResult TestError()
{
    throw new Exception("Test exception");
}
```

**Note :\***

ViewName = "Error" means using Error View that is at Shred File

To use Filter for all actions at different Controllers (For Application ):

At Program.cs

```
builder.Services.AddControllersWithViews(option =>
{
    option.Filters.Add(new MyExceptionHandler());
});
```

**Think of it like this:**

Ahmed Zaher



Step	Happens when...	Example	Filter Type(s)
1	Before action logic	Logging, authorization, model manipulation	OnActionExecuting (in <code>IActionFilter</code> / <code>IAsyncActionFilter</code> )
2	After action method returns	Modify returned data or check exceptions	OnActionExecuted (in <code>IActionFilter</code> / <code>IAsyncActionFilter</code> )
3	Before View rendering	Change ViewData, swap ViewName, log info	OnResultExecuting (in <code>IResultFilter</code> / <code>IAsyncResultFilter</code> )
4	After View is rendered and sent	Cleanup, log completion, post-processing	OnResultExecuted (in <code>IResultFilter</code> / <code>IAsyncResultFilter</code> )

---



Table	Class	Service	Repository	Context
Employee	Employee	EmployeeService	EmployeeRepository	ITContext
DEpartment	DEpartment	DeptService	DEptRepository	
User	IdentityUser	UserManager	UserStore	IdentityDbContext
Role	IdentityRole	RoleManager	RoleStore	

- ◆ Sometimes We need to add layer between Repository and model called Service to make mapping
- ◆ **We Need To Know What Are Identity Classes?**  
In **ASP.NET Core Identity**, Microsoft provides a set of **built-in classes** that help you **manage authentication and authorization** out of the box.

The **core classes** are:

Class	Purpose
IdentityUser	Represents a <b>user account</b> (e.g., a person who logs in).
IdentityRole	Represents a <b>role</b> (e.g., Admin, User, Manager).
IdentityDbContext	The Entity Framework <b>DbContext</b> that contains the tables to store users, roles, etc.



Class	Purpose
UserManager<TUser>	A service to <b>create, update, delete, and manage users.</b>
RoleManager<TRole>	A service to <b>create, update, delete, and manage roles.</b>
SignInManager<TUser>	Handles <b>login, logout, and authentication logic</b> && <b>Stores the user's claims in the cookie for future requests.</b>
UserStore<TUser>	Implements IUserStore and works with EF Core to save users in DB.
RoleStore<TRole>	Implements IRoleStore and works with EF Core to save roles in DB.

then :

**UserManager**--(deals with)-->**UserStore**--(deals with)-->**IdentityDbContext**

IdentityUser has :

```

public class IdentityUser
{
    public string Id { get; set; }           // Unique user ID (usually a GUID)
    public string Username { get; set; }     // The user's login name
    public string NormalizedUsername { get; set; } // Normalized version of Username
    public string Email { get; set; }        // The user's email address
    public string NormalizedEmail { get; set; } // Normalized version of Email
    public bool EmailConfirmed { get; set; }  // True if email is confirmed

    public string PasswordHash { get; set; } // Hashed password
    public string SecurityStamp { get; set; } // Used to invalidate sessions
    public string ConcurrencyStamp { get; set; } // For optimistic concurrency checks

    public string PhoneNumber { get; set; }  // User's phone number
    public bool PhoneNumberConfirmed { get; set; } // True if phone number is confirmed

    public bool TwoFactorEnabled { get; set; } // Is 2FA enabled
    public DateTimeOffset? LockoutEnd { get; set; } // Lockout expiration date

```

Ahmed Zaher



```

    public bool LockoutEnabled { get; set; }           // Can the user be locked out
    public int AccessFailedCount { get; set; }         // Number of failed access attempts
}

```

- ♦ In `IdentityUser`, the `Id` property is **inherited directly** from the base class and is used as the **primary key** for each user in the database.

## Where is `Id` Defined?

It's defined like this:

```

public class IdentityUser<TKey> where TKey : IEquatable<TKey>
{
    public virtual TKey Id { get; set; }
    ...
}

```

- ♦ When you use the non-generic version `IdentityUser` (i.e., `IdentityUser` without `<TKey>`), it **defaults to string**:

```

public class IdentityUser : IdentityUser<string>
{
    public IdentityUser()
    {
        Id = Guid.NewGuid().ToString();
        SecurityStamp = Guid.NewGuid().ToString();
    }
}

```

## Extending `IdentityUser` (Adding Your Own Attributes):

Ahmed Zaher





If you need extra **custom fields** (e.g., FullName, DateOfBirth), you can **inherit** from IdentityUser and Make a New Class to follow Open for Extend Close for Modification :

```
public class ApplicationUser : IdentityUser
{
    public string FullName { get; set; }
    public DateTime DateOfBirth { get; set; }
}
```

- ◆ Now We Have 2 Data bases :
  - 1 - IdentityDbContext
  - 2- Ower Default Data base (ITContext)To Solve it We make ITContext Inherit From IdentityDbContext

◆

```
public class ITContext:IdentityDbContext<ApplicationUser>
{
    public DbSet<Employee> Employee { get; set; }
    public DbSet<Department> Department { get; set; }
    //
    public ITContext() : base()
    {
    }

    public ITContext(DbContextOptions options) : base(options)
    {
    }

    // Required
    protected override void OnModelCreating(ModelBuilder modelBuilder)
    {
        base.OnModelCreating(modelBuilder);
    }
}
```

Ahmed Zaher



```
}  
}
```

- ♦ We Make it Generic to Apply New Attributes (Attribute For Generic Must inherit from identityDbContext )
- ♦ After that we add migration and add update the database
- ♦ **Now** We Finished Our Classes and DataBase

---

**We will make the Controller and ViewModel for mapping , because we don't need to enter all IdentityUser properties**

### ♦ 1- ViewModel:

```
public class RegisterUserViewModel  
{  
    public string UserName { get; set; }  
  
    [DataType(DataType.Password)]  
    public string Password { get; set; }  
  
    [Compare("Password")]  
    [Display(Name = "Confirm Password")]  
    [DataType(DataType.Password)]  
    public string ConfirmPassword { get; set; }  
  
    public string Address { get; set; }  
}
```

- ♦ Used For Mapping from View's Data (Request)

Ahmed Zaher



## • 2- Controller :

```
public class AccountController : Controller
{
    private readonly UserManager<ApplicationUser> userManager;
    private readonly SignInManager<ApplicationUser> signInManager;

    public AccountController
        (UserManager<ApplicationUser> userManager, SignInManager<ApplicationUser> signInManager)
    {
        this.userManager = userManager;
        this.signInManager = signInManager;
    }

    [HttpPost]
    public async Task<IActionResult> SaveRegister
        (RegisterUserViewModel UserViewModel)
    {
        if (ModelState.IsValid)
        {
            //Mapping
            ApplicationUser appUser = new ApplicationUser();
            appUser.Address = UserViewModel.Address;
            appUser.UserName = UserViewModel.UserName;

            //save database
            IdentityResult result =
                await userManager.CreateAsync(appUser, UserViewModel.Password);
            if (result.Succeeded)
            {
                //Cookie
                await signInManager.SignInAsync(appUser, false);
                return RedirectToAction("Index");
            }
        }
    }
}
```



```

        foreach (var item in result.Errors)
        {
            ModelState.AddModelError("", item.Description);
        }
    }
    return View("Register", UserViewModel);
}
}

```

- ◆ Both are injected via Dependency Injection (IoC container) and are ready to use in your controllers or services.

```

private readonly UserManager<ApplicationUser> userManager;
private readonly SignInManager<ApplicationUser> signInManager;

```

Remember :

UserManager Used For CRUD operations , SignInManager for adding Cookies

```

IdentityResult result = await userManager.CreateAsync(appUser, UserViewModel.Password);

```

- ◆ CreateAsync :
  - ◆ Adds the user to the **database**.
  - ◆ Automatically **hashes the password** and saves it securely.
  - ◆ returns IdentityResult that is a **result object** that tells you **whether the operation succeeded or failed**.
  - ◆ When you pass the password to CreateAsync() , **it hashes it immediately** using a secure algorithm (by default, PBKDF2 with HMAC-SHA256).
    - ◆ The result (the **hash**) is saved in the PasswordHash column in the AspNetUsers table.
    - ◆ It has two key members:



Property	Purpose
Succeeded	A <b>bool</b> : <code>true</code> if the user was created successfully; <code>false</code> if there were any errors.
Errors	A collection of <b>IdentityError</b> objects that explain <b>what went wrong</b> (if any errors).

- ♦ `result` tells you if it **succeeded or failed**.
  - ♦ Here We Add the Errors to `ModelErrors`

```
foreach (var item in result.Errors)
{
    ModelState.AddModelError("", item.Description);
}
```

**Note :** Because of `CreateAsync` is Async We Add ***await*** and Convert **\*Action To Task**

- ♦ `SignInAsync`

```
await signInManager.SignInAsync(appUser, false);
```

- ♦ Sign in the user ( `appUser` ) and create an authentication cookie to keep them logged in.

Part	Meaning	
<code>appUser</code>	The user object (of type <code>ApplicationUser</code> ) you just created or fetched.	
<code>false</code>	This is <code>isPersistent</code> : it tells whether the <b>login session (cookie) should be persistent</b> . (The login session <b>will end when the browser is closed</b> .)	

### 3- At Program.cs

Ahmed Zaher



```
builder.Services.AddIdentity<ApplicationUser, IdentityRole>().AddEntityFrameworkStores<ITContext>();
```



- ♦ this line **adds Identity services** with your user ( `ApplicationUser` ) and role ( `IdentityRole` ).
- ♦ It also **registers UserManager, SignInManager, RoleManager, etc.** for **Dependency Injection** automatically.

## What Does It Mean?

This code **registers ASP.NET Core Identity** in the **dependency injection (DI) container** and tells it:

- 1 Which classes to use for Users and Roles.
- 2 Which database context to use for storing Identity data.

## Breaking Down Each Part:

Part	Meaning
<code>AddIdentity&lt;ApplicationUser, IdentityRole&gt;()</code>	 You're telling ASP.NET:
	- <code>ApplicationUser</code> : your <b>custom user class</b> (inherits from <code>IdentityUser</code> ).
	- <code>IdentityRole</code> : the default class to handle <b>roles</b> (like Admin, User, etc.).
<code>.AddEntityFrameworkStores&lt;ITContext&gt;()</code>	 You're telling Identity to <b>use your Entity Framework DbContext ( ITContext ) to store users/roles.</b>



- ◆ Instead Of Build The View From Scratch We Have Built-in Template We Can Use

## Add Razor View

View name:

Template:

Model class:

DbContext class:

Database provider:

Options:

- ☐ Create as a partial view
- ☒ Reference script libraries
- ☒ Use a layout page

...

(Leave empty if it is set in a Razor \_viewstart file)



View name	View
Template	Create
Model class	RegisterUserViewModel (Q3DotNetAssiut.ViewModel)

I chose the Template and the ViewModel That will apply for it

```

/*
1)Install package Identity "Microsoft.AspNetCore.Identity.EntityFrameworkCore"
2)class ApplicationUser:IdentityUser
3)ITContext:IdentityDbContext<ApplicationUser>
4)Add-migration
5) create accountController
6) create registerViewModel
7) Register Action
8) register identityService in Program class
*/

```

- the steps that is listed form the core sequence to implement an authentication module using **ASP.NET Core Identity with Entity Framework Core**. However, to ensure your authentication module is complete and functional, :
  - 1. Install package Identity "Microsoft.AspNetCore.Identity.EntityFrameworkCore"
  - 2. class ApplicationUser : IdentityUser
  - 3. ITContext : IdentityDbContext<ApplicationUser>

Ahmed Zaher





- ♦ 4. Add-migration
  - ♦ 5. Create AccountController (Adding user manager , sign in manager by DI)
  - ♦ 6. Create RegisterViewModel
  - ♦ 7. Register Action
  - ♦ 8. Register IdentityService in Program class
- 

**Note :**

- ♦ Identity For Password Has Some Strict Condition like :

**Password Requirements:**

- ♦ Minimum 6 characters
- ♦ At least one non-alphanumeric character (e.g., !, @, #, etc.)
- ♦ At least one digit (0-9)
- ♦ At least one uppercase letter (A-Z)
- ♦ We Can edit these requirements by (At Program.cs):

```
builder.Services.AddIdentity<ApplicationUser, IdentityRole>(option =>
{
    option.Password.RequiredLength = 4;
    option.Password.RequireDigit = false;
    option.Password.RequireNonAlphanumeric = false;
    option.Password.RequireUppercase = false;
}).AddEntityFrameworkStores<ITContext>();
```

- ♦ When using [Authorize] We need To use app.UseAuthentication(); middleware at programe.cs before app.UseAuthorization();

**app.UseAuthorization(); :**

Ahmed Zaher



- ♦ It checks:
  - ♦ "Does the incoming request have any **authentication data** like:
    - ♦ a Cookie,
    - ♦ a JWT Token,
    - ♦ or any other authentication method?"
- ♦ If it **finds data** :
  - ♦ It **verifies** it (e.g., checks if the token or cookie is valid).
  - ♦ If valid → it **fills** `HttpContext.User` with the user info (like username, roles, claims, etc.).
- ♦ If **nothing is found** or it's invalid :
  - ♦ The request continues with the user as **Anonymous**.

So, it's responsible for **checking and loading who the user is**.

---

## [Authorize] :

### What does it do?

- ♦ After `UseAuthentication()` finishes and has loaded the user info, `[Authorize]` comes in and says:

"Alright, the current user:

- ♦ Are they **authenticated**?
- ♦ Do they have the required **roles or permissions** (if specified)?"
- ♦ If everything is good it allows access.
- ♦ If the user is **not logged in** , returns 401 Unauthorized.
- ♦ If logged in but **missing required role/permission** , returns 403 Forbidden.
- ♦ So, it's responsible for **authorizing access based on user info**.
- ♦ We *usually* need both together if you're using `[Authorize]` .

Ahmed Zaher



---

## To summarize what you said (which is correct):

- ♦ UseAuthentication : **checks if there's a cookie (or token) and verifies it.**
  - ♦ [Authorize] : **checks the loaded user info to decide if access is allowed.**
- 

- ♦ To Make Sign out (Delete Cookies ):

```
public async Task<IActionResult> SignOut()
{
    await signInManager.SignOutAsync();
    return View("Login");
}
```

- ♦ Will Delete User Cookie For Identity
- 

- ♦ How We Login Again :

```
[HttpPost]
[ValidateAntiForgeryToken]
public async Task<IActionResult> SaveLogin(LoginUserViewModel userViewModel)
{
    if (ModelState.IsValid==true)
    {
        //check found
        ApplicationUser appUser=
            await userManager.FindByNameAsync(userViewModel.Name);
```

Ahmed Zaher



```

    if (appUser != null)
    {
        bool found=
            await userManager.CheckPasswordAsync(appUser, userModel.Password);
        if(found==true)
        {
            await signInManager.SignInAsync(appUser,userViewModel.RememberMe);
            return RedirectToAction("Index", "Department");
        }
    }
    ModelState.AddModelError("", "Username OR PAssword wrong");
    //create cookie
}
return View("Login", userModel);
}

```

```

ApplicationUser appUser=
    await userManager.FindByNameAsync(userViewModel.Name);

```

- it returns the User of ApplicationUser type if Found it , if not will return null

```

bool found= await userManager.CheckPasswordAsync(appUser, userModel.Password);

```

- Make Re-hash For Password and compare it

- 
- Controllers in ASP.NET Core **inherit** some properties from the ControllerBase or Controller class (depending on the type of controller). These properties are automatically available to the controller without any additional setup. Specifically:

1- ViewData



## 2 ViewBag

### 3 User , Type: ClaimsPrincipal

- The `User` property represents the **current authenticated user**. It contains information about the user's identity and claims (like roles, email, etc.), If No Authentication Found it Becomes **Null**
- **Inheritance:** `User` is inherited from `ControllerBase` (which is the base class for controllers).
  - **ClaimsPrincipal :**  
In ASP.NET Core, **ClaimsPrincipal** is the class used to represent the **current authenticated user** and contains all the claims associated with that user. The claims provide key information about the user, such as their roles, email address, and any other custom attributes related to their identity.
  - **ClaimsPrincipal** provides:
    - 1 **Identity:** Basic information about the user (like username).
    - 2 **Claims:** A collection of **key-value pairs** containing the user's information, such as roles, permissions, email, etc.

#### Example :

```
public IActionResult TestAuth()
{
    if (User.Identity.IsAuthenticated == true)
    {
        Claim IDClaim= User.Claims
            .FirstOrDefault(c => c.Type == ClaimTypes.NameIdentifier);

        Claim AddressClaim = User.Claims.FirstOrDefault(c => c.Type == "UserAddress");

        string id = IDClaim.Value;
        string address = AddressClaim?.Value ?? "Address not available";
        string name = User.Identity.Name;
        return Content($"welcome {name} \n ID= {id}");
    }
}
```



```
return Content("Welcome Guest");
}
```

- ♦ `User.Identity.IsAuthenticated == true` Used To Get The Authentication like `[Authorize]`
- ♦ `string name = User.Identity.Name;` used to get the Name
- ♦ To Get Other Properties by :
  - ♦ We Deal With User as context , Claims as Class in it , then use the needed property
  - ♦ Claims returns Type of `IEnumerable`
  - ♦ `NameIdentifier` is part of standard identity claims but `"UserAddress"` is A Custom Claim

```
Claim IDClaim= User.Claims
    .FirstOrDefault(c => c.Type == ClaimTypes.NameIdentifier);

Claim AddressClaim = User.Claims.FirstOrDefault(c => c.Type == "UserAddress");
```

### Example:

#### 1 Identity :

```
User.Identity.IsAuthenticated;
User.Identity.Name;
User.Identity.AuthenticationType;
```

#### 2 Claims :

Claim Type	ClaimTypes Constant	Example Value
Name	<code>ClaimTypes.Name</code>	jdoe
Name Identifier (User ID)	<code>ClaimTypes.NameIdentifier</code>	12345
Email	<code>ClaimTypes.Email</code>	<a href="mailto:jdoe@example.com">jdoe@example.com</a>
Role	<code>ClaimTypes.Role</code>	Admin



Claim Type	ClaimTypes Constant	Example Value
Given Name	ClaimTypes.GivenName	John
Surname	ClaimTypes.Surname	Doe
Date of Birth	ClaimTypes.DateOfBirth	1990-01-01
Gender	ClaimTypes.Gender	Male
Mobile Phone	ClaimTypes.MobilePhone	+1234567890
Country	ClaimTypes.Country	US
Locality (City)	ClaimTypes.Locality	New York
Street Address	ClaimTypes.StreetAddress	123 Main St
Postal Code	ClaimTypes.PostalCode	10001
Website	ClaimTypes.Webpage	https://example.com
Authentication Method	ClaimTypes.AuthenticationMethod	Password
Security Stamp (if using ASP.NET Identity)	<i>Custom, often named "AspNet.Identity.SecurityStamp"</i>	(GUID)

## • How Can We Add Custom Claims

- 1 Make Collection of Claims
- 2 Add needed Claim to created collection
- 3 use `SignInWithClaimsAsync` and add Appuser , boolean for long term cookie and collection of claims

```
List<Claim> Claims = new List<Claim>();
Claims.Add(new Claim("UserAddress",appUser.Address));

await signInManager.SignInWithClaimsAsync(appUser, userModel.RememberMe, Claims);
```

## ♦ To get it :

Ahmed Zaher



```
var userAddress = User.FindFirst("UserAddress)?.Value;  
//or  
Claim AddressClaim = User.Claims.FirstOrDefault(c => c.Type == "UserAddress");
```

## ♦ How Can Add Role

- ♦ To Add Role to DataBase We Use **IdentityRole** so we Make an inject for it at Controller
- ♦ then :

```
IdentityRole role = new IdentityRole();  
role.Name = "Admin";  
IdentityResult result= await roleManager.CreateAsync(role);  
if (result.Succeeded == true)  
{  
    ViewBag.sucess = true;  
    return View("AddRole");  
}  
  
foreach (var item in result.Errors)  
{  
    ModelState.AddModelError("", item.Description);  
}  
//code
```

## ♦ Add Role To User

♦

```
IdentityResult result=  
await userManager.CreateAsync(appUser,UserViewModel.Password);
```

Ahmed Zaher





```

if (result.Succeeded)
{
    //assign to role
    await userManager.AddToRoleAsync(appUser, "Admin");
    // or
    await userManager.AddToRolesAsync(appUser, new[] { "Admin", "Manager" });
    //Cookie
    await signInManager.SignInAsync(appUser, false);
    return RedirectToAction("Index", "Department");
}

```

- If you want to **restrict access** so that **only users in the Admin role** can access a controller or an action, you use:

```

[Authorize(Roles = "Admin")]
public class AdminController : Controller
{
    public IActionResult Dashboard()
    {
        return View();
    }
}

```

- To check if User Has a specific Role

```

if (User.IsInRole("Admin")){}

```

**When you assign a role to a user (e.g., with AddToRoleAsync):**

- A new record is created in the `AspNetUserRoles` table.
- This table acts as a **join table** between:
  - `AspNetUsers` (your users)
  - `AspNetRoles` (your roles)

Ahmed Zaher



So , it **creates a foreign key relationship** between the user and the role.

---

#### At login time:

- ♦ The system **queries that table** to find out which roles the user belongs to (following those foreign key links).
  - ♦ It **creates claims for each role** and **loads them into the user's identity (ClaimsPrincipal)**.
  - ♦ Those claims are **stored in the authentication cookie** (or token).
  - ♦ ♦ **Roles → Claims → ClaimsPrincipal → User.**
  - ♦ On every request:
    - ♦ The `ClaimsPrincipal` is rebuilt from the cookie/token and made available via `User` in controllers.
- 

#### After login:

- ♦ When you call:

```
User.IsInRole("Admin")
```

- ♦ it **does NOT** hit the database.
  - ♦ Instead, it **checks the user's already-loaded claims** (from the cookie/session) to see if `"Admin"` is there.
- 

#### Important reminder:

If you assign a role to a user **after they've already logged in**, the user won't see the new role until they **log out and log in again**, unless you force the claims to refresh.



# Day 9


## 1- Partial View:

- **A small, reusable Razor view.**
- **Included in a larger view to render part of the page.**
  - Think of it like a **view *without its own layout*** (no full page structure).
- **Often used for:**
  - Reusable UI pieces (e.g., a product card, menu, footer).
  - Keeping code clean and modular.
  - Loading content dynamically via AJAX (e.g., updating a section without full reload).

---

### How to create:

- The process is the **same as creating a normal view.**
- ✓ Just **check the option "Create as a partial view"** (in Visual Studio, for example).



- it is recommended to start partial view with " \_ " like `\_EmoCard.cshtml`

@model Employee

<h1>@Model.Name</h1>

Ahmed Zaher



```
<h2>@Model.DepartmentID</h2>
<h2>@Model.Salary</h2>
<h2>@Model.Address</h2>
```

## Why you don't include things like:

- ♦ ViewData
- ♦ <head> tags
- ♦ <script> or <link> includes (like jQuery, CSS)

### Because:

- ♦ The **partial view is *injected into* a main view.**
- ♦ The **main view already has the full layout:**
  - ♦ HTML <head> , <body> , title, scripts, styles, etc.
- ♦ The partial view is meant to **focus only on the small section of content** it is responsible for.
- ♦ As we see it can easily take a Model
- ♦ **To include a Partial View in the Main View:**

### 1 Using HTML Helper:

```
@Html.Partial("_NavPartial")
```

OR (recommended for async):

```
@await Html.PartialAsync("_NavPartial")
```

OR using **RenderPartial** (writes directly to the output stream):

Ahmed Zaher



```
@{  
    Html.RenderPartial("_NavPartial");  
    //or  
    await Html.RenderPartialAsync("_NavPartial");  
}
```

#### ✓ Notes:

- `Html.Partial()` returns an `IHtmlContent` (you output it).
- `Html.RenderPartial()` writes directly to the response stream (slightly more efficient but less flexible in Razor pages).

## 2) Using Tag Helper ( *recommended* for Razor Pages and MVC):

```
<partial name="_NavPartial" />
```

## Note:

by default A **partial view** will **inherit the model** from the **parent (main) view** unless you explicitly pass a different model.

### - What if you want to pass a **different model**?

You can **explicitly pass a model** when rendering:

1- By Tag Helper :

```
<partial name="_EmployeeDetails" model="Model.EmployeeDetails" />
```

Ahmed Zaher



model is an attribute , then pass it the new model you need

2- By Html Helper :

```
@await Html.PartialAsync("_EmployeeDetails", Model.EmployeeDetails);
```

- ♦ At Action I Can Return a partial view :

```
public IActionResult EmpCardPartial(int id)
{
    return PartialView("_EmpCard", EmployeeRepository.GetByld(id)); //Model=Null
}
```

## We have a Question why we return a partial view ?


We return a partial view:

- ♦ **When we don't want to refresh the whole page**
  - This is where **AJAX** comes in: you send an AJAX request, and the server returns **only the partial view**, which JavaScript injects into the page dynamically.
- ♦ **When we want to reuse a small, specific part of the UI in multiple places**
  - Even **without AJAX**, you can render partial views **inside other views** to avoid repeating code.



Ajax  
xmlHttpRequest

Ajax:  
Set  
- XMLHttpRequest  
-js "Dom"  
-- CSS...



## ♦ AJAX Request

- ♦ it's used to update part of the page without reloading the whole thing.

## ♦ But technically:

- ♦ The HTTP request itself is a *full request*.

- ♦ When you send an AJAX request using XMLHttpRequest, it **goes through the full HTTP pipeline**:
  - ♦ The browser sends **full HTTP headers, cookies, and body** (if applicable).
  - ♦ The server (like ASP.NET) sees it as a **normal HTTP request**.

- ♦ What makes it **feel "partial"** is **how you handle the response on the client side**.

- ♦ Instead of reloading the **whole page** (like with a normal form submission),

Ahmed Zaher



- You **use JavaScript to update just part of the page** (e.g., a `<div>` , a table, a form section)
- ♦ **XmlHttpRequest:**
  - This is the JavaScript object that **creates and manages AJAX requests.** and received ***XML or JSON***
- **js "Dom":**
  - After the response is received, **JavaScript updates the DOM (HTML content)** dynamically.
- ♦ **CSS:**
  - You can also manipulate CSS (styles) as part of the dynamic update.

Aspect	Normal HTTP Request	AJAX (XMLHttpRequest / Partial Request)
Request type	Full HTTP request	Full HTTP request
How it's sent	Browser reload or form submit	JavaScript sends it (in background)
Page reload?	Yes, whole page reloads	No, page stays as is
What updates on the page?	Entire page is replaced with server response	Only parts of the page are updated via JavaScript
Example	Submitting a contact form that reloads the page	Submitting a form and showing success without reload
Headers & body	Full HTTP headers and body	Full HTTP headers and body
Use case	Full page navigation	Dynamic page updates (e.g., live search, chat updates)

To implement Ajax :

```
@model List<Employee>
@{
    ViewData["Title"] = "Index";
}

<h1>Index</h1>
<a asp-action="New" asp-controller="Employee">NEW</a>
```

Ahmed Zaher





```
<div id="div1" style="border:2px solid blue"></div>
```

```
<table class="table table-bordered table-hover">
```

```
  <tr>
```

```
    <th>ID</th>
```

```
    <th>Name</th>
```

```
    <th>Salary</th>
```

```
    <th></th>
```

```
  </tr>
```

```
  @foreach (var item in Model)
```

```
  {
```

```
    <tr>
```

```
      <td>@item.Id</td>
```

```
      <td>@item.Name</td>
```

```
      <td>@item.Salary</td>
```

```
      <td>
```

```
        <a href="/Employee/Edit/@item.Id">Edit</a>
```

```
      </td>
```

```
      <td>
```

```
        <a href="/Employee/EmpCardPartial/@item.Id" onclick="GetEmpData(@item.Id)">Details</a>
```

```
      </td>
```

```
    </tr>
```

```
  }
```

```
</table>
```

```
<script src="~/lib/jquery/dist/jquery.js" ></script>
```

```
<script>
```

```
  function GetEmpData(EmpID) {
```

```
    event.preventDefault();
```



```
//Ajax Call Endpont using jquery
$.ajax({
  url: "/Employee/EmpCardPartial/" + EmpID,
  success: function (result) {
    console.log(result);
    $("#div1").html(result);
  }
});

}
</script>
```

- 1 We make a div with id="div1" to get the partial view on it
- 2 to use client side we used JS and JQuery , so we uploaded JQuery
- 3 We used event.preventDefault(); → to stop the anchor tag's default behavior (which is to make a full-page HTTP request to the href URL).
- 4 using Ajax Call by JQuery by a popular ready code:

```
$.ajax({
  url: "/Employee/EmpCardPartial/" + EmpID,
  success: function (result) {
    console.log(result);
    $("#div1").html(result);
  }
});
```

- ♦ We put Wanted URL that doing fetch from ,and Dom for Wanted Div
- ♦ So We have made an ajax Call



Example using AJAX :

1- I want to make 2 drop-down lists , one for Department and other for Employees at selected department

- 1 I load all Departments at Model
- 2 add method for Employee to return all Department Id
- 3 at department I return all employee result as a JSON file
- 4 use JQuery and JS to make Partial Request

1 Employee

```
public List<Employee> GetByDEptID(int deptID)
{
    return context.Employee.Where(e=>e.DepartmentID== deptID).ToList();
}
```

2 at Department Controller

```
public IActionResult GetEmpsByDEptId(int deptId)
{
    List<Employee> EmpList= EmployeeREpo.GetByDEptID(deptId);
    return Json(EmpList);
}
```

3 at Department View

```
@model List<Department>
@{
    ViewData["Title"] = "DeptEmps";
}

<h1>DeptEmps</h1>
```

Ahmed Zaher



```

<select id="DeptId" name="DeptID" class="form form-control" onchange="GetEmp()">
  @foreach(var deptItem in Model){
    <option value="@deptItem.Id">@deptItem.Name</option>
  }
</select>
<br />
<select id="Emps" name="Emps" class="form form-control">
</select>

<script src="~/lib/jquery/dist/jquery.min.js"></script>
<script>
  function GetEmp() {
    var deptID= document.getElementById("DeptId").value;
    var empElement = document.getElementById("Emps");
    empElement.innerHTML = "";
    console.log(deptID);
    //Ajax call json

    $.ajax({
      url: "/DEpartment/GetEmpsByDEptId?deptId=" + deptID
      , success: function (result) {
        console.log(result)
        for (let emp of result) {
          empElement.innerHTML += "<option value='" + emp.id + "'>" + emp.name + "</option>";
        }
      }
    });
  }
</script>

```



- First We Loaded All Departments, and use `onChange()` to every time I change the selected department I load it's employees by `GetEmp()` function

```
<select id="DeptId" name="DeptID" class="form form-control" onchange="GetEmp()">
  @foreach(var deptItem in Model){
    <option value="@deptItem.Id">@deptItem.Name</option>
  }
</select>
```

- Then We make an Empty Select To load all Employee Related To Selected Department

```
<select id="Emps" name="Emps" class="form form-control"></select>
```

- We use JQuery

```
<script src="~/lib/jquery/dist/jquery.min.js"></script>
<script>
  function GetEmp() {
    var deptID= document.getElementById("DeptId").value;
    var empElement = document.getElementById("Emps");
    empElement.innerHTML = "";
    console.log(deptID);
    //Ajax call json

    $.ajax({
      url: "/DEpartment/GetEmpsByDEptId?deptId=" + deptID
      , success: function (result) {
        console.log(result)
        for (let emp of result) {
          empElement.innerHTML += "<option value='" + emp.id + "'>" + emp.name + "</option>";
        }
      }
    })
  }
</script>
```

Ahmed Zaher



```
});  
}  
</script>
```

`result` is the **data returned by the server when the AJAX request completes successfully**.

Here's what happens step-by-step:

1. **The browser sends a request** to `/DEpartment/GetEmpsByDEptId?deptId=...`.
2. **Your server handles that request** and returns a response—usually JSON if you're dealing with data.
3. **result holds that response data** (e.g., an array of employee objects like `[{ id: 1, name: 'Alice' }, ...]`).
4. I Add The response values to the empty select

---

## • Routing

- What is Routing :  
**routing** refers to the system that **maps incoming HTTP requests to specific code**—typically controllers, actions, Razor pages, or endpoints.

### What it means:

- ♦ When a user visits a URL like `/products/details/5`, routing figures out **which controller and action** (or page) should handle that request.
- ♦ The routing system **parses the URL** and **binds parameters** (like the `5` in the example) to your method's parameters.

Routing is doing by 2 types :

- ♦ **1 convention-based routing** :You can use **convention-based routing** (via route templates like `{controller}/{action}/{id?}` )
- ♦ **2 attribute routing** (via `[Route()]` attributes).

Ahmed Zaher



---

## 1- Convention-based routing

- ♦ We need to know about URL
  - 1 / → called a delimiter
  - 2 /.../ or /emp/ → called Segment
- ♦ so , **Convention-based routing** means:
- ♦ You define a **general pattern** (a *convention*) that tells ASP.NET **how to map URLs to controller actions**.
- ♦ URLs that follow this **pattern** automatically map to your code **without needing special route definitions for each one**.
- ♦ pattern

```
pattern: "{controller}/{action}/{id?}"
```

- ♦ {controller} → the **name of the controller** (minus Controller ).
- ♦ {action} → the **method (action)** inside that controller.
- ♦ {id?} → an **optional parameter** (like a record ID).
- ♦ the **pattern** can include:

1 Placeholders

2 Literals

---

### 1 Placeholders (Route Parameters)

These are **variable parts** of the URL, written inside { }.

→ Examples:

- ♦ {controller}

Ahmed Zaher



- {action}
- {id}

**What they do:**

- **Capture part of the URL** and map it to a value.
- Are **dynamic**—they change based on what's in the URL.

---

**Example pattern:**

```
`"{controller}/{action}/{id?}"`
```

**URL:** /Products/Details/5

Part of the URL	Placeholder it matches
Products	{controller}
Details	{action}
5	{id}

---

## 2 Literals (Fixed Parts)

These are **hardcoded parts** of the pattern. They are **static** and must **exactly match** part of the URL.

→ Examples:

- shop

Ahmed Zaher





- ♦ products
- ♦ api

### What they do:

- ♦ Must **be present in the URL** exactly as written.
- ♦ Are **not dynamic**—if the literal doesn't match, the route won't match.

---

To enable routing, you need to call:

```
app.UseRouting();
```

This **adds the routing middleware** to the pipeline. It tells ASP.NET Core:

“We are going to process incoming URLs and match them to routes.”

Without `UseRouting()` , **no routing will work.**

- ♦ **then We can customize our Routing**

- ♦ Example :  
At Program .cs

```
app.MapControllerRoute("Route2", "R2",  
    new { controller = "Route", action = "Method2" }  
);
```

At Route Controller

```
public IActionResult Method2()  
{
```

Ahmed Zaher



```
    return Content("M2");  
}
```

The **first parameter** of `MapControllerRoute()` is a **name for the route**. In this case, "Route2" is simply a **name** for the route being defined , **it must be unique**.

## Here's how it breaks down:

1. "Route2" – This is the **name** of the route. It's an identifier that you can use to reference or manage this route later, but it **doesn't affect the URL matching** directly. It's mainly for **internal reference**.
2. "R2" – This is the **URL pattern** that will be used to match incoming requests. So, any request to `/R2` will be mapped to this route.
3. `new { controller = "Route", action = "Method2" }` – This part defines the **controller** and **action** that will be invoked when the route is matched:
  - **Controller:** `RouteController`
  - **Action:** `Method2`
4. We can Directly Write for the URL `/R2/` then Will go to Wanted Method

## How Does It Work?

- When someone visits `/R2` in the browser, this route is triggered.
- The request will then be directed to the **RouteController** and will invoke the **Method2** action inside that controller.
- if the method receives an attribute like :

```
public IActionResult Method2(string name)  
{  
    return Content("M2");  
}
```

we use :

Ahmed Zaher



/R2?name=ali

- attribute must be same name as called in url
- We Can Add constraints like :

Constraint	Description	Example
alpha	Matches uppercase or lowercase Latin alphabet characters (a-z, A-Z)	{x:alpha}
bool	Matches a Boolean value.	{x:bool}
datetime	Matches a <b>DateTime</b> value.	{x:datetime}
decimal	Matches a decimal value.	{x:decimal}
double	Matches a 64-bit floating-point value.	{x:double}
float	Matches a 32-bit floating-point value.	{x:float}
guid	Matches a GUID value.	{x:guid}
int	Matches a 32-bit integer value.	{x:int}
length	Matches a string with the specified length or within a specified range.	{x:length(6)} , {x:length(1,20)}
long	Matches a 64-bit integer value.	{x:long}
max	Matches an integer with a maximum value.	{x:max(10)}
maxlength	Matches a string with a maximum length.	{x:maxlength(10)}
min	Matches an integer with a minimum value.	{x:min(10)}
minlength	Matches a string with a minimum length.	{x:minlength(10)}
range	Matches an integer within a range of values.	{x:range(10,50)}
regex	Matches a regular expression.	{x:regex(^\\d{3}-\\d{3}-\\d{4}\$)}

- like :

Ahmed Zaher



```
app.MapControllerRoute("Route2", "R2/{name}/{age:int}",
    new { controller = "Route", action = "Method2" }
);
```

- makes third segment name must be same for for method attribute like :

```
public IActionResult Method2(string name)
{
    return Content("M2");
}
```

```
app.MapControllerRoute("Route2", "R2/{name}",
    new { controller = "Route", action = "Method2" }
);
```

- Will pass attribute value by /name
- We can also make segment is optional like

```
app.MapControllerRoute("Route2", "R2/{age:int}/{name?}",
    new { controller = "Route", action = "Method2" }
);
```

- we should make optional segment the last segment
- we can make default value for the segment by :

```
app.MapControllerRoute("Route2", "R2/{name=ali}",
    new { controller = "Route", action = "Method2" }
);
```



- **Note :**

- Most Customized Route must be first then we put default Route
- 

```
app.MapControllerRoute("Route2", "R2/{controller}/{action}");
```

- Here We can use Controller , Action For URL , it is the default for Microsoft so , We can put it at last

---

## 2- Attribute-based routing (also called attribute routing)

1- before the Action

```
[Route("M1/{age:int}/{name?}",Name ="R1")]  
public IActionResult Method1(string name,int age)  
{  
    return Content("M1");  
}
```

1 it takes the Routed URL , and name of Route

- **Note:**

- *\*\*Attribute-based routing* : used Most For API
- **2 Convention-based routing** : Used Most For MVC

---


- **How Can I Make Deployment**

- 1- Right Click on project name

Ahmed Zaher





- ♦ 2 choose publish
- ♦ 3 choose Folder if we don't Have Azure or Docker



- ♦
- ♦ 4 then choose location
- ♦ 5 choose setting

Ahmed Zaher





- ♦ 6- We have 2 options :
  - ♦ 1 Framework-dependent :if host has the runtime
  - 2 ♦ Self-contained: download all runtime requirement if host does not have the runtime
- ♦ 7-click save .

♦ **Finally We Finished ( ^ - ^ )**



♦ **Connect with me :-**

 [Ahmed Zaher](#)  [Ahmed Zaher](#)





# Thank



# You

---

Ahmed Zaher

