

# ClarkNet-HTTP Server Analysis

File analysis results

**Name :** Ahmed Mohammed Adel Ibrahim

**COURSE :** Information Security Management

**Doctor :** Mohammed Hassan

**Instructor :** Yahia Ashraf

[Data Link](#) - [Bash Link](#)

## 1.Overview :

### About ClarkNet:

- **ClarkNet** was one of the first **independent commercial Internet Service Providers** in the United States, based in Maryland.
- The dataset originates from the **public web server** of ClarkNet, which hosts user and business web pages.
- It served content via **HTTP/1.0**, mostly static files such as .html, .gif, and .jpg.

### Log Dataset Details:

- Analyzed file: **clarknet\_access\_log\_Sep4**
- Total requests: **1,673,750**
- Date range covered: **September 4–10, 1995**
- Format: **Apache Common Log Format**
- Unique IPs: **94,772**
- Total 404 errors: **35,542**

### Server Stack :

- **Operating System:** Unix-based
- **Web Server:** Apache HTTPD **or** NCSA HTTPD
- **Content Type:** Fully static; ( no AJAX or JavaScript-based interactivity )

## 2.Summary of Script Output Analysis

### Request Statistics:

- Total number of requests: 1,673,750  
GET requests: 1,669,515
  - POST requests: 2,538
  - Unique IP addresses: 94,772
- 

### Requests by IP:

- Most active IP: piweba5y.prodigy.com with 7,239 requests
  - Top 10 most active IPs are primarily from AOL proxies and IBM networks
- 

### Failed Requests :

- Total failed requests: 37,975
  - Failure rate: 2.27%
  - Days with highest failure counts:
    - September 8: 6,485
    - September 7: 6,469
    - September 6: 6,219
-

#### Daily Activity:

- Busiest day: September 8 with 280,342 requests
  - Least active day: September 10 with 192,263 requests
- 

#### Hourly Distribution:

- Peak activity hours: Between 12:00 PM and 3:00 PM
  - Lowest activity: Early morning hours between 03:00 and 06:00 AM
- 

#### HTTP Status Code Breakdown:

- 200 OK: 1,485,020
  - 304 Not Modified: 134,782
  - 404 Not Found: 35,542 <- relatively high
  - 500 Internal Server Error: 1,303
  - 403 Forbidden: 958
-

### Most Requested Pages:

- Product catalog GIF images:
    - </pub/atomicbk/catalog/logo2.gif> -> over 20,000 times
  - Popular HTML pages:
    - </pub/journalism/awesome.html>
    - </pub/job/vk/vendela.html>
- 

### Top 404 Error Pages:

- </pub/atomicbk/images/earlyero.gif>
  - </pub/atomicbk/images/nudistbk.gif>
  - </pub/mjoneill/links.html>
- 

### Most Requested File Types:

- .gif: 839,465
- .jpg: 421,556
- .html: 276,342
- Others like .txt, .wav, .zip, .pl, .cgi were far less frequent

### 3. Analysis Insights & Observations

#### **Request Trend Analysis**

- **Peak Day:** September 8, 1995 — with 280,342 requests.
  - **Lowest Activity:** September 10, 1995 — with 192,263 requests.
  - **Overall Pattern:** There is a steady increase in request volume from September 4 to 8, followed by a noticeable decline on September 9 and 10. This pattern indicates typical weekday traffic peaks and weekend drops.
- 

#### **Failure Requests by Hour**

- **The highest failure activity occurred during:**
    - 16:00 → 2,359 failed requests
    - 14:00 → 2,220 failed requests
    - 17:00 → 2,099 failed requests
  - These hours correspond to high traffic periods, suggesting that the failures could be due to server load or targeted probing attempts.
-

## GET vs POST Breakdown per IP (Top 10)

- **Example:**
  - **piweba5y.prodigy.com: 7,219 GET and 20 POST requests**
  - **www-e5.proxy.aol.com: 5,122 GET and 1 POST**
- **Observation:** The majority of top IPs use only GET, which is consistent with browsing or automated scanning. A few IPs also show POST activity that may require deeper inspection.

## 4.Detailed Security notes from log analysis with suggested improvements

### 1. IPs Sending Over 100 Requests per Hour

#### Observtion :

- These are likely automated bots, vulnerability scanners, **or light DoS attempts.**

#### Risk :

- Can lead to resource exhaustion or prep for **brute-force attacks.**

#### Action needed :

- Implement **rate-limiting**, monitor suspicious IPs, and use tools like **fail2ban** to auto-block them.
- 

### 2. High Volume of 404 Not Found Errors

#### Observtion :

- Many clients are attempting to access **nonexistent files.**

#### Ex :

- **/admin, /backup.zip, or typo variations like /html.**

#### Action needed :

- Monitor recurring 404 patterns.
- block IPs that trigger too many in a short time.

---

### 3. Heavy Traffic on Static Media (.gif, .jpg)

#### Observtion :

- Indicates automated scripts may be scraping site content or causing bandwidth.

#### Risk :

- Can slow down the site or lead to extra hosting costs.

#### Action needed :

- Use **anti-scraping headers**, **CDN protections**, or tools like **Cloudflare** with **bot mitigation enabled**.
- 

### 4. Repeated Requests for the Same Files from Multiple IPs

#### Observtion :

- This could signal distributed probing, where multiple IPs are scripted to try the same URLs to avoid detection.

#### Action needed :

- Use log correlation to track this pattern.
-

## 5. Consistent Traffic Spikes During Specific Hours

### Observtion :

- Traffic peaks between **12 PM and 3 PM** suggest these hours are the busiest — which also makes them prime time **for attacks to blend in.**

### Action needed :

- Strengthen server performance and enable protective measures during peak hours, like **WAF or load balancing.**
- 

## 6. Unusual POST Activity

### Observtion :

- While POST requests are **low in number**, any unexpected POST traffic should be closely analyzed.

### Risk :

- **POST** is often used in attacks like SQL Injection, file upload abuse, or credential stuffing.

### Action needed :

- **Log POST** data paths and parameters.
-

## 7. Suspicious IPs Involved in Multiple Threat Patterns

### Observation :

- Some IPs appear in multiple suspicious contexts “excessive **GETs, POSTs, and 404s** “ indicating they are actively probing the system.

### Action needed :

- **Add such IPs** to blocklists or greylists, and flag them for deeper analysis.
- 

## 8. Presence of HTTP 500 Errors

### Observation :

- Internal server errors may indicate backend instability or trying to crash or exploit the server.

### Action needed :

- **Correlate 500 errors with their IP origin and request path.**
  - review backend logs.
-

## 9. Targeted 404 Errors for Specific Filenames

### Observation:

- Filenames like nudistbk.gif or links.html suggest bots are looking for sensitive or private content, not just random file guessing.

### Risk:

- Indicates targeted probing, potentially based on known file structures or previously leaked data.

### Action needed:

- Track and alert on specific keyword-based URL attempts.
  - consider using honey URLs to catch attackers in the act.
- 

## 10. Unusual File Types Being Requested

### Observation:

- Requests for .cgi, .pl, .zip, or .bak files often indicate attempts to:
  - Execute old vulnerable scripts.
  - Download backup files left on the server.

### Risk:

- May lead to information disclosure or remote code execution.

### Action needed:

- Restrict public access to these file types using .htaccess or web server configs.

### 3.Conclusion

The analyzed log file from the ClarkNet web server provides valuable insights into real-world web traffic behavior from 1995. It reveals common patterns such as high volumes of GET requests, a significant number of 404 errors, and potential signs of automated scanning or denial-of-service attempts. Several IPs showed suspicious activity, making it essential to implement proper security measures like request rate-limiting, 404 monitoring, and protection against content scraping. Overall, the log highlights the importance of regular log analysis for detecting abnormal behavior and strengthening server security.

*Thank You*  
*Ahmed Mohammed*