

# Sectioning tags

Use the following tags to organize your HTML document into structured sections.

## **<header>**

The header of a content section or the web page. The web page header often contains the website branding or logo.

## **<nav>**

The navigation links of a section or the web page.

## **<footer>**

The footer of a content section or the web page. On a web page, it often contains secondary links, the copyright notice, privacy policy and cookie policy links.

## **<main>**

Specifies the main content of a section or the web page.

## **<aside>**

A secondary set of content that is not required to understand the main content.

## **<article>**

An independent, self-contained block of content such as a blog post or product.

### **<section>**

A standalone section of the document that is often used within the body and article elements.

### **<details>**

A collapsed section of content that can be expanded if the user wishes to view it.

### **<summary>**

Specifies the summary or caption of a **<details>** element.

### **<h1><h2><h3><h4><h5><h6>**

Headings on the web page. **<h1>** indicates the most important heading whereas **<h6>** indicates the least important.

## **Content tags**

### **<blockquote>**

Used to describe a quotation.

### **<dd>**

Used to define a description for the preceding **<dt>** element.

### **<d1>**

Used to define a description list.

### **<dt>**

Used to describe terms inside **<d1>** elements.

### **<figcaption>**

Defines a caption for a photo image.

### **<figure>**

Applies markup to a photo image.

### **<hr>**

Adds a horizontal line to the parent element.

### **<li>**

Used to define an item within a list.

### **<menu>**

A semantic alternative to <ul> tag.

### **<ol>**

Defines an ordered list.

### **<p>**

Defines a paragraph.

### **<pre>**

Used to represent preformatted text. Typically rendered in the web browser using a monospace font.

### **<ul>**

Unordered list

## **Inline tags**

**<a>**

An anchor link to another HTML document.

**<abbr>**

Specifies that the containing text is an abbreviation or acronym.

**<b>**

Bolds the containing text. When used to indicate importance use **<strong>** instead.

**<br>**

A line break. Moves the subsequent text to a new line.

**<cite>**

Defines the title of creative work (for example a book, poem, song, movie, painting or sculpture). The text in the **<cite>** element is usually rendered in italics.

**<code>**

Indicates that the containing text is a block of computer code.

**<data>**

Indicates machine-readable data.

**<em>**

Emphasizes the containing text.

**<i>**

The containing text is displayed in italics. Used to indicate

idiomatic text or technical terms.

**<mark>**

The containing text should be marked or highlighted.

**<q>**

The containing text is a short quotation.

**<s>**

Displays the containing text with a strikethrough or line through it.

**<samp>**

The containing text represents a sample.

**<small>**

Used to represent small text, such as copyright and legal text.

**<span>**

A generic element for grouping content for CSS styling.

**<strong>**

Displays the containing text in bold. Used to indicate importance.

**<sub>**

The containing text is subscript text, displayed with a lowered baseline.

**<sup>**

The containing text is superscript text, displayed with a raised

baseline.

**<time>**

A semantic tag used to display both dates and times.

**<u>**

Displays the containing text with a solid underline.

**<var>**

The containing text is a variable in a mathematical expression.

## **Embedded content and media tags**

**<audio>**

Used to embed audio in web pages.

**<canvas>**

Used to render 2D and 3D graphics on web pages.

**<embed>**

Used as a containing element for external content provided by an external application such as a media player or plug-in application.

**<iframe>**

Used to embed a nested web page.

**<img>**

Embeds an image on a web page.

### **<object>**

Similar to **<embed>** but the content is provided by a web browser plug-in.

### **<picture>**

An element that contains one **<img>** element and one or more **<source>** elements to offer alternative images for different displays/devices.

### **<video>**

Embeds a video on a web page.

### **<source>**

Specifies media resources for **<picture>**, **<audio>** and **<video>** elements.

### **<svg>**

Used to define Scalable Vector Graphics within a web page.

## **Table tags**

### **<table>**

Defines a table element to display table data within a web page.

### **<thead>**

Represents the header content of a table. Typically contains one **<tr>** element.

### **<tbody>**

Represents the main content of a table. Contains one or more `<tr>` elements.

`<tfoot>`

Represents the footer content of a table. Typically contains one `<tr>` element.

`<tr>`

Represents a row in a table. Contains one or more `<td>` elements when used within `<tbody>` or `<tfoot>`. When used within `<thead>`, contains one or more `<th>` elements.

`<td>`

Represents a cell in a table. Contains the text content of the cell.

`<th>`

Defines a header cell of a table. Contains the text content of the header.

`<caption>`

Defines the caption of a table element.

`<colgroup>`

Defines a semantic group of one or more columns in a table for formatting.

`<col>`

Defines a semantic column in a table.